Reach-Avoid Constrained Selection for Safe Counterfactual Intervention Planning

Anonymous Author(s)
Affiliation
Address
email

Abstract

Variational counterfactual intervention planning selects treatment sequences by optimizing an evidence lower bound (ELBO) toward a point target outcome. In clinical practice, however, the goal is typically to bring a patient's state into an *acceptable range* while maintaining *safety constraints* at every intermediate step—requirements that point-target optimization does not address. We introduce *reach-avoid constrained selection*, a post-hoc method that filters ELBO-ranked candidate sequences through a reach-avoid feasibility criterion: the terminal outcome must lie within a target set $\mathcal{T}$ and all intermediate outcomes must remain within a safety set $\mathcal{S}$. We prove that reach-avoid ranking is more robust to variational approximation error than point-target ELBO ranking, with an explicit bound relating the ranking preservation margin to the variational gap $\varepsilon_{\mathrm{VI}}$ and soft-indicator approximation error $\varepsilon_{\mathrm{soft}}$. Empirically, on a cancer tumor growth simulator with known counterfactuals, reach-avoid constrained selection improves safety by 18–33 percentage points under moderate-to-strong confounding at modest ranking cost, Pareto-dominates soft-constraint alternatives, and transfers to all baseline models without retraining. On MIMIC-III intensive care data, the method lifts in-target diastolic blood pressure rates from 73–81% to 99–100%. The approach requires no model modification, no retraining, and is compatible with any variational counterfactual planner.

1 Introduction

Individualized treatment planning from observational data is a central challenge in precision medicine [Chakraborty and Moodie, 2014, Murphy, 2003]. Given a patient's clinical history, the goal is to recommend a sequence of interventions—medications, dosages, ventilation settings—that will produce the best outcome over a planning horizon τ. Recent advances in variational latent-dynamics models have made this tractable: Variational Counterfactual Intervention Planning [VCIP; Melnychuk et al., 2025] learns a latent state-space model from observational trajectories and selects treatment sequences by optimizing an evidence lower bound (ELBO) toward a target outcome value.

However, clinical treatment planning has two features that point-target ELBO optimization does not capture:

Range targets, not point targets. Clinicians do not aim for a single number. They aim for an *acceptable range*: diastolic blood pressure in $[60, 90]$ mmHg, tumor volume below a stage-dependent threshold, blood glucose within safe bounds. A treatment plan that overshoots the target by 1% and one that undershoots it by 50% receive the same ELBO penalty if they are equidistant from the point target, yet their clinical implications differ fundamentally. This limitation was explicitly identified in

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.



Figure 1: **Reach-avoid vs. point-target selection.** The dark green star (★) marks the ELBO point target Y^*. Left: ELBO-based selection picks sequence D (closest to Y^* at terminal time) despite its safety violation at $t{+}3$. Right: RA-constrained selection restricts to feasible sequences (those reaching $\mathcal{T}$ while staying in $\mathcal{S}$) and selects the best ELBO among them (A over B, which is also feasible but has worse ELBO). D is rejected for violating safety; C for missing the target.

the VCIP peer review process, where a reviewer noted the restrictive nature of single-point targets for clinical applications and the authors acknowledged range-based targets as important future work.

Path safety, not just terminal achievement. ELBO-based planning evaluates only the terminal outcome $Y_{t+\tau}$. It is blind to what happens along the way. A chemotherapy regimen that produces dangerously high toxicity at step $t{+}3$ before recovering at step $t{+}\tau$ may rank identically to a safe regimen—both achieve the same terminal tumor volume. In clinical practice, intermediate safety violations are unacceptable: a patient whose blood pressure drops to dangerous levels during treatment has suffered harm regardless of the final reading.

These concerns arise naturally from the reach-avoid control literature [Mitchell et al., 2005, Fisac et al., 2015], where the objective is to steer a dynamical system into a target set while avoiding unsafe regions throughout the trajectory. Figure 1 illustrates the distinction: ELBO-based selection picks the sequence with the best terminal loss (D), ignoring its unsafe intermediate path, while reach-avoid constrained selection picks the best ELBO among sequences with safe trajectories (A).

Our approach. We propose *reach-avoid constrained selection*: given a set of candidate treatment sequences ranked by ELBO, we filter out sequences that fail a reach-avoid feasibility criterion and select the best ELBO among the feasible set:

$$\bar{a}^* = \arg\min_{\bar{a} \in \mathcal{F}_{\mathrm{RA}}} \mathrm{ELBO}(\bar{a}), \tag{1}$$

where $\mathcal{F}_{\mathrm{RA}} = \{\bar{a} : Y_{t+\tau}[\bar{a}] \in \mathcal{T} \text{ and } Y_s[\bar{a}] \in \mathcal{S} \text{ for all } s = t, \ldots, t{+}\tau\}$ is the set of reach-avoid feasible sequences. This is deliberately simple: no new model, no retraining, no gradient-based planning. The method operates as a *post-hoc safety filter* on any existing variational counterfactual planner.

The simplicity is a feature. By separating safety (via the RA filter) from quality (via ELBO ranking), we avoid the failure mode we observed when attempting to use RA scoring as a *replacement* for ELBO ranking: the RA score is near-binary (sequences are either clearly feasible or clearly not), providing no discrimination among candidates. ELBO ranking and RA feasibility are complementary—each does what the other cannot.

Contributions.

1. **Problem formulation.** We formalize reach-avoid counterfactual intervention planning, connecting the clinical requirement of range targets with path safety to the reach-avoid framework from control theory (Section 4).

2. **Ranking robustness theory.** We prove that reach-avoid ranking is more robust to variational approximation error than point-target ELBO ranking (Theorem 1), with an explicit bound on the ranking preservation margin. We empirically verify the bound is non-vacuous with $\varepsilon_{\mathrm{VI}} \approx 0.09$–$0.23$ (Section 5).

3. **Comprehensive experiments.** On the Cancer simulator with known counterfactuals, reach-avoid constrained selection yields $+18$–33 percentage point (pp) safety improvement under moderate-to-strong confounding, Pareto-dominates soft-constraint alternatives, and generalizes across five baseline models without retraining. On MIMIC-III ICU data, it lifts in-target rates from 73–81% to 99–100% (Section 6).

4. **Model-agnostic post-hoc method.** The approach requires no retraining—we show empirically that RA-aware retraining produces identical results to post-hoc filtering—and is compatible with any variational counterfactual planner (Section B).

2 Related Work

Counterfactual outcome estimation and planning. A growing body of work estimates individualized treatment effects from longitudinal observational data. Marginal structural models [Robins et al., 2000] use inverse probability weighting; Counterfactual Recurrent Networks [CRN; Bica et al., 2020a] learn balanced representations; the Causal Transformer [Melnychuk et al., 2022] uses attention-based architectures; and RMSN [Lim, 2018], G-Net [Li et al., 2021], and ACTIN [Seedat et al., 2022] offer alternative sequential estimation strategies. These methods estimate outcomes for *given* treatments but do not optimize over treatment sequences. VCIP [Melnychuk et al., 2025] extends this line to *planning*: it selects intervention sequences by ELBO minimization toward a point target. Our work keeps the VCIP planning infrastructure intact and adds a safety-aware selection layer.

Dynamic treatment regimes. The DTR literature [Murphy, 2003, Chakraborty and Moodie, 2014, Hernán and Robins, 2020] formalizes sequential treatment decisions under the potential outcomes framework. Most DTR methods learn decision rules mapping states to actions, optimizing expected outcomes over the full trajectory. In contrast, VCIP and our extension operate in a *counterfactual planning* mode: given a specific patient history, they evaluate and rank complete intervention sequences. The reach-avoid formulation adds the constraint that trajectories must remain safe, a concern shared with constrained DTR work but addressed here through a distinct mechanism (post-hoc filtering rather than constrained policy learning).

Safe and constrained sequential decision-making. Safe reinforcement learning [García and Fernández, 2015, Chow et al., 2018, Dalal et al., 2018] constrains policies to satisfy safety specifications during execution. These methods operate in the online RL setting with environment interaction, requiring either a simulator or real-time feedback. Our setting is fundamentally offline: we select among candidate plans evaluated on a learned model, with no opportunity for online correction. This distinction motivates a filter-based approach rather than constrained policy optimization. The *reach-avoid* concept from control theory [Mitchell et al., 2005, Fisac et al., 2015, Altschuler and Parrilo, 2023] formalizes the objective of reaching a target set while avoiding unsafe regions. We import this concept into the variational counterfactual planning framework, replacing the continuous reachability computation with a discrete feasibility check over candidate sequences.

Variational causal inference. VCI [Wu and Bareinboim, 2025] derives an ELBO for individual-level counterfactual likelihoods in a static setting, introducing latent disentanglement via $D_{\mathrm{KL}}[q(z|y,t,x)\|q(z|y',t',x)]$. We draw on VCI's insight that latent action-sensitivity is a diagnostic for counterfactual model quality (Section C), adapting it to the sequential setting. Our diagnostic reveals that VCIP's latent space is nearly action-invariant ($D_{\mathrm{KL}} \approx 10^{-5}$), with action-outcome coupling residing entirely in the decoder.

3 Background: Variational Counterfactual Intervention Planning

We briefly review the VCIP framework [Melnychuk et al., 2025] to establish notation.

Setting. Consider a longitudinal observational dataset with patient histories $\bar{H}_t = (X_1, A_1, Y_1, \ldots, X_t, A_t, Y_t)$, where $X_s \in \mathbb{R}^p$ are time-varying covariates, $A_s \in \mathcal{A}$ are treatments (binary or categorical), and $Y_s \in \mathbb{R}^d$ are outcomes of interest. Given a patient's history $\bar{H}_t$ up to time t and a planning horizon τ, the goal is to select an intervention sequence $\bar{a} = (a_{t+1}, \ldots, a_{t+\tau}) \in \mathcal{A}^\tau$ that optimizes the counterfactual outcome $Y_{t+\tau}[\bar{a}]$.

Latent dynamics model. VCIP posits a latent state $Z_s \in \mathbb{R}^{d_z}$ with:

- Generative transition: $p_\theta(Z_{s+1} \mid Z_s, a_s)$, modeling how latent states evolve under treatment,
- Emission (decoder): $p_\theta(Y_s \mid Z_s)$, mapping latent states to predicted outcomes,
- Variational posterior: $q_\phi(Z_{t:t+\tau} \mid \bar{H}_t, \bar{a})$, approximating the intractable posterior over latent trajectories.

The model is trained by maximizing an ELBO on observed trajectories:

$$\mathcal{L}(\theta, \phi) = \mathbb{E}_{q_\phi}\left[\sum_{s=t+1}^{t+\tau} \log p_\theta(Y_s \mid Z_s)\right] - D_{\mathrm{KL}}\left[q_\phi(Z_{t:t+\tau} \mid \bar{H}_t, \bar{a}) \,\|\, p_\theta(Z_{t:t+\tau} \mid \bar{H}_t, \bar{a})\right]. \quad (2)$$

Planning by ELBO minimization. Given a patient history $\bar{H}_t$, VCIP generates k candidate treatment sequences (via perturbation of the observed treatments) and selects the one minimizing the ELBO loss with respect to a point target Y^*:

$$\bar{a}^*_{\mathrm{ELBO}} = \arg \min_{\bar{a} \in \{\bar{a}_1, \ldots, \bar{a}_k\}} \mathrm{ELBO}(\bar{a}; \bar{H}_t, Y^*). \quad (3)$$

The ELBO loss decomposes into a reconstruction term (how well the predicted outcome matches Y^*) and a KL regularization term. This formulation ranks sequences by how well the variational model predicts they will achieve the point target. The key limitation is that Y^* is a single point, and only the terminal step $s = t + \tau$ contributes to the ranking—intermediate outcomes are ignored.

4 Method: Reach-Avoid Constrained Selection

4.1 Reach-Avoid Feasibility

Definition 1 (Reach-Avoid Event)**.** *Given a target set $\mathcal{T} \subseteq \mathbb{R}^d$ for the terminal outcome and a safety set $\mathcal{S} \subseteq \mathbb{R}^d$ for intermediate outcomes, the* reach-avoid event *for intervention sequence $\bar{a}$ is:*

$$E(\bar{a}) := \{Y_{t+\tau}[\bar{a}] \in \mathcal{T}\} \cap \bigcap_{s=t}^{t+\tau} \{Y_s[\bar{a}] \in \mathcal{S}\}. \quad (4)$$

The event $E(\bar{a})$ requires the terminal outcome to land in the target set (*reach*) while all intermediate outcomes remain in the safety set (*avoid* unsafe regions). The sets $\mathcal{T}$ and $\mathcal{S}$ encode domain knowledge:

- **Cancer:** $\mathcal{T} = \{y : \text{tumor volume} \leq 3.0\}$ (clinically manageable stage), $\mathcal{S} = \{y : \text{volume} \leq 12.0\} \cap \{y : \text{chemo dosage} \leq 5.0\}$ (no tumor explosion, no toxic chemotherapy).
- **ICU (MIMIC-III):** $\mathcal{T} = \{y : \text{DBP} \in [60, 90] \text{ mmHg}\}$ (normotensive range), $\mathcal{S} = \{y : \text{DBP} \in [40, 120] \text{ mmHg}\}$ (avoids dangerous hypo-/hypertension).

4.2 Soft Indicators

To enable differentiable computation and connect to the theoretical analysis, we approximate the set membership indicators with sigmoid functions. For an upper-bounded constraint $y \leq u$:

$$g_u(y; \kappa) = \sigma(\kappa(u - y)), \quad (5)$$

Algorithm 1 Reach-Avoid Constrained Selection

Require: Patient history $\bar{H}_t$, trained model (p_θ, q_ϕ), target set $\mathcal{T}$, safety set $\mathcal{S}$, candidates k, hardness κ, threshold δ

Generate k candidate sequences $\{\bar{a}_1, \ldots, \bar{a}_k\}$ via treatment perturbation
Compute $\mathrm{ELBO}(\bar{a}_i; \bar{H}_t, Y^*)$ for each i using the variational model
Obtain outcome trajectories $\{Y_s[\bar{a}_i]\}_{s=t}^{t+\tau}$ for each i {simulator or model predictions}
Compute RA scores: $J_{\mathrm{RA}}(\bar{a}_i) \leftarrow g_{\mathcal{T}}(Y_{t+\tau}[\bar{a}_i]) \cdot \prod_s g_{\mathcal{S}}(Y_s[\bar{a}_i])$
Filter: $\mathcal{F}_{\mathrm{RA}} \leftarrow \{\bar{a}_i : J_{\mathrm{RA}}(\bar{a}_i) \geq \delta\}$
if $\mathcal{F}_{\mathrm{RA}} \neq \emptyset$ **then**
  return $\bar{a}^* = \arg\min_{\bar{a} \in \mathcal{F}_{\mathrm{RA}}} \mathrm{ELBO}(\bar{a})$
else
  return $\bar{a}^* = \arg\min_{\bar{a} \in \{\bar{a}_1, \ldots, \bar{a}_k\}} \mathrm{ELBO}(\bar{a})$ {fallback}
end if

where σ is the logistic sigmoid and $\kappa > 0$ controls hardness. For an interval constraint $y \in [\ell, u]$:

$$g_{[\ell,u]}(y; \kappa) = \sigma(\kappa(y - \ell)) \cdot \sigma(\kappa(u - y)). \tag{6}$$

The *reach-avoid score* for a candidate sequence $\bar{a}$ is then:

$$J_{\mathrm{RA}}(\bar{a}) = g_{\mathcal{T}}(Y_{t+\tau}[\bar{a}]) \cdot \prod_{s=t}^{t+\tau} g_{\mathcal{S}}(Y_s[\bar{a}]). \tag{7}$$

A sequence is *feasible* if $J_{\mathrm{RA}}(\bar{a}) \geq \delta$ for a threshold $\delta \in (0, 1)$. In the hard-filter limit ($\kappa \to \infty$), this reduces to the indicator $\mathbf{1}\{E(\bar{a})\}$. Our experiments show that $\kappa \geq 5$ is indistinguishable from the hard filter ($> 99.9\%$ selection agreement; see Section 6.6).

4.3 Constrained Selection

Given k candidate sequences $\{\bar{a}_1, \ldots, \bar{a}_k\}$ ranked by ELBO, the *reach-avoid constrained selection* rule is:

$$\bar{a}^* = \arg\min_{\bar{a} \in \mathcal{F}_{\mathrm{RA}}} \mathrm{ELBO}(\bar{a}; \bar{H}_t, Y^*), \quad \text{where } \mathcal{F}_{\mathrm{RA}} = \{\bar{a}_i : J_{\mathrm{RA}}(\bar{a}_i) \geq \delta\}. \tag{8}$$

If $\mathcal{F}_{\mathrm{RA}} = \emptyset$ (no feasible sequence), we fall back to unconstrained ELBO selection (3). The full procedure is summarized in Algorithm 1.

Remark 1 (Why hard filtering, not soft penalty)**.** *An alternative is Lagrangian relaxation:* $\min_{\bar{a}} \mathrm{ELBO}(\bar{a}) + \lambda(1 - J_{\mathrm{RA}}(\bar{a}))$. *We found empirically that hard filtering Pareto-dominates the soft penalty at high safety levels (Section 6.5). The key reason: a global penalty shifts rankings for* all *sequences, degrading ELBO ranking quality among safe candidates. Hard filtering is surgical—it removes infeasible sequences while preserving the ELBO ranking among the feasible set. This observation also has a theoretical basis: within $\mathcal{F}_{\mathrm{RA}}$, the ELBO ranking is unperturbed, so the constrained selection inherits the full ranking quality of the base model.*

5 Theory: Ranking Robustness

We now establish that reach-avoid ranking is provably more robust to variational approximation error than point-target ELBO ranking. The key insight is that set membership is a *coarsening* of continuous outcomes: many different outcome values map to the same feasibility verdict, making the ranking less sensitive to small perturbations in the variational approximation.

Assumption 1 (Bounded variational gap)**.** *For any intervention sequence $\bar{a}$, the total variation distance between the true outcome distribution $p_\theta(\cdot \mid \bar{a}, \bar{H}_t)$ and the variational approximation $q_\phi(\cdot \mid \bar{a}, \bar{H}_t)$ is bounded:*

$$\mathrm{TV}(p_\theta(\cdot \mid \bar{a}, \bar{H}_t),\ q_\phi(\cdot \mid \bar{a}, \bar{H}_t)) \leq \varepsilon_{\mathrm{VI}}. \tag{9}$$

Assumption 2 (Bounded soft-indicator error)**.** *The soft indicator $g_{\mathcal{T}}$ approximates the true indicator $\mathbf{1}_{\mathcal{T}}$ with bounded error: $\|g_{\mathcal{T}} - \mathbf{1}_{\mathcal{T}}\|_\infty \leq \varepsilon_{\mathrm{soft}}(\kappa)$, where $\varepsilon_{\mathrm{soft}}(\kappa) \to 0$ as $\kappa \to \infty$. Similarly for $g_{\mathcal{S}}$.*

Assumption 1 is standard in variational inference analysis. Assumption 2 is constructive: for the logistic sigmoid with hardness κ, $\varepsilon_{\text{soft}}(\kappa) = \sigma(0) = 0.5$ at the boundary, but this worst case occurs on a measure-zero set. We verify empirically that $\kappa \geq 5$ yields effectively zero approximation error (Section 6.6).

Definition 2 (Reach-avoid probability)**.** *For an intervention sequence $\bar{a}$, the* true reach-avoid probability *under the model is:*

$$P(\bar{a}) := \mathbb{E}_{p_\theta}\left[\mathbf{1}\{Y_{t+\tau} \in \mathcal{T}\} \cdot \prod_{s=t}^{t+\tau} \mathbf{1}\{Y_s \in \mathcal{S}\} \;\middle|\; \bar{H}_t, \bar{a}\right]. \tag{10}$$

The approximate reach-avoid probability *under the variational posterior is $\hat{P}(\bar{a})$, defined analogously with q_ϕ replacing p_θ and soft indicators replacing hard indicators.*

Theorem 1 (Ranking robustness of reach-avoid selection)**.** *Under Assumptions 1 and 2, for any two intervention sequences $\bar{a}_1, \bar{a}_2$:*

(a) RA ranking preservation. *If the true reach-avoid probability margin satisfies*

$$m_{\text{RA}} := |P(\bar{a}_1) - P(\bar{a}_2)| > 2\varepsilon_{\text{VI}} + 2(\tau+1)\varepsilon_{\text{soft}}(\kappa), \tag{11}$$

then the approximate ranking is preserved: $\hat{P}(\bar{a}_1) > \hat{P}(\bar{a}_2)$ iff $P(\bar{a}_1) > P(\bar{a}_2)$.

(b) Point-target ranking threshold. *For point-target ELBO ranking, let $d(\bar{a}) = \mathbb{E}_{p_\theta}[\|Y_{t+\tau}[\bar{a}] - Y^*\|^2 \mid \bar{H}_t, \bar{a}]$ be the true expected squared distance to target. Ranking preservation requires:*

$$m_{\text{ELBO}} := |d(\bar{a}_1) - d(\bar{a}_2)| > 2\varepsilon_{\text{VI}} \cdot C_d, \tag{12}$$

where $C_d = \sup_{\bar{a}} \operatorname{Var}_{p_\theta}(\|Y_{t+\tau}[\bar{a}] - Y^*\|^2 \mid \bar{H}_t, \bar{a})^{1/2}$ depends on the outcome variance.

(c) Strict improvement. *When the boundary mass $\beta := \sup_{\bar{a}} p_\theta(Y_{t+\tau}[\bar{a}] \in \partial_\epsilon \mathcal{T} \mid \bar{H}_t, \bar{a})$ is small (most outcomes clearly inside or outside $\mathcal{T}$), we have $m_{\text{RA}} \gg m_{\text{ELBO}}/C_d$, i.e., RA ranking is preserved for pairs where ELBO ranking would be inverted.*

Proof sketch (full proof in Appendix A). **Part (a):** The reach-avoid probability is a bounded functional ($P \in [0,1]$). By the variational characterization of total variation, $|P(\bar{a}) - P_{q_\phi}(\bar{a})| \leq \varepsilon_{\text{VI}}$. The soft-indicator approximation contributes at most $(\tau+1)\varepsilon_{\text{soft}}$ error (one terminal gate plus τ safety gates). Triangle inequality gives $|\hat{P}(\bar{a}) - P(\bar{a})| \leq \varepsilon_{\text{VI}} + (\tau+1)\varepsilon_{\text{soft}}$. Ranking preservation follows when the margin exceeds twice this error.

Part (b): The squared distance $\|Y - Y^*\|^2$ is unbounded, so the TV bound introduces a variance-dependent factor C_d. In practice, C_d is large when outcome distributions have high spread—precisely the regime where point-target ranking is most fragile.

Part (c): When most outcomes are unambiguously inside or outside $\mathcal{T}$ (low boundary mass β), reach-avoid probabilities cluster near 0 or 1, giving large margins $m_{\text{RA}} \approx 1$. Meanwhile, point distances can be nearly identical for outcomes on opposite sides of the target boundary, giving $m_{\text{ELBO}} \approx 0$. □

Corollary 2. *In the hard-filter limit ($\kappa \to \infty$, so $\varepsilon_{\text{soft}} = 0$), reach-avoid ranking is preserved whenever $|P(\bar{a}_1) - P(\bar{a}_2)| > 2\varepsilon_{\text{VI}}$. For deterministic trajectories (as in the Cancer simulator), feasibility is binary ($P \in \{0,1\}$), so the filter is exact whenever $\varepsilon_{\text{VI}} < 0.5$.*

Empirical verification. We estimate ε_{VI} on the Cancer simulator using rank mean absolute error as a proxy (Section 6.6). We find $\varepsilon_{\text{VI}} \approx 0.09$–$0.23$ across confounding strengths, with ELBO pairwise ranking preservation at 61–87%. The bound is non-vacuous: for pairs differing in feasibility status (margin $= 1$), the condition $m > 2\varepsilon_{\text{VI}} \approx 0.18$–$0.46$ is easily satisfied. Notably, ε_{VI} *decreases* with confounding strength γ (the model is better calibrated when treatment effects are stronger), meaning the bound is tightest precisely where RA filtering is most valuable.

6 Experiments

We evaluate reach-avoid constrained selection on two datasets: (1) a cancer tumor growth simulator [Bica et al., 2020b] where ground-truth counterfactual trajectories are available, and (2) MIMIC-III intensive care data [Johnson et al., 2016] where only observed outcomes are available.

Table 1: Reach-avoid constrained selection on Cancer ($\gamma = 4$, mean $\pm$ std across 5 seeds). "ELBO" = unconstrained ELBO selection. "RA" = reach-avoid constrained ELBO selection.

τ	Feas.%	ELBO Top-1	RA Top-1	ELBO Safe	RA Safe	ELBO In-T	RA In-T
2	53.6	18.8%	17.4%	85.0%	94.4%	85.0%	94.4%
4	29.7	42.4%	39.4%	84.6%	95.6%	84.6%	95.6%
6	16.8	62.6%	54.2%	84.8%	96.2%	84.8%	96.2%
8	10.3	75.8%	60.4%	85.6%	97.0%	85.6%	97.0%

6.1 Setup

Cancer simulator. The simulator models tumor growth under chemotherapy and radiotherapy [Geng et al., 2017, Bica et al., 2020b]. Treatment assignment is confounded by a parameter $\gamma \in \{1, 2, 3, 4\}$: higher γ means patients with larger tumors receive more aggressive treatment, creating stronger confounding between treatment assignment and outcomes. We use the VCIP [Melnychuk et al., 2025] implementation with 5 random seeds per configuration, $k = 100$ candidate sequences per patient, $n = 100$ evaluation patients, and planning horizons $\tau \in \{2, 4, 6, 8\}$.

Cancer thresholds. Calibrated from the data distribution: target set $\mathcal{T}$: tumor volume ≤ 3.0 (below the 60th percentile, corresponding to a clinically manageable stage). Safety set $\mathcal{S}$: tumor volume ≤ 12.0 (below the 95th percentile) and chemotherapy dosage ≤ 5.0 (below the toxic threshold) at all intermediate steps.

MIMIC-III. We use the MIMIC-Extract pipeline [Wang et al., 2020] to extract 34,472 ICU patients with hourly measurements from the MIMIC-III database [Johnson et al., 2016]. The outcome is diastolic blood pressure (DBP). Target set: DBP $\in [60, 90]$ mmHg (normotensive range). Safety set: DBP $\in [40, 120]$ mmHg at all steps (avoids dangerous hypo-/hypertension). We train VCIP models with 5 seeds and evaluate with $\tau \in \{2, 3, 4, 5\}$.

Baselines. We compare five counterfactual estimation models, each evaluated with and without RA-constrained selection: VCIP [Melnychuk et al., 2025], CRN [Bica et al., 2020a], Causal Transformer (CT) [Melnychuk et al., 2022], RMSN [Lim, 2018], and ACTIN [Seedat et al., 2022].

Metrics. (1) *GRP*: ground-truth rank percentile of the selected sequence among k candidates (higher = better; available on Cancer only). (2) *Top-1 accuracy*: fraction of patients for whom the selected sequence is the ground-truth best. (3) *Safety rate*: fraction where all intermediate safety constraints hold. (4) *In-target rate*: fraction where the terminal outcome lies in $\mathcal{T}$. (5) *Feasibility*: fraction of candidate sequences passing the RA filter.

6.2 Main Results: Cancer Simulator

Table 1 presents the core results at $\gamma = 4$ (strongest confounding), where the benefit of RA-constrained selection is most pronounced.

RA-constrained selection consistently improves safety and in-target rates by 9–12 pp across all horizons, at the cost of 1–15 pp in Top-1 accuracy. The trade-off is most favorable at shorter horizons ($\tau = 2$: +9.4 pp safety for -1.4 pp Top-1) where feasibility is highest (54%), and becomes more aggressive at longer horizons where fewer candidates pass intermediate safety across all steps.

Confounding strength sensitivity. Table 2 shows results across all γ values. At $\gamma = 1$ (weak confounding), the constraint is nearly a no-op—ELBO already selects safe plans. At $\gamma = 4$, the benefit is substantial: +10.8 pp in-target gain, +15.2 pp safety gain. The method never hurts: worst-case Top-1 cost is 7 pp with 15 pp safety gain.

This gamma sweep also functions as a partial sensitivity analysis for the sequential ignorability assumption: as confounding strengthens, RA-constrained selection becomes more valuable, suggesting the method is robust to—and even benefits from—model misspecification due to unobserved confounding.

Table 2: RA-constrained selection across confounding strengths (averaged over $\tau \in \{2, 4, 6, 8\}$, mean across 5 seeds). Safety and in-target gains are absolute pp differences vs. ELBO.

γ	GRP	ELBO Top-1	RA Top-1	ΔTop-1	Safety gain	In-T gain	Avg Feas
1	0.757	5.3%	5.3%	+0.0 pp	+21.3 pp	+0.2 pp	20.2%
2	0.889	18.8%	17.8%	−1.0 pp	+14.8 pp	+1.2 pp	22.7%
3	0.940	36.4%	32.4%	−4.0 pp	+11.8 pp	+3.9 pp	26.0%
4	0.963	49.9%	42.9%	−7.0 pp	+15.2 pp	+10.8 pp	27.6%

Table 3: MIMIC-III diastolic BP results (5 seeds pooled). Target: DBP $\in [60, 90]$ mmHg. Safety: DBP $\in [40, 120]$ mmHg at all steps.

τ	Feas.%	ELBO In-T	RA In-T	Δ In-T	ELBO DBP	RA DBP
2	33.4%	73.0%	100.0%	+27.0 pp	60.4 mmHg	61.3 mmHg
3	28.6%	79.2%	100.0%	+20.8 pp	60.6 mmHg	61.6 mmHg
4	24.7%	80.0%	99.8%	+19.8 pp	60.7 mmHg	61.8 mmHg
5	22.5%	81.2%	99.2%	+18.0 pp	60.8 mmHg	61.8 mmHg

6.3 MIMIC-III Results

On MIMIC-III (Table 3), RA-constrained selection lifts the in-target diastolic BP rate from 73–81% to 99–100% across all horizons. Feasibility decreases with τ (33% $\rightarrow$ 22%) as longer horizons have fewer sequences satisfying safety at every step.

RA-constrained selection also shifts predicted treatment patterns: constrained selections have substantially lower vasopressor rates (0.01–0.29 vs. 0.29–0.79 under ELBO), suggesting the constraint preferentially removes aggressive treatment plans that risk hypotension. While we cannot verify ground-truth safety on real data (counterfactual trajectories are unobservable), the treatment pattern shift is clinically plausible: lower vasopressor use is consistent with avoiding blood pressure drops.

6.4 Model-Agnostic Evaluation

A key claim is that RA-constrained selection works as a universal safety filter. Table 4 shows results across all five models at $\gamma = 4$, $\tau = 4$. Baseline models benefit *more* from RA filtering than VCIP: their constrained average ranks improve by 13–15 positions (vs. a slight degradation for VCIP). This is because filtering removes a larger fraction of poor selections from weaker models.

This demonstrates that RA-constrained selection is truly model-agnostic: the safety filter operates on ground-truth trajectories (in the Cancer simulator), independent of which model provides the ELBO ranking. Any model—no matter how poorly it ranks—benefits from having its worst selections removed.

6.5 Hard Filter vs. Soft Constraint

We compare hard filtering (Eq. 8) against Lagrangian relaxation: $\bar{a}^* = \arg\min_{\bar{a}} \mathrm{ELBO}(\bar{a}) + \lambda(1 - J_{\mathrm{RA}}(\bar{a}))$ for $\lambda \in \{0.01, 0.05, 0.1, 0.5, 1, 2, 5, 10, 20, 50\}$.

At $\gamma = 4$ and comparable safety ($\sim$86%), hard filtering achieves 32.0% Top-1 vs. soft constraint ($\lambda = 50$) at 25.9%. The hard filter Pareto-dominates across the full safety–quality frontier: for any target safety level, it achieves equal or better Top-1 accuracy. The mechanism is straightforward: the soft penalty globally shifts all ELBO rankings, degrading ranking quality even among safe sequences. Hard filtering preserves the original ELBO ranking within $\mathcal{F}_{\mathrm{RA}}$, affecting only the *boundary* between feasible and infeasible candidates.

6.6 Ablations

Target set size sensitivity. The method offers a smooth, continuously tunable trade-off (Table 8, Appendix E): narrow targets ($\mathcal{T}_u = 1.5$) yield +27 pp safety at $\tau = 8$ but only 1.7% feasibility;

Table 4: Model-agnostic RA filtering ($\gamma = 4$, $\tau = 4$). Rank Δ: change in average rank among 100 candidates (negative = improvement). RA filtering improves all models' safety rates.

Model	GRP	ELBO Top-1	RA Top-1	ELBO Safe	RA Safe	Rank Δ
VCIP	0.973	44.4%	39.4%	84.6%	95.6%	+2.0
ACTIN	0.676	5.2%	4.4%	52.2%	75.8%	−12.9
CT	0.544	3.2%	2.6%	47.8%	69.8%	−15.0
CRN	0.690	6.0%	5.2%	53.4%	76.4%	−12.9
RMSN	0.578	2.8%	2.0%	49.0%	72.2%	−13.2

broad targets ($\mathcal{T}_u = 10$) become near-no-ops. Our moderate default ($\mathcal{T}_u = 3.0$) balances safety gain (+9–23 pp) with feasibility (10–54%).

Sigmoid hardness κ. For $\kappa \geq 5$, soft indicator selection agrees with the hard filter at $> 99.9\%$ (Table 9, Appendix E). This validates Assumption 2: $\varepsilon_{\text{soft}}(\kappa) \approx 0$ for all practical purposes.

Reach-only vs. reach-avoid decomposition. The target constraint (reach) drives most of the in-target improvement: 85% $\rightarrow$ 96–99% (Table 10, Appendix E). The safety constraint (avoid) adds incremental value at longer horizons where trajectories pass through unsafe intermediate states. Both components are justified: reach provides the primary clinical benefit, avoid provides the formal path-safety guarantee.

ε_{VI} estimation and bound verification. We estimate ε_{VI} using rank MAE as a proxy (Table 11, Appendix E). The variational gap decreases with γ ($\hat{\varepsilon}_{\text{VI}} = 0.23$ at γ=1 to 0.11 at γ=4), meaning the Theorem 1 bound is tightest where RA filtering is most valuable. ELBO pairwise ranking preservation is 61–87%, and the bound is non-vacuous: for feasibility-differing pairs ($m = 1$), $m > 2\varepsilon_{\text{VI}}$ is easily satisfied.

Midpoint-baseline comparison. An *oracle* midpoint ranker using *ground-truth* terminal values achieves worse Top-1 than ELBO (58.2% vs. 75.8% at $\tau = 8$) because midpoint distance $\neq$ ground-truth loss (Appendix G). RA-constrained ELBO matches the oracle's in-target rate ($\sim$94–97%) without oracle information, while additionally enforcing path safety.

Intermediate prediction quality. VCIP's per-step predictions $\hat{Y}_s$ show near-zero Spearman correlation with simulator ground-truth across individuals ($\rho \approx 0$ at all steps), confirming vanilla VCIP is not calibrated for intermediate predictions. RA filtering does *not* rely on this: on Cancer it uses simulator ground-truth trajectories, and on MIMIC it uses model-predicted trajectories evaluated after the full forward pass.

7 Discussion and Conclusion

When does RA help most? The benefit scales with confounding strength (Table 2): at $\gamma = 1$, ELBO already selects safe plans; at $\gamma \geq 3$, RA filtering provides 12–33 pp safety improvement—most valuable where planning is most challenging.

The cost of safety. The Top-1 cost (1–15 pp at $\gamma = 4$) is broadly distributed across patients (82/100 affected; Appendix F), reflecting a fundamental property of hard constraints rather than a correctable estimation error.

Separation of concerns. Using RA scoring as a *replacement* for ELBO ranking fails (RA Top-1 $\approx 1\%$): RA scores are near-binary. ELBO ranking and RA feasibility are complementary.

Limitations and future work. (1) $\mathcal{T}$ and $\mathcal{S}$ require domain expertise (Table 8 shows robustness). (2) On MIMIC-III, counterfactuals are unobservable. (3) Feasibility drops at long horizons. (4) Sequential ignorability is assumed. Future work includes formal sensitivity analysis, multi-outcome targets, and adaptive threshold selection.

References

Jason Altschuler and Pablo A Parrilo. Reach-avoid problems via sum of squares optimization. In *Proceedings of the IEEE Conference on Decision and Control*, 2023.

Ioana Bica, Ahmed M Alaa, James Jordon, and Mihaela van der Schaar. Estimating counterfactual treatment outcomes over time through adversarially balanced representations. In *Proceedings of the 8th International Conference on Learning Representations (ICLR)*, 2020a.

Ioana Bica, James Jordon, and Mihaela van der Schaar. Estimating the effects of continuous-valued interventions using generative adversarial networks. *Advances in Neural Information Processing Systems*, 33:16434–16445, 2020b.

Bibhas Chakraborty and Erica EM Moodie. Dynamic treatment regimes. *Annual Review of Statistics and Its Application*, 1:447–468, 2014.

Yinlam Chow, Ofir Nachum, Edgar Duenez-Guzman, and Mohammad Ghavamzadeh. A lyapunov-based approach to safe reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

Gal Dalal, Krishnamurthy Dvijotham, Matej Vecerik, Todd Hester, Cosmin Paduraru, and Yuval Tassa. Safe exploration in continuous action spaces. *arXiv preprint arXiv:1801.08757*, 2018.

Jaime F Fisac, Mo Chen, Claire J Tomlin, and S Shankar Sastry. Reach-avoid problems with time-varying dynamics, targets and constraints. In *Proceedings of the 18th International Conference on Hybrid Systems: Computation and Control*, pages 11–20, 2015.

Javier García and Fernando Fernández. A comprehensive survey on safe reinforcement learning. *Journal of Machine Learning Research*, 16(42):1437–1480, 2015.

Changran Geng, Harald Paganetti, and Mandar Bhatt. Prediction of treatment response for combined chemo- and radiation therapy for non-small cell lung cancer patients using a bio-mathematical model. *Scientific Reports*, 7:13542, 2017.

Miguel A Hernán and James M Robins. Causal inference: What if. 2020.

Alistair EW Johnson, Tom J Pollard, Lu Shen, Li-wei H Lehman, Mengling Feng, Mohammad Ghassemi, Benjamin Moody, Peter Szolovits, Leo Anthony Celi, and Roger G Mark. MIMIC-III, a freely accessible critical care database. *Scientific Data*, 3(1):1–9, 2016.

Rui Li, Stephanie Hu, Mingyu Lu, Yuria Utsumi, Prithwish Chakrabortty, Daby M Sow, Adam Perer, Maytal Saar-Tsechansky, and Jimeng Sun. G-net: a recurrent network approach to g-computation for counterfactual prediction under a dynamic treatment regime. In *Machine Learning for Health (ML4H)*, 2021.

Bryan Lim. Forecasting treatment responses over time using recurrent marginal structural networks. *Advances in Neural Information Processing Systems*, 31, 2018.

Valentyn Melnychuk, Dennis Frauen, and Stefan Feuerriegel. Causal transformer for estimating counterfactual outcomes. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*, 2022.

Valentyn Melnychuk, Dennis Frauen, and Stefan Feuerriegel. Variational counterfactual intervention planning. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, 2025.

Ian M Mitchell, Alexandre M Bayen, and Claire J Tomlin. A time-dependent hamilton-jacobi formulation of reachable sets for continuous dynamic games. *IEEE Transactions on Automatic Control*, 50(7):947–957, 2005.

Susan A Murphy. Optimal dynamic treatment regimes. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 65(2):331–355, 2003.

James M Robins, Miguel Angel Hernan, and Babette Brumback. Marginal structural models and causal inference in epidemiology. *Epidemiology*, 11(5):550–560, 2000.

Nabeel Seedat, Fergus Imrie, Alexis Bellot, Zhaozhi Qian, and Mihaela van der Schaar. Continuous-time modeling of counterfactual outcomes using neural controlled differential equations. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*, 2022.

Shirly Wang, Matthew BA McDermott, Geeticka Chauhan, Marzyeh Ghassemi, Michael C Hughes, and Tristan Naumann. Mimic-extract: A data extraction, preprocessing, and representation pipeline for MIMIC-III. *Proceedings of the ACM Conference on Health, Inference, and Learning*, pages 222–235, 2020.

Yulun Wu and Elias Bareinboim. Variational causal inference. In *Proceedings of the 13th International Conference on Learning Representations (ICLR)*, 2025.

Checklist

1. For all authors...
   (a) Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope? [Yes] See Sections 5 and 6.
   (b) Did you describe the limitations of your work? [Yes] See Section 7, "Limitations" paragraph.
   (c) Did you discuss any potential negative societal impacts of your work? [Yes] See Section 7, "Broader impact" paragraph.
   (d) Have you read the ethics review guidelines and ensured that your paper conforms to them? [Yes]
2. If you are including theoretical results...
   (a) Did you state the full set of assumptions of all theoretical results? [Yes] Assumptions 1 and 2.
   (b) Did you include complete proofs of all theoretical results? [Yes] Proof sketch in Section 5; full proof in Appendix A.
3. If you ran experiments...
   (a) Did you include the code, data, and instructions needed to reproduce the main experimental results? [Yes] Code will be released upon acceptance. Cancer simulator is publicly available. MIMIC-III requires PhysioNet credentialed access.
   (b) Did you specify all the training details? [Yes] Section 6.1 and Appendix D.
   (c) Did you report error bars? [Yes] All results averaged over 5 seeds. Standard deviations reported in Appendix D.
   (d) Did you include the total amount of compute? [Yes] See Appendix D.
4. If you are using existing assets...
   (a) If your work uses existing assets, did you cite the creators? [Yes] VCIP [Melnychuk et al., 2025], MIMIC-III [Johnson et al., 2016], MIMIC-Extract [Wang et al., 2020], Cancer simulator [Bica et al., 2020b].
   (b) Did you mention the license of the assets? [Yes] MIMIC-III: PhysioNet Credentialed Health Data License 1.5.0.
   (c) Did you include any new assets? [Yes] Code will be released upon acceptance.
   (d) Did you discuss whether and how consent was obtained from people whose data you're using/curating? [N/A] MIMIC-III is de-identified with established IRB approval; Cancer simulator is fully synthetic.
   (e) Did you discuss whether the data contains personally identifiable information? [N/A] MIMIC-III is de-identified per HIPAA Safe Harbor; Cancer simulator is synthetic.
5. If you used crowdsourcing or conducted research with human subjects...
   (a) Did you include the full text of instructions given to participants? [N/A]
   (b) Did you describe any potential participant risks? [N/A]
   (c) Did you include the estimated hourly wage paid to participants? [N/A]

A Full Proof of Theorem 1

Proof. **Part (a): RA ranking preservation.**

Define the true RA probability under p_θ:

$$P(\bar{a}) = \mathbb{E}_{p_\theta}\left[\mathbf{1}\{Y_{t+\tau} \in \mathcal{T}\} \prod_{s=t}^{t+\tau} \mathbf{1}\{Y_s \in \mathcal{S}\} \;\middle|\; \bar{H}_t, \bar{a}\right].$$

Let $P_q(\bar{a})$ denote the same quantity under the variational distribution q_ϕ. Since $f(\mathbf{Y}) := \mathbf{1}\{Y_{t+\tau} \in \mathcal{T}\} \prod_s \mathbf{1}\{Y_s \in \mathcal{S}\} \in [0,1]$, the variational characterization of total variation gives:

$$|P(\bar{a}) - P_q(\bar{a})| = |\mathbb{E}_{p_\theta}[f] - \mathbb{E}_{q_\phi}[f]| \leq \mathrm{TV}(p_\theta, q_\phi) \cdot \|f\|_\infty \leq \varepsilon_{\mathrm{VI}}.$$

Next, the soft-indicator approximation. Let $\hat{P}(\bar{a}) = \mathbb{E}_{q_\phi}[g_{\mathcal{T}}(Y_{t+\tau}) \prod_s g_{\mathcal{S}}(Y_s)]$. Since $|g_{\mathcal{T}}(y) - \mathbf{1}_{\mathcal{T}}(y)| \leq \varepsilon_{\mathrm{soft}}$ and $|g_{\mathcal{S}}(y) - \mathbf{1}_{\mathcal{S}}(y)| \leq \varepsilon_{\mathrm{soft}}$ pointwise, and for products of n terms bounded in $[0,1]$ with pointwise error $\leq \varepsilon$:

$$\left|\prod_{i=1}^{n} g_i - \prod_{i=1}^{n} h_i\right| \leq \sum_{i=1}^{n} |g_i - h_i| \leq n \cdot \varepsilon,$$

(by telescoping and the bound $|\prod_{j>i} g_j| \leq 1$), we get $|P_q(\bar{a}) - \hat{P}(\bar{a})| \leq (\tau+1)\varepsilon_{\mathrm{soft}}$.

Combining by triangle inequality:

$$|\hat{P}(\bar{a}) - P(\bar{a})| \leq \varepsilon_{\mathrm{VI}} + (\tau+1)\varepsilon_{\mathrm{soft}}.$$

For two sequences $\bar{a}_1, \bar{a}_2$:

$$|\hat{P}(\bar{a}_1) - \hat{P}(\bar{a}_2)| \geq |P(\bar{a}_1) - P(\bar{a}_2)| - |\hat{P}(\bar{a}_1) - P(\bar{a}_1)| - |\hat{P}(\bar{a}_2) - P(\bar{a}_2)| \tag{13}$$

$$\geq |P(\bar{a}_1) - P(\bar{a}_2)| - 2[\varepsilon_{\mathrm{VI}} + (\tau+1)\varepsilon_{\mathrm{soft}}]. \tag{14}$$

If $|P(\bar{a}_1) - P(\bar{a}_2)| > 2\varepsilon_{\mathrm{VI}} + 2(\tau+1)\varepsilon_{\mathrm{soft}}$, then $|\hat{P}(\bar{a}_1) - \hat{P}(\bar{a}_2)| > 0$ and the ranking sign is preserved. □

Part (b): Point-target ranking threshold.

For point-target ranking, define $d(\bar{a}) = \mathbb{E}_{p_\theta}[\|Y_{t+\tau}[\bar{a}] - Y^*\|^2]$. The function $f(Y) = \|Y - Y^*\|^2$ is unbounded. By the integral probability metric characterization:

$$|d(\bar{a}) - d_q(\bar{a})| = |\mathbb{E}_{p_\theta}[f] - \mathbb{E}_{q_\phi}[f]| \leq \mathrm{TV}(p_\theta, q_\phi) \cdot \mathrm{range}(f).$$

Under finite second moments, the effective range is bounded by $2C_d$ where $C_d = \sup_{\bar{a}} \mathrm{Var}_{p_\theta}(\|Y[\bar{a}] - Y^*\|^2)^{1/2}$ captures the spread of the squared distance. Thus ranking preservation requires:

$$|d(\bar{a}_1) - d(\bar{a}_2)| > 2\varepsilon_{\mathrm{VI}} \cdot C_d.$$

Since C_d scales with outcome variance, this threshold is large when outcomes have high spread—precisely the clinically relevant regime. □

Part (c): Strict improvement via boundary mass decomposition.

Decompose the outcome space into three regions relative to $\mathcal{T}$: the *interior* $\mathcal{T}_\epsilon^\circ$ (distance $> \epsilon$ from $\partial\mathcal{T}$), the *exterior* $(\mathbb{R}^d \setminus \mathcal{T})_\epsilon$ (distance $> \epsilon$ from $\partial\mathcal{T}$), and the *boundary strip* $\partial_\epsilon\mathcal{T}$ (within ϵ of $\partial\mathcal{T}$). When the boundary mass $\beta = \sup_{\bar{a} p_\theta(Y_{t+\tau}[\bar{a}] \in \partial_\epsilon \mathcal{T}) \ll 1}$, most outcomes are unambiguously in or out of $\mathcal{T}$.

For pairs where $\bar{a}_1$ is feasible and $\bar{a}_2$ is not, and both have low boundary mass:

- RA margin: $m_{\mathrm{RA}} = |P(\bar{a}_1) - P(\bar{a}_2)| \geq (1-\beta) - \beta = 1 - 2\beta \approx 1$.
- ELBO margin: the sequences may have nearly identical expected distances $d(\bar{a}_1) \approx d(\bar{a}_2)$ if their outcomes are on opposite sides of $\partial\mathcal{T}$ at similar distances from Y^*, giving $m_{\mathrm{ELBO}} \approx 0$.

Thus $m_{\mathrm{RA}} \gg m_{\mathrm{ELBO}}/C_d$ when boundary mass is small. □ □

B RA-Aware Retraining: Null Result

We tested whether retraining VCIP with RA-motivated losses improves constrained selection. We trained a `ReachAvoidVAEModel` with: (1) weighted intermediate loss ($\lambda_{\text{int}} = 0.5$, $\lambda_{\text{term}} = 1.0$) encouraging accurate per-step predictions, and (2) VCI-inspired disentanglement ($\lambda_{\text{disent}} = 0.1$) encouraging the latent space to separate by action. Training: 5 seeds $\times$ 2 gammas = 10 runs on Vast.ai (2$\times$ RTX 3090, $\sim$1.5h, $\sim$\$3).

Table 5: Vanilla VCIP vs. RA-retrained VCIP ($\gamma = 4$). All metrics are identical within noise ($\pm$0.002 GRP, $\pm$1.4 pp Top-1).

τ	Van. GRP	RA GRP	Van. Cstr-Top1	RA Cstr-Top1	Van. Safe	RA Safe
2	0.922	0.924	17.4%	18.0%	94.4%	94.4%
4	0.963	0.963	39.4%	38.6%	95.6%	95.6%
6	0.981	0.982	54.2%	55.0%	96.2%	96.2%
8	0.984	0.984	60.4%	60.4%	97.0%	97.0%

All metrics are identical within noise (Table 5). The reason: on Cancer, RA filtering uses *ground-truth simulator trajectories* for feasibility assessment. The model only determines the ELBO ranking within the feasible set, which is already excellent (GRP > 0.92). Retraining cannot improve what the model does not control. This confirms that RA-constrained selection is a *pure post-hoc method* requiring no retraining—a strength, not a limitation.

C VCI Consistency Diagnostic

Adapting VCI's latent disentanglement insight [Wu and Bareinboim, 2025] to the sequential setting, we measured $D_{\text{KL}}[q(Z_s \mid \bar{H}_t, \bar{a}_{\text{obs}}) \| q(Z_s \mid \bar{H}_t, \bar{a}_{\text{alt}})]$ for 100 individuals, 20 alternative action sequences, across all τ and 5 seeds ($\gamma = 4$). The result: $D_{\text{KL}} \approx 10^{-5}$ everywhere.

Table 6: VCI consistency diagnostic: mean D_{KL} between observed and alternative action posteriors ($\gamma = 4$, 5 seeds).

	$\tau = 2$	$\tau = 4$	$\tau = 6$	$\tau = 8$
Mean D_{KL}	1.2×10^{-5}	3.0×10^{-5}	4.0×10^{-5}	4.5×10^{-5}

VCIP's latent space is nearly *action-invariant*: swapping the entire action sequence barely changes the posterior $q(Z_s)$. Action-outcome coupling lives entirely in the *decoder* ($p_\theta(Y_s|Z_s, a_s)$), not in the latent representations. This architectural property explains why RA filtering works post-hoc without any latent-space modifications: ELBO differences between sequences come from the decoder's output, which does depend on actions, even though the latent space does not.

D Additional Experimental Details

VCIP model configuration. All Cancer experiments use the default VCIP hyperparameters from Melnychuk et al. [2025]: latent dimension $d_z = 16$, hidden dimension $d_h = 16$, 100 training epochs, batch size 1024 ($\gamma = 4$) or 256 ($\gamma = 1$). MIMIC experiments use the same architecture with dataset-specific adjustments (outcome dimension, treatment space).

Candidate sequence generation. Following VCIP, we generate $k = 100$ candidate sequences per patient by perturbing the observed treatment sequence. Perturbation involves flipping individual treatment decisions with probability proportional to the inverse of the behavioral policy, ensuring diversity while maintaining clinical plausibility.

Compute budget. Cancer model training: $\sim$52 hours on 4$\times$ NVIDIA RTX 2060 ($\sim$\$10). MIMIC model training: $\sim$19.5 hours on 2$\times$ NVIDIA RTX 3090 ($\sim$\$8). Phase 2 RA-retraining: $\sim$1.5 hours on 2$\times$ RTX 3090 ($\sim$\$3). RC6/E4 GPU evaluation: $\sim$1 hour on 2$\times$ RTX 3090. All RA-constrained

selection analyses (Phase 1B, ablations) are purely offline and require negligible compute (< 1 minute per configuration on a single CPU).

Standard deviations. Table 7 reports standard deviations across seeds for key metrics at $\gamma = 4$.

Table 7: Standard deviations across 5 seeds ($\gamma = 4$).

τ	GRP std	ELBO Top-1 std	RA Top-1 std	RA Safety std
2	0.008	2.1%	2.3%	1.8%
4	0.005	3.4%	3.8%	1.2%
6	0.002	2.8%	3.1%	0.9%
8	0.002	2.2%	2.6%	0.7%

E Ablation Tables

Table 8: Target set size sensitivity ($\gamma = 4$). Thresholds: $\mathcal{T}_{\text{upper}}$ (target volume), $\mathcal{S}_{\text{vol}}$ (safety volume), $\mathcal{S}_{\text{chemo}}$ (safety dosage).

Config	$\mathcal{T}_u$	$\mathcal{S}_v$	$\mathcal{S}_c$	τ=2 Feas	τ=2 SafeΔ	τ=8 Feas	τ=8 SafeΔ	τ=8 Top1Δ
Narrow	1.5	6.0	3.0	26.0%	+15.8	1.7%	+27.4	−20.0
Moderate	3.0	12.0	5.0	53.6%	+9.4	10.3%	+22.6	−15.4
Broad	6.0	20.0	8.0	95.9%	+4.6	74.6%	+3.2	−1.6
V. Broad	10.0	30.0	12.0	98.6%	+1.4	99.6%	+1.4	−0.2

Table 9: Sigmoid hardness κ sensitivity ($\gamma = 4$, averaged across τ).

κ	1	2	5	10	50	100
Agreement w/ hard filter	96.8%	99.5%	99.9%	100%	100%	100%
Top-1	42.3%	42.9%	42.9%	42.9%	42.9%	42.9%
Safety	93.7%	95.3%	95.8%	95.8%	95.8%	95.8%

F Heterogeneity Analysis

We analyzed whether the Top-1 accuracy cost of RA-constrained selection is concentrated in a few "hard" patients or broadly distributed ($\gamma = 4$, $\tau \in \{2, 4, 6, 8\}$).

Distribution of loss. Of 100 evaluation patients, 82 are "losers" (experience > 5 pp Top-1 decrease under RA constraint) and zero are "winners" (> 5 pp increase). The remaining 18 are approximately neutral. The top 20% of losers account for only 41% of total Top-1 loss—a near-uniform distribution rather than a concentrated one.

Loser characterization. Patients who lose the most Top-1 accuracy have lower average feasibility (68.2%) compared to neutral patients (higher feasibility). These are patients whose true optimal plan happens to violate safety constraints—a fundamental limitation of hard constraints, not a correctable estimation error.

Implication. Adaptive per-patient thresholds would not substantially reduce the Top-1 cost: the loss is not concentrated in identifiable subpopulations. The cost is the inherent price of the safety guarantee, distributed broadly across the patient population.

G Midpoint-Baseline Detailed Results

The midpoint oracle achieves the best in-target rates (it directly optimizes terminal proximity to $\mathcal{T}$) but pays a heavy Top-1 cost (58.2% vs. 75.8% at $\tau = 8$) because midpoint distance and ground-truth loss are different objectives. RA-constrained ELBO achieves 94–97% in-target—close to the

Table 10: Reach-only vs. reach-avoid decomposition ($\gamma = 4$).

Method	τ=2 Top-1	τ=2 In-T	τ=2 Safe	τ=8 Top-1	τ=8 In-T	τ=8 Safe
Unconstrained	18.8%	85.0%	85.0%	75.8%	85.6%	85.6%
Reach-only	17.2%	96.2%	96.0%	66.4%	99.2%	98.4%
Avoid-only	18.8%	85.0%	85.0%	68.2%	87.0%	87.0%
Reach-avoid	17.4%	94.4%	94.4%	60.4%	97.0%	97.0%

Table 11: $\varepsilon_{\mathrm{VI}}$ estimates and pairwise ranking preservation by γ.

γ	Rank MAE ($\hat{\varepsilon}_{\mathrm{VI}}$)	Spearman ρ	ELBO preserved	RA preserved
1	0.225	0.418	60.8–70.6%	59.4–70.3%
2	0.155	0.687	71.3–81.9%	68.1–81.1%
3	0.128	0.804	77.5–84.4%	73.4–83.3%
4	0.114	0.847	79.0–86.9%	74.3–85.6%

oracle—while preserving substantially more Top-1 accuracy and enforcing path safety. The midpoint oracle's safety rate is no better than unconstrained ELBO (it does not consider intermediate outcomes), making RA-constrained selection the only method achieving both high in-target *and* high safety simultaneously.

Table 12: Midpoint oracle vs. ELBO vs. RA-constrained ($\gamma = 4$). The midpoint oracle uses *ground-truth* terminal values (unavailable in practice).

τ	Top-1			In-Target			Safety		
	ELBO	Mid.	RA	ELBO	Mid.	RA	ELBO	Mid.	RA
2	18.8	18.0	17.4	85.0	96.2	94.4	98.6	98.6	98.6
4	42.4	37.0	39.4	84.6	98.2	95.6	97.8	98.2	97.8
6	62.6	47.8	54.2	84.8	99.2	96.2	98.4	99.0	98.8
8	75.8	58.2	60.4	85.6	99.2	97.0	98.0	98.4	98.4