

Class 11 - Structural Bioinformatics (Pt. 1)

Anita Wang (PID: A15567878)

11/2/2021

1: Introduction to the RCSB Protein Data Bank (PDB)

- PDB statistics
- Download a CSV file from the PDB site (accessible from “Analyze” > “PDB Statistics” > “by Experimental Method and Molecular Type”. Move this CSV file into your RStudio project and use it to answer the following questions:

```
db <- read.csv("Data Export Summary.csv", row.names=1)
head(db)
```

	X.ray	NMR	EM	Multiple.methods	Neutron	Other	Total
## Protein (only)	142303	11804	5999	177	70	32	160385
## Protein/Oligosaccharide	8414	31	979	5	0	0	9429
## Protein/NA	7491	274	1986	3	0	0	9754
## Nucleic acid (only)	2368	1372	60	8	2	1	3811
## Other	149	31	3	0	0	0	183
## Oligosaccharide (only)	11	6	0	1	0	4	22

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
method.sums <- colSums(db)
round((method.sums/method.sums["Total"]) * 100, 2)
```

	X.ray	NMR	EM	Multiple.methods
##	87.55	7.36	4.92	0.11
##	Neutron	Other	Total	
##	0.04	0.02	100.00	

- 87.55% by X-ray and 4.92% by EM.

Q2: What proportion of structures in the PDB are protein?

```
round((db$Total/method.sums["Total"]) * 100, 2)
```

```
## [1] 87.36  5.14  5.31  2.08  0.10  0.01
```

- 87.36%

Q3: Type HIV in the PDB website search box on the home page and determine how many HIV-1 protease structures are in the current PDB?

- There are 1828 HIV-1 protease structures in the current PDB
- *The PDB format*

2. Visualizing the HIV-1 protease structure

- Using Atom Selections

Q4: Water molecules normally have 3 atoms. Why do we see just one atom per water molecule in this structure?

- Skipped per in-class instructions

Q5: There is a conserved water molecule in the binding site. Can you identify this water molecule? What residue number does this water molecule have (see note below)?

- Skipped per in-class instructions

VMD Structure visualization image

```
#
```

Rmd will not knit with the insertion of this picture as a png file..

3. Introduction to Bio3D in R

```
library(bio3d)
```

- Reading PDB file data into R

```
pdb <- read.pdb("1hsg")
```

```
## Note: Accessing on-line PDB file
```

- To get a quick summary of the contents of the pdb object you just created you can issue the command `print(pdb)` or simply `type pdb` (which is equivalent in this case):

```
pdb
```

```
##
## Call: read.pdb(file = "1hsg")
##
## Total Models#: 1
## Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)
```

```

##
##      Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
##      Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
##
##      Non-protein/nucleic Atoms#: 172 (residues: 128)
##      Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
##
##      Protein sequence:
##      PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
##      QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
##      ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
##      VNIIGRNLLTQIGCTLNF
##
## + attr: atom, xyz, seqres, helix, sheet,
##      calpha, remark, call

```

Q7: How many amino acid residues are there in this pdb object?

- 198

Q8: Name one of the two non-protein residues?

- MK1

Q9: How many protein chains are in this structure?

- 2

```
aa123(pdbseq(pdb))
```

```


##      [1] "PRO" "GLN" "ILE" "THR" "LEU" "TRP" "GLN" "ARG" "PRO" "LEU" "VAL" "THR"
##      [13] "ILE" "LYS" "ILE" "GLY" "GLY" "GLN" "LEU" "LYS" "GLU" "ALA" "LEU" "LEU"
##      [25] "ASP" "THR" "GLY" "ALA" "ASP" "ASP" "THR" "VAL" "LEU" "GLU" "GLU" "MET"
##      [37] "SER" "LEU" "PRO" "GLY" "ARG" "TRP" "LYS" "PRO" "LYS" "MET" "ILE" "GLY"
##      [49] "GLY" "ILE" "GLY" "GLY" "PHE" "ILE" "LYS" "VAL" "ARG" "GLN" "TYR" "ASP"
##      [61] "GLN" "ILE" "LEU" "ILE" "GLU" "ILE" "CYS" "GLY" "HIS" "LYS" "ALA" "ILE"
##      [73] "GLY" "THR" "VAL" "LEU" "VAL" "GLY" "PRO" "THR" "PRO" "VAL" "ASN" "ILE"
##      [85] "ILE" "GLY" "ARG" "ASN" "LEU" "LEU" "THR" "GLN" "ILE" "GLY" "CYS" "THR"
##      [97] "LEU" "ASN" "PHE" "PRO" "GLN" "ILE" "THR" "LEU" "TRP" "GLN" "ARG" "PRO"
##     [109] "LEU" "VAL" "THR" "ILE" "LYS" "ILE" "GLY" "GLY" "GLN" "LEU" "LYS" "GLU"
##     [121] "ALA" "LEU" "LEU" "ASP" "THR" "GLY" "ALA" "ASP" "ASP" "THR" "VAL" "LEU"
##     [133] "GLU" "GLU" "MET" "SER" "LEU" "PRO" "GLY" "ARG" "TRP" "LYS" "PRO" "LYS"
##     [145] "MET" "ILE" "GLY" "GLY" "ILE" "GLY" "GLY" "PHE" "ILE" "LYS" "VAL" "ARG"
##     [157] "GLN" "TYR" "ASP" "GLN" "ILE" "LEU" "ILE" "GLU" "ILE" "CYS" "GLY" "HIS"
##     [169] "LYS" "ALA" "ILE" "GLY" "THR" "VAL" "LEU" "VAL" "GLY" "PRO" "THR" "PRO"
##     [181] "VAL" "ASN" "ILE" "ILE" "GLY" "ARG" "ASN" "LEU" "LEU" "THR" "GLN" "ILE"
##     [193] "GLY" "CYS" "THR" "LEU" "ASN" "PHE"

```

Plot of B-factor

```
plot.bio3d(pdb$atom$b, sse=pdb)
```

```
## Warning in plotb3(...): Length of input 'sse' does not equal the length of input
## 'x'; Ignoring 'sse'
```



The ATOM records

```
head(pdb$atom)
```

```
##   type eleno elety alt resid chain resno insert      x      y      z o      b
## 1 ATOM    1     N <NA>  PRO    A     1 <NA> 29.361 39.686 5.862 1 38.10
## 2 ATOM    2    CA <NA>  PRO    A     1 <NA> 30.307 38.663 5.319 1 40.62
## 3 ATOM    3     C <NA>  PRO    A     1 <NA> 29.760 38.071 4.022 1 42.64
## 4 ATOM    4     O <NA>  PRO    A     1 <NA> 28.600 38.302 3.676 1 43.40
## 5 ATOM    5    CB <NA>  PRO    A     1 <NA> 30.508 37.541 6.342 1 37.87
## 6 ATOM    6    CG <NA>  PRO    A     1 <NA> 29.296 37.591 7.162 1 38.40
##   segid elesy charge
## 1 <NA>     N  <NA>
## 2 <NA>     C  <NA>
## 3 <NA>     C  <NA>
## 4 <NA>     O  <NA>
## 5 <NA>     C  <NA>
## 6 <NA>     C  <NA>
```

Note that the attributes (+ attr:) of this object are listed on the last couple of lines. To find the attributes of any such object you can use:

```
attributes(pdb)
```

```
## $names
## [1] "atom" "xyz" "seqres" "helix" "sheet" "calpha" "remark" "call"
##
## $class
## [1] "pdb" "sse"
```

To access these individual attributes we use the dollar-attribute name convention that is common with R list objects. For example, to access the atom attribute or component use `pdb$atom`:

```
head(pdb$atom)
```

```
##   type eleno elety alt resid chain resno insert      x      y      z o      b
## 1 ATOM     1     N <NA>  PRO     A      1 <NA> 29.361 39.686 5.862 1 38.10
## 2 ATOM     2     CA <NA>  PRO     A      1 <NA> 30.307 38.663 5.319 1 40.62
## 3 ATOM     3     C <NA>  PRO     A      1 <NA> 29.760 38.071 4.022 1 42.64
## 4 ATOM     4     O <NA>  PRO     A      1 <NA> 28.600 38.302 3.676 1 43.40
## 5 ATOM     5     CB <NA>  PRO     A      1 <NA> 30.508 37.541 6.342 1 37.87
## 6 ATOM     6     CG <NA>  PRO     A      1 <NA> 29.296 37.591 7.162 1 38.40
##   segid elesy charge
## 1 <NA>     N  <NA>
## 2 <NA>     C  <NA>
## 3 <NA>     C  <NA>
## 4 <NA>     O  <NA>
## 5 <NA>     C  <NA>
## 6 <NA>     C  <NA>
```