



JOHNS HOPKINS  
WHITING SCHOOL  
*of* ENGINEERING

# Word Embeddings: Applications and Evaluation

# Recap

---

- We want meaningful representations of words that we can use for corpus analytics (and other things)
- By defining a fake task, predicting context from a word (skip-gram) or a word from context (CBOW), we can learn meaningful vector
  - Our training objective specifically encourages words that co-occur together or occur in similar contexts to have similar vectors
- Actual implementation requires additional tricks for reducing computational complexity

# Word2Vec

- Problem:
  - Denominator is computationally expensive!  $O(VN)$
  - Solutions:
    - Hierarchical softmax  $O(\log V)$
    - Negative Sampling  $O(1)$ 
      - Intuition: we don't need to down-weight all other words at once, we can chose a small number of negative samples

$$\frac{\exp(u_o^T v_c)}{\sum_{i=1}^V \exp(u_i^T v_c)}$$

Encourage center word and all other words to have different vectors

# Skip-gram: Negative sampling

$$P(o \mid c) = \frac{\exp(u_o^T v_c)}{\sum_{i=1}^V \exp(u_i^T v_c)} \longrightarrow \frac{1}{1 + \exp(-u_o^T v_c)}$$

- New objective (single context word, k negative samples)

$$\log P(o_+|c) + \sum_{i=1}^k \log(1 - P(o_i|c))$$

- (Problem changes from multiclass to binary)
- Choose negative samples based on frequency

# Pre-trained Word2Vec Embeddings

---

- You can train embeddings on your own data
- Depending on your application, you can also start with embeddings trained on large data set
  - <https://code.google.com/archive/p/word2vec/>

# Other word embeddings: GloVe [Pennington et al. 2014]

---

- <https://nlp.stanford.edu/projects/glove/>
- “Global Vectors”
- Model is based on capturing global corpus statistics
- Incorporates ratios of probabilities from the word-word cooccurrence matrix (intuitions of count-based models) with linear structures used by methods like word2vec

# Other word embeddings: fasttext

## [Bojanowski et al. 2017]

- Word2vec can't handle unknown words and sparsity of rare word-forms (e.g. we should be able to infer "milking" from "milk" + "ing")
- Uses subword models, representing each word as itself plus a bag of constituent n-grams, with special boundary symbols < and > added to each word.
- Each word is represented by the sum of all of the embeddings of its constituent n-grams. Unknown words can be represented by just the sum of the constituent n-grams.

# Gensim: Python Package for working with word embeddings

---

```
>>> from gensim.test.utils import common_texts
>>> from gensim.models import Word2Vec
>>>
>>> model = Word2Vec(sentences=common_texts, vector_size=100, window=5, min_count=1, workers=4)
>>> model.save("word2vec.model")
```

<https://radimrehurek.com/gensim/models/word2vec.html>

# Recap: Word Embeddings Construction

---

- Intuitive ideas behind representing words as vectors
- Distributional Hypothesis
- Basic ideas behind TF-IDF weighting
- Basic ideas behind Word2Vec
  - Difference between CBOW and Skip-gram
  - Practical challenges
- *Know where your embeddings came from and how they were made*

# This class

---


- **Applications**
  - How do we use these embeddings for text analysis?
    - Types of questions we can ask (occupational stereotypes, changes over time)
    - Methods for embedding operations
- **Evaluation**
  - How do we know when embeddings actually capture the content we want?



JOHNS HOPKINS  
WHITING SCHOOL  
*of* ENGINEERING

# Measures of Race/Gender Stereotypes

# Common Use Case for Word Embeddings: Input into neural models



# **Man is to Computer Programmer as Woman is to Homemaker? Debiasing Word Embeddings**

## **Extreme *she* occupations**

- |                 |                       |                        |
|-----------------|-----------------------|------------------------|
| 1. homemaker    | 2. nurse              | 3. receptionist        |
| 4. librarian    | 5. socialite          | 6. hairdresser         |
| 7. nanny        | 8. bookkeeper         | 9. stylist             |
| 10. housekeeper | 11. interior designer | 12. guidance counselor |

## **Extreme *he* occupations**

- |                |                   |                |
|----------------|-------------------|----------------|
| 1. maestro     | 2. skipper        | 3. protege     |
| 4. philosopher | 5. captain        | 6. architect   |
| 7. financier   | 8. warrior        | 9. broadcaster |
| 10. magician   | 11. fighter pilot | 12. boss       |

# Man is to Computer Programmer as Woman is to Homemaker? Debiasing Word Embeddings

nlp debiasing word embeddings


About 3,260 results (0.11 sec)

Man is to computer programmer as woman is to homemaker? **debiasing word embeddings**  
T Bolukbasi, KW Chang, JY Zou ... - Advances in neural ... - 2016 - proceedings.neurips.co...  
... and natural language processing tasks. We show that even word embeddings trained on ...  
is first shown to be captured by a direction in the word embedding. Second, gender neutral ...  
☆ Save 99 Cite

**NLP: Oh no! My models are biased!**

Gender-prejudice in word embeddings  
M Kaneko, DJ ... - 2017 - arxiv.org  
... word embeddings ...  
... Information for common NLP tasks that use these debiased word embeddings. To ...  
☆ Save 99 Cite Cited by 82 Related articles All 5 versions 20

Lipstick on a pig: Debiasing methods cover up systematic gender biases in word embeddings but do not remove them  
H Gonen, Y Goldberg - arXiv preprint arXiv:1903.03862, 2019 - arxiv.org  
... Word embeddings are widely used in NLP for a vast range of ... For each debiased word embedding we quantify the hidden bias ... For HARD-DEBIASED we compare to the embeddings ...  
☆ Save 99 Cite Cited by 400 Related articles All 10 versions 20



# How do we measure similarity between gendered words and stereotype words?

---

- “Programmer” is more similar to “man”; “homemaker” is more similar to “woman”
- We already built embeddings (last class), we just need a measure of distance


# Word Embedding Similarity

- Euclidean distance

$$\sqrt{(u_1 - v_1)^2 + (u_2 - v_2)^2 \dots}$$

$$-\|u - v\|_2$$

- Negate to get a similarity function




# Word Embedding Similarity

- Cosine Similarity

$$\frac{u \cdot v}{\|u\| \|v\|}$$


- Recall: Skip-gram objective function

- $P(w_{t+j} | w_t) = P(o | c) = \frac{\exp(u_o^T v_c)}{\sum_{i=1}^V \exp(u_i^T v_c)}$




# How do we measure similarity between gendered words and stereotype words?

- Vector arithmetic for analogies:
  - “King” – “man” + “woman” = “queen”
  - “computer programmer” – “man” + woman = “homemaker”



- Key idea:
  - There is a gender subspace




- Project embeddings onto he-she direction

# How do we measure similarity between gendered words and stereotype words?

---

- “Programmer” is more similar to “man”; “homemaker” is more similar to “woman”
  - “Oh man”
  - “Man the station”
    - “Programmer” co-occurs more often with “man the station” than “homemaker” – not clearly indicate of gender bias


# Relational properties of the GloVe vector space (Pennington et al., 2014)



# Identify gender subspace: Pairs words + PCA

- Principle Component Analysis
  - Identify directions of greatest variance
- First PCA eigenvector explains most of the variance:
  - Consider this component to be the gender (bias) subspace

$\xrightarrow{\text{she}-\text{he}}$   
 $\xrightarrow{\text{her}-\text{his}}$   
 $\xrightarrow{\text{woman}-\text{man}}$   
 $\xrightarrow{\text{Mary}-\text{John}}$   
 $\xrightarrow{\text{herself}-\text{himself}}$   
 $\xrightarrow{\text{daughter}-\text{son}}$   
 $\xrightarrow{\text{mother}-\text{father}}$   
 $\xrightarrow{\text{gal}-\text{guy}}$   
 $\xrightarrow{\text{girl}-\text{boy}}$   
 $\xrightarrow{\text{female}-\text{male}}$



[In actual formulations, defined gender subspace based on difference from mean of vectors rather than individual vector pairs]

# Man is to Computer Programmer as Woman is to Homemaker?


---

- How do we use this “gender subspace”?
  - Original paper: debias embeddings
  - Follow up work:
    - “De-biasing” isn’t maintained across different ways of measuring bias [Gonen and Goldberg 2019]
    - Not clear that de-biasing does anything if you are using embeddings in downstream model
  - Social science applications:
    - Measuring associations between words
  - Follow-up work also offers different ways of defining the subspace

Gonen, Hila, and Yoav Goldberg. "Lipstick on a Pig: Debiasing Methods Cover up Systematic Gender Biases in Word Embeddings But do not Remove Them." NAACL 2019.

# Alternative "Bias" Metric: Word Embedding Association Test (WEAT)

- Origins: Implicit Association test in psychology measures how quickly you associate unpleasant/pleasant stimuli with Black/white (African American/European American) names or faces



Caliskan, Aylin, Joanna J. Bryson, and Arvind Narayanan. "Semantics derived automatically from language corpora contain human-like biases." *Science* 356.6334 (2017): 183-186.

Greenwald, Anthony G., Debbie E. McGhee, and Jordan LK Schwartz. "Measuring individual differences in implicit cognition: the implicit association test." *Journal of personality and social psychology* 74.6 (1998): 1464.

# WEAT Formulation

- X,Y two sets of target words of equal size
  - X = {programmer, doctor}, Y = {homemaker, nurse}
- A,B the two sets of attribute words
  - A = {man, he}; B = {woman, she}

$$s(X, Y, A, B) = \sum_{x \in X} s(x, A, B) - \sum_{y \in Y} s(y, A, B)$$

Where  $s(w, A, B) = \text{mean}_{a \in A} \cos(\vec{w}, \vec{a}) - \text{mean}_{b \in B} \cos(\vec{w}, \vec{b})$

# Paper results

- Using WEAT metrics, bias in embeddings replicates bias found in humans using IAT

Target words	Attribute words	Original finding				Our finding			
		Ref.	N	d	P	N <sub>T</sub>	N <sub>A</sub>	d	P
Flowers vs. insects	Pleasant vs. unpleasant	(5)	32	1.35	$10^{-8}$	$25 \times 2$	$25 \times 2$	1.50	$10^{-7}$
Instruments vs. weapons	Pleasant vs. unpleasant	(5)	32	1.66	$10^{-10}$	$25 \times 2$	$25 \times 2$	1.53	$10^{-7}$
European-American vs. African-American names	Pleasant vs. unpleasant	(5)	26	1.17	$10^{-5}$	$32 \times 2$	$25 \times 2$	1.41	$10^{-8}$
European-American vs. African-American names	Pleasant vs. unpleasant from (5)	(7)	Not applicable			$16 \times 2$	$25 \times 2$	1.50	$10^{-4}$
European-American vs. African-American names	Pleasant vs. unpleasant from (9)	(7)	Not applicable			$16 \times 2$	$8 \times 2$	1.28	$10^{-3}$
Male vs. female names	Career vs. family	(9)	39k	0.72	$<10^{-2}$	$8 \times 2$	$8 \times 2$	1.81	$10^{-3}$
Math vs. arts	Male vs. female terms	(9)	28k	0.82	$<10^{-2}$	$8 \times 2$	$8 \times 2$	1.06	.018
Science vs. arts	Male vs. female terms	(10)	91	1.47	$10^{-24}$	$8 \times 2$	$8 \times 2$	1.24	$10^{-2}$
Mental vs. physical disease	Temporary vs. permanent	(23)	135	1.01	$10^{-3}$	$6 \times 2$	$7 \times 2$	1.38	$10^{-2}$
Young vs. old people's names	Pleasant vs. unpleasant	(9)	43k	1.42	$<10^{-2}$	$8 \times 2$	$8 \times 2$	1.21	$10^{-2}$






JOHNS HOPKINS  
WHITING SCHOOL  
*of* ENGINEERING

# Diachronic Embeddings

# Diachronic Embeddings (Sociolinguistics)

- Core question in understanding cultural and language evolution: how do words change meaning over time?



Hamilton, William L., Jure Leskovec, and Dan Jurafsky. "Diachronic Word Embeddings Reveal Statistical Laws of Semantic Change." Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers). 2016.


# Compute word2vec embeddings for large text corpora divided by decade

Name	Language	Description	Tokens	Years	POS Source
ENGALL	English	Google books (all genres)	$8.5 \times 10^{11}$	1800-1999	(Davies, 2010)
ENGFIC	English	Fiction from Google books	$7.5 \times 10^{10}$	1800-1999	(Davies, 2010)
COHA	English	Genre-balanced sample	$4.1 \times 10^8$	1810-2009	(Davies, 2010)
FREALL	French	Google books (all genres)	$1.9 \times 10^{11}$	1800-1999	(Sagot et al., 2006)
GERALL	German	Google books (all genres)	$4.3 \times 10^{10}$	1800-1999	(Schneider and Volk, 1998)
CHIALL	Chinese	Google books (all genres)	$6.0 \times 10^{10}$	1950-1999	(Xue et al., 2005)

- Aggregate data by decades
- Train word embeddings on each decade (skip-gram with negative sampling)
  - Problem! Embedding spaces are not aligned!

# Problem: Embedding spaces are not aligned

- Training is a stochastic process conducted on different data sets
  - Our optimization function is about relationship between vectors, not exact values
- We expect relationships between embeddings to be similar for most words (in different decades) but exact learned embedding space may differ



# Procrustes Alignment Method

Define  $W_t$  as the  $V \times D$  matrix of embeddings for decade/time t.  
[ $V$ =vocabulary size,  $D$ =embedding size]

To align  $W_{t+1}$  to  $W_t$ , we solve:

$$\operatorname{argmin}_{Q^T Q = I} \|W_{t+1} Q - W_t\|_F$$

Constrain that relations between embeddings are preserved in transformation

Find a transformation of  $W_{t+1}$

$$\|A\|_F \equiv \sqrt{\sum_{i=1}^m \sum_{j=1}^n |a_{ij}|^2}$$

“Frobenius norm”: the transformation must minimize the difference between elements of  $W_t$  and  $W_{t+1}$

# Procrustes Alignment Method

Define  $W_t$  as the  $V \times D$  matrix of embeddings for decade/time t.  
[ $V$ =vocabulary size,  $D$ =embedding size]


To align  $W_{t+1}$  to  $W_t$ , we solve:

$$\operatorname{argmin}_{Q^T Q = I} \|W_{t+1}Q - W_t\|_F$$

Solution:

- Compute  $U\Sigma V^T = \text{SVD}(W_{t+1}^T W_t)$
- $Q = UV^T$

# Mismatches after alignment indicate semantic change




- We can compute distance between embeddings across aligned corpora
- We can also compute similarities between pairs of embeddings (e.g. ["awful", "majestic"]; ["awful", "terrible"]) without alignment

# Occupation Stereotypes over time


---

- Three word lists:
  - Words representing gender
  - Words representing ethnicity (White, Asian, Hispanic; last names)
  - Occupation and adjective words
- Methods:
  - Average vectors in gender/ethnicity group
  - Compute average Euclidean distance between each group vector and each vector in occupation/adjective words
  - Take the difference of these averages between two groups (e.g. are “men” vectors closer to “programmer” than “women” vectors?) as the “relative norm difference” or “embedding bias”

# Validation: comparison with census-reported occupations




# Comparison with census reports over time (gender)




- Blue: bias score from embeddings (more positive indicates stronger association with women)
- Green: % of difference in women and men in the same occupations

# Comparison with census reports over time (ethnicity)



# Adjectives co-occurring with women over time



- Study how description of women (adjectives) changed over time
- Correlations between distance between women-embeddings and adjective embeddings
- Highest correlations are between adjacent decades
- Weakest correlation is 1960s-1970s corresponding with women's movement



JOHNS HOPKINS  
WHITING SCHOOL  
*of* ENGINEERING

# Embeddings Evaluation

# Evaluation

---

- We're using embeddings for analyzing data sets
- How do we know that the embeddings we trained are meaningful?
- How much do decisions like embedding model (word2vec-CBOW, word2vec-skipgram, fasttext), similarity metric, or seed words (man/woman) matter?

# Evaluation: Intrinsic Metrics of Embedding Quality

---

- Test performance on similarity; correlation between an algorithm's word similarity scores and word similarity ratings assigned by humans
  - WordSim-353 (Finkelstein et al., 2002): is ratings from 0 to 10 for 353 noun pairs; for example (plane, car) had an average score of 5.77.
  - SimLex-999 (Hill et al., 2015): more difficult dataset that quantifies similarity (cup, mug) rather than relatedness (cup, coffee), and including both concrete and abstract adjective, noun and verb pairs
  - TOEFL dataset (Landauer and Dumais, 1997): 80 questions, each consisting of a target word with 4 additional word choices; the task is to choose which is the correct synonym
- Data sets that incorporate context, such as sentence-level similarity (Huang et al., 2012; Pilehvar and Camacho-Collados, 2019)
- Analogy tasks (Turney and Littman, 2005)

# Evaluation: Extrinsic Metrics of Embedding Quality

---

- Performance on downstream task when using embeddings in an NLP model
  - Useful for NLP models, less obviously indicative of analysis reliability
- Comparisons with external data
  - Occupation statistics from the census
  - Crowd-sourced annotations of stereotypes (note that we can crowd-source current stereotypes but it's hard to crowd-source historical ones)

# Evaluation: Capacity to capture social variables

---

- Do word embeddings reflect beliefs about people?
  - E.g. race and gender stereotypes
  - Dimension-level: how well do embeddings capture beliefs about gender relative to race?
  - Belief-level: how well do embeddings capture beliefs about potency (strength) of "children" vs "thugs"?

## Methods

- Collect survey data from Amazon Mechanical Turk
  - Limiting assumption, how do we know if the survey data is reliable?

# Evaluation: Specific Experimental Design Decisions

---

- Corpus/Embedding Selection
- Dimension Selection
  - Dimension-inducing word set
  - Methodology (average embeddings, PCA, etc)
- Word Position Measurement
  - E.g. projection, vector similarity metrics

What approaches work best? How much do these choices matter?

# Design Choices



Measure	Normalized?	Position Measure	Direction-Specification	Multiclass
Ethayarajh et al. (2019)	N	$\frac{\langle w, b \rangle}{\ b\ }$	Same as Bolukbasi et al. (2016)	N
Kozlowski et al. (2019)	Y	$\frac{\langle w, b \rangle}{\ b\  \ w\ }$	$\sum_{p_i \in P} \frac{p_{i,l} - p_{i,r}}{\ P\ }$	N
Bolukbasi et al. (2016)	Y	$\frac{\langle w, b \rangle}{\ b\  \ w\ }$	$SVD \left( c(p_{i,j} - \mu_{p_{ij}}) \quad p_i \in P \right)$	N
Swinger et al. (2019)	Y	$\text{avg}_{p_i \in P} \frac{\langle w, p_{i,l} \rangle}{\ w\  \ p_{i,l}\ } - \text{avg}_{p_i \in P} \frac{\langle w, p_{i,r} \rangle}{\ w\  \ p_{i,r}\ }$	N/A	Y
Garg et al. (2018)	Y	$\ w - b_r\  - \ w - b_l\ $	$b_l := \sum_{p_i \in p_r} \frac{p_i}{\ P\ }$	Y

# Results



- [Generally embedding results do correlate with survey results]
- Selection of embedding model can decrease correlation with survey results
- Less variation for 300D embeddings
- No embedding model is universally the best


# Results



- Selection of dimension-inducing words doesn't really matter (though you could make a particularly bad choice) [Note that other work has found more variance]
- Choice of position measure (e.g. similarity metric) has almost no effect

# Results

- Correlations for some dimensions (e.g. gender) are much stronger than for others (e.g. race)!



# Recap

---

- Example applications:
  - Measuring bias (gender bias / occupational stereotypes)
  - Measuring change in word meanings over time
  - Measuring stereotypes over time
- Embedding manipulation:
  - Cosine similarity, Euclidean distance
  - Gender subspace
  - Averaging keywords
- Evaluations:
  - Analogy tasks, similarity benchmarks, extrinsic metrics
  - Comparisons with hand-curated analyses or benchmarks
  - Comparisons with survey or crowd-sourced data

# References

---

- Jurafsky&Martin 6.11-6.13 <https://web.stanford.edu/~jurafsky/slp3/6.pdf>
- Bolukbasi, Tolga, et al. "Man is to computer programmer as woman is to homemaker? debiasing word embeddings." *Advances in neural information processing systems* 29 (2016).
- Hamilton, William L., Jure Leskovec, and Dan Jurafsky. "Diachronic Word Embeddings Reveal Statistical Laws of Semantic Change." *ACL*. 2016.
- Garg, Nikhil, et al. "Word embeddings quantify 100 years of gender and ethnic stereotypes." *Proceedings of the National Academy of Sciences* 115.16 (2018): E3635-E3644.
- Joseph, Kenneth, and Jonathan Morgan. "When do Word Embeddings Accurately Reflect Surveys on our Beliefs About People?." *ACL*. 2020.