

Jumphost Setup Guide for New Joinees (Mac)

Space: Retail-IP (RETAILIP) · Author: Anjali Jaiswal · Last modified: Jun 23, 2026

Source: <https://flipkart.atlassian.net/wiki/spaces/RETAILIP/pages/489950665/Jumphost+Setup+Guide+for+New+Joinees+Mac>

This guide walks you through setting up Jumphost access on a Mac so you can SSH into Flipkart internal VMs. Written by Anjali Jaiswal based on actual setup experience — includes all the non-obvious fixes you'll likely hit.

Prerequisites: You must have your LDAP username, Flipkart email access for OTP, and your public SSH key registered at <http://console.bastion-prod.fkcloud.in/> before starting.

Step 1 — Install Homebrew

```
/bin/bash -c "$(curl -k --ipv4 https://raw.githubusercontent.com/Homebrew/install/HEAD/install.sh)"
```

If you need sudo access to install Homebrew, check the prerequisites doc first.

Step 2 — Set up Flipkart Homebrew Tap and install Jumphost

```
brew tap flipkart-incubator/taps  
brew install jumphost
```

Step 3 — Run the setup script

```
setup-jumphost-cli.sh
```

When it completes you should see:

```
[OK] Please open a new terminal window, for jumphost changes to take effect.
```

Open a new terminal window after this (Cmd + N on Mac). Do not continue in the same terminal.

Step 4 — Fix the fkst-cli config (Critical — you will likely hit this)

This is the most common point of failure. The `fkst-cli` binary on Apple Silicon Macs is installed under `~/local/homebrew/bin/` but is hardcoded to read its config from `/opt/homebrew/etc/jumphost/fkst-cli.yml`. That

file is usually empty after install, causing this error:

```
Error: Post "/cli/getToken?client_id=jumphost": unsupported protocol scheme ""
```

Fix: Copy the correct config to the path the binary actually reads:

```
cp ~/.local/homebrew/etc/jumphost/fkst-cli.yml /opt/homebrew/etc/jumphost/fkst-cli.yml
```

Then open `/opt/homebrew/etc/jumphost/fkst-cli.yml` in nano and make sure it has the full config below (remove any stray characters like `Z.` at end of lines):

```
server_url: "https://global.jumphost-prod.fkcloud.in"
client_id: "jumphost"

http:
  dial_timeout: 3s
  request_timeout: 7s
  idle_connection_timeout: 30s
  insecure_skip_verify: true
  keep_alive: true
  compression: false
  idle_connections_per_host: 20

env:
  prod:
    authn: https://service.authn-prod.fkcloud.in
    bastion: http://service.bastion-prod.fkcloud.in
  preprod:
    authn: https://service.authn-preprod.fkcloud.in
```

To edit: `nano /opt/homebrew/etc/jumphost/fkst-cli.yml` — save with Ctrl+O, Enter, Ctrl+X

Step 5 — Add your LDAP username to the SSH config

Check the default jumphost SSH config:

```
cat ~/.ssh/jumphost/default
```

If `User <your-ldap>` is missing at the top, add it:

```
nano ~/.ssh/jumphost/default
```

It should look exactly like this (replace with your LDAP username):

```
User your.ldap.username
Host 10.* *.flipkart.com !global.jumphost-prod.fkcloud.in
ProxyJump global.jumphost-prod.fkcloud.in
```

Step 6 — Install the certificate

```
fkst-cli installCert
```

This will prompt you to choose a 2FA method (SMS / Email / Google Authenticator) and enter your OTP. Use whichever you prefer.

If you still get `unsupported protocol scheme ""` after fixing the config, double-check that `/opt/homebrew/etc/jumphost/fkst-cli.yml` is the file with content — not one of the other locations.

Step 7 — Verify the setup

```
# Test 1 — SSH through jumphost tunnel to a CLI machine
ssh iaas-cli-0001.ch.flipkart.com

# Test 2 — SSH directly to an internal VM IP (one you have access to)
ssh <internal-VM-IP>
```

If you see this banner, you're through:

```
*_____*
* You're passing through Jumphost Tunnels. *
*-----*
```

Followed by a Linux login prompt — you're in! 

Troubleshooting

Error	Cause	Fix
<code>unsupported protocol scheme ""</code>	<code>/opt/homebrew/etc/jumphost/fkst-cli.yml</code> is empty or missing <code>server_url</code>	Follow Step 4 above
<code>Permission denied (publickey)</code>	LDAP username missing from SSH config, OR public key not in Bastion	Follow Step 5; check Bastion console

Error	Cause	Fix
gcloud: command not found on megh-cli	gcloud is not installed on internal machines	Run gcloud commands from your Mac terminal, not from megh-cli
curl to external URLs times out on megh-cli	Flipkart network blocks outbound internet from internal machines	Expected behaviour — install tools on your Mac, not on megh-cli

Note: The certificate installed in Step 6 may take up to 1 day to propagate for some users. If SSH still fails after all steps, wait and retry the next day.