

Coding and Web Development — Lecture 04

Topic: Tag & Element

1. Tag Kya Hota Hai?

Tag ek **keyword** hota hai jo **angle brackets** < > ke andar likha jata hai.

<keyword>

Yeh browser ko batata hai — “**yeh content kis type ka hai**”.

Example:

<p>

Yahan p ek tag hai jo bata raha hai ki andar wala content ek *paragraph* hai.

2. Element Kya Hota Hai?

Element = Opening Tag + Content + Closing Tag

Yani element ek **poora package** hota hai — sirf tag nahi, balki uske andar ka content aur closing tag bhi.

```
<p> Hii Anish </p>
  ↑       ↑       ↑
Opening Content Closing
Tag       Tag
```

Part	Kya hai
<p>	Opening tag
Hii Anish	Content
</p>	Closing tag
Poora Hii Anish	Element

Tag ke Types:

- **Opening Tag** → <p>
 - **Closing Tag** → </p>
 - **Self-Closing Tag** → jaise ,
 (inhe closing tag ki zaroorat nahi hoti)
-

3. Attribute Kya Hota Hai?

Attribute ek **extra detail/property** hota hai jo hum **opening tag ke andar** likhte hain — yeh tag ko extra information deta hai.

Example:

- class aur title — yeh dono **attributes** hain.
- Ek tag mein **multiple attributes** bhi ho sakte hain.

4. Heading Tags (<h1> to <h6>)

Heading ek **title ya subtitle** hota hai jo batata hai “**yeh section kis baare mein hai**”.

- HTML mein total **6 headings** hote hain: <h1> se <h6> tak.
- <h1> sabse important/bada heading hota hai, <h6> sabse chhota.
- ⚠ **Rule:** Ek page mein normally **sirf ek hi <h1>** use karna chahiye — yeh page ka **main title** hota hai.

```
<h1>Main Title</h1>
<h2>Sub Heading</h2>
...
<h6>Smallest Heading</h6>
```

5. Paragraph Tag (<p>)

<p> tag **normal text/content** ke liye use hota hai — jaise koi paragraph kisi essay mein hota hai.

```
<p>Yeh ek paragraph hai.</p>
```

6. Text Formatting Tags

Tag	Kaam
	Text ko bold banata hai (important text)
<i> / 	Text ko <i>italic</i> banata hai
<mark>	Text ko highlight karta hai

Example:

Hii Rishikesh	→ Hii **Rishikesh**
Hii <i>Rishikesh</i>	→ Hii <i>*Rishikesh*</i>
Hii <mark>Rishikesh</mark>	→ Hii highlighted-Rishikesh

7. Block-level vs Inline Elements

Block-level Elements

- Apni **poori line** lete hain — jaise ek poora row/box hota hai.
- Example: <div>, <p>, <h1>...<h6>

Inline Elements

- Sirf **content jitni jagah** lete hain — poori line nahi lete.
- Example: , <a>, , <i>

Property	Block	Inline
Line space	Poori line leta hai	Sirf content jitni jagah leta hai

8. <div> Tag

- Ek **generic container/box** hota hai.
 - Iska koi apna **special meaning** nahi hota (jaise <h1> ka matlab “heading” hota hai, waise <div> ka koi fixed meaning nahi).
 - Sirf **content ko group/wrap** karne ke liye use hota hai.
 - **Block-level** element hai.
-

9. Tag

- Yeh bhi ek **generic container** hai, lekin **chhote level** pe.
- Usually ek chhote se hisse (jaise ek **word ya phrase**) ko wrap karne ke liye use hota hai — **poore section ke liye nahi**.
- **Inline** element hai.

Div vs Span

	<div>	
Type	Block-level	Inline
Use	Bada section/group wrap karne ke liye	Chhota text/word wrap karne ke liye

🔑 Quick Recap

- **Tag** = keyword in < > → tells browser content type
 - **Element** = Opening tag + Content + Closing tag
 - **Attribute** = extra info inside opening tag
 - **Headings** h1-h6 = section titles (only 1 h1 per page)
 - **<p>** = normal paragraph text
 - **Block** = full line | **Inline** = only content space
 - **<div>** = block container | **** = inline container
-

Notes based on Lecture 04 — Coding and Web Development (By Nishant Sir)