

Ex 4: Spring Core – Load Country from Spring Configuration XML

country.xml:

```
1 <?xml version="1.0" encoding="UTF-8"?>
2
3 <beans xmlns="http://www.springframework.org/schema/beans"
4       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
5       xsi:schemaLocation="
6         http://www.springframework.org/schema/beans
7         https://www.springframework.org/schema/beans/spring-beans.xsd">
8
9   <bean id="country" class="com.cognizant.springlearn.Country">
10
11     <property name="code" value="IN"/>
12
13     <property name="name" value="India"/>
14
15   </bean>
16
17 https://www.springframework.org/schema/beans/spring-beans.xsd (xsi:schemaLocation)
```

Country.java:

```
1 package com.cognizant.springlearn;
2
3 import org.slf4j.Logger;
4 import org.slf4j.LoggerFactory;
5
6 public class Country {
7
8     private static final Logger LOGGER = LoggerFactory.getLogger(Country.class);
9
10    private String code;
11    private String name;
12
13    public Country() {
14        LOGGER.debug("Inside Country Constructor.");
15    }
16
17    public String getCode() {
18        LOGGER.debug("Inside getCode()");
19        return code;
20    }
21
22    public void setCode(String code) {
23        LOGGER.debug("Inside setCode()");
24        this.code = code;
25    }
26
27    public String getName() {
28        LOGGER.debug("Inside getName()");
29        return name;
30    }
31}
```

```

1 package com.cognizant.springlearn;
2
3 import org.slf4j.Logger;
4 import org.slf4j.LoggerFactory;
5 import org.springframework.boot.SpringApplication;
6 import org.springframework.boot.autoconfigure.SpringBootApplication;
7 import org.springframework.context.ApplicationContext;
8 import org.springframework.context.support.ClassPathXmlApplicationContext;
9
10 @SpringBootApplication
11 public class SpringLearnApplication {
12
13     private static final Logger LOGGER = LoggerFactory.getLogger(SpringLearnApplication.class);
14
15     public static void displayCountry() {
16
17         ApplicationContext context = new ClassPathXmlApplicationContext("country.xml");
18         Country country = context.getBean("country", Country.class);
19
20         LOGGER.debug("Country : {}", country.toString());
21     }
22
23     public static void main(String[] args) {
24
25         LOGGER.info("Inside main() method - Application is starting...");
26
27         SpringApplication.run(SpringLearnApplication.class, args);
28
29         displayCountry();
30
31         LOGGER.info("Spring Boot application started successfully.");
32     }
33 }
34

```

```

2026-07-13T17:04:06.541 [main] INFO com.cognizant.springlearn.SpringLearnApplication -- Inside main() method - Application is starting...
17:04:06.781 [restartMain] INFO com.cognizant.springlearn.SpringLearnApplication -- Inside main() method - Application is starting...

=====
:: Spring Boot ::
(v4.1.0)

2026-07-13T17:04:07.254+05:30 INFO 10900 --- [spring-learn] [restartMain] c.c.springlearn.SpringLearnApplication : Starting SpringLearnApplication using Java 17.0.19 with PID 10900 (C:\
2026-07-13T17:04:07.261+05:30 DEBUG 10900 --- [spring-learn] [restartMain] c.c.springlearn.SpringLearnApplication : Running with Spring Boot v4.1.0, Spring v7.0.8
2026-07-13T17:04:07.263+05:30 INFO 10900 --- [spring-learn] [restartMain] c.c.springlearn.SpringLearnApplication : No active profile set, falling back to 1 default profile: "default"
2026-07-13T17:04:07.361+05:30 INFO 10900 --- [spring-learn] [restartMain] .e.DevToolsPropertyDefaultsPostProcessor : Devtools property defaults active! Set 'spring.devtools.add-properties
2026-07-13T17:04:07.362+05:30 INFO 10900 --- [spring-learn] [restartMain] .e.DevToolsPropertyDefaultsPostProcessor : For additional web related logging consider setting the 'logging.level
2026-07-13T17:04:08.433+05:30 INFO 10900 --- [spring-learn] [restartMain] o.s.boot.tomcat.TomcatWebServer : Tomcat initialized with port 8080 (http)
2026-07-13T17:04:08.447+05:30 INFO 10900 --- [spring-learn] [restartMain] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2026-07-13T17:04:08.447+05:30 INFO 10900 --- [spring-learn] [restartMain] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/11.0.22]
2026-07-13T17:04:08.447+05:30 INFO 10900 --- [spring-learn] [restartMain] b.w.c.s.WebApplicationContextInitializer : Root WebApplicationContext: initialization completed in 1131 ms
2026-07-13T17:04:08.629+05:30 INFO 10900 --- [spring-learn] [restartMain] o.s.boot.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path '/'
2026-07-13T17:04:08.844+05:30 INFO 10900 --- [spring-learn] [restartMain] c.c.springlearn.SpringLearnApplication : Started SpringLearnApplication in 2.255 seconds (process running for 2
2026-07-13T17:04:09.251+05:30 DEBUG 10900 --- [spring-learn] [restartMain] com.cognizant.springlearn.Country : Inside Country Constructor.
2026-07-13T17:04:09.252+05:30 DEBUG 10900 --- [spring-learn] [restartMain] com.cognizant.springlearn.Country : Inside setCode()
2026-07-13T17:04:09.252+05:30 DEBUG 10900 --- [spring-learn] [restartMain] com.cognizant.springlearn.Country : Inside setName()
2026-07-13T17:04:09.254+05:30 DEBUG 10900 --- [spring-learn] [restartMain] c.c.springlearn.SpringLearnApplication : Country : Country [code=IN, name=India]
2026-07-13T17:04:09.255+05:30 INFO 10900 --- [spring-learn] [restartMain] c.c.springlearn.SpringLearnApplication : Spring Boot application started successfully.

```