

Ex: REST - Get country based on country code

country.xml:

```
1 <?xml version="1.0" encoding="UTF-8"?>
2
3 <beans xmlns="http://www.springframework.org/schema/beans"
4       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
5       xsi:schemaLocation="
6         http://www.springframework.org/schema/beans
7         https://www.springframework.org/schema/beans/spring-beans.xsd">
8
9   <bean id="countryList" class="java.util.ArrayList">
10
11     <constructor-arg>
12       <list>
13
14         <bean class="com.cognizant.springlearn.Country">
15           <property name="code" value="IN"/>
16           <property name="name" value="India"/>
17         </bean>
18
19         <bean class="com.cognizant.springlearn.Country">
20           <property name="code" value="US"/>
21           <property name="name" value="United States"/>
22         </bean>
23
24         <bean class="com.cognizant.springlearn.Country">
25           <property name="code" value="JP"/>
26           <property name="name" value="Japan"/>
27         </bean>
28
29         <bean class="com.cognizant.springlearn.Country">
30           <property name="code" value="FR"/>
31           <property name="name" value="France"/>
32         </bean>

```

CountryController.java:

```
1 package com.cognizant.springlearn.controller;
2
3 import org.slf4j.Logger;
4 import org.slf4j.LoggerFactory;
5 import org.springframework.beans.factory.annotation.Autowired;
6 import org.springframework.web.bind.annotation.GetMapping;
7 import org.springframework.web.bind.annotation.PathVariable;
8 import org.springframework.web.bind.annotation.RestController;
9
10 import com.cognizant.springlearn.Country;
11 import com.cognizant.springlearn.service.CountryService;
12
13 @RestController
14 public class CountryController {
15
16     private static final Logger LOGGER =
17         LoggerFactory.getLogger(CountryController.class);
18
19     @Autowired
20     private CountryService countryService;
21
22     @GetMapping("/countries/{code}")
23     public Country getCountry(@PathVariable String code) {
24
25         LOGGER.info("START");
26
27         Country country = countryService.getCountry(code);
28
29         LOGGER.info("END");
30
31         return country;
32     }
33 }
```

CountryService.java:

```
1 package com.cognizant.springlearn.service;
2
3 import java.util.List;
4
5 import org.springframework.context.ApplicationContext;
6 import org.springframework.context.support.ClassPathXmlApplicationContext;
7 import org.springframework.stereotype.Service;
8
9 import com.cognizant.springlearn.Country;
10
11 @Service
12 public class CountryService {
13
14     public Country getCountry(String code) {
15
16         ApplicationContext context =
17             new ClassPathXmlApplicationContext("country.xml");
18
19         List<Country> countries = (List<Country>) context.getBean("countryList");
20
21         for (Country country : countries) {
22             if (country.getCode().equalsIgnoreCase(code)) {
23                 return country;
24             }
25         }
26
27         return null;
28     }
29 }
```

Output:

The screenshot shows a web browser window with the address bar displaying `localhost:8083/countries/in`. The main content area shows a JSON response: `{ "code": "IN", "name": "India" }`. The Network tab is open, showing a single request to `http://localhost:8083/countries/in` with a status of `200 OK`. The response headers are visible, including `Content-Type: application/json` and `Date: Mon, 13 Jul 2026 13:56:07 GMT`.

Name	Headers	Preview	Response	Initiator	Timing
in	- Request URL: <code>http://localhost:8083/countries/in</code> - Request Method: <code>GET</code> - Status Code: <code>200 OK</code> - Remote Address: <code>[-:1]:8083</code> - Referrer Policy: <code>strict-origin-when-cross-origin</code>	- Response headers: - keep-alive - Content-Length: <code>28</code> - Content-Type: <code>application/json</code> - Date: <code>Mon, 13 Jul 2026 13:56:07 GMT</code> - Keep-Alive: <code>timeout=60</code>	<code>{ "code": "IN", "name": "India" }</code>		