

Codebook- Team bits_dont_lie

IIT Delhi, India

Ankesh Gupta, Ronak Agarwal, Anant Chhajwani

Contents

1	Format	2	4.7	General Unweighted Maximum Matching (Edmonds' algorithm)	11
1.1	Format c++	2	4.8	König's Theorem (Text)	12
1.2	String Input c++	2	4.9	Minimum Edge Cover (Text)	12
2	Strings	2	5	Data Structures	12
2.1	KMP	2	5.1	BIT- Range Update + Range Sum	12
2.2	AhoCohrasick	3	5.2	BIT- 2D	13
2.3	Manacher	3	5.3	Ordered Statistics	14
2.4	Suffix_Array	3	5.4	Persistent Tree	14
2.5	Z algo	4	6	Math	15
2.6	Hashing	4	6.1	Convex Hull	15
3	Trees	4	6.2	FFT	15
3.1	Centroid Tree	4	6.3	FFT_Complex	16
3.2	Heavy Light Decomposition	5	6.4	Find Primitive Root	16
3.3	Heavy Light Trick	6	6.5	Convex Hull Trick	16
3.4	LCA	6	6.6	Miscellaneous Geometry	17
4	Graph and Matching, Flows	7	6.7	Gaussian elimination for square matrices of full rank; finds inverses and determinants	19
4.1	Euler Walk	7	7	Number Theory Reference	19
4.2	Articulation Point Pseudo	7	7.1	Modular arithmetic and linear Diophantine solver	19
4.3	Ford Fulkerson Matching	7	7.2	Polynomial Coefficients (Text)	21
4.4	Dinic- Maximum Flow $O(EV^2)$	8	7.3	Möbius Function (Text)	21
4.5	Minimum Cost Bipartite Matching $O(V^3)$	9	7.4	Burnside's Lemma (Text)	21
4.6	Minimum Cost Maximum Flow	10	8	Miscellaneous	21

8.1 2-SAT 21

1 Format

1.1 Format c++

```
#include <bits/stdc++.h>
typedef long double ld ;
#define long long long int
using namespace std;
#define pi 3.141592653589

template<class T> ostream& operator<<(ostream &os, ←
    vector<T> V) {
    os << "[";
    for(auto v : V) os << v << " ";
    return os << "]";
}
template<class L, class R> ostream& operator<<(←
    ostream &os, pair<L,R> P) {
    return os << "(" << P.first << "," << P.second << ←
        ")";
}
#define TRACE
#ifdef TRACE
#define trace(...) __f(#__VA_ARGS__, __VA_ARGS__)
template <typename Arg1>
void __f(const char* name, Arg1&& arg1){
    cerr << name << " : " << arg1 << endl;
}
template <typename Arg1, typename... Args>
void __f(const char* names, Arg1&& arg1, Args&&...←
    args){
    const char* comma = strchr(names + 1, ',');
    cerr.write(names, comma - names) << " : " << arg1←
        << " | ";
    __f(comma+1, args...);
}
#else
#define trace(...)
#endif

long GCD(long a, long b){
    while(a && b){
        a=a%b;
        if(a!=0)
            b=b%a;
    }
}
```

```
    }
    return a+b;
}

long exp(long a, long n){
    long ans=1;
    a=check(a);
    while(n){
        if(n&1)
            ans=check(ans*a);
        a=check(a*a);
        n=(n>>1);
    }
    return ans;
}
```

1.2 String Input c++

```
cin.ignore();
for(int j=0;j<lines;j++){
    getline(cin,x);
    stringstream check1(x);
    string tokens;
    while(getline(check1, tokens, ' ')){
        if(tokens=="import")
            continue;
    }
}
```

2 Strings

2.1 KMP

```
//Takes an array of characters and calculate
//lcp[i] where lcp[i] is the longest proper suffix ←
//of the
//string c[0..i] such that it is also a prefix of ←
//the string.
vector<int> kmp(const string &str){
    int n = str.size();
    vector<int> lcp(n,0);
```

```

for(int i=1 ; i<n ; i++){
    int j = lcp[i-1];
    while(j!=0 && str[i]!=str[j]) j = lcp[j-1];
    if(str[i]==str[j]) j++;
    lcp[i]=j;
}
return lcp;
}

```

2.2 AhoCohrasick

```

int m=0;
struct Trie{
    int chd[26];
    int cnt,mcnt,d=-1,p=-1,pch;
    int sLink = -1;
    Trie(int p,int pch,int d): cnt(0), mcnt(0), d(d), ←
        p(p), pch(pch){
        for(int i=0 ; i<26 ; i++) chd[i]=-1;
    }
};
const int N = 5e5;
Trie* nds[N];
void addVal(const string &str){
    int v=0;
    for(char chr : str){
        int idx = chr-'a';
        if(nds[v]->chd[idx]==-1){
            nds[v]->chd[idx] = m;
            nds[m++] = new Trie(v,idx,(nds[v]->d)+1);
        }
        v = nds[v]->chd[idx];
        nds[v]->cnt+=nds[v]->d;
    }
}
void AhoCorasick(){
    queue<int> q;
    q.push(0);
    while(!q.empty()){
        int v = q.front();
        q.pop();
        for(int i=0 ; i<26 ; i++){
            if(nds[v]->chd[i]!=-1)
                q.push(nds[v]->chd[i]);
        }
        if(nds[v]->p==0 || nds[v]->p==-1){
            nds[v]->sLink = 0;
            nds[v]->mcnt = nds[v]->cnt;
            continue;
        }
    }
}

```

```

}
int b = nds[v]->pch;
int av = nds[nds[v]->p]->sLink;
int nLink = 0;
while(true){
    if(nds[av]->chd[b]!=-1){
        nLink = nds[av]->chd[b];
        break;
    }
    if(av == nds[av]->sLink) break;
    av = nds[av]->sLink;
}
nds[v]->sLink = nLink;
nds[v]->mcnt = max(nds[v]->cnt,nds[nLink]->mcnt);
}
}

```

2.3 Manacher

```

vector<int> manacher(const string &str){
    int n = str.size();
    vector<int> M(n,1);
    int R = 2; int C = 1;
    for(int i=1 ; i<n ; i++){
        int len = 0;
        if(i<R) len = min(manacher[2*C-i],R-i);
        if(i+len==R){
            while(i>len && str[i-len]==str[i+len]){
                C = i;
                len++; R++;
            }
        }
        M[i] = len;
    }
    return M;
}

```

2.4 Suffix_Array

```

struct SuffixArray {
    const int L;
    string s;
    vector<vector<int> > P;
}

```

```

vector<pair<pair<int,int>,int> > M;
vector<int> Suf,rank,LCParr;
// returns the length of the longest common prefix↵
// of s[i...L-1] and s[j...L-1]
int LongestCommonPrefix(int i,int j) {
    int len = 0;
    if(i==j) return (L-i);
    for (int k=P.size()-1 ; k>=0 && i<L && j<L; k--){
        if(P[k][i]==P[k][j]){
            i+=(1<<k); j+=(1<<k);
            len+=(1<<k);
        }
    }
    return len;
}
//Suf[i] denotes the suffix at ith rank
//Rank[i] denotes the rank of the ith suffix
//LCP[i] the longest common prefix of the suffixes↵
// at ith and (i+1)th rank.
SuffixArray(const string &s) : L(s.length()), s(s)↵
, P(1, vector<int>(L, 0)), M(L), rank(L), ↵
LCParr(L-1){
    vector<int> chars(L,0);
    for(int i=0 ; i<L ; i++) chars[i] = int(s[i]);
    sort(chars.begin(), chars.end());
    map<int,int> mymap;
    int ptr=0;
    for(int elem : chars) mymap[elem] = ptr++;

    for(int i=0 ; i<L ; i++) P[0][i] = mymap[int(s[i↵
    ])]];
    for(int skip=1,level=1 ; skip<L ; skip*=2,level↵
    ++){
        P.pb(vector<int>(L, 0));
        for(int i = 0; i < L; i++)
            M[i] = mp(mp(P[level-1][i], (i+skip)<L ? P[↵
            level-1][i+skip] : -1000), i);
        sort(M.begin(),M.end());
        for(int i = 0; i < L; i++)
            P[level][M[i].Y] = (i > 0 && M[i].X == M[i-1].X↵
            ) ? P[level][M[i-1].Y] : i;
    }
    Suf = P.back();
    for(int i=0 ; i<L ; i++) rank[Suf[i]] = i;
    for(int i=0 ; i<(L-1) ; i++) LCParr[i] = ↵
        LongestCommonPrefix(rank[i],rank[i+1]);
}
};

```

2.5 Z algo

```

vector<int> Z_algo(const string &str){
    int n = str.size();
    vector<int> Z(n,0);
    int L=0,R=0;
    for(int i=1 ; i<n ; i++){
        if(i>R){
            L=i; R=i;
            while(R<n && str[R]==str[R-L]) R++;
            R--; Z[i] = (R-L+1);
        }
        else{
            int j = i-L;
            if(Z[j]<(R-i+1)) Z[i] = Z[j];
            else{
                L=i;
                while(R<n && str[R]==str[R-L]) R++;
                R--; Z[i] = (R-L+1);
            }
        }
    }
    return Z;
}

```

2.6 Hashing

```

long p1=2350490027,p2=1628175011;
long p3=2911165193,p4=1040332871;
2350490027,2125898167,1628175011,1749241873,
1593209441,1524872353,1040332871,2911165193,
1387346491,2776808933

```

3 Trees

3.1 Centroid Tree

```

vector<int> graph[3*Max];
int size[3*Max];
bool usable[3*Max];
int centroid_parent[3*Max];

```

```

void calc_size(int i, int pa){
    size[i]=1;
    for(auto itr:graph[i]){
        if(itr!=pa && usable[itr]){
            calc_size(itr,i);
            size[i]+=size[itr];
        }
    }
}

int getCentroid(int i, int len, int pa){
    for(auto itr:graph[i]){
        if(itr!=pa && usable[itr]){
            if(size[itr]>(len/2))
                return getCentroid(itr,len,i);
        }
    }
    return i;
}

void build_centroid(int i, int coun){
    queue<pair<int,int>> q;
    q.push({i,-1});
    while(!q.empty()){
        auto itr=q.front();
        q.pop();
        calc_size(itr.x,-1);
        int centroid=getCentroid(itr.x,size[itr.x],-1);
        centroid_parent[centroid]=itr.y;
        for(auto itr2:graph[centroid]){
            if(usable[itr2]){
                q.push({itr2,centroid});
            }
        }
        usable[centroid]=false;
    }
}

```

3.2 Heavy Light Decomposition

```

int chainNo[Max];
int pos_in_chain[Max];
int parent_in_chain[Max];
int parent[Max];
int chain_count=0;
int total_in_chain[Max];
int pos_count=0;
vector<int> graph[Max];
int arr[Max];
int subtree_count[Max];

```

```

int max_in_subtree[Max];
int height[Max];
vector<vector<pair<int,int>>> vec;
int max_elem,max_count;
void simple_dfs(int i){
    subtree_count[i]=1;
    int max_val=0;
    int ind=-1;
    for(auto itr:graph[i]){
        height[itr]=1+height[i];
        simple_dfs(itr);
        subtree_count[i]+=subtree_count[itr];
        if(max_val<subtree_count[itr]){
            max_val=subtree_count[itr];
            ind=itr;
        }
    }
    max_in_subtree[i]=ind;
}

void dfs(int i){
    if(pos_count==0)
        parent_in_chain[chain_count]=i;
    chainNo[i]=chain_count;
    pos_in_chain[i]=++pos_count;
    total_in_chain[chain_count]++;
    if(max_in_subtree[i]!=-1){
        dfs(max_in_subtree[i]);
    }
    for(auto itr:graph[i]){
        if(itr!=max_in_subtree[i]){
            chain_count++;
            pos_count=0;
            dfs(itr);
        }
    }
}

int pos;int chain;int val;
void update(int s,int e,int n){
    if(pos>e || pos<s)
        return;
    vec[chain][n]={val,1};
    if(s==e)
        return;
    int mid=(s+e)>>1;
    update(s,mid,2*n);
    update(mid+1,e,2*n+1);
    if(vec[chain][2*n].x<vec[chain][2*n+1].x)
        vec[chain][n]=vec[chain][2*n+1];
    else if(vec[chain][2*n].x>vec[chain][2*n+1].x)
        vec[chain][n]=vec[chain][2*n];
    else{
        vec[chain][n]={vec[chain][2*n].x,vec[chain][2*n].x-
            y+vec[chain][2*n+1].y};
    }
}

```

```

}
}
int qs;int qe;
void query_tree(int s,int e,int n){
    if(s>qe || qs>e)
        return;
    if(s>=qs && e<=qe){
        if(vec[chain][n].x>max_elem){
            max_elem=vec[chain][n].x;
            max_count=vec[chain][n].y;
        }
        else if(vec[chain][n].x==max_elem){
            max_count+=vec[chain][n].y;
        }
        return;
    }
    if(vec[chain][n].x < max_elem)
        return;
    int mid=(s+e)>>1;
    query_tree(s,mid,2*n);
    query_tree(mid+1,e,2*n+1);
}
void query(int i){
    if(i==-1)
        return;
    qs=1;qe=pos_in_chain[i];chain=chainNo[i];
    query_tree(1,total_in_chain[chainNo[i]],1);
    i=parent[parent_in_chain[chainNo[i]]];
    query(i);
}

```

3.3 Heavy Light Trick

```

void dfs(int i,int pa){
    int coun=1 ;
    for(auto itr:a[i]){
        if(itr.x!=pa){
            prod[itr.x]=check(prod[i]*itr.y) ;
            dfs(itr.x,i);
            coun+=siz[itr.x] ;
        }
    }
    siz[i]=coun ;
}
long ans=0 ;
void add(int i,int pa,int x){
    coun[mapped_prod[i]]+=x ;
    for(auto itr:a[i])

```

```

        if(itr.x!=pa && !big[itr.x])
            add(itr.x,i,x) ;
    }
    void solve(int i,int pa){
        long temp=check(multi*inv[i]);
        int xx=m[temp];
        ans+=coun[xx];
        for(auto itr:a[i])
            if(itr.x!=pa && !big[itr.x])
                solve(itr.x,i) ;
    }
    void dfs2(int i,int pa,bool keep){
        int mx=-1,bigc=-1;
        for(auto itr:a[i]){
            if(itr.x!=pa){
                if(siz[itr.x]>mx)
                    mx=siz[itr.x],bigc=itr.x;
            }
        }
        for(auto itr:a[i]){
            if(itr.x!=pa && itr.x!=bigc)
                dfs2(itr.x,i,0);
        }
        if(bigc!=-1){
            dfs2(bigc,i,1);
            big[bigc]=true;
        }
        multi=check(p*check(prod[i]*prod[i]));
        long temp=check(p*prod[i]);
        ans+=coun[m[temp]];
        coun[mapped_prod[i]]++;
        for(auto itr:a[i])
            if(itr.x!=pa && !big[itr.x]){
                solve(itr.x,i);
                add(itr.x,i,1);
            }
        if(bigc!=-1)
            big[bigc]=false;
        if(keep==0)
            add(i,pa,-1);
    }
}

```

3.4 LCA

```

int pa[21][3*N], level[3*N];
int lca(int u,int v){
    if(level[u]>level[v])return lca(v,u);

```

```

for(long i=19;i>=0 && level[v]!=level[u];i--){
    if(level[v]>=level[u]+(1<<i))
        v=pa[i][v];
}
if(u==v) return u;
for(long i=19;i>=0;i--){
    if(pa[i][u]!=pa[i][v]){
        u=pa[i][u];v=pa[i][v];
    }
}
return pa[0][u];
}

```

```

        counter[i]++;
        if(!used_edges[itr.y])
        {
            used_edges[itr.y]=true;
            if(itr.y<=tot_edges)
                cout<<i<<" "<<itr.x<<"\n";
            euler_tour(itr.x);
        }
    }
    s.pop();
}

```

4 Graph and Matching, Flows

4.1 Euler Walk

```

vector<pair<int,int> > graph[202];
bool visited[202];
vector<int> odd;
bool used_edges[41000];
stack<int> s;
int tot_edges;
int counter[202];
void dfs(int i)
{
    visited[i]=true;

    int len=graph[i].size();
    if(len&1)
        odd.pb(i);

    for(auto itr:graph[i])
        if(!visited[itr.x])
            dfs(itr.x);
}
void euler_tour(int i)
{
    visited[i]=true;
    s.push(i);

    int x=graph[i].size();
    while(counter[i]<x)
    {
        auto itr=graph[i][counter[i]];

```

4.2 Articulation Point Pseudo

```

ArtPt(v){
    color[v] = gray;
    Low[v] = d[v] = ++time;
    for all w in Adj(v) do {
        if (color[w] == white){
            pred[w] = v;
            ArtPt(w) ;
            if (pred [v] == NULL) {
                if ('w' is v''s second child) output v;
            }
            else if (Low[w] >= d[v]) output v;
            Low[v] = min(Low[v], Low[w]);
        }
        else if (w != pred[v]){
            Low[v] = min(Low[v], d[w]);
        }
    }
    color[v] = black;
}

```

4.3 Ford Fulkerson Matching

```

const int N=250;
const int M=210*26*2;

int n,m;
vector<pair<int,int> > graph[N];
int edge_count=0;

```

```

int visited_from[N];
int edge_entering[N];
int reverse_no[M];
int capacity[M];
int max_flow_dfs[N];

void addEdge(int x,int y,int cap)
{
    ++edge_count;
    capacity[edge_count]=cap;
    graph[x].pb({y,edge_count});
    ++edge_count;
    capacity[edge_count]=0;
    graph[y].pb({x,edge_count});
    reverse_no[edge_count]=edge_count-1;
    reverse_no[edge_count-1]=edge_count;
}

void dfs(int source)
{
    // cout<<source<<endl;
    for(auto itr:graph[source])
    {
        if(visited_from[itr.x]==-1 && capacity[itr.y])
        {
            edge_entering[itr.x]=itr.y;
            visited_from[itr.x]=source;
            max_flow_dfs[itr.x]=min(capacity[itr.y],←
                max_flow_dfs[source]);
            dfs(itr.x);
        }
    }
    // cout<<source<<endl;
}

void reverse_edge(int i,int flow)
{
    while(visited_from[i]!=0)
    {
        capacity[edge_entering[i]]-=flow;
        capacity[reverse_no[edge_entering[i]]]+=flow;
        i=visited_from[i];
    }
}

int ford_faulkerson(int source,int sink,int n)
{
    int ans=0;
    // cout<<n<<endl;
    while(true)
    {
        for(int i=1;i<=n;i++)
            visited_from[i]=-1;

```

```

        visited_from[source]=0;
        max_flow_dfs[source]=1e9;

        dfs(source);
        if(visited_from[sink]==-1)
            break;
        ans+=max_flow_dfs[sink];
        reverse_edge(sink,max_flow_dfs[sink]);
    }
    return ans;
}

```

4.4 Dinic- Maximum Flow $O(EV^2)$

```

struct Edge {
    int a, b, cap, flow;
};

struct MaxFlow {
    int n, s, t;
    vector<int> d, ptr, q;
    vector< Edge > e;
    vector< vector<int> > g;
    int i,j;
    MaxFlow(int n) : n(n), d(n), ptr(n), q(n), g(n)←
    {
        e.clear();
        for(int i=0;i<n;i++) {
            g[i].clear();
            ptr[i] = 0;
        }
    }

    void addEdge(int a, int b, int cap) {
        Edge e1 = { a, b, cap, 0 };
        Edge e2 = { b, a, 0, 0 };
        g[a].push_back( (int) e.size() );
        e.push_back(e1);
        g[b].push_back( (int) e.size() );
        e.push_back(e2);
    }

    int getMaxFlow(int _s, int _t) {
        s = _s; t = _t;
        int flow = 0;
        for (;;) {
            if (!bfs()) break;
            for(int i=0;i<n;i++) ptr[i] = 0;
            while (int pushed = dfs(s, INF))
                flow += pushed;
        }
        return flow;
    }
}

```



```

    }
private:
    bool bfs() {
        int qh = 0, qt = 0;
        q[qt++] = s;
        for(int i=0; i<n; i++) d[i] = -1;
        d[s] = 0;

        while (qh < qt && d[t] == -1) {
            int v = q[qh++];
            int gv_sz = g[v].size();
            for(int i=0; i<gv_sz; i++) {
                int id = g[v][i], to = e[id].b;
                if (d[to] == -1 && e[id].flow < e[id].cap) {
                    q[qt++] = to;
                    d[to] = d[v] + 1;
                }
            }
        }
        return d[t] != -1;
    }

    int dfs (int v, int flow) {
        if (!flow) return 0;
        if (v == t) return flow;
        for (; ptr[v] < (int)g[v].size(); ++ptr[v]) {
            int id = g[v][ptr[v]],
                to = e[id].b;
            if (d[to] != d[v] + 1) continue;
            int pushed = dfs(to, min(flow, e[id].cap - e[id].flow));
            if (pushed) {
                e[id].flow += pushed;
                e[id^1].flow -= pushed;
                return pushed;
            }
        }
        return 0;
    }
};

```

4.5 Minimum Cost Bipartite Matching $O(V^3)$

```

// Min cost bipartite matching via shortest
// augmenting path
// This is an  $O(n^3)$  implementation of a shortest
// augmenting path

```

```

// algorithm for finding min cost perfect matchings
// in dense graphs. In practice, it solves 1000x1000
// problems in around 1 second.
// cost[i][j] = cost for pairing left node i with
// right node j
// Lmate[i] = index of right node that left node i
// pairs with
// Rmate[j] = index of left node that right node j
// pairs with
// The values in cost[i][j] may be positive or
// negative. To perform
// maximization, simply negate the cost[][] matrix.
typedef vector<long> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;
long MinCostMatching(const VVD &cost, VI &Lmate, VI &Rmate) {
    int n = int(cost.size());
    // construct dual feasible solution
    VD u(n); VD v(n);
    for (int i = 0; i < n; i++) {
        u[i] = cost[i][0];
        for (int j = 1; j < n; j++) u[i] = min(u[i], cost[i][j]);
    }
    for (int j = 0; j < n; j++) {
        v[j] = cost[0][j] - u[0];
        for (int i = 1; i < n; i++) v[j] = min(v[j], cost[i][j] - u[i]);
    }
    // construct primal solution satisfying
    // complementary slackness
    Lmate = VI(n, -1);
    Rmate = VI(n, -1);
    int mated = 0;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (Rmate[j] != -1) continue;
            if ((cost[i][j] - u[i] - v[j]) == 0) {
                Lmate[i] = j;
                Rmate[j] = i;
                mated++;
                break;
            }
        }
    }
    VD dist(n); VI dad(n); VI seen(n);
    // repeat until primal solution is feasible
    while (mated < n) { // find an unmatched left
        node
        int s = 0;
        while (Lmate[s] != -1) s++; // initialize
        Dijkstra
        fill(dad.begin(), dad.end(), -1);
    }
}

```

```

fill(seen.begin(), seen.end(), 0);
for (int k = 0; k < n; k++)
    dist[k] = cost[s][k] - u[s] - v[k];
int j = 0;
while (true) { // find closest
    j = -1;
    for (int k = 0; k < n; k++) {
        if (seen[k]) continue;
        if (j == -1 || dist[k] < dist[j]) j = k;
    }
    seen[j] = 1; // termination condition
    if (Rmate[j] == -1) break; // relax ←
        neighbors
    const int i = Rmate[j];
    for (int k = 0; k < n; k++) {
        if (seen[k]) continue;
        const long new_dist = dist[j] + cost[i][k] - u[←
            i] - v[k];
        if (dist[k] > new_dist) {
            dist[k] = new_dist;
            dad[k] = j;
        }
    }
    // update dual variables
    for (int k = 0; k < n; k++) {
        if (k == j || !seen[k]) continue;
        const int i = Rmate[k];
        v[k] += dist[k] - dist[j];
        u[i] -= dist[k] - dist[j];
    }
    u[s] += dist[j]; // augment along path
    while (dad[j] >= 0) {
        const int d = dad[j];
        Rmate[j] = Rmate[d];
        Lmate[Rmate[j]] = j;
        j = d;
    }
    Rmate[j] = s; Lmate[s] = j;
    mated++;
}
long value = 0;
for (int i = 0; i < n; i++)
    value += cost[i][Lmate[i]];
return value;
}
VVD cost;
cost.resize(n+m-1);
VI Lmate, Rmate;
MinCostMatching(cost, Lmate, Rmate)

```

4.6 Minimum Cost Maximum Flow

```

struct Edge {
    int u, v;
    long long cap, cost;
    Edge(int _u, int _v, long long _cap, long long ←
        _cost) {
        u = _u; v = _v; cap = _cap; cost = _cost;
    }
};

struct MinimumCostMaximumFlow {
    int n, s, t;
    long long flow, cost;
    vector<vector<int>> graph;
    vector<Edge> e;
    vector<long long> dist;
    vector<int> parent;
    MinimumCostMaximumFlow(int _n) {
        // 0-based indexing
        n = _n;
        graph.assign(n, vector<int> ());
    }
    void add(int u, int v, long long cap, long long ←
        cost, bool directed = true) {
        graph[u].push_back(e.size());
        e.push_back(Edge(u, v, cap, cost));
        graph[v].push_back(e.size());
        e.push_back(Edge(v, u, 0, -cost));
        if (!directed)
            add(v, u, cap, cost, true);
    }
    pair<long long, long long> getMinCostFlow(int ←
        _s, int _t) {
        s = _s; t = _t;
        flow = 0, cost = 0;
        while (SPFA()) {
            flow += sendFlow(t, 1LL<<62);
        }
        return make_pair(flow, cost);
    }
    bool SPFA() {
        parent.assign(n, -1);
        dist.assign(n, 1LL<<62);
        dist[s] = 0;
        vector<int> queuetime(n, 0);
        queuetime[s] ←
            = 1;
        vector<bool> inqueue(n, 0);
        inqueue[s] ←
            = true;
        queue<int> q;
        q.push(s);
        bool negativecycle = false;
        while (!q.empty() && !negativecycle) {

```

```

int u = q.front(); q.pop(); inqueue[u] ←
= false;
for(int i = 0; i < graph[u].size(); i←
++){
    int eIdx = graph[u][i];
    int v = e[eIdx].v, w = e[eIdx].cost←
    , cap = e[eIdx].cap;
    if(dist[u] + w < dist[v] && cap > ←
    0){
        dist[v] = dist[u] + w;
        parent[v] = eIdx;
        if(!inqueue[v]){
            q.push(v);
            queueTime[v]++;
            inqueue[v] = true;
            if(queueTime[v] == n+2){
                negativecycle = true;
                break;
            }
        }
    }
}
return dist[t] != (1LL<<62);
}
long long sendFlow(int v, long long curFlow){
    if(parent[v] == -1)
        return curFlow;
    int eIdx = parent[v];
    int u = e[eIdx].u, w = e[eIdx].cost;
    long long f = sendFlow(u, min(curFlow, e[←
    eIdx].cap));
    cost += f*w;
    e[eIdx].cap -= f;
    e[eIdx^1].cap += f;
    return f;
}
};
int source=2*n+1;
int sink=2*n+2;
MinimumCostMaximumFlow mcmf(id+10);
mcmf.add(source,i,1,k);
cout<<mcmf.getMinCostFlow(source,sink).second<<endl←
;

```

4.7 General Unweighted Maximum Matching (Edmonds' algorithm)

```

// Unweighted general matching.
// Vertices are numbered from 1 to V.
// G is an adjlist.
// G[x][0] contains the number of neighbours of x.
// The neighbours are then stored in G[x][1] .. G[x]←
][G[x][0]].
// Mate[x] will contain the matching node for x.
// V and E are the number of edges and vertices.
// Slow Version (2x on random graphs) of Gabow's ←
implementation
// of Edmonds' algorithm (O(V^3)).
const int MAXV = 250;
int G[MAXV][MAXV];
int VLabel[MAXV];
int Queue[MAXV];
int Mate[MAXV];
int Save[MAXV];
int Used[MAXV];
int Up, Down;
int V;

void ReMatch(int x, int y)
{
    int m = Mate[x]; Mate[x] = y;
    if (Mate[m] == x)
    {
        if (VLabel[x] <= V)
        {
            Mate[m] = VLabel[x];
            ReMatch(VLabel[x], m);
        }
        else
        {
            int a = 1 + (VLabel[x] - V - 1) / V;
            int b = 1 + (VLabel[x] - V - 1) % V;
            ReMatch(a, b); ReMatch(b, a);
        }
    }
}

void Traverse(int x)
{
    for (int i = 1; i <= V; i++) Save[i] = Mate[i];
    ReMatch(x, x);
    for (int i = 1; i <= V; i++)
    {
        if (Mate[i] != Save[i]) Used[i]++;
        Mate[i] = Save[i];
    }
}

void ReLabel(int x, int y)

```

```

{
    for (int i = 1; i <= V; i++) Used[i] = 0;
    Traverse(x); Traverse(y);
    for (int i = 1; i <= V; i++)
    {
        if (Used[i] == 1 && VLabel[i] < 0)
        {
            VLabel[i] = V + x + (y - 1) * V;
            Queue[Up++] = i;
        }
    }
}

// Call this after constructing G
void Solve()
{
    for (int i = 1; i <= V; i++)
        if (Mate[i] == 0)
        {
            for (int j = 1; j <= V; j++) VLabel[j] = ←
                -1;
            VLabel[i] = 0; Down = 1; Up = 1; Queue[Up←
                ++] = i;
            while (Down != Up)
            {
                int x = Queue[Down++];
                for (int p = 1; p <= G[x][0]; p++)
                {
                    int y = G[x][p];
                    if (Mate[y] == 0 && i != y)
                    {
                        Mate[y] = x; ReMatch(x, y);
                        Down = Up; break;
                    }
                }
                if (VLabel[y] >= 0)
                {
                    ReLabel(x, y);
                    continue;
                }
                if (VLabel[Mate[y]] < 0)
                {
                    VLabel[Mate[y]] = x;
                    Queue[Up++] = Mate[y];
                }
            }
        }
    }

    // Call this after Solve(). Returns number of edges←
    // in matching (half the number of matched ←
    // vertices)
    int get_match()

```

```

{
    int Count = 0;
    for (int i = 1; i <= V; i++)
        if (Mate[i] > i) Count++;
    return Count;
}

```

4.8 König's Theorem (Text)

In any bipartite graph, the number of edges in a maximum matching equals the number of vertices in a minimum vertex cover. To exhibit the vertex cover:

1. Find a maximum matching
2. Change each edge **used** in the matching into a directed edge from **right to left**
3. Change each edge **not used** in the matching into a directed edge from **left to right**
4. Compute the set T of all vertices reachable from unmatched vertices on the left (including themselves)
5. The vertex cover consists of all vertices on the right that are **in** T , and all vertices on the left that are **not in** T

4.9 Minimum Edge Cover (Text)

If a minimum edge cover contains C edges, and a maximum matching contains M edges, then $C + M = |V|$. To obtain the edge cover, start with a maximum matching, and then, for every vertex not matched, just select some edge incident upon it and add it to the edge set.

5 Data Structures

5.1 BIT- Range Update + Range Sum

```
// BIT with range updates, inspired by Petr ←
// Mitrichev
struct BIT {
    int n;
    vector<int> slope;
    vector<int> intercept;
    // BIT can be thought of as having entries f←
    // [1], ..., f[n]
    // which are 0-initialized
    BIT(int n): n(n), slope(n+1), intercept(n+1) {}
    // returns f[1] + ... + f[idx-1]
    // precondition idx ≤ n+1
    int query(int idx) {
        int m = 0, b = 0;
        for (int i = idx-1; i > 0; i -= i&-i) {
            m += slope[i];
            b += intercept[i];
        }
        return m*idx + b;
    }
    // adds amt to f[i] for i in [idx1, idx2)
    // precondition 1 ≤ idx1 ≤ idx2 ≤ n+1 (you ←
    // can't update element 0)
    void update(int idx1, int idx2, int amt) {
        for (int i = idx1; i ≤ n; i += i&-i) {
            slope[i] += amt;
            intercept[i] -= idx1*amt;
        }
        for (int i = idx2; i ≤ n; i += i&-i) {
            slope[i] -= amt;
            intercept[i] += idx2*amt;
        }
    }
};

update(ft, p, v):
    for (; p ≤ N; p += p&(-p))
        ft[p] += v

# Add v to A[a...b]
update(a, b, v):
    update(B1, a, v)
    update(B1, b + 1, -v)
    update(B2, a, v * (a-1))
    update(B2, b + 1, -v * b)
```

```
query(ft, b):
    sum = 0
    for(; b > 0; b -= b&(-b))
        sum += ft[b]
    return sum

# Return sum A[1...b]
query(b):
    return query(B1, b) * b - query(B2, b)

# Return sum A[a...b]
query(a, b):
    return query(b) - query(a-1)
```

5.2 BIT- 2D

```
void update(int x, int y, int val){
    while (x ≤ max_x){
        updatey(x, y, val);
        // this function should update array tree[x←
        ]
        x += (x & -x);
    }
}

void updatey(int x, int y, int val){
    while (y ≤ max_y){
        tree[x][y] += val;
        y += (y & -y);
    }
}

void update(int x, int y, int val){
    int y1;
    while (x ≤ max_x){
        y1 = y;
        while (y1 ≤ max_y){
            tree[x][y1] += val;
            y1 += (y1 & -y1);
        }
        x += (x & -x);
    }
}

int getSum(int BIT[][N+1], int x, int y)
{
    int sum = 0;
    for(; x > 0; x -= x&-x)
    {
        // This loop sum through all the 1D BIT
```

```

    // inside the array of 1D BIT = BIT[x]
    for(; y > 0; y -= y&-y)
    {
        sum += BIT[x][y];
    }
    return sum;
}

```

5.3 Ordered Statistics

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

template <typename T> using ordered_set = tree<T, ←
    null_type, less<T>, rb_tree_tag, ←
    tree_order_statistics_node_update>;

// typedef
// tree<
//     pair<int,int>,
//     null_type,
//     less<pair<int,int>>,
//     rb_tree_tag,
//     tree_order_statistics_node_update>
// ordered_set;

ordered_set t;
int x,y;
for(int i=0;i<n;i++)
{
    cin>>x>>y;
    ans[t.order_of_key({x,++sz})]++;
    t.insert({x,sz});
}

// If we want to get map but not the set, as the ←
// second argument type must be used mapped type. ←
// Apparently, the tree supports the same ←
// operations as the set (at least I haven't any ←
// problems with them before), but also there are ←
// two new features it is find_by_order() and ←
// order_of_key(). The first returns an iterator to ←
// the k-th largest element (counting from zero), ←
// the second the number of items in a set that ←
// are strictly smaller than our item. Example of ←
// use:
//     ordered_set X;
//     X.insert(1);

```

```

//     X.insert(2);
//     X.insert(4);
//     X.insert(8);
//     X.insert(16);
//     cout<<*X.find_by_order(1)<<endl; // 2
//     cout<<*X.find_by_order(2)<<endl; // 4
//     cout<<*X.find_by_order(4)<<endl; // 16
//     cout<<(end(X)==X.find_by_order(6))<<endl; //←
// true
//     cout<<X.order_of_key(-5)<<endl; // 0
//     cout<<X.order_of_key(1)<<endl; // 0
//     cout<<X.order_of_key(3)<<endl; // 2
//     cout<<X.order_of_key(4)<<endl; // 2
//     cout<<X.order_of_key(400)<<endl; // 5

```

5.4 Persistent Tree

```

struct node{
    int coun;
    node *l,*r ;
    node(int coun,node *l,node *r):
        coun(coun),l(l),r(r){}
    node *inser(int l,int r,int pos) ;
};

node* node::inser(int l,int r,int pos){
    if(l<=pos && pos<=r){
        if(l==r){
            return new node(this->coun+1,NULL,NULL);
        }
        int mid=(l+r)>>1;
        return new node(this->coun+1,this->l->inser(l,mid←
            ,pos),this->r->inser(mid+1,r,pos));
    }
    return this;
}

int query(node *lef,node *rig,int cc,int s,int e){
    if(s==e)
        return s;
    int co=rig->l->coun-lef->l->coun;
    int mid=(s+e)>>1;
    if(co>=cc)
        return query(lef->l,rig->l,cc,s,mid);
    return query(lef->r,rig->r,cc-co,mid+1,e);
}

node *null=new node(0,NULL,NULL);
node *root[100100];
null->l=null->r=null;
root[0]=null;

```

```

for(int i=1;i<=n;i++)
    root[i]=root[i-1]->inser(0,maxy,m[arr[i]]);
while(mmm-->0){
    int i,j,k;cin>>i>>j>>k;
    cout<<mm[query(root[i-1],root[j],k,0,maxy)]<<"\n";
}

```

6 Math

6.1 Convex Hull

```

struct point{
    int x, y;
    point(int _x = 0, int _y = 0){
        x = _x, y = _y;
    }
    friend bool operator < (point a, point b){
        return (a.x == b.x) ? (a.y < b.y) : (a.x < b.x);
    }
};
point pt[2*Max], hull[2*Max];
//Here idx is the new length of the hull
int idx=0,cur;
inline long area(point a, point b, point c){
    return (b.x - a.x) * 1LL * (c.y - a.y) - (b.y - a.y) * 1LL * (c.x - a.x);
}
inline long dist(point a, point b){
    return (a.x - b.x) * 1LL * (a.x - b.x) + (a.y - b.y) * 1LL * (a.y - b.y);
}
inline bool is_right(point a, point b){
    int dx = (b.x - a.x);
    int dy = (b.y - a.y);
    return (dx > 0) || (dx == 0 && dy > 0);
}
inline bool compare(point b, point c){
    long det = area(pt[1], b, c);
    if(det == 0){
        if(is_right(pt[1], b) != is_right(pt[1], c))
            return is_right(pt[1], b);
        return (dist(pt[1], b) < dist(pt[1], c));
    }
    return (det > 0);
}
void convexHull(){

```

```

int min_x = pt[1].x, min_y = pt[1].y, min_idx = 1;
for(int i = 2; i <= cur; i++){
    if(pt[i].y < min_y || (pt[i].y == min_y && pt[i].x < min_x)){
        min_x = pt[i].x;
        min_y = pt[i].y;
        min_idx = i;
    }
}
swap(pt[1], pt[min_idx]);
sort(pt + 2, pt + 1 + cur, compare);
idx = 2;
hull[1] = pt[1], hull[2] = pt[2];
for(int i = 3; i <= cur; i++){
    while(idx >= 2 && (area(hull[idx - 1], hull[idx], pt[i]) <= 0)) idx--;
    hull[++idx] = pt[i];
}
}

```

6.2 FFT

```

const long mod = 5 * (1 << 25) + 1;
long root = 243;
long root_1 = 114609789;
const long root_pw = 1 << 25;

inline void fft (vector < long > & a, bool invert) {
    {
        int n = (int) a.size();
        for (int i = 1, j = 0; i < n; i++) {
            int bit = n >> 1;
            for (; j >= bit; bit >= 1) {
                j -= bit;
            }
            j += bit;
            if (i < j) {
                swap(a[i], a[j]);
            }
        }
        for (int len = 2; len <= n; len <= 1) {
            long wlen = invert ? root_1 : root;
            for (long i = len; i < root_pw; i <= 1)
                wlen = (long) (wlen * 1LL * wlen % mod);
            for (int i = 0; i < n; i += len) {
                long w = 1;
                for (int j = 0; j < len / 2; j++) {
                    long u = a[i + j];

```

```

        long v = (long) (a[i + j + len / 2] ←
            * 1ll * w % mod);
        a[i + j] = u + v < mod ? u + v : u ←
            + v - mod;
        a[i + j + len / 2] = u - v >= 0 ? u ←
            - v : u - v + mod;
        w = (long) (w * 1ll * wlen % mod);
    }
}
if (invert) {
    long nrev = exp(n, mod-2);
    for (int i = 0; i < n; i++)
        a[i] = (long) (a[i] * 1ll * nrev % mod);
}
}

```

6.3 FFT_Complex

```

// Instructions for using this: Nothing it is very ←
// obvious to use

typedef complex<long double> Cld;
class FFT{
public:
    static const ld PI;
    static void cfft (vector<Cld> &L,int invert) {
        int n = (int) L.size();
        for(int i=1,j=0 ; i<n ; i++){
            int bit = n>>1 ;
            for( ; j>=bit ; bit>>=1) j-=bit ;
            j+=bit ;
            if(i<j) swap(L[i],L[j]);
        }
        for(int len=2 ; len<=n ; len<=1){
            int l2 = (len/2);
            ld theta = (PI/l2);
            Cld wlen = polar(1.0L,(invert ? -1 : 1)*theta);
            for(int i=0 ; i<n ; i+=len){
                Cld w(1.0,0.0);
                for(int j=0 ; j<l2 ; j++, w=(w*wlen)){
                    Cld u = L[i+j]; Cld v = w*L[i+j+l2];
                    L[i+j] = (u+v); L[i+j+l2] = (u-v);
                }
            }
        }
        if(invert)
            for(int i=0 ; i<n ; i++) L[i] = L[i]/((ld) n);
    }
}

```

```

    }
};
const ld FFT::PI = acos(-1.0);

```

6.4 Find Primitive Root

```

vector < lli > factorize(lli x) {
    // Returns prime factors of x
    vector < lli > primes;
    for (lli i = 2; i * i <= x; i++) {
        if (x % i == 0) {
            primes.push_back(i);
            while (x % i == 0) {
                x /= i;
            }
        }
    }
    if (x != 1) {
        primes.push_back(x);
    }
    return primes;
}

inline bool test_primitive_root(lli a, lli m) {
    // Is 'a' a primitive root of modulus 'm'?
    // m must be of the form 2^k * x + 1
    lli exp = m - 1;
    lli val = power(a, exp, m);
    if (val != 1) {
        return false;
    }
    vector < lli > factors = factorize(exp);
    for (lli f: factors) {
        lli cur = exp / f;
        val = power(a, cur, m);
        if (val == 1) {
            return false;
        }
    }
    return true;
}

inline lli find_primitive_root(lli m) {
    // Find primitive root of the modulus 'm'.
    // m must be of the form 2^k * x + 1
    for (lli i = 2; ; i++) {
        if (test_primitive_root(i, m)) {
            return i;
        }
    }
}

```



```

    }
}
}

```

6.5 Convex Hull Trick

```

mylist hull(mylist pts){
    int n = pts.size();
    if(n<2) return pts;
    Collections.sort(pts,new Comparator<pair>(){
        public int compare(pair p1,pair p2){
            if(p1.x!=p2.x) return Double.compare(p1.x,p2.x) ←
            ;
            return Double.compare(p2.y,p1.y);
        }
    });
    mylist h = new mylist();
    h.add(pts.get(0)); h.add(pts.get(1));
    int idx=1;
    for(int i=2; i<n; i++){
        pair p = pts.get(i);
        while(idx>0){
            if(isOriented(h.get(idx-1),h.get(idx),p))
                break;
            else
                h.remove(idx--);
        }
        h.add(p);
        idx++;
    }
    while(idx>0 && h.get(idx).x==h.get(idx-1).x) h.←
        remove(idx--);
    Collections.reverse(h);
    return h;
}

public boolean isOriented(pair p1,pair p2,pair p3){
    double val = ((p2.y-p1.y)*(p3.x-p2.x))-((p2.x-p1.x←
        )*(p3.y-p2.y));
    return val>=0;
}

```

6.6 Miscellaneous Geometry

```

const ld EPS = 1e-12;
struct PT{
    ld x,y,z;
    PT(ld x=0,ld y=0,ld z=0): x(x),y(y),z(z){}
    bool operator<(const PT &t){ return make_tuple(x,y,←
        z)<make_tuple(t.x,t.y,t.z); }
    bool operator==(const PT &t){ return make_tuple(x,←
        y,z)==make_tuple(t.x,t.y,t.z); }
    PT operator+(const PT &t){ return PT(x+t.x,y+t.y,z←
        +t.z); }
    PT operator-(const PT &t){ return PT(x-t.x,y-t.y,z←
        -t.z); }
    PT operator*(const ld &d){ return PT(x*d,y*d,z*d);←
        }
    PT operator/(const ld &d){ return PT(x/d,y/d,z/d);←
        }
    ld norm2(){ return (x*x + y*y + z*z); }
    ld norm(){ return sqrt1(norm2()); }
};
PT cross(const PT &p,const PT &q){
    return PT(p.y*q.z - p.z*q.y, p.z*q.x - p.x*q.z, p.←
        x*q.y - p.y*q.x);
}
ld dot(const PT &p, const PT &q){
    return (p.x*q.x + p.y*q.y + p.z*q.z);
}
// rotate a point CCW or CW around the origin
PT RotateCCW90(PT p){ return PT(-p.y,p.x); }
PT RotateCW90(PT p){ return PT(p.y,-p.x); }
PT RotateCCW(PT p, double t) {
    return PT(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*←
        cos(t));
}
// project point c onto line segment through a and ←
// b
// if the projection doesn't lie on the segment, ←
// returns closest vertex
PT ProjectPointSegment(PT a, PT b, PT c) {
    double r = dot(b-a,b-a);
    if(fabs(r)<EPS) return a;
    r = dot(c-a,b-a)/r;
    if(r<0) return a;
    if(r>1) return b;
    return a+(b-a)*r;
}
// project point c onto line through a and b
// assuming a != b
PT ProjectPointLine(PT a, PT b, PT c) {
    return a + (b-a)*dot(c-a,b-a)/dot(b-a, b-a);
}
// determine if lines from a to b and c to d are ←
// parallel or collinear

```

```

bool LinesParallel(PT a, PT b, PT c, PT d) {
    return fabs(cross(b-a, c-d)) < EPS;
}
bool LinesCollinear(PT a, PT b, PT c, PT d) {
    return LinesParallel(a, b, c, d)
    && fabs(cross(a-b, a-c)) < EPS
    && fabs(cross(c-d, c-a)) < EPS;
}
// determine if line segment from a to b intersects
// with
// line segment from c to d
bool SegmentsIntersect(PT a, PT b, PT c, PT d) {
    if (LinesCollinear(a, b, c, d)) {
        if (dist2(a, c) < EPS || dist2(a, d) < EPS ||
            dist2(b, c) < EPS || dist2(b, d) < EPS)
            return true;
        if (dot(c-a, c-b) > 0 && dot(d-a, d-b) > 0 && dot(c-b, d-b) > 0)
            return false;
        return true;
    }
    if (cross(d-a, b-a) * cross(c-a, b-a) > 0) return false;
    if (cross(a-c, d-c) * cross(b-c, d-c) > 0) return false;
    return true;
}
PT ComputeLineIntersection(PT a, PT b, PT c, PT d) {
    b=b-a; d=c-d; c=c-a;
    assert(b.norm() > EPS && d.norm() > EPS);
    return (a + b*cross(c, d)/cross(b, d));
}
// determine if c and d are on same side of line
// passing through a and b
bool OnSameSide(PT a, PT b, PT c, PT d) {
    return (cross(c-a, c-b)*cross(d-a, d-b))>0;
}
PT ComputeCircleCenter(PT a, PT b, PT c) {
    b=(a+b)/2;
    c=(a+c)/2;
    return ComputeLineIntersection(b, b+RotateCW90(a-b), c, c+RotateCW90(a-c));
}
vector<PT> CircleCircleIntersection(PT a, PT b, ld r, ld R) {
    vector<PT> ret;
    ld d = (a-b).norm();
    if (d>(r+R) || d+min(r,R) < max(r,R)) return ret;
    ld x = (d*d-R*R+r*r)/(2*d);
    ld y = sqrtl(r*r-x*x);
    PT v = (b-a)/d;
    ret.push_back(a+v*x + RotateCCW90(v)*y);
    if(y>0) ret.push_back(a+v*x - RotateCCW90(v)*y);
    return ret;
}
ld ComputeSignedArea(const vector<PT> &p) {
    ld area = 0;
    int n = p.size();
    for(int i=0 ; i<n ; i++)
        area += cross(p[i],p[(i+1)%n]);
    return area/2.0;
}
ld ComputeArea(const vector<PT> &p) {
    return fabs(ComputeSignedArea(p));
}
bool IsSimple(const vector<PT> &p) {
    for (int i = 0; i < p.size(); i++) {
        for (int k = i+1; k < p.size(); k++) {
            int j = (i+1) % p.size(); int l = (k+1) % p.size();
            if (i == l || j == k) continue;
            if (SegmentsIntersect(p[i], p[j], p[k], p[l]))
                return false;
        }
    }
    return true;
}
// determine if point is in a possibly non-convex
// polygon (by William
// Randolph Franklin); returns 1 for strictly
// interior points, 0 for
// strictly exterior points, and 0 or 1 for the
// remaining points.
// Note that it is possible to convert this into an
// *exact* test using
// integer arithmetic by taking care of the
// division appropriately
// (making sure to deal with signs properly) and
// then by writing exact
// tests for checking point on polygon boundary
bool PointInPolygon(const vector<PT> &p, PT q) {
    bool c = false;
    for (int i = 0; i < p.size(); i++){
        int j = (i+1)%p.size();
        bool test1 = (p[i].y <= q.y && q.y < p[j].y || p[j].y <= q.y && q.y < p[i].y);
        bool test2 = q.x < (p[i].x + (p[j].x - p[i].x)*((q.y - p[i].y)/(p[j].y - p[i].y)));
        if(test1 && test2) c = !c;
    }
    return c;
}
// determine if point is on the boundary of a
// polygon
bool PointOnPolygon(const vector<PT> &p, PT q) {
    for (int i = 0; i < p.size(); i++)

```

```

    if (dist2(ProjectPointSegment(p[i], p[(i+1)%p.size()], q), q) < EPS)
        return true;
    return false;
}
struct Line{
    ld a,b,c;
    Line(ld a=0,ld b=0,ld c=0): a(a),b(b),c(c){}
};
pdd LineIntersection(const Line &l1,const Line &l2){
    {
        ld a1 = l1.a; ld b1 = l1.b; ld c1 = l1.c;
        ld a2 = l2.a; ld b2 = l2.b; ld c2 = l2.c;
        ld det = (a1*b2 - a2*b1);
        assert(abs(det)>eps);
        ld x = (b1*c2 - b2*c1)/det;
        ld y = (c1*a2 - c2*a1)/det;
        return mp(x,y);
    }
}

```

6.7 Gaussian elimination for square matrices of full rank; finds inverses and determinants

```

// Gauss-Jordan elimination with full pivoting.
// Uses:
// (1) solving systems of linear equations (AX=B)
// (2) inverting matrices (AX=I)
// (3) computing determinants of square matrices
//
// Running time: O(n^3)
//
// INPUT:      a[][] = an nxn matrix
//             b[][] = an nxm matrix
//             A MUST BE INVERTIBLE!
//
// OUTPUT:     X      = an nxm matrix (stored in b[])
//             A^{-1} = an nxn matrix (stored in a[])
//             returns determinant of a[][]
const double EPS = 1e-10;
typedef vector<int> VI;
typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;

```

```

T GaussJordan(VVT &a, VVT &b) {
    const int n = a.size();
    const int m = b[0].size();
    VI irow(n), icol(n), ipiv(n);
    T det = 1;

    for (int i = 0; i < n; i++) {
        int pj = -1, pk = -1;
        for (int j = 0; j < n; j++) if (!ipiv[j])
            for (int k = 0; k < n; k++) if (!ipiv[k])
                if (pj == -1 || fabs(a[j][k]) > fabs(a[pj][pk])) {
                    pj = j; pk = k;
                }
        if (fabs(a[pj][pk]) < EPS) { return 0; }
        ipiv[pj]++;
        swap(a[pj], a[pk]);
        swap(b[pj], b[pk]);
        if (pj != pk) det *= -1;
        irow[i] = pj;
        icol[i] = pk;

        T c = 1.0 / a[pk][pk];
        det *= a[pk][pk];
        a[pk][pk] = 1.0;
        for (int p = 0; p < n; p++) a[pk][p] *= c;
        for (int p = 0; p < m; p++) b[pk][p] *= c;
        for (int p = 0; p < n; p++) if (p != pk) {
            c = a[p][pk];
            a[p][pk] = 0;
            for (int q = 0; q < n; q++) a[p][q] -= a[pk][q] * c;
            for (int q = 0; q < m; q++) b[p][q] -= b[pk][q] * c;
        }
    }

    for (int p = n-1; p >= 0; p--) if (irow[p] != icol[p]) {
        for (int k = 0; k < n; k++) swap(a[k][irow[p]], a[k][icol[p]]);
    }

    return det;
}

```

7 Number Theory Reference

7.1 Modular arithmetic and linear Diophantine solver

```
// This is a collection of useful code for solving ←
// problems that
// involve modular linear equations. Note that all ←
// of the
// algorithms described here work on nonnegative ←
// integers.

typedef vector<int> VI;
typedef pair<int,int> PII;

// return a % b (positive value)
int mod(int a, int b) {
    return ((a%b)+b)%b;
}

// computes gcd(a,b)
int gcd(int a, int b) {
    int tmp;
    while(b){a%=b; tmp=a; a=b; b=tmp;}
    return a;
}

// computes lcm(a,b)
int lcm(int a, int b) {
    return a/gcd(a,b)*b;
}

// returns d = gcd(a,b); finds x,y such that d = ax ←
// + by
int extended_euclid(int a, int b, int &x, int &y) {
    int xx = y = 0;
    int yy = x = 1;
    while (b) {
        int q = a/b;
        int t = b; b = a%b; a = t;
        t = xx; xx = x-q*xx; x = t;
        t = yy; yy = y-q*yy; y = t;
    }
    return a;
}

// finds all solutions to ax = b (mod n)
VI modular_linear_equation_solver(int a, int b, int ←
n) {
    int x, y;
```

```
VI solutions;
int d = extended_euclid(a, n, x, y);
if (!(b%d)) {
    x = mod (x*(b/d), n);
    for (int i = 0; i < d; i++)
        solutions.push_back(mod(x + i*(n/d), n));
}
return solutions;
}

// computes b such that ab = 1 (mod n), returns -1 ←
// on failure
int mod_inverse(int a, int n) {
    int x, y;
    int d = extended_euclid(a, n, x, y);
    if (d > 1) return -1;
    return mod(x,n);
}

// Chinese remainder theorem (special case): find z ←
// such that
// z % x = a, z % y = b. Here, z is unique modulo ←
// M = lcm(x,y).
// Return (z,M). On failure, M = -1.
PII chinese_remainder_theorem(int x, int a, int y, ←
int b) {
    int s, t;
    int d = extended_euclid(x, y, s, t);
    if (a%d != b%d) return make_pair(0, -1);
    return make_pair(mod(s*b*x+t*a*y,x*y)/d, x*y/d);
}

// Chinese remainder theorem: find z such that
// z % x[i] = a[i] for all i. Note that the ←
// solution is
// unique modulo M = lcm_i (x[i]). Return (z,M). ←
// On
// failure, M = -1. Note that we do not require ←
// the a[i]'s
// to be relatively prime.
PII chinese_remainder_theorem(const VI &x, const VI ←
&a) {
    PII ret = make_pair(a[0], x[0]);
    for (int i = 1; i < x.size(); i++) {
        ret = chinese_remainder_theorem(ret.first, ret. ←
second, x[i], a[i]);
        if (ret.second == -1) break;
    }
    return ret;
}

// computes x and y such that ax + by = c; on ←
// failure, x = y = -1
```

```

void linear_diophantine(int a, int b, int c, int &x,
    int &y) {
    int d = gcd(a,b);
    if (c%d) {
        x = y = -1;
    } else {
        x = c/d * mod_inverse(a/d, b/d);
        y = (c-a*x)/b;
    }
}

```

7.2 Polynomial Coefficients (Text)

$$(x_1 + x_2 + \dots + x_k)^n = \sum_{c_1+c_2+\dots+c_k=n} \frac{n!}{c_1!c_2!\dots c_k!} x_1^{c_1} x_2^{c_2} \dots x_k^{c_k}$$

7.3 Möbius Function (Text)

$$\mu(n) = \begin{cases} 0 & n \text{ not squarefree} \\ 1 & n \text{ squarefree w/ even no. of prime factors} \\ -1 & n \text{ squarefree w/ odd no. of prime factors} \end{cases}$$

Note that

$$\mu(a)\mu(b) = \mu(ab) \text{ for } a, b \text{ relatively prime}$$

Also $\sum_{d|n} \mu(d) = \begin{cases} 1 & \text{if } n = 1 \\ 0 & \text{otherwise} \end{cases}$

Möbius Inversion If $g(n) = \sum_{d|n} f(d)$ for all $n \geq 1$, then $f(n) = \sum_{d|n} \mu(d)g(n/d)$ for all $n \geq 1$.

7.4 Burnside's Lemma (Text)

The number of orbits of a set X under the group action G equals the average number of elements of X fixed by the elements of G .

Here's an example. Consider a square of $2n$ times $2n$ cells. How many ways are there to color it into X colors, up to rotations and/or reflections? Here, the group has only 8 elements (rotations by 0, 90, 180 and 270 degrees, reflections over two diagonals, over a vertical line and

over a horizontal line). Every coloring stays itself after rotating by 0 degrees, so that rotation has X^{4n^2} fixed points. Rotation by 180 degrees and reflections over a horizontal/vertical line split all cells in pairs that must be of the same color for a coloring to be unaffected by such rotation/reflection, thus there exist X^{2n^2} such colorings for each of them. Rotations by 90 and 270 degrees split cells in groups of four, thus yielding X^{n^2} fixed colorings. Reflections over diagonals split cells into $2n$ groups of 1 (the diagonal itself) and $2n^2 - n$ groups of 2 (all remaining cells), thus yielding $X^{2n^2-n+2n} = X^{2n^2+n}$ unaffected colorings. So, the answer is $(X^{4n^2} + 3X^{2n^2} + 2X^{n^2} + 2X^{2n^2+n})/8$.

8 Miscellaneous

8.1 2-SAT

```

// 2-SAT solver based on Kosaraju's algorithm.
// Variables are 0-based. Positive variables are
// stored in vertices 2n, corresponding negative
// variables in 2n+1
// TODO: This is quite slow (3x-4x slower than
// Gabow's algorithm)
struct TwoSat {
    int n;
    vector<vector<int>> > adj, radj, scc;
    vector<int> sid, vis, val;
    stack<int> stk;
    int scnt;

    // n: number of variables, including negations
    TwoSat(int n): n(n), adj(n), radj(n), sid(n), vis(
        n), val(n, -1) {}

    // adds an implication
    void impl(int x, int y) { adj[x].push_back(y);
        radj[y].push_back(x); }
    // adds a disjunction
    void vee(int x, int y) { impl(x^1, y); impl(y^1, x
        ); }
    // forces variables to be equal
    void eq(int x, int y) { impl(x, y); impl(y, x);
        impl(x^1, y^1); impl(y^1, x^1); }
    // forces variable to be true
    void tru(int x) { impl(x^1, x); }
}

```

```

void dfs1(int x) {
    if (vis[x]++) return;
    for (int i = 0; i < adj[x].size(); i++) {
        dfs1(adj[x][i]);
    }
    stk.push(x);
}

void dfs2(int x) {
    if (!vis[x]) return; vis[x] = 0;
    sid[x] = scnt; scc.back().push_back(x);
    for (int i = 0; i < radj[x].size(); i++) {
        dfs2(radj[x][i]);
    }
}

// returns true if satisfiable, false otherwise
// on completion, val[x] is the assigned value of ↔
// variable x
// note, val[x] = 0 implies val[x^1] = 1
bool two_sat() {
    scnt = 0;
    for (int i = 0; i < n; i++) {
        dfs1(i);
    }
    while (!stk.empty()) {
        int v = stk.top(); stk.pop();
        if (vis[v]) {
            scc.push_back(vector<int>());
            dfs2(v);
            scnt++;
        }
    }
    for (int i = 0; i < n; i += 2) {
        if (sid[i] == sid[i+1]) return false;
    }
    vector<int> must(scnt);
    for (int i = 0; i < scnt; i++) {
        for (int j = 0; j < scc[i].size(); j++) {
            val[scc[i][j]] = must[i];
            must[sid[scc[i][j]^1]] = !must[i];
        }
    }
    return true;
}
};

```