DDL Commands

```
CREATE DATABASE employee;
USE employee;

CREATE TABLE Departments (
   Department_ID INT,
   Department_Name VARCHAR(100)
);

CREATE TABLE Location (
   Location_ID INT,
   Location VARCHAR(30)
);

CREATE TABLE Employees (
   employee_id INT,
   employee_name VARCHAR(50),
   gender ENUM('M', 'F'),
   age INT,
   hire_date DATE,
   designation VARCHAR(100),
   department_id INT,
   location_id INT,
   salary DECIMAL(10,2)
);

SELECT * FROM Departments;
SELECT * FROM Location;
SELECT * FROM Employees;
```

```
ALTER TABLE Employees
ADD email VARCHAR(100);

ALTER TABLE Employees
MODIFY designation VARCHAR(255);

ALTER TABLE Employees
DROP COLUMN age;

ALTER TABLE Employees
RENAME COLUMN hire_date TO date_of_joining;

RENAME TABLE Departments TO Departments_Info;
SELECT * FROM Departments_Info;

RENAME TABLE Location TO Locations;
SELECT * FROM Locations;

INSERT INTO Departments_Info (Department_ID, Department_Name)
VALUES
(101, 'IT'),
(102, 'HR'),
(103, 'Finance'),
(104, 'Management');

INSERT INTO Locations (Location_ID, Location)
VALUES
(1, 'Kochi'),
(2, 'Chennai'),
(3, 'Bengaluru');
```

```
INSERT INTO Employees
(employee_id, employee_name, gender, date_of_joining, designation,
 department_id, location_id, salary, email)
VALUES
(1, 'Arun Kumar', 'M', '2023-01-15', 'Software Engineer', 101, 1, 35000.00, 'arun@gmail.com'),
(2, 'Anjali Nair', 'F', '2022-06-10', 'HR Manager', 102, 2, 45000.00, 'anjali@gmail.com'),
(3, 'Rahul Menon', 'M', '2021-03-20', 'Data Analyst', 101, 1, 40000.00, 'rahul@gmail.com'),
(4, 'Meera Das', 'F', '2024-02-01', 'Accountant', 103, 3, 30000.00, 'meera@gmail.com'),
(5, 'Vishnu Raj', 'M', '2023-09-12', 'Project Manager', 104, 2, 60000.00, 'vishnu@gmail.com');

TRUNCATE TABLE Employees;
DROP TABLE Employees;
DROP DATABASE employee;
```

Constraints

```
DROP DATABASE IF EXISTS employee;
CREATE DATABASE employee;
USE employee;

CREATE TABLE Departments (
   department_id INT PRIMARY KEY,
   department_name VARCHAR(100) NOT NULL UNIQUE
);
SELECT * FROM Departments;

CREATE TABLE Location (
   location_id INT AUTO_INCREMENT PRIMARY KEY,
   location VARCHAR(100) NOT NULL UNIQUE
);
SELECT * FROM Location;
```

```
CREATE TABLE Employees (
    employee_id INT PRIMARY KEY,
    employee_name VARCHAR(100) NOT NULL,
    gender ENUM('M', 'F') NOT NULL,
    age INT NOT NULL CHECK (age >= 18),
    hire_date DATE DEFAULT (CURRENT_DATE),
    designation VARCHAR(100),
    department_id INT,
    location_id INT,
    salary DECIMAL(10,2),
    email VARCHAR(100),
    FOREIGN KEY (department_id)
        REFERENCES Departments(department_id),
    FOREIGN KEY (location_id)
        REFERENCES Location(location_id)
);
SELECT * FROM Employees;

SHOW TABLES;

DESCRIBE Departments;
DESCRIBE Location;
DESCRIBE Employees;
```