

# Audio signal

---

- Representation of sound
- Encodes all info we need to reproduce sound

Houston we have a problem!

---

# Houston we have a problem!

---

Analog



vs

Digital




# Analog signal

---

- Continuous values for time
- Continuous values for amplitude

# Analog signal

---



# Digital signal

---

- Sequence of discrete values
- Data points can only take on a finite number of values

# Analog to digital conversion

---


- Sampling
- Quantization

# Pulse-code modulation




# Sampling

---




# Sampling period

---




# Sampling period

---



# Sampling period

---



## Locating samples

---

$$t_n = n \cdot T$$


Sampling rate

---

$$s_r = \frac{1}{T}$$

# Sampling rate

---



Why sampling rate = 44100hz?

---





## Nyquist frequency

---

$$f_N = \frac{s_r}{2}$$


Nyquist frequency for CD

---

$$f_N = \frac{44100}{2} = 22050$$


# Aliasing

---



# Quantization

---



# Quantization

---

- Resolution = num. of bits

# Quantization

---

- Resolution = num. of bits
- Bit depth

# Quantization

---

- Resolution = num. of bits
- Bit depth
- CD resolution = 16 bits



# Quantization

---

- Resolution = num. of bits
- Bit depth
- CD resolution = 16 bits

$$2^{16} = 65536$$





# Memory for 1' of sound

---

- Sampling rate = 44100 Hz
- Bit depth = 16 bits

## Memory for 1' of sound

---

- Sampling rate = 44100 Hz
- Bit depth = 16 bits

$$(((16 \cdot 44,100)/1,048,576)/8) \cdot 60$$

## Memory for 1' of sound

---

- Sampling rate = 44100 Hz
- Bit depth = 16 bits

$$(((16 \cdot 44,100)/1,048,576)/8) \cdot 60$$

## Memory for 1' of sound

---

- Sampling rate = 44100 Hz
- Bit depth = 16 bits

$$(((16 \cdot 44,100)/1,048,576)/8) \cdot 60$$

## Memory for 1' of sound

---

- Sampling rate = 44100 Hz
- Bit depth = 16 bits

$$(((16 \cdot 44,100)/1,048,576)/8) \cdot 60$$

## Memory for 1' of sound

---

- Sampling rate = 44100 Hz
- Bit depth = 16 bits

$$(((16 \cdot 44,100)/1,048,576)/8) \cdot 60$$

## Memory for 1' of sound

---

- Sampling rate = 44100 Hz
- Bit depth = 16 bits

$$(((16 \cdot 44,100)/1,048,576)/8) \cdot 60$$

## Memory for 1' of sound

---

- Sampling rate = 44100 Hz
- Bit depth = 16 bits

$$(((16 \cdot 44,100)/1,048,576)/8) \cdot 60 = 5.49MB$$




# Dynamic range

---


- Difference between largest/smallest signal a system can record

# Dynamic range

---



resolution



dynamic range

# Signal-to-quantization-noise ratio

---

- Relationship between max signal strength and quantization error
- Correlates with dynamic range

# Signal-to-quantization-noise ratio

---

- Relationship between max signal strength and quantization error
- Correlates with dynamic range

$$SQNR \approx 6.02 \cdot Q$$

# Signal-to-quantization-noise ratio

---

- Relationship between max signal strength and quantization error
- Correlates with dynamic range


$$SQNR(16) \approx 96dB$$

# How do we record sound?

---

# How do we record sound?

---



# How do we record sound?

---



ADC





# How do we record sound?

---



# How do we reproduce sound?

---

# How do we reproduce sound?

---



# How do we reproduce sound?

---



DAC



# How do we reproduce sound?

---



# What's up next?

---

- Overview of audio features