

The intervalx package^{*}

Valentin Dao[†]

Released 2025-11-16

Abstract

The purpose of this package is to extend interval's¹ functionalities by improving the main macro and adding a few new ones. Although the implementation has been modernised through the use of expl3, the approach is very similar to that used by Lars Madsen. As such, most keys will have the same name. Even though intervalx is presented as an extension of interval, new macros for composing inequalities have nevertheless been implemented.

Contents

1	Package options	2
2	Typeset an interval	2
3	Interval product, union, and intersection	4
3.1	Product	4
3.2	Union	5
3.3	Intersection	5
4	Inequalities	6
	Changelog	6

^{*}This file describes v1.0.0

[†]E-mail: vdao.texdev@gmail.com

¹See on CTAN.

License

© 2025 Valentin Dao, published under the L^AT_EX Project Public License (LPPL) 1.3c

Fonts

Mercury Text G4 Roman

© 1996, 2007 Hoefler & Co.

Whitney-Medium

© 1996, 2009 Hoefler & Frere-Jones.

Repository

 See [GitHub repository](#).

1 Package options

Here are the options that can be declared using `\usepackage`:

<code>soft fences</code>	<code>\langle booléen \rangle</code>	<code>(défaut: false)</code>
--------------------------	--------------------------------------	------------------------------

This key replaces open brackets with parentheses.

<code>smart fences</code>	<code>\langle booléen \rangle</code>	<code>(défaut: true)</code>
---------------------------	--------------------------------------	-----------------------------

This key automatically adapts the direction of the brackets to the presence of $+\infty$ and $-\infty$

<code>separator</code>	<code>\langle token \rangle</code>	<code>(défaut: ,)</code>
------------------------	------------------------------------	--------------------------

Controls the character inserted between the interval endpoints.

2 Typeset an interval

`\interval` * $\langle keys \rangle$ $\{ \langle list\ of\ endpoints \rangle \}$

To typeset an interval, simply use the macro in math mode, entering the endpoints in the form of a list:

LaTeXcode	Result
<pre>1 \begin{equation} 2 \interval{a, b} 3 \end{equation}</pre>	$[a, b]$ (1)

open
open right
open left

To change the direction of the brackets, use the option provided here.

LaTeXcode	Result
<pre>1 \begin{gather} 2 \interval[open right]{a, b} \\ 3 \interval[open left]{a, b} \\ 4 \interval[open]{a, b} 5 \end{gather}</pre>	$[a, b[$ (2) $]a, b]$ (3) $]a, b[$ (4)

The direction of the brackets also adapts itself to $-\infty$ and $+\infty$, provided that the corresponding option remains enabled.

LaTeXcode	Result
<pre>1 \begin{equation} 2 \interval{-\infty, +\infty} 3 \end{equation}</pre>	$] -\infty, +\infty[$ (5)

scaled big, Big, bigg, Bigg, auto (défaut: auto)

It is also possible to adjust the brackets/parentheses' size through the scaled key, which has the same usage as in the interval package: auto applies `\left` and `\right`, while the other options use the delimiters `\bigl/\bigr...`

LaTeXcode	Result
<pre> 1 \begin{equation} 2 \interval[scaled]{\frac{1}{2}, 3 \frac{3}{2}} \end{equation}</pre>	$\left[\frac{1}{2}, \frac{3}{2}\right] \quad (6)$

Finally, the starred variant typesets integer intervals by using the `stmaryrd` package.² All the keys described above are compatible with these symbols.

LaTeXcode	Result
<pre> 1 \begin{equation} 2 \interval*[2, 10] 3 \end{equation}</pre>	$\llbracket 2, 10 \rrbracket \quad (7)$

3 Interval product, union, and intersection

`intervalx` also makes it easier to typeset product, union, and intersection relations between intervals.

3.1 Product

`\xinterval` [*keys*] {**-list*}

For the product, the main argument takes the same form as with `\interval`, but the different intervals are delimited by an asterisk.

Mnemonic: The “x” at the beginning of the macro name evokes the product symbol \times , while the asterisk is a way of denoting it in programming.

LaTeXcode	Result
<pre> 1 \begin{equation} 2 \xinterval{2, 10 * 1, 15 * -3, 3 19} \end{equation}</pre>	$[2, 10] \times [1, 15] \times [-3, 19] \quad (8)$

To combine this macro with the keys of `\interval`, the latter must be spec-

²See on CTAN

ified as a list delimited by semicolons (the comma being already used to separate the different keys). Here is an example to clarify this point.

L ^A T _E Xcode	Result
<pre> 1 \begin{equation} 2 \xinterval[open right, scaled; open left, scaled]{2, 10 * 1, 15} 3 \end{equation} </pre>	$[2, 10[\times]1, 15] \quad (9)$

3.2 Union

`\uinterval` [*<keys>*]{*</-list>*}

Similarly, interval union is typeset using the vertical bar as a delimiter.

Mnemonic: The “u” at the beginning of the macro name evokes the union symbol \cup , while the vertical bar is a way in programming to denote the logical *or*.

L ^A T _E Xcode	Result
<pre> 1 \begin{equation} 2 \uinterval{2, 10 1, 15} 3 \end{equation} </pre>	$[2, 10] \cup [1, 15] \quad (10)$

3.3 Intersection

`\ninterval` [*<keys>*]{*<&-list>*}

Again, interval intersection is typeset using the ampersand as a delimiter. The use of keys is also identical to `\xinterval` and `\uinterval`.

Mnemonic: The “n” evokes the intersection symbol \cap , with the ampersand denoting the logical *and* in programming.

L ^A T _E Xcode	Result
<pre> 1 \begin{equation} 2 \ninterval{3, 20 & \pi, e^3} 3 \end{equation} </pre>	$[3, 20] \cap [\pi, e^3] \quad (11)$

4 Inequalities

`\ineq` * [*keys*] { [*list of bounds*] } [*variable*]

The composition of inequalities is quite similar to that of intervals, with a few differences. The keys `open right`, `open left` and `open` are also available to make it easy to write strict or non-strict inequalities. In addition to the bounds, you can also specify the variable, which defaults to x . Finally, the starred variant of the macro uses the alternative symbols from `amssymb` for non-strict inequalities.

LaTeXcode	Result
<pre> 1 \begin{gather} 2 \ineq{a, b} \\ 3 \ineq*[a, b][y] \\ 4 \ineq[open right]{a, b} \\ 5 \ineq[open left]{a, b} \\ 6 \ineq[open]{a, b} 7 \end{gather} </pre>	$a \leq x \leq b \quad (12)$ $a \leqslant y \leqslant b \quad (13)$ $a \leq x < b \quad (14)$ $a < x \leq b \quad (15)$ $a < x < b \quad (16)$

Changelog

1.0.0 (2025-11-16) — Initial version

Index

	B		L
<code>\bigl</code>	3	<code>\left</code>	3
<code>\bigr</code>	3		N
		<code>\ninterval</code>	5
	I		O
<code>\ineq</code>	6	<code>open</code>	3
<code>\interval</code>	2, 4	<code>open_ left</code>	3

open _{right}	3	soft _{fences}	2
R		U	
\right	3	\uinterval	5
S		X	
scaled	3	\usepackage	2
separator	2		
smart _{fences}	2	\xinterval	4,5