

BASIC GRAPHICS FUNCTION

1) INITGRAPH

- Initializes the graphics system.

Declaration

- Void far initgraph(int far *graphdriver)

Remarks

- To start the graphic system, you must first call initgraph.
- Initgraph initializes the graphic system by loading a graphics driver from disk (or validating a registered driver) then putting the system into graphics mode.
- Initgraph also resets all graphics settings (color, palette, current position, viewport, etc) to their defaults then resets graph.

2) GETPIXEL, PUTPIXEL

- Getpixel gets the color of a specified pixel.
- Putpixel places a pixel at a specified point.

Declaration

- Unsigned far getpixel(int x, int y)
- Void far putpixel(int x, int y, int color)

Remarks

- Getpixel gets the color of the pixel located at (x,y);
- Putpixel plots a point in the color defined at (x, y).

Return value

- Getpixel returns the color of the given pixel.
- Putpixel does not return.

3) CLOSE GRAPH

- Shuts down the graphic system.

Declaration

- Void far closegraph(void);

Remarks

- Close graph deallocates all memory allocated by the graphic system.
- It then restores the screen to the mode it was in before you called initgraph.

Return value

- None.

4) ARC, CIRCLE, PIESLICE

- arc draws a circular arc.
- Circle draws a circle
- Pieslice draws and fills a circular pieslice

Declaration

- Void far arc(int x, int y, int stangle, int endangle, int radius);
- Void far circle(int x, int y, int radius);
- Void far pieslice(int x, int y, int stangle, int endangle, int radius); **Remarks**
- Arc draws a circular arc in the current drawing color
- Circle draws a circle in the current drawing color
- Pieslice draws a pieslice in the current drawing color, then fills it using the current fill pattern and fill color.

5) ELLIPSE, FILLELIPSE, SECTOR

- Ellipse draws an elliptical arc.
- Fillellipse draws and fills ellipse.
- Sector draws and fills an elliptical pie slice.

Declaration

- Void far ellipse(int x, int y, int stangle, int endangle, int xradius, int yradius)
- Void far fillellipse(int x, int y, int xradius, int yradius)
- Void farsectoe(int x, int y, int stangle, int endangle, int xradius, int yradius) **Remarks**
- Ellipse draws an elliptical arc in the current drawing color.
- Fillellipse draws an elliptical arc in the current drawing color and than fills it with fill

color and fill pattern.

- Sector draws an elliptical pie slice in the current drawing color and then fills it using the pattern and color defined by setfillstyle or setfillpattern.

6) FLOODFILL

- Flood-fills a bounded region.

Declaration

- Void far floodfill(int x, int y, int border)

Remarks

- Floodfills an enclosed area on bitmap device.
- The area bounded by the color border is flooded with the current fill pattern and fill color.

- (x,y) is a “seed point”

$\frac{3}{4}$ If the seed is within an enclosed area, the inside will be filled.

$\frac{3}{4}$ If the seed is outside the enclosed area, the exterior will be filled.

- Use fillpoly instead of floodfill wherever possible so you can maintain code compatibility with future versions.

- Floodfill doesnot work with the IBM-8514 driver.

Return value

- If an error occurs while flooding a region, graph result returns '1'.

7) GETCOLOR, SETCOLOR

- Getcolor returns the current drawing color.
- Setcolor returns the current drawing color.

Declaration

- Int far getcolor(void);
- Void far setcolor(int color)

Remarks

- Getcolor returns the current drawing color.
- Setcolor sets the current drawing color to color, which can range from 0 to

getmaxcolor.

- To set a drawing color with setcolor , you can pass either the color number or the equivalent color name.

8) LINE,LINEREL,LINETO

- Line draws a line between two specified points.
- Lonerel draws a line relative distance from current position(CP).
- Linrto draws a line from the current position (CP) to(x,y).

Declaration

- Void far lineto(int x, int y)

Remarks

- Line draws a line from (x1, y1) to (x2, y2) using the current color, line style and thickness.

It does not update the current position (CP).

- Linerel draws a line from the CP to a point that is relative distance (dx, dy) from the CP, then advances the CP by (dx, dy).

- Line to draws a line from the CP to (x, y), then moves the CP to (x,y).

Return value

- None

9) RECTANGLE

- Draws a rectangle in graphics mode.

Declaration

- Void far rectangle(int left, int top, int right, int bottom) **Remarks**

- It draws a rectangle in the current line style, thickness and drawing color.
- (left, top) is the upper left corner of the rectangle, and (right, bottom) is its lower right corner.

Return value

- None.