

NOTES:

- 1) REMOVE ALL SLAG & WELD SPATTER.
- 2) ALL HOLES DRILLED AFTER WELDING.
- 3) FINSH: COAT CUMMINS RED PER SPECS #21055 & #60027.


REV	ENF	DESCRIPTION OF REVISION	REV BY	DATE
A	2010-018	CHANGE PER 1710 DRIVE SHAFT. UPDATE PAINT SPEC, ADD WELD SYMBOLS.	S DUBICK	01/25/2010

This document contains confidential and trade secret information, is the property of Cummins Fire Power LLC and is given to the receiver in confidence. The receiver, by receiving and retaining of the document accepts the document in confidence and agrees that, except as authorized in writing by Cummins NPower, it will (1) not use the document or any copy thereof or the confidential or trade secret information therein, (2) not copy the document, (3) not disclose to others either the document or the confidential or trade secret information therein, and (4) upon completion of the need to retain the document, or upon demand, return the document, all copies thereof, and all material copied therefrom. COPYRIGHT Cummins Fire Power LLC

UNLESS OTHERWISE SPECIFIED ALL DIMENSION TOLERANCES ARE

ANGULAR DIMENSIONS ± 1° IMPERIAL UNITS METRIC UNITS

THIRD ANGLE PROJECTION



Fire Power

CUMMINS FIRE POWER LLC
CORPORATE OFFICE
1600 BUEKLE ROAD
WHITE BEAR LAKE, MN
WWW.CUMMINSFIREPOWER.COM

CUSTOM DESIGN
AND UPFIT CENTER
875 LAWRENCE DRIVE
DEPERE, WISCONSIN

FRAME, AURORA PUMP #129
CFP8.3, 1710 UL LISTED

DWG UNITS:
IN/LB/S

DRAWN BY: S DUBICK
PRO-ENGINEER

DATE: 04/21/09

REF DRWG:

SCALE: 0.100
EST WEIGHT: 465.887

SHEET
1 OF 1

DRAWING NO:
12402-14