

MySql Task Adv Python:

```
mysql> show databases
```

```
-> ;
```

```
+-----+
| Database |
+-----+
| giet      |
| information_schema |
| mysql     |
| performance_schema |
| sys       |
+-----+
```

```
5 rows in set (0.00 sec)
```

```
mysql> USE giet;
```

```
Database changed
```

```
mysql> CREATE TABLE students (
```

```
-> roll_no INT PRIMARY KEY,
-> name VARCHAR(50) NOT NULL,
-> address VARCHAR(100) NOT NULL,
-> gender CHAR(1),
-> salary INT,
-> designation VARCHAR(50)
-> );
```

```
ERROR 1050 (42S01): Table 'students' already exists
```

```
mysql> drop table students;
```

```
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> CREATE TABLE student (
```

```
-> roll_no INT PRIMARY KEY,
-> name VARCHAR(50) NOT NULL,
-> address VARCHAR(100) NOT NULL,
-> gender CHAR(1),
-> salary INT,
-> designation VARCHAR(50)
-> );
```

```
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> INSERT INTO students (name, roll_no, address, designation, salary, gender)
```

```
-> -> VALUES
```

```
-> -> ('Ankita', 101, 'Kolkata', 'Manager', 50000, 'Female'),
```

```
-> -> ('Riya', 102, 'Delhi', 'Engineer', 40000, 'Female'),
```

```
-> -> ('Aman', 103, 'Mumbai', 'Developer', 45000, 'Male'),
-> -> ('Rahul', 104, 'Chennai', 'Analyst', 42000, 'Male'),
-> -> ('Sneha', 105, 'Pune', 'HR', 38000, 'Female'),
-> -> ('Karan', 106, 'Bangalore', 'Tester', 36000, 'Male'),
-> -> ('Priya', 107, 'Hyderabad', 'Designer', 39000, 'Female'),
-> -> ('Arjun', 108, 'Jaipur', 'Manager', 52000, 'Male'),
-> -> ('Neha', 109, 'Lucknow', 'Engineer', 41000, 'Female'),
-> -> ('Vikram', 110, 'Kolkata', 'Developer', 46000, 'Male');
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '-> VALUES

```
-> ('Ankita', 101, 'Kolkata', 'Manager', 50000, 'Female'),
-> ' at line 2
```

mysql> INSERT INTO student (roll_no, name, address, gender, salary, designation) VALUES

```
-> (1, 'Rahul', 'Kolkata', 'M', 25000, 'Manager'),
-> (2, 'Priya', 'Delhi', 'F', 20000, 'Developer'),
-> (3, 'Amit', 'Mumbai', 'M', 22000, 'Analyst'),
-> (4, 'Sneha', 'Chennai', 'F', 24000, 'HR'),
-> (5, 'Rohit', 'Pune', 'M', 26000, 'Engineer'),
-> (6, 'Anjali', 'Hyderabad', 'F', 23000, 'Designer'),
-> (7, 'Vikas', 'Bangalore', 'M', 27000, 'Developer'),
-> (8, 'Neha', 'Jaipur', 'F', 21000, 'Tester'),
-> (9, 'Arjun', 'Lucknow', 'M', 28000, 'Manager'),
-> (10, 'Kavita', 'Bhubaneswar', 'F', 22000, 'HR');
```

Query OK, 10 rows affected (0.01 sec)

Records: 10 Duplicates: 0 Warnings: 0

mysql> select *from students;

ERROR 1146 (42S02): Table 'giet.students' doesn't exist

mysql> select * from students

```
-> ;
```

ERROR 1146 (42S02): Table 'giet.students' doesn't exist

mysql> SELECT * FROM student;

```
+-----+-----+-----+-----+-----+-----+
| roll_no | name  | address  | gender | salary | designation |
+-----+-----+-----+-----+-----+-----+
| 1 | Rahul | Kolkata  | M      | 25000 | Manager     |
| 2 | Priya | Delhi    | F      | 20000 | Developer   |
| 3 | Amit  | Mumbai   | M      | 22000 | Analyst     |
| 4 | Sneha | Chennai  | F      | 24000 | HR          |
| 5 | Rohit | Pune     | M      | 26000 | Engineer    |
| 6 | Anjali | Hyderabad | F      | 23000 | Designer    |
| 7 | Vikas | Bangalore | M      | 27000 | Developer   |
| 8 | Neha  | Jaipur   | F      | 21000 | Tester      |
| 9 | Arjun | Lucknow  | M      | 28000 | Manager     |
```

10	Kavita	Bhubaneswar	F	22000	HR
----	--------	-------------	---	-------	----

10 rows in set (0.00 sec)

```
mysql> drop table students;
ERROR 1051 (42S02): Unknown table 'giet.students'
mysql> DROP TABLE giet;
ERROR 1051 (42S02): Unknown table 'giet.giet'
mysql> drop table student
-> ;
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> CREATE TABLE giet (
-> roll INT PRIMARY KEY,
-> name VARCHAR(50) NOT NULL,
-> address VARCHAR(50) NOT NULL,
-> desig VARCHAR(50),
-> salary INT,
-> gender CHAR(1)
-> );
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> INSERT INTO giet VALUES
-> (101, 'aman', 'delhi', 'doctor', 25000, 'M'),
-> (102, 'naman', 'gunupur', 'teacher', 15000, 'M'),
-> (103, 'raman', 'rayagada', 'plumber', 15000, 'M'),
-> (104, 'Navi', 'raipur', 'nurse', 15000, 'F'),
-> (105, 'Pavi', 'raigarh', 'police', 25000, 'F'),
-> (106, 'Ankit', 'china', 'singer', 45000, 'M'),
-> (107, 'Umesh', 'vizag', 'dancer', 45000, 'M'),
-> (108, 'ramesh', 'bihar', 'manager', 25000, 'M'),
-> (109, 'mahesh', 'patna', 'thied', 55000, 'M');
Query OK, 9 rows affected (0.03 sec)
Records: 9 Duplicates: 0 Warnings: 0
```

```
mysql> select * from student;
ERROR 1146 (42S02): Table 'giet.student' doesn't exist
mysql> select * from students;
ERROR 1146 (42S02): Table 'giet.students' doesn't exist
mysql> SELECT * FROM student;
ERROR 1146 (42S02): Table 'giet.student' doesn't exist
mysql> select * from giet;
+-----+-----+-----+-----+-----+-----+
| roll | name  | address | desig  | salary | gender |
```

```

+-----+-----+-----+-----+-----+-----+
| 101 | aman  | delhi  | doctor | 25000 | M    |
| 102 | naman | gunupur | teacher | 15000 | M    |
| 103 | raman | rayagada | plumber | 15000 | M    |
| 104 | Navi  | raipur  | nurse  | 15000 | F    |
| 105 | Pavi  | raigarh | police | 25000 | F    |
| 106 | Ankit | china   | singer | 45000 | M    |
| 107 | Umesh | vizag   | dancer | 45000 | M    |
| 108 | ramesh | bihar  | manager | 25000 | M    |
| 109 | mahesh | patna  | thied  | 55000 | M    |
+-----+-----+-----+-----+-----+-----+

```

9 rows in set (0.00 sec)

```

mysql> INSERT INTO giet (roll, name, address, desig, salary, gender)
-> VALUES (110, 'Rahul', 'kolkata', 'engineer', 30000, 'M');
Query OK, 1 row affected (0.03 sec)

```

```

mysql> select * from giet;

```

```

+-----+-----+-----+-----+-----+-----+
| roll | name  | address | desig  | salary | gender |
+-----+-----+-----+-----+-----+-----+
| 101 | aman  | delhi   | doctor | 25000 | M      |
| 102 | naman | gunupur | teacher | 15000 | M      |
| 103 | raman | rayagada | plumber | 15000 | M      |
| 104 | Navi  | raipur  | nurse  | 15000 | F      |
| 105 | Pavi  | raigarh | police | 25000 | F      |
| 106 | Ankit | china   | singer | 45000 | M      |
| 107 | Umesh | vizag   | dancer | 45000 | M      |
| 108 | ramesh | bihar  | manager | 25000 | M      |
| 109 | mahesh | patna  | thied  | 55000 | M      |
| 110 | Rahul | kolkata | engineer | 30000 | M      |
+-----+-----+-----+-----+-----+-----+

```

10 rows in set (0.00 sec)

```

mysql> SELECT * FROM giet;

```

```

+-----+-----+-----+-----+-----+-----+
| roll | name  | address | desig  | salary | gender |
+-----+-----+-----+-----+-----+-----+
| 101 | aman  | delhi   | doctor | 25000 | M      |
| 102 | naman | gunupur | teacher | 15000 | M      |
| 103 | raman | rayagada | plumber | 15000 | M      |
| 104 | Navi  | raipur  | nurse  | 15000 | F      |
| 105 | Pavi  | raigarh | police | 25000 | F      |
| 106 | Ankit | china   | singer | 45000 | M      |

```

107	Umesh	vizag	dancer	45000	M
108	ramesh	bihar	manager	25000	M
109	mahesh	patna	thied	55000	M
110	Rahul	kolkata	engineer	30000	M

+-----+-----+-----+-----+-----+-----+

10 rows in set (0.00 sec)

mysql> SELECT name FROM giet;

+-----+

name

+-----+

aman

naman

raman

Navi

Pavi

Ankit

Umesh

ramesh

mahesh

Rahul

+-----+

10 rows in set (0.00 sec)

mysql> SELECT name, address FROM giet;

+-----+-----+

name	address
------	---------

+-----+-----+

aman	delhi
------	-------

naman	gunupur
-------	---------

raman	rayagada
-------	----------

Navi	raipur
------	--------

Pavi	raigarh
------	---------

Ankit	china
-------	-------

Umesh	vizag
-------	-------

ramesh	bihar
--------	-------

mahesh	patna
--------	-------

Rahul	kolkata
-------	---------

+-----+-----+

10 rows in set (0.00 sec)

mysql> SELECT roll, salary FROM giet;

+-----+-----+

roll	salary
------	--------

101	25000	
102	15000	
103	15000	
104	15000	
105	25000	
106	45000	
107	45000	
108	25000	
109	55000	
110	30000	

+-----+-----+

10 rows in set (0.00 sec)

```
mysql> SELECT * FROM giet
-> WHERE name = 'aman';
```

roll	name	address	desig	salary	gender	
101	aman	delhi	doctor	25000	M	

1 row in set (0.00 sec)

```
mysql> -- 6. Show employees who live in 'delhi'
```

```
mysql> SELECT * FROM employee
-> WHERE address = 'delhi';
```

ERROR 1146 (42S02): Table 'giet.employee' doesn't exist

```
mysql> select * from giet
```

```
-> where address='delhi';
```

roll	name	address	desig	salary	gender	
101	aman	delhi	doctor	25000	M	

1 row in set (0.00 sec)

```
mysql> select * from giet
```

```
-> where gender='m';
```

roll	name	address	desig	salary	gender	
101	aman	delhi	doctor	25000	M	
102	naman	gunupur	teacher	15000	M	
103	raman	rayagada	plumber	15000	M	

106	Ankit	china	singer	45000	M
107	Umesh	vizag	dancer	45000	M
108	ramesh	bihar	manager	25000	M
109	mahesh	patna	thied	55000	M
110	Rahul	kolkata	engineer	30000	M

8 rows in set (0.00 sec)

```
mysql> select * from giet
```

```
-> where designation='doctor';
```

ERROR 1054 (42S22): Unknown column 'designation' in 'where clause'

```
mysql> select * from giet
```

```
-> where desig='doctor';
```

roll	name	address	desig	salary	gender
101	aman	delhi	doctor	25000	M

1 row in set (0.00 sec)

```
mysql> select * from giet
```

```
-> where salary=15000;
```

roll	name	address	desig	salary	gender
102	naman	gunupur	teacher	15000	M
103	raman	rayagada	plumber	15000	M
104	Navi	raipur	nurse	15000	F

3 rows in set (0.00 sec)

```
mysql> select * from giet
```

```
-> where salary.20000;
```

ERROR 1054 (42S22): Unknown column 'salary.20000' in 'where clause'

```
mysql> select * from giet
```

```
-> where salary>20000;
```

roll	name	address	desig	salary	gender
101	aman	delhi	doctor	25000	M
105	Pavi	raigarh	police	25000	F
106	Ankit	china	singer	45000	M
107	Umesh	vizag	dancer	45000	M
108	ramesh	bihar	manager	25000	M

109	mahesh	patna	thied	55000	M
110	Rahul	kolkata	engineer	30000	M

7 rows in set (0.02 sec)

```
mysql> select * from giet
-> where salary < 30000;
```

roll	name	address	desig	salary	gender
101	aman	delhi	doctor	25000	M
102	naman	gunupur	teacher	15000	M
103	raman	rayagada	plumber	15000	M
104	Navi	raipur	nurse	15000	F
105	Pavi	raigarh	police	25000	F
108	ramesh	bihar	manager	25000	M

6 rows in set (0.00 sec)

```
mysql> select * from giet
-> where gender='m' and salary >20000;
```

roll	name	address	desig	salary	gender
101	aman	delhi	doctor	25000	M
106	Ankit	china	singer	45000	M
107	Umesh	vizag	dancer	45000	M
108	ramesh	bihar	manager	25000	M
109	mahesh	patna	thied	55000	M
110	Rahul	kolkata	engineer	30000	M

6 rows in set (0.00 sec)

```
mysql> select *from giet
-> where gender='f' or address='raipur';
```

roll	name	address	desig	salary	gender
104	Navi	raipur	nurse	15000	F
105	Pavi	raigarh	police	25000	F

2 rows in set (0.00 sec)

```
mysql> select * from giet
```


-> where name like 'a%';

```
+-----+-----+-----+-----+-----+-----+
| roll | name  | address | desig  | salary | gender |
+-----+-----+-----+-----+-----+-----+
| 101 | aman  | delhi   | doctor | 25000 | M      |
| 106 | Ankit | china   | singer | 45000 | M      |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

mysql> select * from giet

-> where name like '%h';

```
+-----+-----+-----+-----+-----+-----+
| roll | name  | address | desig  | salary | gender |
+-----+-----+-----+-----+-----+-----+
| 107 | Umesh | vizag   | dancer | 45000 | M      |
| 108 | ramesh | bihar  | manager | 25000 | M      |
| 109 | mahesh | patna   | thied  | 55000 | M      |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

mysql> select * from giet

-> where address like '%pur%';

```
+-----+-----+-----+-----+-----+-----+
| roll | name  | address | desig  | salary | gender |
+-----+-----+-----+-----+-----+-----+
| 102 | naman | gunupur | teacher | 15000 | M      |
| 104 | Navi  | raipur  | nurse  | 15000 | F      |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

mysql> select * from giet

-> order by name asc;

```
+-----+-----+-----+-----+-----+-----+
| roll | name  | address | desig  | salary | gender |
+-----+-----+-----+-----+-----+-----+
| 101 | aman  | delhi   | doctor | 25000 | M      |
| 106 | Ankit | china   | singer | 45000 | M      |
| 109 | mahesh | patna   | thied  | 55000 | M      |
| 102 | naman | gunupur | teacher | 15000 | M      |
| 104 | Navi  | raipur  | nurse  | 15000 | F      |
| 105 | Pavi  | raigarh | police | 25000 | F      |
| 110 | Rahul | kolkata | engineer | 30000 | M      |
| 103 | raman | rayagada | plumber | 15000 | M      |
| 108 | ramesh | bihar  | manager | 25000 | M      |
+-----+-----+-----+-----+-----+-----+
```

107	Umesh	vizag	dancer	45000	M
-----	-------	-------	--------	-------	---

10 rows in set (0.00 sec)

mysql> select * from giet

-> order by salary desc;

roll	name	address	desig	salary	gender
109	mahesh	patna	thied	55000	M
106	Ankit	china	singer	45000	M
107	Umesh	vizag	dancer	45000	M
110	Rahul	kolkata	engineer	30000	M
101	aman	delhi	doctor	25000	M
105	Pavi	raigarh	police	25000	F
108	ramesh	bihar	manager	25000	M
102	naman	gunupur	teacher	15000	M
103	raman	rayagada	plumber	15000	M
104	Navi	raipur	nurse	15000	F

10 rows in set (0.00 sec)

mysql> select count(*) as total_employees from giet;

total_employees
10

1 row in set (0.00 sec)

mysql> select * from giet

-> where gender='m';

roll	name	address	desig	salary	gender
101	aman	delhi	doctor	25000	M
102	naman	gunupur	teacher	15000	M
103	raman	rayagada	plumber	15000	M
106	Ankit	china	singer	45000	M
107	Umesh	vizag	dancer	45000	M
108	ramesh	bihar	manager	25000	M
109	mahesh	patna	thied	55000	M
110	Rahul	kolkata	engineer	30000	M

8 rows in set (0.00 sec)