

AIM: IMPLEMENTATION OF CLASSIFYING DATA USING SUPPORT VECTOR MACHINES (SVMS).**THEORY:**

“Support Vector Machine” (SVM) is a supervised machine learning algorithm which can be used for both classification or regression challenges. However, it is mostly used in classification problems. In the SVM algorithm, we plot each data item as a point in n-dimensional space (where n is number of features you have) with the value of each feature being the value of a particular coordinate. Then, we perform classification by finding the hyper-plane that differentiates the two classes very well. Support Vectors are simply the co-ordinates of individual observation. The SVM classifier is a frontier which best segregates the two classes (hyper plane/ line) In the SVM classifier, it is easy to have a linear hyper-plane between these two classes. But, another burning question which arises is, should we need to add this feature manually to have a hyper-plane. No, the SVM algorithm has a technique called the kernel trick. The SVM kernel is a function that takes low dimensional input space and transforms it to a higher dimensional space i.e. it converts not separable problem to separable problem. It is mostly useful in non linear separation problem. Simply put, it does some extremely complex data transformations, then finds out the process to separate the data based on the labels or outputs you’ve defined. In Python, scikit-learn is a widely used library for implementing machine learning algorithms. SVM is also available in the scikit-learn library and we follow the same structure for using it (Import library, object creation, fitting model and prediction)

Linear SVM is used for linearly separable data, which means if a dataset can be classified into two classes by using a single straight line, then such data is termed as linearly separable data, and classifier is used called as Linear SVM classifier.

SOURCE CODE:**1) IMPORTING LIBRARIES:**

```
#Import python packages
import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split # Import train_test_split function
from sklearn import svm #Import svm model
from sklearn import metrics #Import scikit-learn metrics module for accuracy calculation
from sklearn.metrics import confusion_matrix
```

2) READING DATASET:

```
#Import the heart data
data = pd.read_csv("heart.csv")
#Display first 5 lines of heart data
data.head()
```

	age	sex	cp	trestbps	chol	fbs	restecg	thalach	exang	oldpeak	slope	ca	thal	target
0	52	1	0	125	212	0	1	168	0	1.0	2	2	3	0
1	53	1	0	140	203	1	0	155	1	3.1	0	0	3	0
2	70	1	0	145	174	0	1	125	1	2.6	0	0	3	0
3	61	1	0	148	203	0	1	161	0	0.0	2	1	3	0
4	62	0	0	138	294	1	1	106	0	1.9	1	3	2	0

3) CHECKING INFO OF DATASET & COUNT OF NOT NULL:

```
#Display basic info about the data
data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1025 entries, 0 to 1024
Data columns (total 14 columns):
#   Column      Non-Null Count  Dtype
---  -
0   age         1025 non-null   int64
1   sex         1025 non-null   int64
2   cp          1025 non-null   int64
3   trestbps    1025 non-null   int64
4   chol        1025 non-null   int64
5   fbs         1025 non-null   int64
6   restecg     1025 non-null   int64
7   thalach     1025 non-null   int64
8   exang       1025 non-null   int64
9   oldpeak     1025 non-null   float64
10  slope       1025 non-null   int64
11  ca          1025 non-null   int64
12  thal        1025 non-null   int64
13  target      1025 non-null   int64
dtypes: float64(1), int64(13)
memory usage: 112.2 KB
```

4) SEPARATE TARGET & FEATURES DATA:

```
#Separate Feature and Target Matrix
x = data.drop('target',axis = 1)
y = data.target
```

5) SPLITTING DATA INTO TRAINING & TESTING DATA:

```
# Split dataset into training set and test set
x_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.3,random_state=109) # 70% training and 30% test
```

6) CREATING CLASSIFIER & PREDICTING VALUES:

```
#Create a svm Classifier
ml = svm.SVC(kernel='linear') # Linear Kernel

#Train the model using the training sets
ml.fit(x_train, y_train)

#Predict the response for test dataset
y_pred = ml.predict(x_test)
y_pred

array([0, 1, 1, 0, 0, 1, 1, 1, 1, 0, 0, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1,
       1, 0, 1, 1, 0, 0, 0, 1, 0, 1, 0, 1, 1, 1, 1, 0, 1, 0, 0, 1, 1, 1,
       0, 1, 1, 0, 1, 0, 0, 1, 1, 1, 1, 0, 0, 1, 0, 0, 1, 1, 0, 1, 0, 1,
       0, 0, 1, 0, 1, 0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 0, 0, 1, 1, 1,
       0, 1, 0, 0, 1, 1, 0, 1, 0, 1, 1, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0,
       1, 1, 1, 1, 1, 1, 0, 1, 0, 1, 0, 0, 1, 0, 1, 1, 1, 0, 1, 0, 1,
       1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1,
       1, 1, 0, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 1, 1, 0, 1, 1, 1, 0, 0, 0,
       0, 1, 0, 0, 0, 1, 0, 1, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 0, 1,
       0, 0, 1, 1, 1, 0, 0, 0, 0, 1, 1, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 1,
       0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 1, 0, 0, 0, 1,
       0, 1, 0, 0, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 1, 0, 1, 0, 0, 1,
       1, 0, 1, 1, 1, 1, 0, 1, 1, 1, 0, 0, 0, 1, 0, 0, 0, 0, 1, 1, 0, 1,
       1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 1, 1, 1, 1])
```

7) CHECKING ACCURACY OF THE MODEL:

```
# Model Accuracy: how often is the classifier correct?
ml.score(x_test,y_test)
```

```
0.8733766233766234
```

8) CONFUSION MATRIX:

```
confusion_matrix(y_test,y_pred)

array([[124,  26],
       [ 13, 145]])
```

CONCLUSION:

From this practical, I have learned and implemented Linear Support Vector Machine(SVM) in python.