

Chapter 8: Sorting: (5hrs)

Definition: Sorting is the process of arranging data into meaningful order so that you can analyze it more effectively.

In computer science, a sorting algorithm is an algorithm that puts elements of a list into an order. The most frequently used orders are numerical order which is either ascending or descending.

Internal Vs External Sort

If the data sorting process takes place entirely within the Main Memory (RAM) of a computer, it's called **internal sorting**. This is possible whenever the size of the dataset to be sorted is small enough to be held in RAM.

Example of internal sorting algorithms: Bubble Sort, Insertion Sort, Quick Sort, Heap Sort, Radix Sort, Selection sort.

For sorting larger datasets, it may be necessary to hold only a smaller chunk of data in memory at a time, since it won't all fit in the RAM. The rest of the data is normally held on some larger, but slower medium, like a hard disk. The sorting of these large datasets will require different sets of algorithms which are called **external sorting**.

Example of external sorting algorithm: Merge Sort

Exchange sort: Comparison based. The basic idea is to compare two elements; if out of order, swap them or move one of the elements. E.g. Bubble sort, Quick sort.

Selection sort: An element is selected and is placed in its correct position. e. g. Selection sort, Heap sort.

Insertion sort: Sorts by inserting an element into a sorted list. E.g. insertion sort, merge sort.

Bubble sort:

Basic Idea: Pass through the list sequentially several times. At each pass, each element in the list is compared to its successor and they are interchanged if they are not in proper order.

At each pass, one element will be in its proper position. In general, $A[n-i]$ will be in its place after pass i . Since each pass place a new element in its proper position, a total of $N-1$ passes are required for a list of N elements. Also, all the elements in positions greater than or equal to $N-i$ are already in proper position after pass i , so they need not be considered in succeeding passes.

Procedure:

```
void bubblesort (int a[], int N)
{
    int pass, j;
    for(pass=0; pass<N-1; pass++)
    {
        for (j=0; j<N-i-1; j++)
            if (a[j]>a[j+1])
                swap (&a[j], &a [j+1]);
    }
}
```

Tracing example, total no. of items $N = 8$

Original list **25, 57, 48, 37, 12, 92, 86, 33**.

25	57	48	37	12	92	86	33	Interchange	
<u>25</u>	<u>57</u>	48	37	12	92	86	33	No	} 1 st Pass
25	<u>57</u>	<u>48</u>	37	12	92	86	33	Yes	
25	48	<u>57</u>	<u>37</u>	12	92	86	33	Yes	
25	48	37	<u>57</u>	<u>12</u>	92	86	33	Yes	
25	48	37	12	<u>57</u>	<u>92</u>	86	33	No	
25	48	37	12	57	<u>92</u>	<u>86</u>	33	Yes	
25	48	37	12	57	86	<u>92</u>	<u>33</u>	Yes	
25	48	37	12	57	86	33	92		

<u>25</u>	<u>48</u>	37	12	57	86	33	92	No	} 2 nd Pass
25	<u>48</u>	<u>37</u>	12	57	86	33	92	Yes	
25	37	<u>48</u>	<u>12</u>	57	86	33	92	Yes	
25	37	12	<u>48</u>	<u>57</u>	86	33	92	No	
25	37	12	48	<u>57</u>	<u>86</u>	33	92	No	
25	37	12	48	57	<u>86</u>	<u>33</u>	92	Yes	
25	37	12	48	57	33	86	92		

25 37 12 48 57 33 86 **92 Interchange**

<u>25</u>	<u>37</u>	12	48	57	33	86	92	No	} 3 rd Pass
25	<u>37</u>	<u>12</u>	48	57	33	86	92	Yes	
25	12	<u>37</u>	<u>48</u>	57	33	86	92	No	
25	12	37	<u>48</u>	<u>57</u>	33	86	92	No	
25	12	37	48	<u>57</u>	<u>33</u>	86	92	Yes	
25	12	37	48	33	57	86	92		

25	12	37	48	33	57	86	92 Interchange		} 4 th Pass
<u>25</u>	<u>12</u>	37	48	33	57	86	92	Yes	
12	<u>25</u>	<u>37</u>	48	33	57	86	92	No	
12	25	<u>37</u>	<u>48</u>	33	57	86	92	No	
12	25	37	<u>48</u>	<u>33</u>	57	86	92	Yes	
12	25	37	33	48	57	86	92		

12	25	37	33	48	57	86	92 Interchange		} 5 th Pass
<u>12</u>	<u>25</u>	37	33	48	57	86	92	No	
12	<u>25</u>	<u>37</u>	33	48	57	86	92	No	
12	25	<u>37</u>	<u>33</u>	48	57	86	92	Yes	
12	25	33	37	48	57	86	92		

12	25	33	37	48	57	86	92 Interchange		} 6 th Pass
<u>12</u>	<u>25</u>	33	37	48	57	86	92	No	
12	<u>25</u>	<u>33</u>	37	48	57	86	92	No	
12	25	33	37	48	57	86	92		

12	25	33	37	48	57	86	92 Interchange		} 7 th Pass
<u>12</u>	<u>25</u>	33	37	48	57	86	92	No	
12	25	33	37	48	57	86	92		

Algorithm:

- Given a list A of size N, the following algorithm uses bubble sort to sort the list
 - For $pass = 0$ To $N - 2$
 - For $j = 0$ To $N - pass - 2$
 - If $A[j] > A[j + 1]$
Swap the elements $A[j]$ and $A[j + 1]$
End If
 - End For
 - End For

Efficiency:

This algorithm is good for small n usually less than 100 elements.

$$\begin{aligned}\text{No. of comparisons} &= (n-1) + (n-2) + \dots + 2 + 1 \\ &= (n-1)(n-1+1)/2 \\ &= n(n-1)/2 \\ &= O(n^2)\end{aligned}$$

No. of Interchanges:

- This cannot be greater than no. of comparisons
- In the best case, there are no interchanges
- In the worst case, this equals no of comparisons

The average and worse case running time of bubble sort is $O(n^2)$.

It is actually the no of interchanges which takes up most time of the program's execution than the no of comparisons. When elements are large and interchange operation is expensive, it is better to maintain an array of pointers to the elements. One can then interchange pointers rather than the elements itself.

Insertion Sort

Basic idea: Sorts a list of record by inserting new element into an existing sorted list. An initial list with only one item is considered to be sorted list. For a list of size N, N-1 passes are made, and for each pass the elements from a [0] through a [i-1] are sorted.

Take the element $a[i]$, find the proper place to insert $a[i]$ within 0, 1... i-1 and insert $a[i]$ at that place.

To insert new item into the list

- Search the position in the sorted sub list from last toward first

- While searching, move elements one position right to make a room to insert $a[i]$
- Place $a[i]$ in its proper place

Initially 25 57 48 37 12 92 86 33

Pass 1	<u>25 57</u>	48 37 12 92 86 33	<i>Insert 57</i>
Pass 2	<u>25 48 57</u>	37 12 92 86 33	<i>Insert 48</i>
Pass 3	<u>25 37 48 57</u>	12 92 86 33	<i>Insert 37</i>
Pass 4	<u>12 25 37 48 57</u>	92 86 33	<i>Insert 12</i>
Pass 5	<u>12 25 37 48 57 92</u>	86 33	<i>Insert 92</i>
Pass 6	<u>12 25 37 48 57 86 92</u>	33	<i>Insert 86</i>
Pass 7	<u>12 25 33 37 48 57 86 92</u>		<i>Insert 33</i>

C-Procedure

```
void InsertionSort(int a[], int N)
{
    int i, j;
    int hold; /* the current element to insert */

    for (i = 1; i < N; i++) // Insert a[i] into the sorted list
    {
        hold = a[i]; /* hold the element to be inserted */
        for (j = i-1; j >= 0 && a[j] > hold; j--) //Move right 1 position all
            a[j+1] = a[j];                       //elements greater than hold

        a[j+1] = hold; /* Place hold in its proper place */
    }
}
```

Efficiency:

No of comparisons:

Best case: $n - 1$

Worst case: $n^2/2 + O(n)$

Average case: $n^2/4 + O(n)$

No of assignments (movements)

Best case: $2*(n-1)$ // moving from $a[i]$ to hold and back

Worst case: $n^2/2 + O(n)$

Average case: $n^2/4 + O(n)$

Hence running time of insertion sort is $O(n^2)$ in worst and average case and $O(n)$ in best case and space requirement is $O(1)$.

Advantages:

It is an excellent method whenever a list is nearly in the correct order and few items are removed from their correct locations

Since there is no swapping, it is twice as faster than bubble sort

Disadvantage:

It makes a large amount of shifting of sorted elements when inserting later elements.

Selection Sort:

The selection sort algorithm sorts a list by selecting successive elements in order and placing into their proper sorted positions.

A list of size N require N-1 passes:

For each pass I,

- Find the position of i^{th} largest (or smallest) element.
- To place the i^{th} largest (of smallest) in its proper position, swap this element with the element currently in the position of its largest (or smallest) element.

C – Procedure

```
void SelectionSort(int a[], int N)
{
    int i, j;
    int maxpos;
    for (i = N-1; i > 0; i--)          //Find the position of largest element from 0 to i
    {
        maxpos = 0;
        for (j = 1; j <= i; j++)
            if (a[j] > a[maxpos])
                maxpos = j;
        if(maxpos != i)
            swap(&a[maxpos], &a[i]);    //Place the ith largest element
    }                                  // in its place
}
```

Tracing: Initially 25 57 48 37 12 92 86 33

Find largest between $a[0]$ and $a[7]$ \rightarrow 92, swap 92 with the last element 33

Pass 1 25 57 48 37 12 33 86 92

Find largest between $a[0]$ and $a[6]$ \rightarrow 86, since 86 is in 6th position and so is i , no interchange.

Pass 2 25 57 48 37 12 33 86 92

Find largest between $a[0]$ and $a[5]$ \rightarrow 57, swap with 33

Pass 3 25 33 48 37 12 57 86 92

Find largest between $a[0]$ and $a[4]$ \rightarrow 48, swap 48 with 12

Pass 4 25 33 12 37 48 57 86 92

Find largest between $a[0]$ and $a[3]$ \rightarrow 37, No swap since $i = \text{maxpos}$

Pass 5 25 33 12 37 48 57 86 92

Find largest between $a[0]$ and $a[2]$ \rightarrow 33, swap 33 with 12

Pass 6 25 12 33 37 48 57 86 92

Find largest between $a[0]$ and $a[1]$ \rightarrow 25, swap 12 with 25

Pass 7 12 25 33 37 48 57 86 92

Finally the list is sorted.

Efficiency:

No of comparisons:

Best, average and worst case: $n(n - 1)/2$

No of assignments (movements)

Best, average and worst case: $3(n - 1)$, (total $n - 1$ swaps)

If we include a test, to prevent interchanging an element with itself, the number of interchanges in the best case would be 0.

Hence running time of selection sort is $O(n^2)$ and additional space requirements is $O(1)$.

- **Advantages:**

- It is the best algorithm in regard to data movement
- An element that is in its correct final position will never be moved and only one swap is needed to place an element in its proper position

- **Disadvantages**

- In case of number of comparisons, it pays no attention to the original ordering of the list. For a list that is nearly correct to begin with, selection sort is slower than insertion sort

Divide and Conquer Sorting Algorithms

- The idea of dividing a problem into smaller but similar sub problems is called *divide and conquer*
- Divide and Conquer Sorting
 - Procedure Sort(list)
 - if (list has length greater than 1)
 - Partition the list into two sublists lowlist, highlist
 - Sort(lowlist)
 - Sort(highlist)
 - Combine (lowlist, highlist)
 - End If
 - End Procedure

Quick Sort: (Imp.)

It is the fastest known sorting algorithms used in practice.

Basic idea

Divide the list into two sub lists such that all elements in the first list is less than some pivot key and all elements in the second list is greater than the pivot key,
And finally sort the sub lists independently and combine them.

Algorithm:

If size of list A is greater than 1

- Pick any element v from A . This is called the *pivot*
- Partition the list A by placing v in some position j , such that
 - all elements before position j are less than or equal to v
 - all elements after position j are greater than or equal to v
- Recursively sort the sub lists $A[0]$ through $A[j-1]$ and $A[j+1]$ and $A[N-1]$
- Return $A[0]$ through $A[j-1]$ followed by $A[j]$ (the pivot) followed by $A[j+1]$ through $A[N-1]$

25 57 48 37 12 92 86 33

Choose the first element 25 as the pivot and partition the array

(12) 25 (57 48 37 92 86 33)

The first subarray is automatically sorted

12 25 (57 48 37 92 86 33)

Choose the first element 57 of the second subarray as the pivot and partition the subarray

12 25 (48 37 33) 57 (92 86)

12 25 (48 37 33) 57 (92 86)

12 25 (37 33) 48 57 (92 86)

12 25 (33) 37 48 57 (92 86)

12 25 33 37 48 57 (92 86)

12 25 33 37 48 57 (92 86)

12 25 33 37 48 57 (86) 92

12 25 33 37 48 57 86 92

Quick Sort Code:

void QuickSort(int A[], int N)

```
{
    QSort(A, 0, N - 1);
}
```

void QSort(ItemType A[], int low, int high)

```
{
    int pivotloc;
    if (low < high)
    {
        pivotloc = partition(A, low, high);
        QSort(A, low, pivotloc - 1);
        QSort(A, pivotloc + 1, high);
    }
}
```

int partition(int A[], int low, int high)

```
{
    int down, up;
    int pivot;
    pivot = A[low]; /* choose first element as the pivot
    down = low;      /* Initialize pointers */
    up = high;

    while (down < up)
    {
        while (A[down] <= pivot && down < high) /* move right */
            down++;
        while (A[up] > pivot) /* move left */
            up--;
        if (down < up) /* exchange element at up and down */
            swap (&A[down], &A[up]);
    }
    swap (&A[low], &A[up]); /* Place pivot at its proper position */
    return up; /* return the pivot location */
}
```

Method for choosing pivot:

First element: Choose the first item in the list.

Random element: Choose any item from the list. Swap it with the first item to apply the algorithm.

Median: Pick three elements randomly and use their median as pivot.

Efficiency:

No. of comparisons:

Average case: $O(n \log n)$

Worst case: $O(n^2)$

No of interchanges (swaps)

Average case: $O(n \log n)$

Worst case: $O(n^2)$

Hence, the time complexity of Quicksort is $O(n \log n)$ for average case and $O(n^2)$ for worst case.

Merge Sort:

The merge sort also uses divide and conquer approach. It divides the list into sub lists. Then merge two sorted into a single list.

Algorithm outline


If size of list is greater than 1

- divide the list into two sub lists of sizes nearly equal as possible
- Recursively sort the sub list separately.
- Merge the two sorted sub lists into a single sorted list


End if

25 12 48 37 57 92 86 33

- **First Phase:** Partition the list in two equal halves, until the list size is 1



- **Second Phase:** Merge the sorted sub lists



C-Code:

```

void main()
{
    clrscr();
    int n,i;
    int x[N];
    int temp[N];
    printf("\nEnter no. of elements to sort: ");
    scanf("%d",&n);
    printf("\nEnter elements to sort:\n");
    for (i = 0; i < n; i++)
        scanf("%d",&x[i]);
    //perform merge sort on array
    msort(x,temp,0,n-1);
    printf("Sorted List \n");
    for (i = 0; i < n; i++)
        printf("%d\n", x[i]);
    getch();
}
  
```

```

void msort(int x[], int temp[], int left, int
right)
{
    int mid;
    if(left<right)
    {
        mid = (right + left) / 2;
        msort(x, temp, left, mid);
        msort(x, temp, mid+1, right);

        merge(x, temp, left, mid+1, right);
    }
}
  
```

```
void merge(int x[], int temp[], int left, int
mid, int right)
{
    int i, lend, no_element, tmpos;

    lend = mid - 1;
    tmpos = left;
    no_element = right - left + 1;

    while ((left <= lend) && (mid <= right))
    {
        if (x[left] <= x[mid])
        {
            temp[tmpos] = x[left];
            tmpos = tmpos + 1;
            left = left + 1;
        }
        else
        {
            temp[tmpos] = x[mid];
            tmpos = tmpos + 1;
            mid = mid + 1;
        }
    }

    while (left <= lend)
    {
        temp[tmpos] = x[left];
        left = left + 1;
        tmpos = tmpos + 1;
    }
}
```

```
}  
while (mid <= right)  
{  
    temp[tmpos] = x[mid];  
    mid = mid + 1;  
    tmpos = tmpos + 1;  
}  
for (i=0; i <= no_element; i++)  
{  
    x[right] = temp[right];  
    right = right - 1;  
}  
}
```

Efficiency:**No. of Comparisons:**

For all cases the number of comparisons is to be $O(n \log n)$, the constant term is different for different cases. On average, it requires fewer than $n \log n - n + 1$ comparisons.

No. of assignments:

For our implementation, it is twice the no of comparisons, merging in the temporary array and copying back to the original array which is still $O(n \log n)$

Space Complexity:

In contrast to other sorting algorithms, we have studied, MergeSort requires $O(n)$ extra space for the temporary memory used while merging. Algorithm has been developed for performing in-place merge in $O(n)$ time, but this would increase the no of assignments. If recursive version is used, additional space is required for the implicit stack, which is $O(\log n)$. Hence, Space complexity for MergeSort is $O(n)$

Notes on Merge sort:

Even though the worst-case running-time of MergeSort is $O(n \log n)$, it is **not** an algorithm of choice for sorting contiguous lists. MergeSort can prove superior over other sorting algorithms when used with linked lists.

Heap Sort

A Binary Heap is a Complete Binary Tree where items are stored in a special order such that the value in a parent node is greater (or smaller) than the values in its two children nodes.

The former is called max heap and the latter is called min-heap. The heap can be represented by a binary tree or array.

Heap Sort Algorithm for sorting in increasing order:

1. Build a max heap from the input data.
2. At this point, the largest item is stored at the root of the heap. Replace it with the last item of the heap followed by reducing the size of heap by 1.
3. Repeat step 2 while the size of the heap is greater than 1.


First Phase:

1. The entries in the array being sorted are interpreted as a binary tree in array implementation
2. Tree with only one node automatically satisfies the heap property. So, we don't need to worry about any of the leaves.
3. Start from the level above the leaf nodes, and work out backward towards the root.


Let's take an example for tracing following elements.

37	33	26	92	57	18	48	25	12	86	42	22
----	----	----	----	----	----	----	----	----	----	----	----


This array can be represented as following binary tree:




This is not a heap. So, adjust to convert it to max heap as follows:
Leave the leaf nodes. Adjust heap property at 22




Adjust property at 57




At 92 the subtree already satisfies the heap property, so it will remain as it is. Adjust property at 26, here, 48 should be come up.



Adjust at 33



Adjust at 37




Second Phase:

- Note that the root (the first element of the array) has the largest key
- Repeat these steps until the size of heap becomes 1
 1. Move the largest key at root to the last position of the heap, replacing an entry x currently at the last position
 2. Decrease a counter i that keeps track of the size of the heap, thereby excluding the largest key from further sorting
 3. The element x may not belong to the root of the heap, so insert x into the proper position to restore the heap property

Move the largest element, 92, to the last position of the heap, thus replacing 18


Now we must find a way to put 18 in its proper position, thus restoring the heap property




Adjusting the Heap Properties:


- When the last element, x , is replaced by the largest element at the root, a hole is created at the root and the heap size becomes smaller by 1
- We must move x somewhere to restore the heap property
 1. First we look if x can be placed in the hole, by looking at the two children of that hole
 2. If x belongs to the hole, then we put x there and we are done
 3. Else we slide the larger of the two children to the hole, thus pushing the hole down one level
 4. We repeat this process on the sub tree until x can be placed in the hole or there are no children
 5. Thus, our action is to place x in its correct spot along a path from the root containing minimum children.

Delete 92







Delete 86




86	57	48	33	42	22	26	25	12	37	18	92
0	1	2	3	4	5	6	7	8	9	10	11




57	42	48	33	37	22	26	25	12	18	86	92
0	1	2	3	4	5	6	7	8	9	10	11

Delete 57

48	42	26	33	37	22	18	25	12	57	86	92
0	1	2	3	4	5	6	7	8	9	10	11


Delete 48

42	37	26	33	12	22	18	25	48	57	86	92
0	1	2	3	4	5	6	7	8	9	10	11


Delete 42

37	33	26	25	12	22	18	42	48	57	86	92
0	1	2	3	4	5	6	7	8	9	10	11


Delete 37




Delete 33




Delete 26




Delete 25




Delete 22



Delete 18



Delete 12



Finally, the data are sorted

Heap Sort Efficiency

- No of comparisons and assignments
 - Worst-case: $O(n \log n)$
 - Average case: $O(n \log n)$
- Hence time complexity of heapsort is $O(n \log n)$ for both worst case and average case and space complexity is $O(1)$. In average case, it is not as efficient as quick sort, however, it is far superior to quick sort in worse case. Generally, heap sort is used for large amount of data.

Heap as Priority Queue:

- A *priority queue* is a data structure with the following primitive operations
 - Insert an item
 - Remove the item having the largest (or smallest) key
- Implementations
 - Use a sorted contiguous list, removal takes $O(1)$ but insertion takes $O(n)$
 - Use an unsorted list, insertion takes $O(1)$ but removal takes $O(n)$

Efficiency Priority Queue:

- Consider the properties of heap:
 - The item with largest key is on the top and can be removed immediately. However it will take time $O(\log n)$ to restore the heap property for remaining keys
 - For insertion we shift the new item from down to up which also takes $O(\log n)$
- Hence, implementation of a priority queue as a heap proves advantageous for large n
 - It efficiently represents in contiguous storage and is guaranteed to require only logarithmic time for both insertions and deletions

Questions:

- Write short notes on: Heap sort

Shell Sort

Significant improvement on simple insertion sort can be achieved by using shell sort (or diminishing increment sort).

This method separates original file into subfiles. These subfiles contain every k th element of the original file. The value of k is called an increment. Eg. If $k=5$, then subfile consists of $x[0], x[5], x[10], \dots$ is first sorted.

After the first k subfiles are sorted (usually by simply insertion), a new smaller value of k is chosen and the file is again partitioned into a new set of subfiles. Each of these larger subfiles is sorted and the process is repeated yet again, until eventually the value of the k is set to 1.

The decreasing sequence of increments can

Either be fixed at the start of the entire process. The last value must be 1

Or take the first increment to $h_k = \text{floor}(N/2)$ and $h_{k+1} = \text{floor}(h_k/2)$ until $h_k = 1$. h_k = subsequent increment.

Tracing for following numbers:

81, 94, 11, 96, 12, 35, 17, 95, 28, 58, 41, 75, 15

Let $h_t = 13 / 2 = 6$, so here increment is 6, the shell sort will be sub divided into 6 sub files.

Sub files			Sorted sub files		
81	17	15	15	17	81
94	95		94	95	
11	28		11	28	
96	58		58	96	
12	41		12	41	
35	75		35	75	

After 1st iteration, the list will look like:

15 94 11 58 12 35 17 95 28 96 41 75 81

Now, in second iteration $h_k = \text{floor}((h_k+1)/2) = \text{floor}(6/2) = 3$

Sub files					Sorted sub files				
15	58	17	96	81	15	17	58	81	96
94	12	95	41		12	41	94	95	
11	35	28	75		11	28	35	75	

After 2nd iteration, the list will be as follows:

15 12 11 17 41 28 58 94 35 81 95 75 96

Now, $hk = \text{floor}((hk+1)/2) = 3 / 2 = 1$

15 12 11 17 41 28 58 94 35 81 95 75 96

Now, using simple insertion sort we get,

15 12 11 17 41 28 58 94 35 81 95 75 96

12 15 11 17 41 28 58 94 35 81 95 75 96

11 12 15 17 41 28 58 94 35 81 95 75 96

11 12 15 17 41 28 58 94 35 81 95 75 96

11 12 15 17 41 28 58 94 35 81 95 75 96

11 12 15 17 28 41 58 94 35 81 95 75 96

11 12 15 17 28 41 58 94 35 81 95 75 96

11 12 15 17 28 41 58 94 35 81 95 75 96

11 12 15 17 35 28 41 58 94 81 95 75 96

11 12 15 17 35 28 41 58 81 94 95 75 96

11 12 15 17 35 28 41 58 81 94 95 75 96

11 12 15 17 35 28 41 58 75 81 94 95 96

11 12 15 17 35 28 41 58 75 81 94 95 96

Hence, the list is finally sorted.

Efficiency

Worse case : $O(n^2)$

Average case : $O(n(\log n)^2)$ (if appropriate increment sequent is used)

Radix Sort or Bucket Sort

The sorting is based on the values of the actual digits in the positional representations of the numbers being sorted.

Process

- Beginning with the least-significant digit and ending with the most-significant digit, perform the following action,
- Take each number in the order in which it appears in the file and place it into one of the ten queues, depending on the value of the digit currently being processed.
- Then restore each queue to the original file starting with the queue of numbers with a 0 digit and ending with the queue of numbers with a 9 digit.
- When these actions have been performed for each digit, starting with the least significant digit and ending with the most significant, the file is sorted.

Tracing example: We have **64, 8, 216, 512, 27, 729, 0, 1, 343, 125**

First Pass

	0	1	512	343	64	125	216	27	8	729
no%10	0	1	2	3	4	5	6	7	8	9

Second Pass

	8		729							
	1	216	27							
	0	512	125		343		64			
(no/10)%10	0	1	2	3	4	5	6	7	8	9

Third Pass

	64									
	27									
	8									
	1									
	0	125	216	343		512		729		
(no/100)%10	0	1	2	3	4	5	6	7	8	9

Finally, we have, **0, 1, 8, 27, 34, 125, 216, 343, 512, 729**

Here, the no. of passes equals maximum number of digits in the given numbers to be sorted.

Efficiency: **O (n.logn)**

Binary Sort:

The binary sort algorithm is a variant of the insertion sort method. We additionally keep one sorted and one unsorted subarray in this technique.

The main difference is that we use binary search instead of linear search to determine the correct position of an element.

Algorithm:

Let us assume that we have an unsorted array $L[]$ containing n elements. The first element, array $L[0]$, is already sorted and in the sorted subarray.

- ✓ Mark the first element from the unsorted subarray $L[1]$ as the key.
- ✓ Use binary search to find the correct position p of $L[1]$ inside the sorted subarray.
- ✓ Shift the elements from $p-1$ steps rightwards and insert $L[1]$ in its correct position.
- ✓ Repeat the above steps for all the elements in the unsorted subarray.

Comparison table:

Algorithms	Worse Case	Average Case
Bubble Sort	$O(n^2)$	$O(n^2)$
Quick Sort	$O(n^2)$	$O(n \cdot \log n)$
Insertion Sort	$O(n^2)$	$O(n^2)$
Selection Sort	$O(n^2)$	$O(n^2)$
Merge Sort	$O(n \cdot \log n)$	$O(n \cdot \log n)$
Heap Sort	$O(n \cdot \log n)$	$O(n \cdot \log n)$
Radix Sort	$O(n \cdot \log n)$	$O(n \cdot \log n)$

Selecting a sort algorithm:

Algorithms	Comments
Bubble Sort	Good for small n usually less than 10
Quick Sort	Excellent for virtual memory environment
Insertion Sort	Good for almost sorted records
Selection Sort	Good for partially sorted data and small ' n '
Merge Sort	Good for external file sorting
Heap Sort	As efficient as quick sort in average case and far superior to quick sort in the worse case
Radix Sort	Good when number of digits(letters) are less

Questions:

1. *Trace the quick sort algorithm for following unordered list.*
 - 25,30,18,16,45,40,60,20,10,7,30,100,12,14
2. *What is sorting? Explain the divide and conquer approach in quick sort algorithm.*
Trace the algorithm to sort the following unordered list 40,20,10,80,60,50,7,30,100
3. *Define selection sort. Trace quick sort algorithm for the data:*
25,57,48,37,12,92,86,33