

LANGCHAIN2

OpenAI functions & Custom Agents

Source: README.md

LLM applications with etrieval-augmented generation (RAG) to start using Atlas Vector Search with LangChain and perform semantic search

■ Install Python

A [Quick Guide for Installing](#) Python on Common Operating Systems

...

■ Create a virtual environment :

MacOS/Linux:

```
python3 -m venv env
```

Windows:

```
python -m venv env
```

■ Activate the virtual environment :

MacOS/Linux:

```
source env/bin/activate
```

Windows:

```
.\env\Scripts\activate
```

■ Installation: Install the necessary dependencies by running the following command:

MacOS/Linux:

```
pip3 install -r requirements.txt
pip3 install -U langchain-community
pip3 install -U langchain-openai
```

Windows:

```
pip install -r requirements.txt
pip install -U langchain-community
pip install -U langchain-openai
```

■ Get an API key

Set the key as an environment variable:

Additionally, you need to obtain an OpenAI API key and add it to the `.env` file.

```
export OPENAI_API_KEY='sk-brHeh...A39v5iXsM2'
```

```
OPENAI_API_KEY=sk-brHeh...A39v5iXsM2
```

■ Tavily Search API

Tavily's Search API is a search engine built specifically for AI agents (LLMs), delivering real-time, accurate, and factual results at speed.

- [LangChain documentation](#)

■ Run the script:

MacOS/Linux:

```
python3 main.py
streamlit run app.py
```

Windows:

```
python main.py
```

■ Deploy Streamlit app

1. Create an account [signup](#) You will be required to verify your email.
2. Create a new app - [create app](#)
3. Deploy App - [deploy](#)