

Chapter_12_Advanced_pandas

March 7, 2024

0.1 12.1 Categorical Data

I will show how you can achieve better performance and memory use in some pandas operations by using it. I also introduce some tools for using categorical data in statistics and machine learning applications.

0.1.1 Background and Motivation

Frequently, a column in a table may contain repeated instances of a smaller set of distinct values. We have already seen functions like `unique` and `value_counts`, which enable us to extract the distinct values from an array and compute their frequencies, respectively

```
[1]: import numpy as np; import pandas as pd
values = pd.Series(['apple', 'orange', 'apple', 'apple'] * 2)
values
```

```
[1]: 0    apple
     1    orange
     2    apple
     3    apple
     4    apple
     5    orange
     6    apple
     7    apple
     dtype: object
```

```
[2]: pd.unique(values)
```

```
[2]: array(['apple', 'orange'], dtype=object)
```

```
[3]: pd.value_counts(values)
```

```
[3]: apple      6
     orange     2
     dtype: int64
```

Many data systems (for data warehousing, statistical computing, or other uses) have developed specialized approaches for representing data with repeated values for more efficient storage and computation. In data warehousing, a best practice is to use so-called dimension tables containing

the distinct values and storing the primary observations as integer keys referencing the dimension table:

```
[4]: values = pd.Series([0, 1, 0, 0] * 2)
      dim = pd.Series(['apple', 'orange'])
      values
```

```
[4]: 0    0
      1    1
      2    0
      3    0
      4    0
      5    1
      6    0
      7    0
      dtype: int64
```

```
[5]: dim
```

```
[5]: 0    apple
      1    orange
      dtype: object
```

We can use the take method to restore the original Series of strings:

```
[6]: dim.take(values)
```

```
[6]: 0    apple
      1    orange
      0    apple
      0    apple
      0    apple
      1    orange
      0    apple
      0    apple
      dtype: object
```

This representation as integers is called the categorical or dictionary-encoded representation. The array of distinct values can be called the categories, dictionary, or levels of the data. In this book we will use the terms categorical and categories. The integer values that reference the categories are called the category codes or simply codes.

The categorical representation can yield significant performance improvements when you are doing analytics. You can also perform transformations on the categories while leaving the codes unmodified. Some example transformations that can be made at relatively low cost are:

- Renaming categories
- Appending a new category without changing the order or position of the existing categories

0.1.2 Categorical Type in pandas

pandas has a special Categorical type for holding data that uses the integer-based categorical representation or encoding. Let's consider the example Series from before:

```
[7]: fruits = ['apple', 'orange', 'apple', 'apple'] * 2
N = len(fruits)
df = pd.DataFrame({'fruit': fruits, 'basket_id': np.arange(N), 'count': np.random.
    ↳ randint(3, 15, size=N), 'weight': np.random.uniform(0, 4,
    ↳ size=N)}, columns=['basket_id', 'fruit', 'count', 'weight'])
df
```

```
[7]:   basket_id  fruit  count  weight
0         0  apple     3  3.516063
1         1  orange     5  3.602808
2         2  apple     6  2.808427
3         3  apple    13  3.138310
4         4  apple    12  1.889745
5         5  orange    13  3.975940
6         6  apple    14  0.017706
7         7  apple     7  3.191929
```

Here, `df['fruit']` is an array of Python string objects. We can convert it to categorical by calling:

```
[8]: fruit_cat = df['fruit'].astype('category')
fruit_cat
```

```
[8]: 0    apple
1    orange
2    apple
3    apple
4    apple
5    orange
6    apple
7    apple
Name: fruit, dtype: category
Categories (2, object): ['apple', 'orange']
```

The values for `fruit_cat` are not a NumPy array, but an instance of `pandas.Categorical`:

```
[9]: c = fruit_cat.values
type(c)
```

```
[9]: pandas.core.arrays.categorical.Categorical
```

The Categorical object has `categories` and `codes` attributes:

```
[10]: c.categories
```

```
[10]: Index(['apple', 'orange'], dtype='object')
```

```
[11]: c.codes
```

```
[11]: array([0, 1, 0, 0, 0, 1, 0, 0], dtype=int8)
```

You can convert a DataFrame column to categorical by assigning the converted result:

```
[12]: df['fruit'] = df['fruit'].astype('category')
df.fruit
```

```
[12]: 0    apple
      1    orange
      2    apple
      3    apple
      4    apple
      5    orange
      6    apple
      7    apple
      Name: fruit, dtype: category
      Categories (2, object): ['apple', 'orange']
```

You can also create pandas.Categorical directly from other types of Python sequences

```
[13]: my_categories = pd.Categorical(['foo', 'bar', 'baz', 'foo', 'bar'])
my_categories
```

```
[13]: ['foo', 'bar', 'baz', 'foo', 'bar']
      Categories (3, object): ['bar', 'baz', 'foo']
```

If you have obtained categorical encoded data from another source, you can use the alternative `from_codes` constructor:

```
[14]: categories = ['foo', 'bar', 'baz']
      codes = [0, 1, 2, 0, 0, 1]
      my_cats_2 = pd.Categorical.from_codes(codes, categories)
      my_cats_2
```

```
[14]: ['foo', 'bar', 'baz', 'foo', 'foo', 'bar']
      Categories (3, object): ['foo', 'bar', 'baz']
```

Unless explicitly specified, categorical conversions assume no specific ordering of the categories. So the categories array may be in a different order depending on the ordering of the input data. When using `from_codes` or any of the other constructors, you can indicate that the categories have a meaningful ordering:

```
[15]: ordered_cat = pd.Categorical.from_codes(codes, categories, ordered=True)
ordered_cat
```

```
[15]: ['foo', 'bar', 'baz', 'foo', 'foo', 'bar']
      Categories (3, object): ['foo' < 'bar' < 'baz']
```

The output `[foo < bar < baz]` indicates that ‘foo’ precedes ‘bar’ in the ordering, and so on. An unordered categorical instance can be made ordered with `as_ordered`:

```
[16]: my_cats_2.as_ordered()
```

```
[16]: ['foo', 'bar', 'baz', 'foo', 'foo', 'bar']  
Categories (3, object): ['foo' < 'bar' < 'baz']
```

As a last note, categorical data need not be strings, even though I have only showed string examples. A categorical array can consist of any immutable value types.

0.2 Computations with Categoricals

Using Categorical in pandas compared with the non-encoded version (like an array of strings) generally behaves the same way. Some parts of pandas, like the groupby function, perform better when working with categoricals. There are also some functions that can utilize the ordered flag.

Let’s consider some random numeric data, and use the `pandas.qcut` binning function. This returns `pandas.Categorical`; we used `pandas.cut` earlier in the book but glossed over the details of how categoricals work:

```
[17]: np.random.seed(12345)  
draws = np.random.randn(1000)  
draws[:5]
```

```
[17]: array([-0.20470766,  0.47894334, -0.51943872, -0.5557303 ,  1.96578057])
```

Let’s compute a quartile binning of this data and extract some statistics:

```
[18]: bins = pd.qcut(draws, 4)  
bins
```

```
[18]: [(-0.684, -0.0101], (-0.0101, 0.63], (-0.684, -0.0101], (-0.684, -0.0101],  
(0.63, 3.928], ..., (-0.0101, 0.63], (-0.684, -0.0101], (-2.9499999999999997,  
-0.684], (-0.0101, 0.63], (0.63, 3.928]]  
Length: 1000  
Categories (4, interval[float64]): [(-2.9499999999999997, -0.684] < (-0.684,  
-0.0101] < (-0.0101, 0.63] < (0.63, 3.928]]
```

While useful, the exact sample quartiles may be less useful for producing a report than quartile names. We can achieve this with the `labels` argument to `qcut`:

```
[19]: bins = pd.qcut(draws, 4, labels=['Q1', 'Q2', 'Q3', 'Q4'])  
bins
```

```
[19]: ['Q2', 'Q3', 'Q2', 'Q2', 'Q4', ..., 'Q3', 'Q2', 'Q1', 'Q3', 'Q4']  
Length: 1000  
Categories (4, object): ['Q1' < 'Q2' < 'Q3' < 'Q4']
```

```
[20]: bins.codes[:10]
```

```
[20]: array([1, 2, 1, 1, 3, 3, 2, 2, 3, 3], dtype=int8)
```

The labeled bins categorical does not contain information about the bin edges in the data, so we can use groupby to extract some summary statistics:

```
[21]: bins = pd.Series(bins, name='quartile')
results = (pd.Series(draws).groupby(bins).agg(['count', 'min', 'max']).
    ↪reset_index())
results
```

```
[21]:  quartile  count      min      max
0      Q1     250 -2.949343 -0.685484
1      Q2     250 -0.683066 -0.010115
2      Q3     250 -0.010032  0.628894
3      Q4     250  0.634238  3.927528
```

The 'quartile' column in the result retains the original categorical information, including ordering, from bins:

```
[22]: results['quartile']
```

```
[22]: 0    Q1
      1    Q2
      2    Q3
      3    Q4
      Name: quartile, dtype: category
      Categories (4, object): ['Q1' < 'Q2' < 'Q3' < 'Q4']
```

0.2.1 Better performance with categoricals

If you do a lot of analytics on a particular dataset, converting to categorical can yield substantial overall performance gains. A categorical version of a DataFrame column will often use significantly less memory, too. Let's consider some Series with 10 million elements and a small number of distinct categories:

```
[23]: N = 10000000
draws = pd.Series(np.random.randn(N))
labels = pd.Series(['foo', 'bar', 'baz', 'qux'] * (N // 4))
```

Now we convert labels to categorical:

```
[24]: categories = labels.astype('category')
```

Now we note that labels uses significantly more memory than categories:

```
[25]: labels.memory_usage()
```

```
[25]: 80000128
```

```
[26]: categories.memory_usage()
```

```
[26]: 10000320
```

The conversion to category is not free, of course, but it is a one-time cost:

```
[27]: %time _ = labels.astype('category')
```

Wall time: 379 ms

GroupBy operations can be significantly faster with categoricals because the underlying algorithms use the integer-based codes array instead of an array of strings.

0.3 Categorical Methods

Series containing categorical data have several special methods similar to the `Series.str` specialized string methods. This also provides convenient access to the categories and codes. Consider the Series:

```
[28]: s = pd.Series(['a', 'b', 'c', 'd'] * 2)
      cat_s = s.astype('category')
      cat_s
```

```
[28]: 0    a
      1    b
      2    c
      3    d
      4    a
      5    b
      6    c
      7    d
      dtype: category
      Categories (4, object): ['a', 'b', 'c', 'd']
```

The special attribute `cat` provides access to categorical methods:

```
[29]: cat_s.cat.codes
```

```
[29]: 0    0
      1    1
      2    2
      3    3
      4    0
      5    1
      6    2
      7    3
      dtype: int8
```

Suppose that we know the actual set of categories for this data extends beyond the four values observed in the data. We can use the `set_categories` method to change them:

```
[30]: actual_categories = ['a', 'b', 'c', 'd', 'e']
      cat_s2 = cat_s.cat.set_categories(actual_categories)
      cat_s2
```

```
[30]: 0    a
      1    b
      2    c
      3    d
      4    a
      5    b
      6    c
      7    d
      dtype: category
      Categories (5, object): ['a', 'b', 'c', 'd', 'e']
```

While it appears that the data is unchanged, the new categories will be reflected in operations that use them. For example, `value_counts` respects the categories, if present:

```
[31]: cat_s.value_counts()
```

```
[31]: d    2
      c    2
      b    2
      a    2
      dtype: int64
```

```
[32]: cat_s2.value_counts()
```

```
[32]: d    2
      c    2
      b    2
      a    2
      e    0
      dtype: int64
```

In large datasets, categoricals are often used as a convenient tool for memory savings and better performance. After you filter a large DataFrame or Series, many of the categories may not appear in the data. To help with this, we can use the `remove_unused_categories` method to trim unobserved categories:

```
[33]: cat_s3 = cat_s[cat_s.isin(['a', 'b'])]
      cat_s3
```

```
[33]: 0    a
      1    b
      4    a
      5    b
      dtype: category
      Categories (4, object): ['a', 'b', 'c', 'd']
```



```
[34]: cat_s3.cat.remove_unused_categories()
```

```
[34]: 0    a
      1    b
      4    a
      5    b
      dtype: category
      Categories (2, object): ['a', 'b']
```

0.4 Table 12-1. Categorical methods for Series in pandas

Method → Description

add_categories → Append new (unused) categories at end of existing categories

as_ordered → Make categories ordered

as_unordered → Make categories unordered

remove_categories → Remove categories, setting any removed values to null

remove_unused_categories → Remove any category values which do not appear in the data

rename_categories → Replace categories with indicated set of new category names; cannot change the number of categories

reorder_categories → Behaves like rename_categories, but can also change the result to have ordered categories

set_categories → Replace the categories with the indicated set of new categories; can add or remove categories

0.4.1 Creating dummy variables for modeling

When you're using statistics or machine learning tools, you'll often transform categorical data into dummy variables, also known as one-hot encoding. This involves creating a DataFrame with a column for each distinct category; these columns contain 1s for occurrences of a given category and 0 otherwise.

Consider the previous example:

```
[35]: cat_s = pd.Series(['a', 'b', 'c', 'd'] * 2, dtype='category')
```

As mentioned previously in Chapter 7, the `pandas.get_dummies` function converts this one-dimensional categorical data into a DataFrame containing the dummy variable:

```
[36]: pd.get_dummies(cat_s)
```

```
[36]:   a  b  c  d
      0  1  0  0  0
      1  0  1  0  0
      2  0  0  1  0
      3  0  0  0  1
```

```
4  1  0  0  0
5  0  1  0  0
6  0  0  1  0
7  0  0  0  1
```

0.5 12.2 Advanced GroupBy Use

0.5.1 Group Transforms and “Unwrapped” GroupBys

In Chapter 10 we looked at the `apply` method in grouped operations for performing transformations. There is another built-in method called `transform`, which is similar to `apply` but imposes more constraints on the kind of function you can use:

- It can produce a scalar value to be broadcast to the shape of the group
- It can produce an object of the same shape as the input group
- It must not mutate its input

Let’s consider a simple example for illustration:

```
[37]: df = pd.DataFrame({'key': ['a', 'b', 'c'] * 4, 'value': np.arange(12.)})
df
```

```
[37]:
```

	key	value
0	a	0.0
1	b	1.0
2	c	2.0
3	a	3.0
4	b	4.0
5	c	5.0
6	a	6.0
7	b	7.0
8	c	8.0
9	a	9.0
10	b	10.0
11	c	11.0

Here are the group means by key:

```
[38]: g = df.groupby('key').value
g.mean()
```

```
[38]: key
a    4.5
b    5.5
c    6.5
Name: value, dtype: float64
```

Suppose instead we wanted to produce a Series of the same shape as `df['value']` but with values

replaced by the average grouped by 'key'. We can pass the function `lambda x: x.mean()` to transform:

```
[39]: g.transform(lambda x: x.mean())
```

```
[39]: 0      4.5
      1      5.5
      2      6.5
      3      4.5
      4      5.5
      5      6.5
      6      4.5
      7      5.5
      8      6.5
      9      4.5
     10      5.5
     11      6.5
      Name: value, dtype: float64
```

For built-in aggregation functions, we can pass a string alias as with the `GroupBy.agg` method:

```
[40]: g.transform('mean')
```

```
[40]: 0      4.5
      1      5.5
      2      6.5
      3      4.5
      4      5.5
      5      6.5
      6      4.5
      7      5.5
      8      6.5
      9      4.5
     10      5.5
     11      6.5
      Name: value, dtype: float64
```

Like `apply`, `transform` works with functions that return `Series`, but the result must be the same size as the input. For example, we can multiply each group by 2 using a `lambda` function:

```
[41]: g.transform(lambda x: x * 2)
```

```
[41]: 0      0.0
      1      2.0
      2      4.0
      3      6.0
      4      8.0
      5     10.0
      6     12.0
```

```
7      14.0
8      16.0
9      18.0
10     20.0
11     22.0
Name: value, dtype: float64
```

As a more complicated example, we can compute the ranks in descending order for each group:

```
[42]: g.transform(lambda x: x.rank(ascending=False))
```

```
[42]: 0      4.0
      1      4.0
      2      4.0
      3      3.0
      4      3.0
      5      3.0
      6      2.0
      7      2.0
      8      2.0
      9      1.0
     10      1.0
     11      1.0
Name: value, dtype: float64
```

Consider a group transformation function composed from simple aggregations:

```
[43]: def normalize(x):
      return (x - x.mean()) / x.std()
```

We can obtain equivalent results in this case either using transform or apply:

```
[44]: g.transform(normalize)
```

```
[44]: 0     -1.161895
      1     -1.161895
      2     -1.161895
      3     -0.387298
      4     -0.387298
      5     -0.387298
      6      0.387298
      7      0.387298
      8      0.387298
      9      1.161895
     10      1.161895
     11      1.161895
Name: value, dtype: float64
```

```
[45]: g.apply(normalize)
```

```
[45]: 0    -1.161895
      1    -1.161895
      2    -1.161895
      3    -0.387298
      4    -0.387298
      5    -0.387298
      6     0.387298
      7     0.387298
      8     0.387298
      9     1.161895
     10     1.161895
     11     1.161895
      Name: value, dtype: float64
```

Built-in aggregate functions like ‘mean’ or ‘sum’ are often much faster than a general apply function. These also have a “fast path” when used with transform. This allows us to perform a so-called unwrapped group operation:

```
[46]: g.transform('mean')
```

```
[46]: 0     4.5
      1     5.5
      2     6.5
      3     4.5
      4     5.5
      5     6.5
      6     4.5
      7     5.5
      8     6.5
      9     4.5
     10     5.5
     11     6.5
      Name: value, dtype: float64
```

```
[47]: normalized = (df['value'] - g.transform('mean')) / g.transform('std')
      normalized
```

```
[47]: 0    -1.161895
      1    -1.161895
      2    -1.161895
      3    -0.387298
      4    -0.387298
      5    -0.387298
      6     0.387298
      7     0.387298
      8     0.387298
      9     1.161895
     10     1.161895
```

```
11      1.161895
Name: value, dtype: float64
```

While an unwrapped group operation may involve multiple group aggregations, the overall benefit of vectorized operations often outweighs this.

0.6 Grouped Time Resampling

For time series data, the `resample` method is semantically a group operation based on a time intervalization. Here's a small example table:

```
[48]: N = 15
times = pd.date_range('2017-05-20 00:00', freq='1min', periods=N)
df = pd.DataFrame({'time': times, 'value': np.arange(N)})
df
```

```
[48]:
```

	time	value
0	2017-05-20 00:00:00	0
1	2017-05-20 00:01:00	1
2	2017-05-20 00:02:00	2
3	2017-05-20 00:03:00	3
4	2017-05-20 00:04:00	4
5	2017-05-20 00:05:00	5
6	2017-05-20 00:06:00	6
7	2017-05-20 00:07:00	7
8	2017-05-20 00:08:00	8
9	2017-05-20 00:09:00	9
10	2017-05-20 00:10:00	10
11	2017-05-20 00:11:00	11
12	2017-05-20 00:12:00	12
13	2017-05-20 00:13:00	13
14	2017-05-20 00:14:00	14

Here, we can index by 'time' and then resample:

```
[49]: df.set_index('time').resample('5min').count()
```

```
[49]:
```

	value
time	
2017-05-20 00:00:00	5
2017-05-20 00:05:00	5
2017-05-20 00:10:00	5

Suppose that a DataFrame contains multiple time series, marked by an additional group key column:

```
[50]: df2 = pd.DataFrame({'time': times.repeat(3), 'key': np.tile(['a', 'b', 'c'], 3), 'value': np.arange(N * 3)})
df2[:7]
```

```
[50]:
```

	time	key	value
0	2017-05-20 00:00:00	a	0.0
1	2017-05-20 00:00:00	b	1.0
2	2017-05-20 00:00:00	c	2.0
3	2017-05-20 00:01:00	a	3.0
4	2017-05-20 00:01:00	b	4.0
5	2017-05-20 00:01:00	c	5.0
6	2017-05-20 00:02:00	a	6.0

To do the same resampling for each value of 'key', we introduce the pandas.Time Grouper object:

```
[54]: time_key = pd.Grouper(freq='5min')
```

```
[ ]:
```

We can then set the time index, group by 'key' and time_key, and aggregate:

```
[55]: resampled = (df2.set_index('time').groupby(['key', time_key]).sum())
resampled
```

```
[55]:
```

	key	time	value
a	2017-05-20 00:00:00	30.0	
	2017-05-20 00:05:00	105.0	
	2017-05-20 00:10:00	180.0	
b	2017-05-20 00:00:00	35.0	
	2017-05-20 00:05:00	110.0	
	2017-05-20 00:10:00	185.0	
c	2017-05-20 00:00:00	40.0	
	2017-05-20 00:05:00	115.0	
	2017-05-20 00:10:00	190.0	

```
[56]: resampled.reset_index()
```

```
[56]:
```

	key	time	value
0	a	2017-05-20 00:00:00	30.0
1	a	2017-05-20 00:05:00	105.0
2	a	2017-05-20 00:10:00	180.0
3	b	2017-05-20 00:00:00	35.0
4	b	2017-05-20 00:05:00	110.0
5	b	2017-05-20 00:10:00	185.0
6	c	2017-05-20 00:00:00	40.0
7	c	2017-05-20 00:05:00	115.0
8	c	2017-05-20 00:10:00	190.0

One constraint with using TimeGrouper is that the time must be the index of the Series or DataFrame

0.7 12.3 Techniques for Method Chaining

When applying a sequence of transformations to a dataset, you may find yourself creating numerous temporary variables that are never used in your analysis. Consider this example, for instance:

```
[59]: # df = load_data()
      # df2 = df[df['col2'] < 0]
      # df2['col1_demeaned'] = df2['col1'] - df2['col1'].mean()
      # result = df2.groupby('key').col1_demeaned.std()
```

While we're not using any real data here, this example highlights some new methods. First, the `DataFrame.assign` method is a functional alternative to column assignments of the form `df[k] = v`. Rather than modifying the object in-place, it returns a new `DataFrame` with the indicated modifications. So these statements are equivalent:

```
[60]: # # Usual non-functional way
      # df2 = df.copy()
      # df2['k'] = v
      # # Functional assign way
      # df2 = df.assign(k=v)
```

Assigning in-place may execute faster than using `assign`, but `assign` enables easier method chaining:

```
[61]: # result = (df2.assign(col1_demeaned=df2.col1 - df2.col2.mean())
      #         .groupby('key')
      #         .col1_demeaned.std())
```

I used the outer parentheses to make it more convenient to add line breaks.

One thing to keep in mind when doing method chaining is that you may need to refer to temporary objects. In the preceding example, we cannot refer to the result of `load_data` until it has been assigned to the temporary variable `df`. To help with this, `assign` and many other pandas functions accept function-like arguments, also known as callables.

To show callables in action, consider a fragment of the example from before:

```
[62]: # df = load_data()
      # df2 = df[df['col2'] < 0]
```

This can be rewritten as:

```
[63]: # df = (load_data()
      #      [lambda x: x['col2'] < 0])
```

Here, the result of `load_data` is not assigned to a variable, so the function passed into `[]` is then bound to the object at that stage of the method chain.

We can continue, then, and write the entire sequence as a single chained expression:

```
[64]: # result = (load_data()
      #      [lambda x: x.col2 < 0]
      #      .assign(col1_demeaned=lambda x: x.col1 - x.col1.mean()))
```



```
# .groupby('key')
# .col1_demeaned.std()
```

Whether you prefer to write code in this style is a matter of taste, and splitting up the expression into multiple steps may make your code more readable.

0.8 The pipe Method

You can accomplish a lot with built-in pandas functions and the approaches to method chaining with callables that we just looked at. However, sometimes you need to use your own functions or functions from third-party libraries. This is where the pipe method comes in.

Consider a sequence of function calls:

```
[66]: # a = f(df, arg1=v1)
      # b = g(a, v2, arg3=v3)
      # c = h(b, arg4=v4)
```

When using functions that accept and return Series or DataFrame objects, you can rewrite this using calls to pipe:

```
[67]: # result = (df.pipe(f, arg1=v1)
      # .pipe(g, v2, arg3=v3)
      # .pipe(h, arg4=v4))
```

The statement `f(df)` and `df.pipe(f)` are equivalent, but pipe makes chained invocation easier.

A potentially useful pattern for pipe is to generalize sequences of operations into reusable functions. As an example, let's consider subtracting group means from a column:

```
[68]: # g = df.groupby(['key1', 'key2'])
      # df['col1'] = df['col1'] - g.transform('mean')
```

Suppose that you wanted to be able to demean more than one column and easily change the group keys. Additionally, you might want to perform this transformation in a method chain. Here is an example implementation:

```
[69]: # def group_demean(df, by, cols):
      # result = df.copy()
      # g = df.groupby(by)
      # for c in cols:
      # result[c] = df[c] - g[c].transform('mean')
      # return result
```

Then it is possible to write:

```
[70]: # result = (df[df.col1 < 0].pipe(group_demean, ['key1', 'key2'], ['col1']))
```

```
[ ]:
```