

Chapter_9_Embedding_a_Machine_Learning_Model_into_a_Web_Application

March 19, 2024

0.1 Serializing fitted Scikit-Learn Estimators

```
[6]: from nltk.corpus import stopwords
stop = stopwords.words('english')
```

```
[7]: import numpy as np
import re
from nltk.corpus import stopwords
stop = stopwords.words('english')
def tokenizer(text):
    text = re.sub('<[^\>]*>', '', text)
    emoticons = re.findall('(?:::|;|=)(?:-)?(?:\)|\(|D|P)', text.lower())
    text = re.sub('[\W]+', ' ', text.lower()) \
+ ' '.join(emoticons).replace('-', '')
    tokenized = [w for w in text.split() if w not in stop]
    return tokenized
```

```
[8]: def stream_docs(path):
    with open(path, 'r', encoding='utf-8') as csv:
        next(csv) # skip header
        for line in csv:
            text, label = line[:-3], int(line[-2])
            yield text, label
```

```
[9]: def get_minibatch(doc_stream, size):
    docs, y = [], []
    try:
        for _ in range(size):
            text, label = next(doc_stream)
            docs.append(text)
            y.append(label)
    except StopIteration:
        return None, None
    return docs, y
```

```
[10]: from sklearn.feature_extraction.text import HashingVectorizer
      from sklearn.linear_model import SGDClassifier
      vect =
      ↪HashingVectorizer(decode_error='ignore',n_features=2**21,preprocessor=None,tokenizer=tokeni
      clf = SGDClassifier(loss='log', random_state=1, max_iter=1)
      doc_stream = stream_docs(path='movie_data.csv')
```

```
[11]: import pyprind
      pbar = pyprind.ProgBar(45)
      classes = np.array([0, 1])
      for _ in range(45):
          X_train, y_train = get_minibatch(doc_stream, size=1000)
          if not X_train:
              break
          X_train = vect.transform(X_train)
          clf.partial_fit(X_train, y_train, classes=classes)
          pbar.update()
```

0% [#####] 100% | ETA: 00:00:00
Total time elapsed: 00:00:28

```
[12]: import pickle
      import os
      dest = os.path.join('movieclassifier', 'pkl_objects')
```

```
[13]: if not os.path.exists(dest):
      os.makedirs(dest)
      pickle.dump(stop,open(os.path.join(dest, 'stopwords.pkl'),'wb'),protocol=4)
      pickle.dump(clf,open(os.path.join(dest, 'classifier.pkl'), 'wb'),protocol=4)
```

Go to the movieclassifier directory and run the code under untitled.ipynb file

0.2 Setting up an SQLite database for data storage

check moviesclassifier director and untitled ipynb file

1 Turning the movie classifier into a web application

```
[1]: # run app.py in current location
```

```
[ ]:
```