

Name - Atansha Sundaryal
University roll no. - 2023020
Subject - Operating System

Atansha Sundaryal

Ques 2 Write a C program to implement Scan Disk Scheduling Algorithm & Calculate the total distance that disk arm moves.

Code :-

```
#include <stdio.h>
int absoluteValue (int);
void main ()
{
    int
    queue [25], n, headposition, i, j, k, seek = 0,
    maxrange,
    difference, temp, queue 1 [20], queue 2 [20], tc
    mp1 = 0, temp 2 = 0;
    float average Seek Time;
    printf ("Enter the maximum range of Disk:");
    scanf ("%d", &maxrange);
    printf ("Enter the number of queue requests:");
    scanf ("%d", &n);
    printf ("Enter the initial head position:");
    scanf ("%d", &headposition);
    printf ("Enter the disk positions to be read(queue):");
    for (i = 1; i <= n; i++)
    {
        scanf ("%d", &temp);
        if (temp > headposition)
        {
            queue 1 [temp 1] = temp;
            temp 1 ++;
        }
    }
```

Atansha Sundaryal

Name - Akansha Sundariyal
University roll no. - 2023020
Subject - operating System

Akansha Sundariyal

```
else
{
    queue2[temp2] = temp;
    temp2++;
}
}

for (i=0; i<temp1-1; i++)
{
    for (j=i+1; j<temp1; j++)
    {
        if (queue1[i] > queue1[j])
        {
            temp = queue1[i];
            queue1[i] = queue1[j];
            queue1[j] = temp;
        }
    }
}

for (i=0; i<temp2-1; i++)
{
    for (j=i+1; j<temp2; j++)
    {
        if (queue2[i] < queue2[j])
        {
            temp = queue2[i];
            queue2[i] = queue2[j];
            queue2[j] = temp;
        }
    }
}
}
```


Name - Akansha Sundariyal
University roll no. - 2023020
Subject - operating system

Akansha Sundariyal

```
for (i=1, j=0; j < temp1; i++, j++)
{
    queue[i] = queue1[j];
}
queue[i] = maxrange;
for (i=temp1+2, j=0; j < temp2; i++, j++)
{
    queue[i] = queue2[j];
}
queue[i] = 0;
queue[0] = headposition;
for (j=0; j < n; j++)
{
    difference = absolute value (queue[j+1] - queue[j]);
    seek = seek + difference;
    printf ("Disk head moves from position %d to %d with  
seek %d \n", queue[j], queue[j+1], difference);
}
average seek Time = seek / (float) n;
printf ("Total seek Time = %d \n", seek);
printf ("Average seek Time = %f \n", average seek Time);
}

int absolute value (int x)
{
    if (x > 0)
    {
        return x;
    }
    else {
        return x * -1;
    }
}
```

Akansha Sundariyal

Enter the number of queue requests: 4
Enter the initial head position: 20
Enter the disk positions to be read(queue): 23
15
36
78
Disk head moves from position 20 to 23 with Seek 3
Disk head moves from position 23 to 36 with Seek 13
Disk head moves from position 36 to 78 with Seek 42
Disk head moves from position 78 to 200 with Seek 122
Disk head moves from position 200 to 15 with Seek 185
Total Seek Time= 365
Average Seek Time= 91.250000

...Program finished with exit code 0
Press ENTER to exit console.