

A PERFECT PLUMBING SOLUTION



WHY CHOOSE US?

Since establishing our presence in 1971, we have successfully diversified into manufacturing the widest range of pipes & fittings for Agricultural, Residential and Industrial applications. We have built a durable product range and have cemented our position as a true pioneer of the Piping Industry in India.

DUTRON CPVC PIPES AND FITTINGS

IS : 15778



CM/L-3808568

Key Features:

- High Tolerance to both High & Low Temperatures
- Resistant to Household Chemicals
- No Corrosion Led Longer Maintenance-Free Service Life
- Combustion Resistant
- Handles Pressure Requirements of any Industry's Process Plants
- Solvent Cement Makes It Easy to Install
- Affordable, Strong, Long-Lasting, Light in Weight
- Higher Abrasion Resistance
- Wide Range of Pipes (Copper Tube as per ASTM-D-2846 & Iron Tube as per ASTM-F-441)
- Wide Range of Fittings (As per ASTM-D-2846 (SDR-11) & ASTM-F-439(SCH-80))
- CPVC Compounds, sourced from Sekisui Chemical Ltd., Japan, Certified by NSF International USA)



Applications:

- Distribution of Hot & Cold Potable Water in Residential & Commercial Structures (Plumbing System)
- Ideal for Use in Fire-Fighting Systems (Sprinklers etc.)
- Used in Industries that deal with Corrosive Fluids

Working Pressure:

- SDR11 – @23°C 28.1kg/cm² and @82°C 7kg/cm²
- SDR13.5 – @23°C 22.5kg/cm² and @82°C 5.6kg/cm²

Available Sizes:

- Available from 15 mm to 150 mm I.D.

Also Available:

- High-Quality Solvent Cement Specially Formulated for CPVC

Specifications:

Nominal Pipe Size		Outer Diameter in (mm)		SDR 11				SDR 13.5			
				Wall Thickness in (mm)		Working Pressure at		Wall Thickness in (mm)		Working Pressure at	
inch	mm	Average	Tolerance	Minimum	Tolerance	kg/cm ²		Minimum	Tolerance	kg/cm ²	
½	15	0.625 (15.90)	±0.003 (±0.08)	0.068 (1.73)	±0.020 (±0.51)	28.1	7.0	0.055 (1.40)	±0.020 (±0.51)	22.5	5.6
¾	20	0.875 (22.20)	±0.003 (±0.08)	0.080 (2.03)	±0.020 (±0.51)	28.1	7.0	0.065 (1.65)	±0.020 (±0.51)	22.5	5.6
1	25	1.125 (28.60)	±0.003 (±0.08)	0.102 (2.59)	±0.020 (±0.51)	28.1	7.0	0.083 (2.12)	±0.020 (±0.51)	22.5	5.6
1¼	32	1.375 (34.90)	±0.003 (±0.08)	0.125 (3.18)	±0.020 (±0.51)	28.1	7.0	0.102 (2.59)	±0.020 (±0.51)	22.5	5.6
1½	40	1.625 (41.30)	±0.004 (±0.010)	0.148 (3.76)	±0.020 (±0.51)	28.1	7.0	0.120 (3.06)	±0.020 (±0.51)	22.5	5.6
2	50	2.125 (54.00)	±0.004 (±0.010)	0.193 (4.90)	±0.023 (±0.58)	28.1	7.0	0.157 (4.00)	±0.023 (±0.58)	22.5	5.6

Size mm (inch)	Outer Diameter in (mm)	Schedule 40 Wall Thickness in (mm)	Schedule 80 Wall Thickness in (mm)
65 (2½")	73.0 ± 0.18 (72.82 - 73.18)	5.16 - 5.77	7.01 - 7.85
80 (3")	88.9 ± 0.20 (88.7 - 89.1)	5.49 - 6.15	7.62 - 8.53
100 (4")	114.3 ± 0.23 (114.07 - 114.53)	6.02 - 6.73	8.56 - 9.58
150 (6")	168.3 ± 0.28 (168.02 - 168.58)	7.11 - 7.97	10.97 - 12.29

DUTRON HIFLO uPVC PLUMBING SYSTEM

Key Features:

- Lead Free
- Complete Range of Pipes as per ASTM D1785 & Fittings as per ASTM D2467
- Excellent Tensile & Impact Strength
- Non-Corrosive & Non-Toxic
- Longer Service Life and a more Cost-Effective Alternative to the GI Pipe System
- Flat & Smooth Surface
- Solvent Cement Joints make the Pipes Leak-Proof and Easy to Install
- 100% Lead-Free - Maintains the Purity of Water
- It is UV-Stabilized and Harmless in the Outer Atmosphere



Applications:

- High-Pressure Water Distribution Plumbing in Residential, Commercial & Industrial Buildings

Working Pressure:

- Schedule 40 – 12.4kg/cm² to 41.4kg/cm² @23°C
- Schedule 80 – 19.3kg/cm² to 58.6kg/cm² @23°C

Available Sizes:

- Available from 15 mm to 150 mm I.D.

Also Available:

- High-Quality Solvent Cement

Specifications:

Nominal Bore		Mean Outside Diameter (mm)		PVC Schedule 40			PVC Schedule 80		
				Wall Thickness		Working Pressure at 23°C	Wall Thickness		Working Pressure at 23°C
(inch)	(mm)	(min.)	(max.)	(min.)	(max.)	kg/cm ²	(min.)	(max.)	kg/cm ²
½	15	21.2	21.5	2.8	3.3	41.4	3.7	4.2	58.6
¾	20	26.6	26.8	2.9	3.4	33.1	3.9	4.4	47.6
1	25	33.3	33.6	3.4	3.9	31.1	4.6	5.0	43.4
1¼	32	42.0	42.3	3.6	4.1	25.5	4.9	5.4	35.9
1½	40	48.1	48.4	3.7	4.2	22.8	5.1	5.7	32.4
2	50	60.2	60.6	3.9	4.4	19.3	5.5	6.2	27.6
2½	65	72.8	73.2	5.2	5.8	20.7	7.0	7.8	29.0
3	75	88.7	89.1	5.5	6.1	17.9	7.6	8.5	25.5
4	100	114.1	114.5	6.0	6.7	15.2	8.6	9.6	22.1
6	150	168.3	168.5	7.1	7.9	12.4	11.0	12.3	19.3

Consumption of Solvent Cement:

Pipe (inch)	½"	¾"	1"	1¼"	1½"	2"	3"	4"	6"
Size (mm)	15	20	25	32	40	50	75	100	150
No of Joints/Ltr.	274	169	148	106	74	42	32	21	6

DUTRON UNDERGROUND DRAINAGE PVC-U PIPES

Key Features:

- Lead Free
- Specially Designed for Underground Non-Pressure Applications
- Simple Installation Process
- Hygienic and Water-Tight
- Smooth Inner Surface for Better Water Flow
- Lower Maintenance & Installation Costs as Compared to Conventional Pipes
- Excellent Stiffness and Impact Resistance
- Easy to join when using uPVC Joints & Fittings Compared to Conventional Pipes
- Resistant to Soil and Liquid Chemicals
- Longer Service Life

Applications:

- Underground Drainage Usage in Residential and Commercial Buildings

Available Sizes:

- Available in 3-meter & 6-meter lengths
- Available from 110mm to 315mm

IS : 15328



CM/L-7200108090



Specifications:

Wall Thickness in mm	SN 2		SN 4		SN 8	
SDR	51		41		34	
OD (mm)	Wall Thickness in mm					
	Min.	Max.	Min.	Max.	Min.	Max.
110	-	-	-	-	3.2	3.7
160	3.2	3.7	4.0	4.6	4.7	5.4
200	3.9	4.5	4.9	5.6	5.9	6.7
250	4.9	5.6	6.2	7.0	7.3	8.3
315	6.2	7.0	7.7	8.7	9.2	10.4

DUTRON SWR uPVC PIPES AND FITTINGS

Key Features:

- Lead Free
- Superior Quality Standards with a Wide Range of Pipes & Fittings (IS 14735) (IS 13592)
- Easy to Carry and Transfer
- Chemical, Fire and Corrosion-Resistant
- Easy Installation and Maintenance
- Excellent Durability and Longer Life
- Leakage-Free Rubber Joints
- UV Stabilized

Applications:

- Wastewater Management Systems;
Drainage of Soil, Waste and Rainwater
in Residential, Commercial and Industrial Structures

Available Sizes:

- Available from 75 mm to 160 mm O.D.



Specifications:

Size (mm)	OD (mm)		Wall Thickness (Type A) in mm		Wall Thickness (Type B) in mm	
	Min.	Max.	Min.	Max.	Min.	Max.
75	75.0	75.3	1.8	2.2	3.2	3.8
90	90.0	90.3	1.9	2.3	3.2	3.8
110	110.0	110.4	2.2	2.7	3.2	3.8
160	160.0	160.5	3.2	3.8	4.0	4.6

DUTRON UPVC PRESSURE PIPES & FITTINGS

Key Features:

- Light weight
- Lead free
- Maintenance Free - Resistant to any type of corrosion
- Safe for conveying potable water
- Self-extinguishing quality
- Conforming to IS 4985:2000 & IS 7834/1987



Applications:

- Irrigation in agriculture, potable water supply, conveying of water under pressure.

Available Sizes:

- Available from 20 mm to 400 mm O.D.

Specifications:

IS 4985 : 2000 (Extract)		Wall Thickness for working pressure classes (mm)									
Outside Diameter (mm)	Tolerance on outside diameter (mm)	Class 1 2.5 kg/cm ²		Class 2 4 kg/cm ²		Class 3 6 kg/cm ²		Class 5 10 kg/cm ²		Plumbing Pipes	
		(min.)	(max.)	(min.)	(max.)	(min.)	(max.)	(min.)	(max.)		
20	+0.3	-	-	-	-	-	-	1.1	1.5	2.8	3.3
25	+0.3	-	-	-	-	-	-	1.4	1.8	2.9	3.4
32	+0.3	-	-	-	-	-	-	1.8	2.2	3.4	3.9
40	+0.3	-	-	-	-	1.4	1.8	2.2	2.7	3.6	4.2
50	+0.3	-	-	-	-	1.7	2.1	2.8	3.3	3.7	4.3
63	+0.3	-	-	1.5	1.9	2.2	2.7	3.5	4.1	-	-
75	+0.3	-	-	1.8	2.2	2.6	3.1	4.2	4.9	-	-
90	+0.3	1.3	1.7	2.1	2.6	3.1	3.7	5.0	5.7	-	-
110	+0.4	1.6	2.0	2.5	3.0	3.7	4.3	6.1	7.1	-	-
125	+0.5	1.8	2.2	2.9	3.4	4.3	5.0	6.9	8.0	-	-
140	+0.5	2.0	2.4	3.2	3.8	4.8	5.5	7.7	8.9	-	-
160	+0.5	2.3	2.8	3.7	4.3	5.4	6.2	8.8	10.2	-	-
180	+0.6	2.6	3.1	4.2	4.9	6.1	7.1	9.9	11.4	-	-
200	+0.6	2.9	3.4	4.6	5.3	6.8	7.9	11.0	12.7	-	-
225	+0.7	3.3	3.9	5.2	6.0	7.6	8.8	12.4	14.3	-	-
250	+0.8	3.6	4.2	5.7	6.5	8.5	9.8	13.8	15.9	-	-
280	+0.9	4.1	4.8	6.4	7.4	9.5	11.0	15.4	17.8	-	-
315	+1.0	4.6	5.3	7.2	8.3	10.7	12.4	17.3	19.9	-	-
355	+1.1	5.1	5.9	8.1	9.4	12.0	13.8	19.6	22.6	-	-
400	+1.2	5.8	6.7	9.1	10.5	13.5	15.6	22.0	25.3	-	-

DUTRON WATER TANKS

Key Features:

- 100% Virgin Material
- Food Grade Material - Safe for Drinking Water
- Ribbed Design adds Strength and Durability
- Multi-Layer Protection with Dual Foam Technology
- Threaded Lid with Air Vent makes Water Hygienic and Odourless
- Robust and Visually Appealing Design
- Anti-Bacterial Properties keep the Water Safe
- Loft Tank with Dual Layered UV Stabilized Protection
- Capacity range 100 to 10,000 Litres



Applications:

- Ideal for bungalow, apartment, school, college, office complex, construction site, industries and for agricultural uses

IS : 12701



CM/L-7200101581

Available Sizes & Range

- Triple Layer Water Tanks - 200 - 10,000 Litres
- ISI Tanks - 200 - 5000 Litres
- Loft Tanks - 100 - 500 Litres
- Double Layer Loft Tanks - 100 - 500 Litres
- Chemical Tanks - 500 - 10,000 Litres
- 2/3/4/5 Layers



OUR PRODUCT PORTFOLIO

Dutron Pipes & Fittings

- CPVC Pipes & Fittings
- Hiflo Pipes & Fittings
- PVC Agri Pipes & Fittings
- SWR Pipes & Fittings
- Casing Pipes
- Column Pipes
- Drain Pipes
- HDPE, DWC Pipes & Fittings

Dutron Kanaflex

- Medium Duty Hose
- Heavy Duty Hose
- Steel Wire Hose
- Non Toxic Hose
- Oil Hose
- Duct Hose

Duplon

- High Pressure Air Hose
- Water, Garden, Construction
- Weldings Hose (Red & Blue)
- Spray or Power Hose
- Rock Drill Hose
- Flat Hose
- Car Washing Hose

Dutroflex Corrugated Pipes

Dutron Water Tanks



DUTRON POLYMERS LIMITED

Near Mithakhali Underbridge
Navrangpura, Ahmedabad 380 009
Gujarat, INDIA

Tel: +91 79 2656 1849, +91 79 2642 7522

Email: sales@dutronindia.com

Website: www.dutronindia.com

