

A Hello world program

Public Class Main {

public static void main (String []) {

System.out.println("Hello Java world!");

}

}

B variable & Data type

Public Class Main {

public static void main (String []) {

int age = 18;

double height = 5.9;

boolean isStudent = true;

char grade = 'A';

String name = "Ankit";

System.out.println("Age" + age);

System.out.println("Height:" + height);

System.out.println("Student:" + isStudent);

System.out.println("Grade:" + grade);

System.out.println("Name:" + name);

}
}

output

Age = 18
Height = 5.9
Student : True
Grade : A
Name : Ankit

C Operators program

• Arithmetic operators.

```
public main class Main {  
    public static void main (String [] ) {  
        int a = 10;  
        int b = 5;
```

```
        System.out.println ("Arithmetic operators:");  
        System.out.println ("a+b = " + (a+b));  
        System.out.println ("a-b = " + (a-b));  
        System.out.println ("a*b = " + (a*b));  
        System.out.println ("a/b = " + (a/b));  
        System.out.println ("a%.b = " + (a%b));  
    }  
}
```

}

out put

$$a+b = 15$$

$$a-b = 5$$

$$a \times b = 50$$

$$a/b = 2$$

$$a \% b = 0$$

Relational Operators

```
public class Main {
```

```
    public static void main(String [] args) {
```

```
        System.out.println("In Relational operators:");
```

```
        System.out.println("a > b = " + (a > b));
```

```
        System.out.println("a < b = " + (a < b));
```

```
        System.out.println("a == b = " + (a == b));
```

```
        System.out.println("a != b = " + (a != b));
```

```
    }
```

```
}
```

Output

a > b = true

a < b = false

a == b = false

a != b = true

logical operators

```
public class Main {  
    public static void main (String []) {
```

```
        boolean x = true;
```

```
        boolean y = false;
```

```
        System.out.println ("In logical operators:");
```

```
        System.out.println ("x && y = " + (x && y));
```

```
        System.out.println ("x || y = " + (x || y));
```

```
        System.out.println ("!x = " + (!x));
```

```
    }
```

```
}
```

Output

x && y = false

x || y = true

!x = false

1) User input program

```
import java.util. Scanner;
```

```
public class Main {
```

```
    public static void main (String [] ) {
```

```
        Scanner SC = new Scanner (System.in);
```

```
        System.out. print ("Enter first number : ");
        int num1 = SC.nextInt();
```

```
        System.out. print ("Enter second number : ");
        int num2 = SC. nextInt ();
```

```
        int Sum = num1 + num2;
```

```
        System.out. println ("Sum = " + Sum);
```

```
        SC. Close ();
```

```
    }
```

```
}
```

Output

Enter first number : 12

Enter second number : 14

Sum = 26