

JQuery

2022

Install

```
<head>  
  <script src="jquery-3.5.1.min.js"></script>  
</head>
```

```
<head>  
  
<script sr  
c="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js">  
  </script>  
</head>
```

Syntax

```
$(selector).action()
```

Place JQuery code on head and run it after the document is loaded (ready).

```
$(document).ready(function(){  
  
  // jQuery methods go here...  
  
});
```

Selectors

```
$("p")
```

selects all <p>

```
$("#test")
```

selects id="test"

```
$(".test")
```

selects the class="test"

```
$(this)
```

selects the current HTML element

```
$("p:first")
```

selects the first <p> element

```
$("p.intro")
```

selects all <p> with class="intro"

```
$("#*")
```

selects all elements in the document

```
$("[href]")
```

selects all elements with href attribute

```
$("tr:even")
```

selects all even table rows

Events

```
$("#p").click(function(){  
    // action goes here!!  
});
```

Some events are:

- click
- dblclick
- mouseenter
- mouseleave
- mousedown
- mouseup
- keypress
- keydown
- keyup
- hover
- focus
- blur (when the element loses focus)
- css (applies a css action)
- on (attaches one or more event handlers on the selected element)

```
$("#p").on({  
    mouseenter: function(){  
        $(this).css("background-color", "lightgray");  
    },  
    mouseleave: function(){  
        $(this).css("background-color", "lightblue");  
    },  
    click: function(){  
        $(this).css("background-color", "yellow");  
    }  
});
```

Effects

show/hide

The optional speed parameter can take the following values: "slow", "fast", or milliseconds.

```
$( selector ).hide( speed, callback );
```

```
$( selector ).show( speed, callback );
```

toggle

```
$( selector ).toggle( speed, callback );
```

fade

```
$( selector ).fadeIn( speed, callback );
```

```
$( selector ).fadeOut( speed, callback );
```

```
$( selector ).fadeToggle( speed, callback );
```

```
$( selector ).fadeTo( speed, opacity, callback );
```

Slide

```
$( selector ).slideDown( speed, callback );
```

```
$( selector ).slideUp( speed, callback );
```

```
$( selector ).slideToggle( speed, callback );
```

Animation

```
$( selector ).animate( { params }, speed, callback );
```

params defines the CSS property to animate. For example,

```
$( "button" ).click( function() {  
    $( "div" ).animate( { left: '250px' } );  
} );
```

```
$("#button").click(function(){
    $("#div").animate({
        left: '250px',
        opacity: '0.5',
        height: '150px',
        width: '150px'
    });
});
```

Stop

```
$(selector).stop(stopAll,goToEnd);
```

Stops an animation or an effect before it is finished.

Chaining

```
$("#p1").css("color", "red").slideUp(2000).slideDown(2000);
```

Διαδοχικές ενέργειες στην ίδια γραμμή κώδικα.

DOM Manipulation

Get or Set

- `text()` - Gets or sets the text content of selected elements
- `html()` - Gets or sets the content of selected elements (including HTML markup)
- `val()` - Gets or sets the value of form fields
- `attr()` - Gets attribute values.

Gets

```
$("#test").text()
```

```
$("#w3s").attr("href")
```

Sets

```
$("#test1").text("Hello world!")
```

```
$("#w3s").attr("href", "https://www.w3schools.com/jquery/")
```

Add

- `append()` - Inserts content at the end of the selected elements
- `prepend()` - Inserts content at the beginning of the selected elements
- `after()` - Inserts content after the selected elements
- `before()` - Inserts content before the selected elements

Προσθέτει στο τέλος κάθε `<p>` το συγκεκριμένο κείμενο

```
$("#p").append("Some appended text.");
```

```
$("#body").append("text1", "txt2", "txt3");
```

```
$("#img").after("Some text after");
```

```
$("#img").before("Some text before");
```

Remove

- `remove()` - Removes the selected element (and its child elements)
- `empty()` - Removes the child elements from the selected element

Removes the `<p>` elements with classes `test` or `demo`:

```
$("#p").remove(".test, .demo");
```

Manipulate CSS

- `addClass()` - Adds one or more classes to the selected elements
- `removeClass()` - Removes one or more classes from the selected elements
- `toggleClass()` - Toggles between adding/removing classes from the selected elements
- `css()` - Sets or returns the style attribute

```
$("#div").addClass("important");
```

```
$("#h1, h2, p").removeClass("blue");
```

```
$("#h1, h2, p").toggleClass("blue");
```

```
$("#div1").addClass("important blue");
```

```
$("#p").css("background-color");
```

 gets the background color

```
$("#p").css("background-color", "yellow");
```

 sets the background color

```
$("#p").css({"background-color": "yellow", "font-size": "200%"});
```

 sets multiple attributes

Dimensions

- `width()` : sets or returns the width of an element (excludes padding, border and margin)
- `height()` : sets or returns the height of an element (excludes padding, border and margin)
- `innerWidth()` : returns the width of an element (includes padding)
- `innerHeight()` : returns the height of an element (includes padding)
- `outerWidth()` : returns the width of an element (includes padding and border)
- `outerHeight()` : returns the height of an element (includes padding and border)

The `outerWidth(true)` method returns the width of an element (includes padding, border, and margin).

The `outerHeight(true)` method returns the height of an element (includes padding, border, and margin).