

Auto Configuration Setup

This is a tool that automates the configuration of the IDEAL application. It can be used to configure both the technical and functional aspects of the application.

Prerequisites

- **Node.js**
- **Git**

Instructions

1. Clone the repository:

```
$ git clone https://gitlab.credenceanalytics.com/apac-development-team/interface/common-module/system-configuration-automation.git
```

2. Go to the `config` folder and open the `config.json` file. This is where you will need to specify the configuration for the tool.

```
$ cd system-configuration-automation/config  
$ open config.json
```

The following are the required parameters:

- **sourcepath** : The path to the source code for the IDEAL application.
- **wildfly_folder** : The name of the WildFly/JBoss folder.
- **war_folder** : The name of the WAR folder.
- **oracledb** : An array of objects that define the Oracle database connections.
- **JAVA_PATH** : The path to the Java installation.
- **quname** : The username for connecting to the message queue.
- **qpwd** : The password for the message queue user.
- **metabase** : An object that defines the Metabase configuration.
- **client_name** : The name of the client.
- **client_address** : The address of the client's location.
- **lcy_curr_main** : The main local currency.
- **gcy_curr_main** : The main global currency.
- **defaultDealLocationName** : The default location name for deals.
- **defaultDealLocationCode** : The default location code for deals.
- **default_payment_mode** : The default payment mode.
- **Default_Delivery_Location** : The default delivery location.
- **domesticcurrency** : The domestic currency.
- **globalcurrency** : The global currency.
- **groupcurrency** : The group currency.

Running the tool

Once you have configured the `config.json` file, you can run the tool by going to the `run` folder and running the following commands:

For Linux systems

- For technical configuration:

```
$ cd system-configuration-automation/run
$ sh run_techfile.sh
$ sh run_techdb.sh
```

- For functional configuration:

```
$ sh run_funcfile.sh
$ sh run_funcdb.sh
```

For Windows systems

Go to the `Run` folder.

- For technical configuration:

--- Double click on the `run_techfile.bat` file. --- Double click on the `run_techdb.bat` file.

- For functional configuration

--- Double click on the `run_funcfile.bat` file. --- Double click on the `run_funcdb.bat` file.

Notes The tool will create logs in the `log` folder and will also create backups of the previous files in the `filebackup` folder.

If you have any problems running the tool, please check the following:

- Make sure that you have the required prerequisites installed.
- Make sure that the `config.json` file is properly formatted.
- Make sure that the paths in the `config.json` file are correct.
- If you are still having problems, please contact the development team.