

Install Anaconda/Miniconda on local laptop

1. Install Anaconda/Miniconda if not done
2. conda create --name <Your Env Name> python=3.10
E.g. conda create -- name langflowdemo python=3.10
3. conda activate <Your Env Name>
4. pip install uv
5. uv pip install langflow
6. langflow run

Configure Models

1. Go to settings-> Model Providers
2. Configure OpenAI -> provide the Base URL and API Key. Make sure to enable gpt-4o-mini and text-embeddings-3-small model.

Flow 1: Ingest data into VectorStore (FAISS)

1. Create a new flow and give it a name
2. Drag and Drop the Read file component. Provide the file location (or directory location)
3. Add a Type Convert component and connect it to Read file component. Make sure the Type Convert output is set to the JSON.
4. Add a Recursive Character Text Splitter component and connect this to the Type Convert. Specify the chunk size and chunk overlap parameters.
5. Add an FAISS component and connect the Recursive Character Text Splitter component to the Ingest of FAISS.
6. Click on parameters and add the "Allow Dangerous Deserialization" parameter and enable it. This is to show that the source is trusted. Define the name of the index and also provide the persist location. Make sure that the index name is mentioned at the end of the persist location.
7. Add an Embeddings model and connect to the Embeddings endpoint of the FAISS. Make sure that the model is text-embedding-small-3 model.
8. Run the flow from FAISS component.
9. Make sure that the flow is built/run successfully.

Flow 2: Create a Chatbot Agent

1. Create a new flow and give it a name.
2. Drag and drop the FAISS component and give the same Index Name and the same persist location. Add the Allow Dangerous Deserialization. Make sure that "Tool" slider is enabled and the FAISS component shows "Toolset".
3. Add an embeddings model and connect to the Embeddings endpoint of the FAISS. Make sure that the model is text-embedding-small-3 model.
4. Add a "Tool calling Agent" to the flow. Use the model gpt-4o-mini.
5. Connect the FAISS component to the Tools input of Agent.
6. Add a new chat input component and connect it to the input of Agent.
7. Add a new chat output component and connect it to the output of Agent
8. Build the flow from the Agent and click on Playground to enter into a chat session to interact with the agent.