
STATISTICAL TABLES 1

Table A.1

Cumulative Standardized Normal Distribution



A(z) is the integral of the standardized normal distribution from $-\infty$ to z (in other words, the area under the curve to the left of z). It gives the probability of a normal random variable not being more than z standard deviations above its mean. Values of z of particular importance:

Z	A(z)	
1.645	0.9500	Lower limit of right 5% tail
1.960	0.9750	Lower limit of right 2.5% tail
2.326	0.9900	Lower limit of right 1% tail
2.576	0.9950	Lower limit of right 0.5% tail
3.090	0.9990	Lower limit of right 0.1% tail
3.291	0.9995	Lower limit of right 0.05% tail

Z	0.00	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09
0.0	0.5000	0.5040	0.5080	0.5120	0.5160	0.5199	0.5239	0.5279	0.5319	0.5359
0.1	0.5398	0.5438	0.5478	0.5517	0.5557	0.5596	0.5636	0.5675	0.5714	0.5753
0.2	0.5793	0.5832	0.5871	0.5910	0.5948	0.5987	0.6026	0.6064	0.6103	0.6141
0.3	0.6179	0.6217	0.6255	0.6293	0.6331	0.6368	0.6406	0.6443	0.6480	0.6517
0.4	0.6554	0.6591	0.6628	0.6664	0.6700	0.6736	0.6772	0.6808	0.6844	0.6879
0.5	0.6915	0.6950	0.6985	0.7019	0.7054	0.7088	0.7123	0.7157	0.7190	0.7224
0.6	0.7257	0.7291	0.7324	0.7357	0.7389	0.7422	0.7454	0.7486	0.7517	0.7549
0.7	0.7580	0.7611	0.7642	0.7673	0.7704	0.7734	0.7764	0.7794	0.7823	0.7852
0.8	0.7881	0.7910	0.7939	0.7967	0.7995	0.8023	0.8051	0.8078	0.8106	0.8133
0.9	0.8159	0.8186	0.8212	0.8238	0.8264	0.8289	0.8315	0.8340	0.8365	0.8389
1.0	0.8413	0.8438	0.8461	0.8485	0.8508	0.8531	0.8554	0.8577	0.8599	0.8621
1.1	0.8643	0.8665	0.8686	0.8708	0.8729	0.8749	0.8770	0.8790	0.8810	0.8830
1.2	0.8849	0.8869	0.8888	0.8907	0.8925	0.8944	0.8962	0.8980	0.8997	0.9015
1.3	0.9032	0.9049	0.9066	0.9082	0.9099	0.9115	0.9131	0.9147	0.9162	0.9177
1.4	0.9192	0.9207	0.9222	0.9236	0.9251	0.9265	0.9279	0.9292	0.9306	0.9319
1.5	0.9332	0.9345	0.9357	0.9370	0.9382	0.9394	0.9406	0.9418	0.9429	0.9441
1.6	0.9452	0.9463	0.9474	0.9484	0.9495	0.9505	0.9515	0.9525	0.9535	0.9545
1.7	0.9554	0.9564	0.9573	0.9582	0.9591	0.9599	0.9608	0.9616	0.9625	0.9633
1.8	0.9641	0.9649	0.9656	0.9664	0.9671	0.9678	0.9686	0.9693	0.9699	0.9706
1.9	0.9713	0.9719	0.9726	0.9732	0.9738	0.9744	0.9750	0.9756	0.9761	0.9767
2.0	0.9772	0.9778	0.9783	0.9788	0.9793	0.9798	0.9803	0.9808	0.9812	0.9817
2.1	0.9821	0.9826	0.9830	0.9834	0.9838	0.9842	0.9846	0.9850	0.9854	0.9857
2.2	0.9861	0.9864	0.9868	0.9871	0.9875	0.9878	0.9881	0.9884	0.9887	0.9890
2.3	0.9893	0.9896	0.9898	0.9901	0.9904	0.9906	0.9909	0.9911	0.9913	0.9916
2.4	0.9918	0.9920	0.9922	0.9925	0.9927	0.9929	0.9931	0.9932	0.9934	0.9936
2.5	0.9938	0.9940	0.9941	0.9943	0.9945	0.9946	0.9948	0.9949	0.9951	0.9952
2.6	0.9953	0.9955	0.9956	0.9957	0.9959	0.9960	0.9961	0.9962	0.9963	0.9964
2.7	0.9965	0.9966	0.9967	0.9968	0.9969	0.9970	0.9971	0.9972	0.9973	0.9974
2.8	0.9974	0.9975	0.9976	0.9977	0.9977	0.9978	0.9979	0.9979	0.9980	0.9981
2.9	0.9981	0.9982	0.9982	0.9983	0.9984	0.9984	0.9985	0.9985	0.9986	0.9986
3.0	0.9987	0.9987	0.9987	0.9988	0.9988	0.9989	0.9989	0.9989	0.9990	0.9990
3.1	0.9990	0.9991	0.9991	0.9991	0.9992	0.9992	0.9992	0.9992	0.9993	0.9993
3.2	0.9993	0.9993	0.9994	0.9994	0.9994	0.9994	0.9994	0.9995	0.9995	0.9995
3.3	0.9995	0.9995	0.9995	0.9996	0.9996	0.9996	0.9996	0.9996	0.9996	0.9997
3.4	0.9997	0.9997	0.9997	0.9997	0.9997	0.9997	0.9997	0.9997	0.9997	0.9998
3.5	0.9998	0.9998	0.9998	0.9998	0.9998	0.9998	0.9998	0.9998	0.9998	0.9998
3.6	0.9998	0.9998	0.9999							

.

Chapter 4

Special Continuous Distributions

Problems on Uniform , Exponential and Normal Distribution

- 1. A random variable X follows normal distribution with mean=4.35 and standard deviation 0.59. Find
- (a) P(4 < X < 5)
- (b) $P(X \ge 5.5)$

Ans:(a) 0.5867 (b) 0.0256

- 2. The time for a superglue to set can be treated as a random variable having normal distribution with mean 40 secs. Find its standard deviation if the probability is 0.16 that it will take on a value greater than 50 secs. Ans: 10.
- 3. The average monthly sales of 5000 firms are normally distributed with mean Rs. 36000 and standard deviation Rs. 10000. Find
- (a) number of firms with sales over Rs. 40000
- (b) percentage of firms with sales between Rs. 38500 and Rs. 41000.

Given, $P(0 \le z \le 0.4) = 0.1554, P(0 \le z \le 0.5) = 0.1915, P(0 \le z \le 0.25) = 0.0987$

Ans:(a) 1723 (b) 9.28%

- 4. The local authorities in a certain city installed 2000 electric lamps in a street of the city. If the lamps have an average life of 1000 burning hours with a standard deviation of 200 hours, then
- (i) What number of the lamps might be expected to fail in the first 700 burning hours?
- (ii) After what period of burning hours would we expect that 10% of the lamps

would have failed?

(iii) After what periods of burning hours would we expect 10% of the lamps to be still burning?

Ans: (i) 134 (ii) 744 (iii) 1256

- 5. Steel rods are manufactured to be 3cm in diameter but they are acceptable if they are inside the limits 2.99 cms and 3.01 cms. It is observed that 5% are rejected as oversize and 5% are rejected as undersize. Assuming that the diameters are normally distributed, find the mean and standard deviation of the distribution. Hence calculate, what would be the proportion of rejected rods if the permissible limits were widened to 2.985cms and 3.015cms? Ans: $\mu = 3$, $\sigma = 1/165$, 1.34%
- 6. Two chips are being considered for use in a certain system. The lifetime of chip 1 is modeled by a normal random variable with mean 20,000 hours and standard deviation 5000 hours. (The probability of negative lifetime is negligible.) The lifetime of chip 2 is also a normal random variable but with mean 22,000 hours and standard deviation 1000 hours. Which chip is preferred if the target lifetime of the system is 20,000 hours? 24,000 hours?
- 7. Find the mean and variance of the uniform distribution.
- 8. Find the mean and variance of the exponential distribution.
- 9. Buses arrive at a specified stop at 15 minutes interval starting at 7 am. That is, they arrive at 7,7:15,7:30 and so on. If a passenger arrives at the stop at a time that is uniformly distributed between 7 and 7:30, find the probability that he waits
- (a) less than 5 minutes for a bus
- (b) at least 12 minutes for a bus

Ans: (a) 1/3 (b) 1/5

10. A communication system accepts a positive voltage V as input and outputs a voltage Y = aV + N, where $a = 10^{-2}$ and N is a Gaussian random variable with parameters $\mu = 0$, $\sigma = 2$. Find the value of V that gives P(Y < 0) = 0.1.