

Kelpwright Instruments

Tideline benchtop instruments — datasheet

March 2025

The Tideline benchtop range measures water quality in laboratory and depot settings. All models share the same sample handling, the same reagent packs and the same service interface.

Warranty and support

All Tideline benchtop instruments carry a 24-month warranty from the date of shipment.

Next-business-day support response is included as standard with every instrument.

Specifications

- Tideline 1100 — 4 measurement channels, benchtop enclosure.
- Tideline 2200 — 8 measurement channels, benchtop enclosure.
- Tideline 3400 — 16 measurement channels with integrated autosampler.
- Sample volume: 20 mL minimum per determination.
- Operating range: 5 to 40 degrees Celsius, non-condensing.

Installation and power

Instruments are supplied ready for benchtop installation. A stable bench, a mains outlet and a waste container are required.

- Power: 230 V, 50 Hz, single phase.
- Typical consumption: 180 W in measurement, 40 W idle.
- Dimensions: 480 mm wide, 420 mm deep, 350 mm high.
- Mass: 18 kg (1100), 24 kg (2200), 31 kg (3400).

Calibration

Calibration is performed against reference solutions supplied by the customer or by Kelpwright. Calibration records are stored on the instrument and exported through the service interface.

Ordering

Part codes and list prices are published in the current price list. Lead times vary by model and are confirmed at order acknowledgement.