

**CS/B.Tech /IT (NEW)/SEM-7/IT-704C/2013-14**

**2013**

**DATA WAREHOUSING AND DATA MINING**

**Duration : 3 Hours**

**Full Marks : 70**

*The figures in the margin indicate full marks.*

*Candidates are required to give their answers in their own words as far as practicable.*

**GROUP - A**

**( Multiple Choice Type Questions )**

**Choose the correct alternatives for the following : 10 × 1 = 10**

- i) A data warehouse is said to contain a 'time-varying' collection of data because**
  - a) its contents vary automatically with time
  - b) its life-span is very limited
  - c) it contains historical data
  - d) its content has explicit time-stamp.
- ii) A data warehouse is said to contain a 'subject-oriented' collection of data because**
  - a) its contents have a common theme
  - b) it is built for a specific application
  - c) it cannot support multiple subjects
  - d) it is generalization of 'object-oriented'.

- iii) A data warehouse is built as a separate repository of data, different from the operational data of an enterprise because
- it is necessary to keep the operational data free of any warehouse operation
  - a data warehouse cannot afford to allow corrupted data within it
  - a data warehouse contains summarized data whereas the operational database contains transactional data
  - it is just needed.
- iv) ROLAP is preferred over MOLAP when
- a data warehouse and relational database are inseparable
  - the data warehouse is in relational tables, but slice and dice operations are required
  - the multidimensional model does not support query optimization
  - A data warehouse contains many fact tables and many dimension tables.
- v) The 'Slice operation' deals with
- selecting all but one dimension of the data cube
  - merging the cells along one dimension
  - merging cells of all but one dimension
  - selecting the cells of any one dimension of the data cube.

- i) Which of the following indexing techniques are appropriate for data warehousing?
- Hashing on primary key
  - Indexing on foreign keys of fact table
  - Bit-map indexing
  - Join indexing.
- What is 'MOLAP'?
- MOLAP is an OLAP engine for (i) relational models and (ii) multidimensional OLAP operations
  - MOLAP is an OLAP engine for (i) multidimensional models and (ii) SQL based OLAP operations
  - MOLAP is an OLAP engine for (i) multidimensional models and (ii) supports multidimensional OLAP operations.
  - MOLAP is an ROLAP with a supporting multidimensional model.
- iii) The advantage of FP-tree Growth Algorithm is
- it counts the support values of the item sets in the dashed structure as it moves along from one stop point to another
  - it avoids the generation of large numbers of candidate sets
  - to update the association rules when the database discover the set of frequent items sets
  - to prune the item sets which are not frequent.

- ix) The ID3 generates a
- binary decision tree
  - a decision tree with as many branches as there are distinct values of the attribute
  - a tree with a variable number of branches, not related to the domain of the attributes
  - a tree with an exponential number of branches.
- x) An oblique tree is relevant when
- the attributes are correlated
  - the attributes are independent
  - there are only two attributes
  - all attributes are categorical.

**GROUP - B**

**( Short Answer Type Questions )**

Answer any *three* of the following.  $3 \times 5 = 15$

- Differentiate among Enterprise Warehouse, Data mart and Virtual warehouse.
- Distinguish between OLTP and OLAP systems.
- Explain support, confidence, frequent itemset and give formal definition of association rule.
- Compare between HOLAP, ROLAP and MOLAP.
- Describe the basic algorithm for decision tree induction.

**GROUP - C**

**( Long Answer Type Questions )**

Answer any *three* of the following.  $3 \times 15 = 45$

- How is data warehouse different from a database ?
- What is the significance of a multi-dimensional data model in data-warehousing ? Briefly compare the snowflake schema and fact constellation concepts with a suitable example.
- Suppose that a data warehouse consists of the three dimensions time, doctor and patient and two measures count and charge, where charge is the fee that a doctor charges a patient for a visit.
  - Draw a star schema for the above warehouse.
  - Starting with the base cuboid (month, doctor, patient), what specific OLAP operations should be performed in order to list the total fee collected by each doctor in 2012 ?  $3 + 6 + 6$
- What is FP-tree ?
  - Discuss the different phases of FP-tree growth algorithm.

CS/B.Tech /IT (NEW)/SEM-7/IT-704C/2013-14

CS/B.Tech /IT (NEW)/SEM-7/IT-704C/2013-14

- c) Consider the following transaction database T, which contains 15 records :

A1	A2	A3	A4	A5	A6	A7	A8	A9
1	0	0	0	1	1	0	1	0
0	1	0	1	0	0	0	1	0
0	0	0	1	1	0	1	0	0
0	1	1	0	0	0	0	0	0
0	0	0	0	1	1	1	0	0
0	1	1	1	0	0	0	0	0
0	1	0	0	0	1	1	0	1
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	1	0
0	0	1	0	1	0	1	0	0
0	0	1	0	1	0	1	0	0
0	0	0	0	1	1	0	1	0
0	1	0	1	0	1	1	0	0
1	0	1	0	1	0	1	0	0
0	1	1	0	0	0	0	0	1

The set of items,  $A = \{ A1, A2, A3, A4, A5, A6, A7, A8, A9 \}$ .

Assume  $\sigma = 20\%$ .

Illustrate the working of a FP-tree growth algorithm for the above database. 2 + 4 + 9

9. a) Define with suitable examples of each of the following data mining functionalities : data characterization, data association and data discrimination.
- b) What is conceptual hierarchy ? How many cuboids are there in an  $n$ -dimensional data cube considering the hierarchies in each dimension ?

- c) In real world data, tuples with missing values for some attributes are a common occurrence. Suggest two different approaches for handling such event. 5 + 5 + 5

9. a) What is clustering ? What are the features of good cluster ?

- b) What do you mean by *hierarchical* clustering technique ?

- c) Suppose that the data mining task is to divide the following eight points representing locations into 3 clusters : A1 (2, 10), A2 (2, 5), A3 (8, 4), B1 (5, 8), B2 (7, 5), B3 (6, 4), C1 (1, 2), C2 (4, 9). The distance function is Euclidian distance. Initially, we assign A1, B1 and C1 as the center of each cluster. Use  $k$ -means algorithm to determine the 3 clusters. 3 + 4 + 8

1. a) What is tree pruning ? What are the different tree pruning techniques ?

- b) Describe PAM algorithm in brief.

- c) Evaluate Information Gain and Gain Ratio with suitable example. 5 + 5 + 5