

Traveleo – Frontend Handoff Document

Backend Base URL: `http://localhost:5000/api`

Authentication: JWT (Authorization: Bearer <token>)

Authentication Flow

1. User logs in using email and password.
2. Backend returns JWT token and user details.
3. Frontend stores token in `localStorage` or memory.
4. Token is sent in Authorization header for every protected request.

Axios Setup (Recommended)

Create a centralized Axios instance to automatically attach JWT token to requests.

```
import axios from "axios";

const api = axios.create({
  baseURL: "http://localhost:5000/api"
});

api.interceptors.request.use((config) => {
  const token = localStorage.getItem("token");
  if (token) {
    config.headers.Authorization = `Bearer ${token}`;
  }
  return config;
});

export default api;
```

Common API Usage Examples

Login → `POST /login`

Get Trips → `GET /trips`

Create Trip → `POST /trips`

Add Expense → `POST /expenses`

Get Budget Insights → `GET /trips/:tripId/insights`

Error Handling Convention

```
{
  "success": false,
  "message": "Error description"
}
```

Common Mistakes to Avoid

- Do not send password after login.
- Do not forget Authorization header.
- Do not send JWT in request body.
- Categories are user-level, not trip-level.
- Do not call protected APIs before login.

Suggested Frontend Page Flow

1. Login / Register
2. Dashboard – Trips List
3. Trip Details – Expenses, Budget, Insights
4. Add Expense Modal
5. Add Category Modal