

C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4      int i = 1;
5
6      while(i <= 10){
7          printf("%d\n", i);
8          i++;
9      }
10     return 0;
11 }
12
13
14 |
```

C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4      int i = 10;
5
6      while(i >= 1){
7          printf("%d\n", i);
8          i--;
9      }
10     return 0;
11 }
12
13
14
```


C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      for(int i = 2; i <= 10; i+=2){
6          printf("%d\n", i);
7      }
8      return 0;
9  }
10
11
12
```


C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      for(int i = 10; i <= 50; i+=10){
6          printf("%d\n", i);
7      }
8      return 0;
9  }
10
11
12
```

C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      for(int i = 10; i >= 1; i--){
6          printf("%d\n", i);
7      }
8      return 0;
9  }
10
11
12
```


C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int i = 10;
6
7      do{
8          printf("%d\n", i);
9      }
10     while(i <= 5);
11
12     return 0;
13 }
14
15
16
```

C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int i = 10;
6
7      while(i <= 5){
8          printf("%d\n", i);
9          i++;
10     }
11
12     return 0;
13 }
14
15
16
```

C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int sum = 0;
6      for(int i = 1; i <= 10; i++){
7          sum += i;
8      }
9      printf("sum = %d\n", sum);
10     return 0;
11 }
12
13
14
```

Day3.c

c > Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int sum = 0;
6      for(int i = 2; i <= 10; i+=2){
7          sum += i;
8      }
9      printf("sum = %d\n", sum);
10     return 0;
11 }
12
13
14
```

Day3.c X



c > Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int num;
6      int sum = 0;
7
8      printf("Enter number: ");
9      scanf("%d", &num);
10
11     for(int i = 1; i <= 10; i++){
12         printf("%d * %d = %d\n", num, i, num * i);
13     }
14     return 0;
15 }
16
17
18
```

C Day3.c X

c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int i;
6      int num;
7
8      printf("Enter number: ");
9      scanf("%d", &num);
10
11     for(int i = 1; i <= num; i++){
12         printf("%d\n", i);
13     }
14     return 0;
15 }
16
17
18
```

Day3.c X

c > Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int i;
6      int num;
7      int sum = 0;
8
9      printf("Enter number: ");
10     scanf("%d", &num);
11
12     for(int i = 1; i <= num; i++){
13         sum += i;
14     }
15     printf("%d\n", sum);
16     return 0;
17 }
```

c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int n;
6      int factorial = 1;
7
8      printf("Enter number: ");
9      scanf("%d", &n);
10
11     if(n < 0){
12         printf("Negative factorial deosn't exists.\n");
13     }
14     else{
15         for(int i = 1; i <= n; i++){
16             factorial *= i;
17         }
18     }
19     printf("Factorial is %d = %d\n", n, factorial);
20     return 0;
21 }
22
23
24
```


C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      for(int i = 1; i <= 20; i++){
6          printf("%d\n", i);
7      }
8
9      return 0;|
10 }
11
12
13
```


C Day3.c X



c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      for(int i = 2; i <= 50; i += 2){
6          printf("%d\n", i);
7      }
8
9      return 0;
10 }
11
12
13
```


c Day3.c X



c > c Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int n;
6
7      printf("Enter number: ");
8      scanf("%d", &n);
9
10     for(int i = 1; i <= 10; i++){
11         printf("%d * %d = %d\n", n, i, n * i);
12     }
13
14     return 0;
15 }
16
17
18
```

c Day3.c X



c > c Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int n;
6      int sum = 0;
7
8      printf("Enter number: ");
9      scanf("%d", &n);
10
11     for(int i = 1; i <= n; i++){
12         sum += i;
13     }
14     printf("sum = %d\n", sum);
15
16     return 0;
17 }
18
19
20
```

c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int n;
6      int factorial = 1;
7
8      printf("Enter number: ");
9      scanf("%d", &n);
10
11     if(n < 0){
12         printf("Negative number doesn't exists.\n");
13     }
14     else{
15         for(int i = 1; i <= n; i++){
16             factorial *= i;
17         }
18     }
19     printf("Factorial of %d = %d\n", n, factorial);
20
21     return 0;
22 }
23
24
25
```

```
1  #include <stdio.h>
2
3  int main(){
4
5      int n;
6      int factorial = 1;
7
8      printf("Enter number: ");
9      scanf("%d", &n);
10
11     if(n <= 0){
12         printf("Negative number doesn't exists.\n");
13     }
14     else{
15         for(int i = 1; i <= n; i++){
16             factorial *= i;
17         }
18         printf("Factorial of %d = %d\n", n, factorial);
19     }
20
21
22     return 0;
23
24
```

C Day3.c X

c > C Day3.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int number, originalNumber;
6      int count = 0;
7
8      printf("Enter number: ");
9      scanf("%d", &number);
10
11     originalNumber = number;
12
13     if(number == 0){
14         count = 1;
15     }
16     else{
17         if(number < 0){
18             number = -number;
19         }
20         while(number > 0){
21             number = number / 10;
22             count++;
23         }
24     }
25
26     printf("Number of digits in %d = %d\n", originalNumber, count);
27
28
29     return 0;
30 }
31
```