

C Day4.c X



c > C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int num, count = 0;
6
7      printf("Enter Number: ");
8      scanf("%d", &num);
9
10     if(num < 0){
11         printf("Negative number cannot be processed.\n");
12     }
13     for(int i = 1; i <= num; i++){
14         if(num % i == 0){
15             count++;
16         }
17     }
18     printf("Number of factors : %d", count);
19     return 0;
20 }
```

Day4.c X



c > Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int num;
6
7      printf("Enter Number: ");
8      scanf("%d", &num);
9
10     if(num < 0){
11         printf("Negative number cannot be processed.\n");
12     }
13     for(int i = 1; i <= num; i++){
14         if(num % i == 0){
15             printf("Factor of %d = %d\n", num, i);
16         }
17     }
18     return 0;
19 }
```

```
1  #include <stdio.h>
2
3  int main(){
4
5      int num, count = 0;
6
7      printf("Enter Number: ");
8      scanf("%d", &num);
9
10     if(num <= 1){
11         printf("not Prime\n");
12     }
13     else{
14         for(int i = 1; i <= num; i++){
15             if(num % i == 0){
16                 count++;
17             }
18         }
19         if(count == 2){
20             printf("Prime\n");
21         }
22         else{
23             printf("Not Prime\n");
24         }
25     }
26     return 0;
27 }
```

c > C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int num, count = 0;
6
7      printf("Enter Number: ");
8      scanf("%d", &num);
9
10     if(num <= 1){
11         printf("not Prime\n");
12     }
13     else{
14         for(int i = 1; i <= num; i++){
15             if(num % i == 0){
16                 count++;
17             }
18         }
19         if(count == 2){
20             printf("Prime\n");
21         }
22         else{
23             printf("Not Prime\n");
24         }
25     }
26     return 0;
27 }
```

Day4.c X

c > Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4      int TotalRows = 5;
5
6      for(int i = 1; i <= TotalRows; i++){
7          for(int j = 1; j <= i; j++){
8              printf("* ");
9          }
10         printf("\n");
11     }
12     return 0;
13 }
```

C Day4.c X



c > C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4      int TotalRows = 5;
5
6      for(int i = TotalRows; i >= 1; i--){
7          for(int j = 1; j <= i; j++){
8              printf("* ");
9          }
10         printf("\n");
11     }
12     return 0;
13 }
```

C Day4.c X

c > C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4
5
6      for(int i = 1; i <= 5; i++){
7          for(int j = 1; j <= 5; j++){
8              printf("%d", j);
9          }
10         printf("\n");
11     }
12     return 0;
13 }
```

C Day4.c X



c > C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4      int TotalRows = 5;
5      int totalCols = 5;
6
7      for(int i = 1; i <= TotalRows; i++){
8          for(int j = 1; j <= totalCols; j++){
9              printf("%d\t", i * j); // \t for tab space
10             }
11             printf("\n");
12         }
13         return 0;
14     }
```

c > C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4      int num;
5      int sum = 0;
6
7      printf("Enter the Number: ");
8      scanf("%d", &num);
9
10     if(num <= 0){
11         printf("Negative Number cannot be processed.");
12     }
13     else{
14         for(int i = 1; i < num; i++){
15             if(num % i == 0){
16                 sum += i;
17             }
18         }
19         if(sum == num){
20             printf("%d is a perfect Number\n", num);
21         }
22         else{
23             printf("%d is Not perfect Number\n", num);
24         }
25     }
26     return 0;
27 }
```

c > C Day4.c

```
1  #include <stdio.h>
2
3  ✓ int main(){
4      int N;
5
6
7      printf("Enter the Number: ");
8      scanf("%d", &N);
9
10
11  ✓   for(int num = 2; num <= N; num++){
12       int count = 0;
13       |
14  ✓   for(int i = 1; i <= num; i++){
15  ✓       if(num % i == 0){
16           count++;
17       }
18   }
19
20  ✓   if(count == 2){
21       printf("%d\n", num);
22   }
23   }
24
25
26   return 0;
27 }
```

c Day4.c X



c > c Day4.c

```
2
3  int main(){
4      int num;
5
6      printf("Enter Number: ");
7      scanf("%d", &num);
8
9      if(num <= 0){
10         printf("Type positive Number.");
11     }
12     else{
13         printf("Factor of %d are:\n", num);
14         for(int i = 1; i <= num; i++){
15             if(num % i == 0){
16                 printf("%d\n", i);
17             }
18         }
19     }
20
21     return 0;
22 }
```

C Day4.c X




c > C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4      int num;
5      int count = 0;
6
7      printf("Enter Number: ");
8      scanf("%d", &num);
9
10     if(num <= 0){
11         printf("Type positive Number.");
12     }
13     else{
14         for(int i = 1; i <= num; i++){
15             if(num % i == 0){
16                 count++;
17             }
18         }
19         printf("Count Factors: %d", count);
20     }
21
22     return 0;
23 }
```

```
1  #include <stdio.h>
2
3  int main(){
4      int num;
5      int count = 0;
6
7      printf("Enter Number: ");
8      scanf("%d", &num);
9
10     if(num <= 1){
11         printf("Not Prime.");
12     }
13     else{
14         for(int i = 1; i <= num; i++){
15             if(num % i == 0){
16                 count++;
17             }
18         }
19         if(count == 2){
20             printf("%d is Prime.", num);
21         }
22         else{
23             printf("%d is Not Prime.", num);
24         }
25     }
26
27     return 0;
28 }
```

C Day4.c X



C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      for(int i = 1; i <= 5; i++){
6          for(int j = 1; j <= i; j++){
7              printf("* ", j);
8          }
9          printf("\n");
10     }
11     return 0;
12 }
```

C Day4.c X

c > C Day4.c

```
1  #include <stdio.h>
2
3  int main(){
4      int num;
5      int sum = 0;
6
7      printf("Enter Number: ");
8      scanf("%d", &num);
9
10     if(num <= 0){
11         printf("Type Positive Number.");
12     }
13     else{
14         for(int i = 1; i < num; i++){
15             if(num % i == 0){
16                 sum += i;
17             }
18         }
19         if(sum == num){
20             printf("%d is Perfect Number.\n", num);
21         }
22         else{
23             printf("%d is not Perfect Number.\n", num);
24         }
25     }
26     return 0;
27 }
```

```
1  #include <stdio.h>
2
3  int main(){
4      int N;
5
6      printf("Enter Number: ");
7      scanf("%d", &N);
8
9      if(N <= 1){
10         printf("Not Number Prime.");
11     }
12     else{
13         for(int num = 2; num <= N; num++){
14             int count = 0;
15
16             for(int i = 1; i <= num; i++){
17                 if(num % i == 0){
18                     count++;
19                 }
20             }
21             if(count == 2){
22                 printf("%d is Prime.\n", num);
23             }
24             else{
25                 printf("%d Not Prime.\n", num);
26             }
27         }
28     }
29     return 0;
30 }
```

```
1  #include <stdio.h>
2
3  int main(){
4      int N;
5
6      printf("Enter Number: ");
7      scanf("%d", &N);
8
9      if(N <= 1){
10         printf("Not Number Prime.");
11     }
12     else{
13         for(int num = 2; num <= N; num++){
14             int count = 0;
15
16             for(int i = 1; i <= num; i++){
17                 if(num % i == 0){
18                     count++;
19                 }
20             }
21             if(count == 2){
22                 printf("%d is Prime.\n", num);
23             }
24         }
25     }
26     return 0;
27 }
```