


Day5.c X



c > Day5.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6
7      printf("Enter 5 number:\n");
8      for(int i = 0; i < 5; i++){
9          scanf("%d", &numbers[i]);
10     }
11
12     printf("\nYou entered:\n");
13     for(int i = 0; i < 5; i++){
14         printf("number[%d] = %d\n", i, numbers[i]);
15     }
16     return 0;
17 }
```

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6
7      printf("Enter 5 number:\n");
8      for(int i = 0; i < 5; i++){
9          scanf("%d", &numbers[i]);
10     }
11
12     int largest = numbers[0];
13
14     for(int i = 1; i < 5; i++){
15         if(numbers[i] > largest){
16             largest = numbers[i];
17         }
18     }
19
20     printf("Largest = %d\n", largest);
21
22     return 0;
23 }
```

c > C Day5.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6
7      printf("Enter 5 number:\n");
8      for(int i = 0; i < 5; i++){
9          scanf("%d", &numbers[i]);
10     }
11
12     int smallest = numbers[0];
13
14     for(int i = 1; i < 5; i++){
15         if(numbers[i] < smallest){
16             smallest = numbers[i];
17         }
18     }
19
20     printf("smallest = %d\n", smallest);
21
22     return 0;
23 }
```

ers\Ankush\Desktop\coding\c\problems.exe

C Day5.c X



c > C Day5.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6      int sum = 0;
7      float average;
8
9      printf("Enter 5 number:\n");
10     for(int i = 0; i < 5; i++){
11         scanf("%d", &numbers[i]);
12         sum += numbers[i];
13     }
14
15     average = (float)sum / 5;
16
17     printf("Average is %.2f\n", average);
18     return 0;
19 }
```

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6      int sum = 0;
7      float average;
8
9      printf("Enter 5 number:\n");
10     for(int i = 0; i < 5; i++){
11         scanf("%d", &numbers[i]);
12     }
13
14     for(int i = 0; i < 5; i++){
15         sum += numbers[i];
16     }
17     printf("sum = %d", sum);|
18     return 0;
19 }
```

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6      int evencount = 0;
7      int oddcount = 0;
8
9      printf("Enter 5 number:\n");
10     for(int i = 0; i < 5; i++){
11         scanf("%d", &numbers[i]);
12     }
13
14     for(int i = 0; i < 5; i++){
15         if(numbers[i] % 2 == 0){
16             evencount++;
17         }
18         else{
19             oddcount++;
20         }
21     }
22     printf("Evencount = %d\n", evencount);
23     printf("Oddcount = %d\n", oddcount);
24     return 0;
25 }
```

c > C Day5.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6      int found = 0;
7      int target;
8
9      printf("Enter 5 number: ");
10     for(int i = 0; i < 5; i++){
11         scanf("%d", &numbers[i]);
12     }
13
14     printf("Enter number to search: ");
15     scanf("%d", &target);
16
17     for(int i = 0; i < 5; i++){
18         if(numbers[i] == target){
19             found = 1;
20             break;
21         }
22     }
23     if(found == 1){
24         printf("Found\n");
25     }
26     else{
27         printf("Not Found\n");
28     }
29     return 0;
30 }
```

C Day5.c X



c > C Day5.c

```
1  #include <stdio.h>
2
3  ✓ int main(){
4
5      int numbers[5];
6
7      printf("Enter 5 number: ");
8  ✓  for(int i = 0; i < 5; i++){
9      scanf("%d", &numbers[i]);
10     }
11
12     printf("\nReversed Array: ");
13
14  ✓  for(int i = 4; i >= 0; i--){
15     printf("%d ", numbers[i]);
16     }
17     printf("\n");
18     return 0;
19 }
```


Day5.c X



c > Day5.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6
7      printf("Enter 5 number: ");
8      for(int i = 0; i < 5; i++){
9          scanf("%d", &numbers[i]);
10     }
11
12     for(int i = 0; i < 5; i++){
13         printf("%d ", numbers[i]);
14     }
15     printf("\n");
16     return 0;
17 }
```

C Day5.c X



c > C Day5.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6      int sum = 0;
7
8      printf("Enter 5 number: ");
9      for(int i = 0; i < 5; i++){
10         scanf("%d", &numbers[i]);
11     }
12
13     for(int i = 0; i < 5; i++){
14         sum += numbers[i];
15     }
16     printf("Sum = %d\n", sum);
17     return 0;
18 }
```

C Day5.c X

c > C Day5.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6      int sum = 0;
7      float average;
8
9      printf("Enter 5 number: ");
10     for(int i = 0; i < 5; i++){
11         scanf("%d", &numbers[i]);
12         sum += numbers[i];
13     }
14
15     average = (float)sum / 5;
16
17     printf("Average is %.2f\n", average);
18
19     return 0;
20 }
```

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6
7      printf("Enter 5 number: ");
8      for(int i = 0; i < 5; i++){
9          scanf("%d", &numbers[i]);
10     }
11
12     int largest = numbers[0];
13
14     for(int i = 0; i < 5; i++){
15         if(numbers[i] > largest){
16             largest = numbers[i];
17         }
18     }
19     printf("Largest number = %d\n", largest);
20
21     return 0;
22 }
```

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6      int evencount = 0;
7      int oddcount = 0;
8
9      printf("Enter 5 number: ");
10     for(int i = 0; i < 5; i++){
11         scanf("%d", &numbers[i]);
12     }
13
14     for(int i = 0; i < 5; i++){
15         if(numbers[i] % 2 == 0){
16             evencount++;
17         }
18         else{
19             oddcount++;
20         }
21     }
22     printf("Even = %d\n", evencount);
23     printf("Odd = %d\n", oddcount);
24     return 0;
25 }
```

c > C Day5.c

```
3  int main(){
10     for(int i = 0; i < 5; i++){
11         scanf("%d", &numbers[i]);
12     }
13
14     printf("Enter search number: ");
15     scanf("%d", &target);
16
17     for(int i = 0; i < 5; i++){
18         if(numbers[i] == target){
19             found = 1;
20             break;
21         }
22     }
23     if(found == 1){
24         printf("Found");
25     }
26     else{
27         printf("Not Found");
28     }
29     return 0;
30 }
```

c > C Day5.c

```
1  #include <stdio.h>
2
3  int main(){
4
5      int numbers[5];
6
7      printf("Enter 5 number: ");
8      for(int i = 0; i < 5; i++){
9          scanf("%d", &numbers[i]);
10     }
11
12     printf("Reversed Array: ");
13
14     for(int i = 4; i >= 0; i--){
15         printf("%d ", numbers[i]);
16     }
17     printf("\n");
18     return 0;
19 }
```

c > C Day5.c

```
1  #include <stdio.h>
2  #include <limits.h>
3
4  int main(){
5
6      int numbers[5];
7
8      printf("Enter 5 numbers: ");
9      for(int i = 0; i < 5; i++){
10         scanf("%d", &numbers[i]);
11     }
12
13     int largest = INT_MIN;
14     int secondlargest = INT_MIN;
15
16     for(int i = 0; i < 5; i++) {
17         if(numbers[i] > largest){
18             secondlargest = largest;
19             largest = numbers[i];
20         }
21         else if(numbers[i] > secondlargest && numbers[i] !=
22             secondlargest = numbers[i];
23         }
24     }
25     if(secondlargest == INT_MIN){
26         printf("No second largest number.\n");
27     }
28     else{
29         printf("second largest is %d", secondlargest);
30     }
31
32     return 0;
33 }
```