
Step 1 : We give Spring a Bean (Bean means a normal Java class)

- a default constructor
- properties (variables)
- getters and setters
- methods (business logics)

Step 2 : We give details via Bean Metadata (Configuration Files)

- which class is a bean
- what values should be set in its properties
- which method is init and which is destroy
- This metadata can be given using (XML configuration files or Annotations (modern))

Step 3 : When we call `getBean()` Spring performs these steps

1) Create the Bean Object

Spring first creates the object of the bean class.

2) Set Property Values (Dependency Injection)

Then Spring sets values inside the bean's properties (variables).

3) Call Init Method

After setting values, Spring calls the init method (`public void init()` or custom init method).

- This is where we can write
- database connection code
- loading config
- opening webservice connection

4) Now the Bean is ready to use

Now we can use the bean normally and call its methods without any issue.

Step 4 : When Spring container is shutting down

1) Call Destroy Method

Before removing the bean object Spring calls the destroy method (public void destroy() or custom destroy method).

This is used for cleanup like

- closing DB connection
- closing webservice connection
- releasing resources
- stopping background threads

--

Configuration Technique (how to call init / destroy methods)

--

1. Using XML files (We can mention custom init/destroy methods in XML using : init-method and destroy-method)
2. Using Spring Interface (We can implement Spring interfaces and override methods)
3. Using Annotation (We can use @PostConstruct → init || @PreDestroy → destroy)