# Modelling Somatic Hypermutations with Reinforcement Learning



## for PD1 and Pembrolizumab

Anmol Singh, Prof. Subhashini Srinivasan, Dr. Nithya Ramakrishnan
Institute of Bioinformatics and Applied Biotechnology - Biotech Park, Electronics City Phase 1, Electronic City, Bengaluru, Karnataka 560100

#### **ABSTRACT**

We present a reinforcement learning (RL) model for Somatic Hypermutations (SHM), which mimics the natural selection process in a very short time scale. In this model, the agent can learn to preferentially mutate amino acids in the antibody, leading to affinity maturation. The model thus predicts a higher binding affinity antibody than the initial antibody-antigen complex. We have used the Pembrolizumab-PD1 (5b8c) complex to create the model, as Pembrolizumab (Pembro) is widely used in immunotherapy.

We use Q-Learning in RL to model SHM on a reduced state space to provide better binding affinity antibodies. We validated the structure of the antibodies predicted by the RL model using AlphaFold2 and inter-residue distance plots to check for proper folding of chains and protein-protein interactions. This study provides a proof of concept that RL can be used for modeling the biological process of SHM and can further be employed for creating novel antibodies.

#### **OBJECTIVES**

Major Objective: To create a reinforcement learning model for somatic hypermutations using Pembro and PD1.

Minor Objective: To find states/antibodies which have better binding affinity than Pembro, and validating the good states using AlphaFold2 and C-alpha distance plots of the predicted structures.

**DESIGN AND WORKFLOW** 




Figure 4. A Flowchart of Basic Q-learning, B Representation of Q-Table, C a Scoring vector, b Score to

reward function, **D** Flowchart of Deep Q Learning,

#### INTRODUCTION

Somatic Hypermutations (SHM) are an important part of the affinity maturation (AM) in B-cells.

We express the biological process of AM as a Markov decision process (MDP), creating a RL model of SHM and AM. Model Assumptions:

- The <u>relative configuration of PD1-Pembro complex remains</u> the same irrespective of the type of amino acids mutations at the 17 positions
- The 3D folds of light and heavy chains are not disrupted by the mutations in loops on Pembro

#### DISCUSSION AND FUTURE WORK

Q-Learning simulated SHM and provided a better binding Pembro-PD1 complex using a reduced state space.

Deep Q-Learning can be employed to predict alternate complexes to Pembro-PD1 – Currently underway.

Protein Language Models (PLM) can be employed in conjunction with our SHM-RL model for drug discovery.





Figure 3. A Reference crystal structure of Pembrolizumab (PDB ID: 5B8C), B A schematic diagram of interactions between PD1 and antiPD1. Direct protein/protein hydrogen bonds are in blue; water-mediated hydrogen bonds are in green; and salt bridges are in red (Horita S et al., 2016)

SYYYSDTYYNWNTNTHL




RESULTS

Action: Point mutations on Pembrolizumab (using PyMOL)


**Environment:** Affinity Maturation of Pembrolizumab-PD1

State: Pembrolizumab with mutated amino acids




A b Higher Affinity States/Abs


Residues position




-13.5 2.061


A,D,E,F,G,H,I,K,L,N,Q,R,S,T,V,W,Y









**Mutations Residues** 



C-alpha residues chain A





-13.5 2.172

Figure 5. A a RL SHM simulations, A b Higher Binding affinity(BA) states after AlphaFold2(AF), Red: Using Soft-Max: Mutating 3 residues on Heavy chain into 17 residues, Blue: Epsilon Greedy: Mutating 6 residues in Light chain into 6 a.a. Orange: Epsilon greedy: Mutating 4 residues in Heavy chain into 16 a.a. With constraint looping Yellow: DQL: Epsilon Greedy: mutating 3 residues on Heavy chain into 17 a.a. B AF predicted structures aligned with Pembro and their corresponding C-alpha distance plots Purple: DDDSGDTYYNSNTNRYR (Folded Properly) Red: SYYYSDTWYNYNTNGYR (improper folding)

#### REFERENCES

- Faris, J. G., Orbidan, D., Wells, C., Petersen, B. K., & Sprenger, K. G. (2022). Moving the needle: Employing deep reinforcement learning to push the boundaries of coarse-grained vaccine models. Frontiers in Immunology, 13. <a href="https://doi.org/10.3389/FIMMU.2022.1029167">https://doi.org/10.3389/FIMMU.2022.1029167</a>
- Horita, Shoichiro, et al. "High-resolution crystal structure of the therapeutic antibody pembrolizumab bound to the human PD-1." Scientific reports 6.1 (2016): 35297
   Sutton, R. S., & Barto, A. G. (2018). Reinforcement learning: An introduction, 2nd ed. In Reinforcement learning: An introduction, 2nd ed. The MIT Press.
- Vangone, A., & Bonvin, A. M. J. J. (2017). PRODIGY: A Contact-based Predictor of Binding Affinity in Protein-protein Complexes. *Bio-Protocol*, 7(3). <a href="https://doi.org/10.21769/BIOPROTOC.2124">https://doi.org/10.21769/BIOPROTOC.2124</a>

  ACKNOWLEDGEMENT

C-alpha residues chain A

## This study is supported by Dept. of electronics, IT, BT and S&T, Government of Karnataka. We would also like to extend our gratitude to the faculty of IBAB and Mr. Balakrishna Prabhu B N, Ms. Namita Menon, Mr. Yash Chindarkar and Ms. Apoorva Ganesh for their contribution and guidance.

-14.5 -14.0 -13.5 -13.0 -12.5 -12.0 -11.5

# Modelling Somatic Hypermutations with Reinforcement Learning

# Institute of Bioinformatics and Applied Biotechnology

# for PD1 and Pembrolizumab

Anmol Singh, Prof. Subhashini Srinivasan, Dr. Nithya Ramakrishnan Institute of Bioinformatics and Applied Biotechnology - Biotech Park, Electronics City Phase 1, Electronic City, Bengaluru, Karnataka 560100

#### **ABSTRACT**

We present a reinforcement learning (RL) model for Somatic Hypermutations (SHM), which mimics the natural selection process in a very short time scale. In this model, the agent can learn to preferentially mutate amino acids in the antibody, leading to affinity maturation. The model thus predicts a higher binding affinity antibody than the initial antibody-antigen complex. We have used the Pembrolizumab-PD1 (5b8c) complex to create the model, as Pembrolizumab (Pembro) is widely used in immunotherapy.

We use Q-Learning in RL to model SHM on a reduced state space to provide better binding affinity antibodies. We validated the structure of the antibodies predicted by the RL model using AlphaFold2 and inter-residue distance plots to check for proper folding of chains and protein-protein interactions. This study provides a proof of concept that RL can be used for modeling the biological process of SHM and can further be employed for creating novel antibodies.

#### **OBJECTIVES**

Major Objective: To create a reinforcement learning model for somatic hypermutations using Pembro and PD1.

Minor Objective: To find states/antibodies which have better binding affinity than Pembro, and validating the good states using AlphaFold2 and C-alpha distance plots of the predicted structures.

## INTRODUCTION

- Somatic Hypermutations (SHM) are an important part of the affinity maturation (AM) in B-cells.
- We express the biological process of AM as a Markov decision process (MDP), creating a RL model of SHM. **Model Assumptions:**
- The relative configuration of PD1-Pembro complex remains the same irrespective of the type of amino acids mutations at the 17 positions
- The 3D folds of light and heavy chains are not disrupted by the mutations in loops on Pembro





Figure 1. Broad overview of the affinity maturation (AM) process by which antibodies (Abs) evolve against vaccine-candidate antigens (Ags) in a germina center (GC) reaction (Faris J et al., 2022)

Figure 2. The interaction of agent and environment in a MDP Agent: B-cells Action: Point mutations on Pembrolizumab (using PyMOL) Environment: Affinity Maturation of Pembrolizumab-PD1



Reward

Histogram of last 10000 episodes

Binding affinity

-23.3

-13.5

-13.4

-13.3

-13.3

-13.3

RMSD

19.48

2.061

2.058

2.072

1.987

2.072

Reward Crystal BA AF BA

-13.4

-13.6

-13.4

Pembrolizumab (PDB ID: 5B8C), B A schematic diagram of interactions between PD1 and antiPD1. Direct protein/protein hydrogen bonds are in blue, water-mediated hydrogen bonds are in green and salt bridges are in red (Horita S et al., 2016)

Simulations and Predicted Antibodies

сь Table. Score to Reward function C a Binding Affinity (kcal/mole) < -12.6 >= -12.6 < -12.6 3>score>-> -12.6 3 > score > -1-1>= score > -10< -10 -0.2 Percentage Charged NIS Residues

**Prodigy Parameters** 

2e+05

DRRTSYTYYNSNTNRYR

STRNYYTYYNSNTNRYR

YRNNSRTYYNSNTNRYR

3e+05

45

141

### **DESIGN AND WORKFLOW**






Figure 5. General Representation of Deep Q-Learning


## <s<sub>1</sub>,a<sub>1</sub>,r<sub>2</sub>,s<sub>2</sub>>, <s<sub>2</sub>,a<sub>2</sub>,r<sub>3</sub>,s<sub>3</sub>>, <s<sub>2</sub>,a<sub>2</sub>,r<sub>3</sub>,s<sub>3</sub>>,2 Optimization Memory Mini Batch Replay Memory


## RESULTS

















## DSRNYYTYYNSNTNRYR -13.7 41 DTRNYYTYYNSNTNRYR -13.7 YRNNNRTYYNSNTNRYR Histogram of last 10000 episodes AND HARMAN PARTY AND THE PROPERTY OF THE PROPE

*Looping from starting state upon reaching -10 reward, simulating apoptosis					
State	Freq	Reward	Crystal BA	AF BA	RMSD
SYYYSDTYYNFNTNRYR	5	1	-13.4	-13.1	2.179
SYYYSDTYYNLNTNRYR	6	1	-13.5	-13	2.153
SYYYSDTYYNWNTNRYR	6	1	-13.4	-13	2.286
SYYYSDTYYNYNTNRYR	9	1	-13.6	-12.8	2.193

# C-alpha residues chain B

## DISCUSSION AND FUTURE WORK

Q-Learning simulated SHM and provided a better binding Pembro-PD1 complex using a reduced state space.

Deep Q-Learning can be employed to predict alternate complexes to Pembro-PD1 – Currently underway.

Protein Language Models (PLM) can be employed in conjunction with our SHM-RL model for drug discovery. Further validation of predicted antibodies using molecular

dynamics and different binding affinity tools is required.

This study is supported by Dept. of electronics, IT, BT and S&T, Government of Karnataka. We would also like to extend our gratitude to the faculty of IBAB and Mr. Balakrishna Prabhu B N, Ms. Namita Menon, Mr. Yash Chindarkar and Ms. Apoorva Ganesh for their contribution and guidance.

ACKNOWLEDGEMENT

- REFERENCES
- deep reinforcement learning to push the boundaries of coarse-grained vaccine models. Frontiers in Immunology, 13. https://doi.org/10.3389/FIMMU.2022.1029167 • Horita, Shoichiro, et al. "High-resolution crystal structure of the therapeutic antibody pembrolizumab bound to the human PD-1." Scientific reports 6.1 (2016): 35297

• Faris, J. G., Orbidan, D., Wells, C., Petersen, B. K., & Sprenger, K. G. (2022). Moving the needle: Employing

- Sutton, R. S., & Barto, A. G. (2018). Reinforcement learning: An introduction, 2nd ed. In Reinforcement learning: An introduction, 2nd ed. The MIT Press. • Vangone, A., & Bonvin, A. M. J. J. (2017). PRODIGY: A Contact-based Predictor of Binding Affinity in
- Protein-protein Complexes. *Bio-Protocol*, 7(3). <a href="https://doi.org/10.21769/BIOPROTOC.2124">https://doi.org/10.21769/BIOPROTOC.2124</a>