Smart-ASHA Pro Workstation

Zero-App Telemetry & Wireless Patient Sync (Web-Bluetooth 5.0)

Disconnect BLE | Connect USB (Serial) | Dump Vault | Save JSON | Export CSV | Print Report

Status: Connected to Smart-ASHA | Standby (Insert Finger to Scan)

Device: Smart-ASHA-Pro | Bus: BLE 5.0 GATT

10
SEVERITY / 100

INSERT FINGER STANDBY

उंगली लगाएं (जांच शुरू करने के लिए)

Workstation is connected over Bluetooth. Insert finger into MAX30105 sensor on breadboard to begin the 60-second diagnostic scan.

THE 4 STAR PERFORMERS CLINICAL METRICS

MAX30105 Hemodynamics — NORMAL

99 % SpO_2

Pulse Rate:	72 BPM
Perfusion Index (PI %):	1.89 %
Sensor Die Temp:	-- °C

MLX90640 Thermal Vision — NORMAL

36.6 °C Core

AI Fever Probability:	0.0 %
Temporal Asymmetry (dT):	0.00 °C
Thermal Gradient:	Central Core

AD8232 Cardiac HRV — STABLE

AS7343 Multi-Spectral — NORMAL

0.0 ms SDNN

1.00 Hb (F5/F8)

RMSSD (Vagal Tone):	0.0 ms	Jaundice Index (F1/FZ):	1.00
pNN50 (Autonomic):	0.0 %	Dehydration (NIR/FXL):	1.00
Rhythm Source:	PPG Fallback / ECG	Active Channels:	14-Band Spectral

📋 Wireless Screening History (Current Session)

Time	Severity	Triage Verdict (EN)	Triage (Hindi)	SpO_2	BPM	PI %	Temp (°C)	SDNN (ms)	Hb Ratio
11:11:48 PM	**10/100**	NORMAL (HEALTHY)	सामान्य (स्वस्थ)	99%	72	1.89%	36.6°C	0.0	1.00

Smart-ASHA v12.0 Clinical Workstation • ESP32-S3 Dual-Core FreeRTOS • Zero-App Web-Bluetooth Architecture