International Journal of Computing and Artificial Intelligence

E-ISSN: 2707-658X
P-ISSN: 2707-6571
Impact Factor (RJIF): 5.57
https://www.computersciencejournals.com/ijcai/
IJCAI 2026; 7(7): 72-87
Received: 22-04-2026
Accepted: 26-05-2026

Ritika Godela
Department of Computer Science, University of Delhi, Delhi, India

Corresponding Author:
Ritika Godela
Department of Computer Science, University of Delhi, Delhi, India

Agentic artificial intelligence: Architectures, planning mechanisms, multi-agent collaboration, applications, challenges, and future research directions-A comprehensive review

Ritika Godela

DOI: https://www.doi.org/10.33545/27076571.2026.v7.i7a.358

Abstract
Agentic Artificial Intelligence (Agentic AI) represents a significant advancement in intelligent systems by enabling autonomous planning, reasoning, memory utilization, tool interaction, and adaptive decision-making to accomplish complex objectives with minimal human intervention. Unlike conventional Artificial Intelligence systems that perform predefined tasks or Large Language Models (LLMs) that primarily generate text, Agentic AI systems integrate planning algorithms, persistent memory, external tools, retrieval mechanisms, and feedback loops to execute multi-step workflows and continuously improve task performance. Recent progress in foundation models, retrieval-augmented generation, tool-use frameworks, and multi-agent collaboration has accelerated the development of intelligent agents capable of solving increasingly sophisticated real-world problems.

This review provides a comprehensive overview of Agentic AI by examining its historical evolution, theoretical foundations, architectural components, and implementation frameworks. The paper discusses the roles of reasoning, planning, memory management, tool integration, reflection mechanisms, and multi-agent coordination in building autonomous systems. Popular development frameworks including AutoGen, LangGraph, CrewAI, Semantic Kernel, and OpenAI's Agents SDK are analyzed to highlight their design principles, strengths, and limitations. Furthermore, the review explores applications of Agentic AI across healthcare, finance, cybersecurity, education, robotics, software engineering, and scientific research.

The paper also identifies critical research challenges related to hallucination, safety, explainability, privacy, computational cost, governance, and human oversight. Ethical considerations surrounding autonomous decision-making, accountability, and trustworthy AI are discussed in detail. Finally, emerging research directions including lifelong learning, self-improving agents, embodied intelligence, and collaborative multi-agent ecosystems are presented. By synthesizing recent advances and identifying open research problems, this review aims to provide researchers and practitioners with a comprehensive understanding of the current landscape and future trajectory of Agentic AI.

Keywords: Agentic AI; artificial intelligence, large language models, autonomous agents, multi-agent systems, planning, reasoning, retrieval-augmented generation, tool use, generative AI

1. Introduction

Artificial Intelligence (AI) has evolved from rule-based expert systems to machine learning and, more recently, to foundation models capable of performing complex cognitive tasks. The rapid advancement of deep learning and transformer-based architectures has enabled Large Language Models (LLMs) to achieve remarkable performance in natural language understanding, reasoning, code generation, and knowledge synthesis. Models such as GPT, Llama, Gemini, and Claude have significantly expanded the capabilities of AI-powered applications by generating contextually relevant responses across a wide range of domains (Brown *et al*., 2020; OpenAI, 2023).

Despite these advances, conventional LLMs remain predominantly reactive. They generate outputs in response to user prompts but generally lack persistent goals, autonomous planning, long-term memory, and the ability to execute complex workflows independently. This limitation has motivated the emergence of Agentic Artificial Intelligence (Agentic AI), a paradigm in which intelligent systems operate as autonomous agents capable of perceiving objectives, planning multi-step actions, utilizing external tools, interacting with dynamic

Environments, and adapting their strategies based on feedback (Yao *et al*., 2023; Schick *et al*., 2023).

Agentic AI extends the capabilities of generative AI by integrating reasoning, planning, memory management, tool invocation, and self-reflection into unified autonomous systems. Instead of merely generating text, an agent can decompose a high-level objective into subtasks, retrieve relevant information from external knowledge sources, invoke APIs or software tools, evaluate intermediate results, and iteratively refine its actions until the desired objective is achieved. These characteristics make Agentic AI particularly suitable for solving complex real-world problems that require sequential decision-making, adaptive reasoning, and collaboration among multiple specialized agents (Wu *et al*., 2023).

Recent advances in agent orchestration frameworks-including AutoGen, LangGraph, CrewAI, Semantic Kernel, and OpenAI's agent development ecosystem-have accelerated research and industrial adoption of autonomous AI systems. These frameworks provide mechanisms for state management, tool integration, multi-agent communication, memory Persistence, and human-in-the-loop supervision, enabling the deployment of increasingly sophisticated intelligent workflows across healthcare, education, finance, cybersecurity, robotics, scientific discovery, and software engineering. As a result, Agentic AI has emerged as one of the fastest-growing research areas in artificial intelligence, attracting significant attention from both academia and industry.

Although Agentic AI demonstrates remarkable potential, several research challenges remain unresolved. Autonomous agents may generate hallucinated information, exhibit unreliable reasoning, misuse external tools, or make decisions that lack transparency and accountability. Additional concerns include computational cost, privacy preservation, security vulnerabilities, ethical governance, and the alignment of autonomous behavior with human values. Addressing these challenges is essential for developing trustworthy and reliable agentic systems suitable for deployment in high-stakes environments.

Therefore, this review aims to provide a comprehensive synthesis of the rapidly evolving Agentic AI landscape. Specifically, the objectives of this paper are to:

- Review the evolution from traditional AI and generative AI to Agentic AI.
- Explain the architectural components of autonomous intelligent agents.
- Compare major Agentic AI frameworks and orchestration approaches.
- Analyze applications across multiple domains.
- Discuss current technical, ethical, and security challenges.
- Identify emerging research directions and future opportunities.

By consolidating recent advances in autonomous intelligent systems, this review intends to serve as a comprehensive reference for researchers, practitioners, and policymakers seeking to understand the design principles, implementation frameworks, applications, and future trajectory of Agentic AI.

2. Evolution of artificial intelligence towards agentic AI

Artificial Intelligence has progressed through several major phases, moving from manually programmed systems toward increasingly autonomous and adaptive computational entities. The earliest AI approaches were based on symbolic reasoning and expert systems, where domain knowledge was represented through predefined rules and logical structures. These systems achieved success in restricted environments but struggled with uncertainty, scalability, and changing real-world conditions.

The emergence of machine learning introduced a paradigm shift by enabling systems to learn patterns from data rather than relying exclusively on human-designed rules. Statistical learning methods improved classification, prediction, and decision-making capabilities across multiple domains. However, these approaches generally remained task-specific and required carefully prepared datasets.

Deep learning further transformed AI by enabling automatic feature extraction from large-scale data. Neural architectures such as convolutional neural networks and recurrent neural networks achieved significant progress in computer vision, speech processing, and natural language processing. The introduction of the Transformer architecture by Vaswani *et al*. (2017) represented a major breakthrough by allowing models to efficiently capture long-range dependencies in sequential data through self-attention mechanisms.

The development of Large Language Models (LLMs) based on transformer architectures resulted in a new generation of AI systems capable of performing diverse language-based tasks. Models such as GPT demonstrated strong few-shot learning, reasoning, summarization, programming, and knowledge synthesis capabilities (Brown *et al*., 2020). However, despite their impressive performance, LLMs primarily operate as response-generation systems and lack inherent autonomy, persistent objectives, and environmental interaction.

Agentic AI emerged as an extension of LLM capabilities by integrating autonomous decision-making mechanisms with foundation models. Instead of only responding to prompts, AI agents can:

- Interpret complex objectives,
- Decompose tasks into smaller goals,
- Develop execution plans,
- Interact with external tools,
- Maintain memory,
- Evaluate outcomes,
- And modify their behavior based on feedback.

The concept of intelligent agents has existed for decades within Artificial Intelligence research. Russell and Norvig (2021) described agents as systems that perceive their environment and take actions to maximize performance. Modern Agentic AI combines this classical agent concept with advanced foundation models, creating systems capable of flexible reasoning and natural language interaction.

Recent research such as ReAct (Reasoning and Acting) demonstrated that combining reasoning traces with external

actions improves the ability of language models to solve complex tasks by allowing them to interact with tools and environments (Yao *et al*., 2023). Similarly, Toolformer showed that language models can learn to use external tools, including calculators, search systems, and APIs, improving their ability to perform tasks beyond their internal knowledge (Schick *et al*., 2023).

The evolution can therefore be summarized as

Table 1: Rule-Based AI → Machine Learning → Deep Learning → Generative AI → Agentic AI

Generation	Main Capability	Limitation
Rule-Based AI	Logical decision making	No learning ability
Machine Learning	Pattern recognition	Task-specific
Deep Learning	Automatic feature learning	Requires large datasets
Generative AI	Content generation and reasoning	Limited autonomy
Agentic AI	Autonomous planning and execution	Safety and reliability challenges

Agentic AI represents a transition from AI systems that generate outputs to systems that actively pursue objectives. This transition introduces new possibilities for automation, scientific discovery, personalized assistance, and complex decision support while simultaneously creating challenges related to trust, governance, and human oversight.

3. Fundamentals of agentic artificial intelligence

Agentic Artificial Intelligence represents a new generation of intelligent systems that combine the capabilities of foundation models with autonomous decision-making mechanisms. The fundamental idea behind Agentic AI is to transform AI systems from passive response generators into active entities capable of pursuing objectives, interacting with environments, and completing complex tasks with limited human intervention. An AI agent can traditionally be defined as a computational system that perceives its environment through inputs and performs actions to achieve specific goals. Russell and Norvig described an intelligent agent as an entity that perceives its environment and acts upon that environment to maximize the achievement of predefined objectives [1]. Modern Agentic AI extends this concept by integrating advanced neural models, particularly Large Language Models (LLMs), with planning, reasoning, memory, and external tool interaction capabilities.

Unlike conventional software systems that follow fixed instructions, Agentic AI systems demonstrate several important characteristics:

A. Goal-oriented behaviour

The primary characteristic of Agentic AI is goal-directed operation. Instead of responding only to direct user queries, an agent receives a high-level objective and determines the necessary steps required to achieve it.

For example, a traditional chatbot may answer:

"Provide information about climate change."

An agentic system may:

1. Search scientific databases.
2. Analyze recent research papers.
3. Summarize important findings.
4. Compare different viewpoints.
5. Generate a structured report.

This ability to autonomously plan and execute tasks differentiates Agentic AI from traditional conversational systems.

B. Autonomous planning

Planning is one of the central capabilities of intelligent agents. Planning allows an AI system to divide complex problems into smaller, achievable subtasks.

Recent research has shown that prompting language models with explicit reasoning strategies can significantly improve complex problem-solving abilities. Chain-of-Thought (CoT) prompting introduced by Wei *et al*. demonstrated that encouraging intermediate reasoning steps improves performance on mathematical and logical tasks [2].

However, reasoning alone does not provide complete autonomy. Agentic systems combine reasoning with action execution. The ReAct framework proposed by Yao *et al*. introduced a method where language models alternate between reasoning and taking actions using external tools [3].

The ReAct cycle can be represented as:

Goal → Reason → Plan → Act → Observe Result → Update Plan

This iterative process enables agents to adapt their behaviour based on environmental feedback.

C. Memory mechanisms

Memory is a critical component that enables agents to maintain context beyond a single interaction. Traditional LLMs have limited context windows and do not inherently remember previous interactions.

Agentic systems generally use three types of memory:

1. Short-term memory

Short-term memory maintains information relevant to the current task.

Examples:

- Current conversation history
- Temporary reasoning states
- Intermediate results

2. Long-term memory

Long-term memory stores information that can be retrieved in future interactions.

Examples:

- User preferences
- Previous task outcomes
- Domain knowledge

3. External memory

External memory systems use databases or retrieval systems to provide additional knowledge.

Retrieval-Augmented Generation (RAG), introduced by Lewis *et al*., combines language models with external knowledge retrieval to improve factual accuracy and reduce dependence on static model parameters [4].

D. Tool usage and external interaction

One of the defining characteristics of Agentic AI is the ability to use external tools.

Tools may include:
- Web search engines
- Databases
- APIs
- Code execution environments
- Scientific computing tools
- Enterprise software systems

Schick *et al*. introduced Toolformer, demonstrating that language models can learn to decide when and how to call external tools to improve task performance [5].
Tool integration enables agents to overcome limitations such as outdated knowledge, computational restrictions, and lack of access to real-time information.

E. Reflection and self-correction
Modern Agentic AI systems increasingly incorporate self-evaluation mechanisms. Reflection allows agents to analyze their own outputs, identify errors, and improve future decisions.
The Reflexion framework proposed by Shinn *et al*. demonstrated that language agents can improve performance by generating verbal feedback about previous failures and using this feedback in future attempts [6].
A typical reflection process includes:
1. Generate solution.
2. Evaluate output quality.
3. Identify mistakes.
4. Modify strategy.
5. Generate improved solution.

This capability is essential for developing reliable autonomous systems.

F. Architecture of agentic AI systems
A complete Agentic AI system consists of multiple interconnected components working together to achieve autonomous behaviour.

G. High-level architecture
The general architecture contains the following layers:

1. Perception layer
Responsible for receiving information from:
- User instructions
- Sensors
- Documents
- Databases
- External environments

2. Reasoning engine
The reasoning engine is usually powered by an LLM that interprets objectives and determines appropriate actions.
Examples:
- GPT models
- Claude models
- Gemini models
- Llama models

3. Planning module
The planning module converts objectives into sequences of actions.
Example:
UserGoal:
"Prepare a market analysis report."
Agent Plan:
1. Collect market data.
2. Analyze competitors.
3. Identify trends.
4. Generate report.
5. Validate findings.

4. Memory layer
Stores and retrieves information required for decision-making.

5. Tool execution layer
Allows interaction with external systems.
Examples:
- Search APIs
- Databases
- Programming environments
- Business applications

6. Feedback loop
The feedback mechanism evaluates outcomes and improves future actions.

4. Multi-agent systems and collaboration in agentic AI

A. Introduction to multi-agent Systems
While single-agent systems can perform complex tasks by combining reasoning, planning, and tool utilization, many real-world problems require collaboration among multiple specialized agents. Multi-Agent Systems (MAS) address this requirement by enabling multiple autonomous entities to communicate, coordinate, and collectively solve problems.
The concept of Multi-Agent Systems has its foundation in distributed Artificial Intelligence, where multiple intelligent entities cooperate or compete within a shared environment. According to Wooldridge, an agent is an autonomous computational system capable of flexible actions in dynamic environments, and multi-agent collaboration extends this capability through communication and coordination mechanisms [7].
Recent developments in Large Language Models have significantly expanded the capabilities of MAS. Instead of designing agents manually with fixed rules, modern approaches use LLM-powered agents that can dynamically reason, communicate, assign responsibilities, and adapt their behaviour.
A multi-agent Agentic AI system may contain
- Planner Agent: Responsible for task decomposition and workflow creation.
- Research Agent: Collects and analyzes information.
- Coding Agent: Generates and executes software code.
- Verification Agent: Reviews outputs and detects errors.
- Communication Agent: Manages interaction between agents.

This specialization allows complex tasks to be solved more efficiently than using a single general-purpose agent.

B. Agent communication and coordination
Communication is the foundation of multi-agent collaboration. Agents exchange information through

structured messages, shared memory, or conversation protocols.

A typical multi-agent workflow involves

1. A user provides a high-level objective.
2. A manager agent divides the objective into subtasks.
3. Specialized agents perform individual tasks.
4. Results are shared among agents.
5. A final agent integrates outputs into a complete solution.

For example, generating a research paper may involve:

- Literature review agent
- Citation verification agent
- Writing agent
- Editing agent
- Formatting agent

The collaboration between these agents reduces workload and improves quality.

C. Role-based agent architecture

Modern Agentic AI systems frequently adopt role-based architectures where each agent is assigned a specific responsibility.

Example:

Research Agent

Responsibilities

- Search academic databases
- Extract important findings
- Summarize papers

Analyst Agent

Responsibilities

- Compare studies
- Identify trends
- Generate insights

Writer Agent

Responsibilities

- Prepare manuscript sections
- Maintain academic style

Reviewer Agent

Responsibilities

- Identify weaknesses
- Suggest improvements

This approach resembles human organizational structures where specialists collaborate to accomplish complex objectives.

D. Auto Gen: Multi-agent conversation framework

Auto Gen, introduced by Microsoft Research, is a framework designed to enable development of LLM-based applications using multiple interacting agents. It allows developers to create conversational agent networks where agents can exchange messages, execute code, and collaborate on tasks [8].

Important features of Auto Gen include:

- Agent-to-agent communication
- Human-in-the-loop interaction
- Code execution capability
- Customizable agent roles
- Automated workflow management




Fig 1: A typical AutoGen architecture contains

AutoGen has demonstrated effectiveness in software development, data analysis, and complex reasoning tasks.

E. CrewAI framework

CrewAI is another emerging framework focused on creating collaborative AI agent teams. It introduces the concept of "crews," where agents are assigned specific roles, goals, and responsibilities.

A CrewAI workflow generally consists of:

- Agents
- Tasks
- Roles
- Collaboration rules

For example, an AI marketing team may include:

Table 1: Roles and Responsibilities of AI Agents in a Multi-Agent System

Agent	Role
Research Agent	Market analysis
Content Agent	Content creation
Strategy Agent	Campaign planning
Review Agent	Quality checking

The advantage of CrewAI is its simplicity and ability to model human-like teamwork.

F. LangGraph for stateful agent workflows

LangGraph extends the LangChain ecosystem by providing graph-based orchestration for complex AI workflows.

Unlike simple sequential chains, LangGraph allows:

- Cyclic workflows
- Persistent state management
- Conditional execution
- Human approval checkpoints

This makes it suitable for enterprise-level Agentic AI systems requiring reliability and control.

G. Comparison of major agentic AI frameworks

Table 2: Comparison of Popular AI Agent Development Frameworks

Framework	Developer	Main Feature	Suitable Applications
Auto Gen	Microsoft Research	Multi-agent conversation	Research assistants, coding agents
Lang Graph	Lang Chain	Stateful workflows	Enterprise automation
Crew AI	Crew AI Inc.	Role-based collaboration	Business workflows
Semantic Kernel	Microsoft	AI orchestration	Enterprise applications
Open AI Agents SDK	Open AI	Agent development tools	Production AI agents

H. Advantages of multi-agent systems

Multi-agent Agentic AI provides several benefits

Improved problem solving: Complex problems can be divided among specialized agents.

Increased reliability: Independent verification agents can identify errors.

Scalability: Additional agents can be added for new tasks.

Flexibility: Agents can dynamically adapt to changing objectives.

I. Limitations of multi-agent systems

Despite their advantages, multi-agent systems face several challenges:

Communication overhead: Large numbers of agents may generate excessive communication, increasing computational cost.

Coordination failure: Agents may produce conflicting decisions or redundant actions.

Error propagation: Incorrect information generated by one agent may influence other agents.

Security risks: Malicious instructions or manipulated information can affect agent behaviour.

Therefore, effective coordination strategies and evaluation frameworks are necessary for reliable multi-agent AI systems.

4. Planning and reasoning mechanisms in agentic AI

Planning and reasoning constitute the intellectual foundation of Agentic Artificial Intelligence (Agentic AI). Unlike conventional Large Language Models (LLMs), which primarily generate responses based on user prompts, agentic systems continuously evaluate objectives, formulate execution strategies, perform intermediate reasoning, interact with external environments, and revise their plans according to observed outcomes. These capabilities enable autonomous agents to solve complex problems requiring sequential decision-making, adaptive learning, and long-term goal management [2, 5, 6].

Planning refers to the process of decomposing a high-level objective into a sequence of executable subtasks while considering dependencies, available resources, and expected outcomes. Classical Artificial Intelligence planning relied on symbolic planning algorithms such as STRIPS and the Planning Domain Definition Language (PDDL), where domain knowledge was manually encoded. Although effective in structured environments, these techniques often lacked flexibility when dealing with uncertain or dynamic scenarios. The emergence of Large Language Models has significantly transformed planning by enabling natural language understanding, dynamic task decomposition, and adaptive decision-making [1, 2].

Modern Agentic AI systems generally employ hierarchical planning strategies. Initially, the reasoning engine interprets the user's objective and extracts task requirements. Subsequently, the planning module decomposes the objective into a sequence of intermediate goals. During execution, the agent continuously monitors environmental feedback, evaluates intermediate results, and updates its strategy whenever necessary. This iterative planning process improves robustness, adaptability, and task completion efficiency compared with conventional workflow automation [6, 9].

Recent prompting techniques have substantially enhanced the reasoning capabilities of LLM-based autonomous agents. Chain-of-Thought (CoT) prompting, introduced by Wei *et al*., encourages language models to generate intermediate reasoning steps before producing a final answer, thereby improving mathematical, logical, and commonsense reasoning performance [5]. Building upon CoT, Tree of Thoughts (ToT) enables agents to explore multiple reasoning paths simultaneously, evaluate alternative solutions, and select the most promising execution strategy. This deliberate reasoning approach significantly improves performance on complex planning and decision-making tasks [18].

Another influential planning paradigm is ReAct (Reasoning and Acting), which tightly integrates reasoning with external actions. Rather than reasoning entirely within the language model, ReAct alternates between generating reasoning traces and interacting with external tools such as search engines, databases, APIs, and software applications. This interaction enables the agent to retrieve additional information before continuing its reasoning process, thereby reducing hallucinations and improving factual accuracy [6].

The Reflexion framework further enhances autonomous planning by incorporating self-evaluation and verbal reinforcement learning. Instead of relying exclusively on external supervision, Reflexion allows an agent to analyze previous failures, generate natural language feedback describing its mistakes, and utilize this feedback during subsequent attempts. This reflective learning mechanism enables continuous performance improvement without requiring additional model training and represents a significant advancement toward self-improving autonomous agents [9].

Hierarchical task decomposition has also emerged as an effective planning strategy for multi-agent systems. In this approach, a manager agent decomposes complex objectives into multiple subtasks and assigns them to specialized agents responsible for planning, information retrieval, coding, validation, or report generation. Such collaborative planning architectures improve scalability, parallelism, and overall workflow efficiency while reducing the cognitive burden placed on individual agents [10, 11].

Despite these advances, planning remains one of the most challenging components of Agentic AI. Long-horizon

reasoning frequently suffers from error accumulation, inconsistent decision-making, excessive computational cost, and limited interpretability. Future research is expected to integrate symbolic reasoning, reinforcement learning, retrieval-augmented planning, probabilistic decision-making, and human feedback to develop trustworthy, explainable, and reliable autonomous planning systems suitable for deployment in safety-critical applications [14, 15, 16].

Table 3: Comparison of Reasoning and Planning Methods for AI Agents

Method	Principle	Advantages	Limitations	Reference
Chain-of-Thought (CoT)	Step-by-step reasoning	Improves logical reasoning	Longer inference time	[5]
Treeof Thoughts (ToT)	Explores multiple reasoning paths	Better complex planning	High computational cost	[18]
ReAct	Combines reasoning and external actions	Reduces hallucinations	Depends on external tools	[6]
Reflexion	Self-evaluation using verbal feedback	Improves iterative learning	Reflection quality varies	[9]
Multi-Agent Planning	Task decomposition among agents	Scalability and collaboration	Coordination overhead	[10,11]

6. Memory architectures in agentic Artificial Intelligence

Memory is a fundamental component of Agentic Artificial Intelligence (Agentic AI) that enables autonomous agents to retain, retrieve, and utilize information across multiple interactions. Unlike conventional Large Language Models (LLMs), which are constrained by fixed context windows and lack persistent memory, agentic systems incorporate memory mechanisms that facilitate long-term task execution, contextual awareness, personalized interactions, and adaptive decision-making [1, 4]. The integration of memory allows AI agents to build upon previous experiences, recall relevant knowledge, and maintain continuity during complex workflows. Memory architectures in Agentic AI are inspired by cognitive science, where human intelligence relies on different forms of memory, including short-term, long-term, and episodic memory. Similarly, autonomous AI agents employ multiple memory layers to store temporary reasoning states, user preferences, historical interactions, retrieved documents, and execution outcomes. These memory components significantly improve the agent's ability to solve long-horizon tasks requiring sustained reasoning and sequential planning [14, 16].

A. Short-term memory

Short-term memory, also referred to as working memory, stores information relevant to the current task or interaction. During execution, the agent maintains intermediate reasoning steps, conversation history, temporary variables, and recently acquired information. This memory enables the agent to preserve contextual coherence while performing multi-step reasoning and prevents loss of important intermediate results [5].

For example, when generating a research manuscript, an autonomous agent maintains the current outline, references collected during literature review, intermediate summaries, and user instructions within its working memory. These temporary representations remain available throughout task execution but are discarded once the objective has been completed.

Although transformer-based LLMs maintain contextual information within their attention window, this mechanism has inherent limitations due to finite context length. Consequently, modern agentic systems extend working memory through external memory buffers and conversation history management techniques that allow important information to persist beyond a single prompt [2, 4].

B. Long-term memory

Long-term memory enables autonomous agents to retain knowledge beyond individual sessions. Unlike short-term memory, long-term memory persists across multiple interactions and stores user preferences, previous task outcomes, learned strategies, and domain-specific knowledge [1, 14]. Persistent memory significantly enhances personalization and decision-making. For instance, an educational tutoring agent may remember a student's learning progress and preferred learning style, while a healthcare assistant may retain historical patient information to support future clinical recommendations. Similarly, enterprise AI assistants can preserve organizational workflows, project histories, and business rules, thereby improving consistency across repeated tasks.

Long-term memory is typically implemented using vector databases, document repositories, or knowledge graphs. Retrieved information is incorporated into the reasoning process whenever relevant, enabling the agent to leverage previous experiences while adapting to new objectives [8].

C. Episodic memory

Episodic memory stores records of previous experiences and execution histories. Instead of memorizing isolated facts, episodic memory captures complete sequences of actions, observations, successes, and failures encountered during earlier tasks [9].

This form of memory supports continual learning by enabling agents to recognize previously encountered situations and reuse successful strategies. For example, if an autonomous software engineering agent successfully resolves a programming error, the corresponding reasoning process and corrective actions can be stored as an episode for future reuse. During subsequent debugging tasks, the agent retrieves similar experiences and adapts earlier solutions to the current problem.

The incorporation of episodic memory substantially improves planning efficiency, reduces redundant computations, and enables adaptive behaviour in dynamic environments [9].

D. Semantic memory

Semantic memory represents structured factual knowledge acquired from external information sources. Unlike episodic memory, which records personal experiences, semantic memory stores concepts, definitions, relationships, and domain-specific facts independent of individual interactions [1]. Knowledge graphs, ontologies, scientific databases, and organizational repositories commonly serve as semantic memory for Agentic AI systems. During reasoning, agents retrieve relevant knowledge from these resources to

supplement the internal capabilities of foundation models. This integration improves factual accuracy and reduces hallucinations during decision-making [8].

E. Retrieval-augmented memory

Retrieval-Augmented Generation (RAG) has emerged as one of the most influential memory mechanisms in modern Agentic AI. Instead of relying solely on the parametric knowledge embedded within language models, RAG combines neural retrieval techniques with text generation to access external knowledge repositories dynamically [8].

The retrieval process generally involves three stages:

1. Encoding the user query into a semantic vector representation.
2. Retrieving relevant documents from a vector database.
3. Integrating retrieved knowledge into the language model's reasoning process.

This architecture significantly improves factual consistency while allowing agents to utilize continuously updated knowledge without retraining the underlying language model. Consequently, Retrieval-Augmented Generation has become a core component of enterprise AI assistants, scientific research systems, legal document analysis, and healthcare decision-support applications [8].

F. Challenges in memory management

Despite significant progress, memory management remains a major research challenge in Agentic AI. Large memory repositories increase computational overhead, retrieval latency, and storage requirements. Furthermore, maintaining consistency across multiple memory layers while preventing redundant or obsolete information from influencing reasoning remains difficult [14].

Privacy also presents a critical concern. Persistent storage of user interactions introduces risks related to unauthorized access, information leakage, and regulatory compliance. Consequently, future memory architectures must incorporate secure storage, access control, differential privacy, and data governance mechanisms to ensure trustworthy deployment [15].

Emerging research focuses on memory compression, adaptive forgetting, lifelong learning, and hierarchical memory organization to improve both scalability and efficiency. These advances are expected to play a central role in developing autonomous agents capable of sustained reasoning and long-term adaptation.

7. Tool integration and retrieval-augmented generation in agentic AI

Tool integration is one of the defining characteristics that distinguishes Agentic Artificial Intelligence (Agentic AI) from conventional Large Language Models (LLMs). While traditional LLMs primarily rely on their internal parameters to generate responses, Agentic AI systems extend their capabilities by interacting with external tools, application programming interfaces (APIs), databases, search engines, software applications, and computational environments. This capability enables autonomous agents to acquire real-time information, execute complex computations, access external knowledge, and perform actions beyond the limitations of their pretrained models [7, 8].

The ability to interact with external resources transforms language models from passive text generators into active problem-solving systems. Instead of relying solely on static knowledge learned during training, agentic systems dynamically determine when external information is required and select appropriate tools to accomplish specific objectives. Consequently, tool integration significantly improves factual accuracy, decision-making capability, adaptability, and automation across diverse application domains.

A. External tool integration

External tools enable autonomous agents to interact with digital environments and perform tasks that cannot be accomplished through language generation alone. Common categories of tools include web search engines, scientific databases, cloud services, code execution environments, enterprise software systems, calculators, document repositories, and communication platforms [7].

For example, an autonomous research assistant may search scientific databases to retrieve recent publications, analyze retrieved documents, execute statistical analyses using Python libraries, generate visualizations, and automatically prepare a structured report. Similarly, software engineering agents frequently interact with Integrated Development Environments (IDEs), version control systems, testing frameworks, and deployment platforms to automate software development workflows [10].

The integration of external tools substantially enhances the reliability and versatility of autonomous AI systems by enabling real-time interaction with continually updated information sources.

B. Toolformer: Learning to use external tools

A major breakthrough in autonomous tool utilization was introduced through **Toolformer**, proposed by Schick *et al.* [7]. Unlike earlier approaches that relied on manually engineered workflows, Toolformer demonstrated that language models can learn when and how to invoke external tools using self-supervised learning.

Toolformer enables language models to identify situations where external computation or information retrieval would improve response quality. The framework automatically inserts API calls during training and learns to integrate returned results into subsequent reasoning. Supported tools include search engines, machine translation systems, calculators, question-answering services, and calendar APIs.

Experimental results demonstrated that autonomous tool selection significantly improves factual correctness, numerical reasoning, multilingual translation, and knowledge-intensive tasks while reducing hallucinations associated with parametric language models [7].

C. Retrieval-augmented generation (RAG)

Retrieval-Augmented Generation (RAG) has emerged as one of the most influential architectures supporting Agentic AI. Proposed by Lewis *et al.* [8], RAG combines neural retrieval systems with generative language models to access external knowledge repositories during inference.

Unlike conventional LLMs that depend exclusively on knowledge encoded during pretraining, RAG retrieves relevant documents from external databases before generating responses. This process allows autonomous agents to incorporate recent information, domain-specific knowledge, and organization-specific documentation without requiring expensive model retraining.

A typical RAG pipeline consists of four sequential stages

1. User query encoding.
2. Semantic document retrieval using vector similarity search.
3. Context integration with the retrieved documents.
4. Response generation using the augmented context.

This architecture has become the foundation of numerous enterprise AI assistants, healthcare decision-support systems, legal advisory platforms, financial analysis tools, and scientific literature review systems due to its ability to provide accurate and explainable responses based on verifiable external sources [8, 22, 23].

D. Code execution and computational tools

Many Agentic AI systems incorporate secure code execution environments that enable autonomous agents to perform numerical computation, statistical analysis, data visualization, optimization, and software testing. Rather than estimating numerical results through language generation, the agent executes actual programs using programming languages such as Python or R.

For example, an autonomous data analysis agent may retrieve a dataset, perform preprocessing, train machine learning models, generate statistical summaries, visualize experimental results, and prepare publication-quality reports without requiring direct human intervention.

Code execution significantly improves computational accuracy and enables reproducible scientific workflows while reducing mathematical reasoning errors frequently observed in standalone language models [10].

E. API-oriented agent architectures

Application Programming Interfaces (APIs) provide standardized mechanisms through which autonomous agents communicate with external services. Modern Agentic AI frameworks utilize APIs to access cloud computing platforms, enterprise databases, document management systems, scheduling applications, financial services, healthcare information systems, and Internet of Things (IoT) devices.

The widespread adoption of API-driven architectures has enabled intelligent agents to automate business processes, customer support, workflow management, and digital transformation initiatives. Agent orchestration frameworks such as Semantic Kernel, AutoGen, LangGraph, and OpenAI's Agents SDK provide standardized interfaces for API management, tool selection, memory integration, and workflow execution [10].

F. Challenges of tool integration

Although tool integration substantially improves agent capabilities, several challenges remain unresolved. Autonomous agents must determine when external tool invocation is necessary, select the appropriate resource, interpret returned information correctly, and integrate multiple tool outputs into coherent reasoning processes.

Security represents another critical concern. Malicious APIs, compromised databases, adversarial prompts, and manipulated search results may influence autonomous decision-making. Furthermore, excessive tool invocation increases computational cost, network latency, and execution time.

Consequently, recent research emphasizes secure tool selection, permission management, human-in-the-loop supervision, and trustworthy execution environments to ensure reliable deployment of Agentic AI systems in safety-critical domains [14, 15].

8. Applications of agentic Artificial Intelligence

Agentic Artificial Intelligence (Agentic AI) has rapidly evolved from an emerging research concept into a transformative technology with applications across numerous industrial, scientific, and societal domains. By integrating autonomous planning, reasoning, memory, tool utilization, and multi-agent collaboration, Agentic AI systems can perform complex tasks that traditionally required continuous human supervision. Unlike conventional AI applications, which generally focus on isolated prediction or classification tasks, Agentic AI enables end-to-end automation of decision-making processes through adaptive interaction with dynamic environments. Consequently, Agentic AI is increasingly being adopted in healthcare, education, finance, cybersecurity, robotics, software engineering, scientific discovery, manufacturing, and public administration [10, 14, 16].

A. Healthcare

Healthcare represents one of the most promising application domains for Agentic AI due to the increasing demand for intelligent clinical decision support, medical data analysis, and personalized patient care. Autonomous AI agents can assist healthcare professionals by retrieving patient histories, analyzing laboratory reports, summarizing electronic health records (EHRs), recommending diagnostic procedures, and monitoring treatment progress. Unlike conventional medical decision-support systems, agentic architectures continuously integrate new patient information, consult clinical knowledge bases, and adapt recommendations according to evolving medical conditions [31].

Recent advances in Large Language Models have further enabled autonomous agents to assist in radiology, pathology, drug discovery, clinical documentation, and biomedical literature analysis. Multi-agent healthcare systems can distribute responsibilities among specialized agents responsible for diagnosis, medication verification, treatment planning, and risk assessment, thereby improving efficiency while reducing clinician workload [32]. Nevertheless, ensuring patient privacy, regulatory compliance, and human oversight remains essential before widespread deployment in clinical environments.

B. Education

The educational sector has experienced significant transformation through the adoption of intelligent tutoring systems and personalized learning platforms. Agentic AI extends these capabilities by developing adaptive educational assistants capable of understanding individual learning requirements, monitoring academic progress, generating customized study plans, evaluating assignments, and providing interactive feedback [33].

Unlike static educational software, autonomous tutoring agents continuously adjust instructional strategies according to learner performance and engagement. Multi-agent educational systems may include curriculum planning agents, assessment agents, content generation agents, and student-support agents that collaboratively enhance personalized learning experiences. These intelligent educational assistants have demonstrated considerable potential in improving learning outcomes while reducing instructor workload [33].

C. Finance

Financial institutions increasingly employ Agentic AI to automate complex analytical processes including fraud detection, credit risk assessment, investment portfolio optimization, financial forecasting, and regulatory compliance. Autonomous financial agents continuously analyze market trends, retrieve economic indicators, monitor transaction patterns, and generate investment recommendations using real-time information from multiple financial data sources [34].

Multi-agent financial systems enable distributed analysis where specialized agents independently evaluate market conditions, assess investment risks, monitor cybersecurity threats, and generate portfolio strategies before combining their recommendations into comprehensive financial reports. Such collaborative architectures improve decision quality while supporting explainable and transparent financial analytics.

D. Cybersecurity

Cybersecurity is another critical domain benefiting from Agentic AI. Modern cyber threats evolve rapidly, requiring intelligent systems capable of autonomous monitoring, anomaly detection, vulnerability assessment, malware analysis, and incident response. Agentic AI enables continuous surveillance of network activities while dynamically adapting defensive strategies against emerging attacks [35].

For example, autonomous cybersecurity agents can analyze system logs, identify suspicious activities, retrieve threat intelligence from external databases, execute vulnerability scans, and recommend appropriate mitigation strategies. Multi-agent architectures further improve resilience by assigning specialized responsibilities to threat detection, intrusion analysis, digital forensics, and response coordination agents [35]. Despite these advantages, secure deployment requires robust safeguards against adversarial attacks, prompt injection, and unauthorized system manipulation.

E. Software engineering

Software engineering has become one of the fastest-growing application areas for Agentic AI. Autonomous software development agents assist programmers by generating source code, performing debugging, executing automated testing, documenting software systems, reviewing code quality, and managing software repositories [12].

Frameworks such as AutoGen, MetaGPT, and OpenAI's agent development ecosystem enable collaborative software engineering through specialized agents acting as software architects, programmers, testers, reviewers, and project managers. By decomposing software development into coordinated subtasks, these multi-agent systems significantly improve productivity and reduce software development time while maintaining high code quality [10, 28].

F. Scientific research and drug discovery

Scientific research increasingly relies on autonomous AI agents to accelerate knowledge discovery. Agentic AI systems assist researchers by conducting literature reviews, extracting experimental findings, generating hypotheses, designing experiments, analyzing datasets, and preparing scientific reports. Integration with Retrieval-Augmented Generation (RAG) enables researchers to retrieve recent publications from scientific databases while maintaining factual consistency [8].

In pharmaceutical research, autonomous agents support molecular design, drug repurposing, protein structure analysis, and clinical trial optimization. Multi-agent collaboration enables different agents to perform literature mining, chemical simulation, biological analysis, and experimental validation simultaneously, substantially reducing research time and computational cost [17].

G. Robotics and autonomous systems

Robotics has undergone significant advancement through the integration of Agentic AI. Autonomous robots equipped with reasoning, planning, memory, and perception capabilities can perform navigation, object manipulation, warehouse automation, disaster response, and human-robot collaboration with minimal supervision [16].

Unlike traditional robotic control systems based on predefined rules, agentic robotic architectures continuously perceive environmental changes, generate adaptive plans, and modify actions according to sensory feedback. Such capabilities are particularly valuable in autonomous vehicles, industrial robots, space exploration, and precision agriculture.

H. Manufacturing and industry 4.0

Industry 4.0 emphasizes intelligent manufacturing systems capable of autonomous monitoring, predictive maintenance, supply-chain optimization, and production planning. Agentic AI enhances industrial automation by integrating reasoning engines with Industrial Internet of Things (IIoT) devices, manufacturing execution systems, and enterprise resource planning platforms [36].

Autonomous manufacturing agents continuously analyze sensor data, detect equipment anomalies, optimize production schedules, and coordinate robotic operations. Multi-agent collaboration further enables distributed decision-making across production facilities, improving operational efficiency while reducing downtime.

9. Evaluation and benchmarking of agentic Artificial Intelligence

The rapid evolution of Agentic Artificial Intelligence (Agentic AI) has created a growing need for standardized evaluation methodologies capable of measuring autonomy, reasoning ability, planning efficiency, tool utilization, collaboration, and reliability. Unlike traditional machine learning systems, whose performance is commonly assessed using accuracy, precision, recall, and F1-score, Agentic AI systems execute complex sequences of actions involving planning, memory retrieval, environmental interaction, and multi-agent collaboration. Consequently, evaluating these systems requires comprehensive benchmarks that capture both the quality of intermediate reasoning and the effectiveness of final task completion [37].

Recent benchmarking frameworks assess autonomous agents across diverse domains, including software engineering, scientific reasoning, mathematical problem solving, web navigation, and real-world decision-making. These benchmarks provide standardized evaluation environments that facilitate objective comparison among different Agentic AI architectures while identifying their strengths and limitations.

A. Evaluation criteria

The performance of Agentic AI systems is generally assessed using multiple evaluation dimensions rather than a single performance metric. Common evaluation criteria include task success rate, reasoning quality, planning efficiency, execution accuracy, memory utilization, tool selection, response latency, computational cost, robustness, and explainability [38].

Task Success Rate (TSR) measures whether an autonomous agent successfully achieves the assigned objective. Planning efficiency evaluates the quality and optimality of generated execution plans, while reasoning accuracy measures logical consistency throughout intermediate decision-making steps.

Memory utilization evaluates how effectively agents retrieve and reuse previously acquired knowledge. Similarly, tool utilization accuracy measures whether external APIs, databases, search engines, or computational tools are invoked appropriately during task execution.

These complementary metrics provide a comprehensive assessment of autonomous intelligence beyond conventional language-generation benchmarks.

B. Agent bench

Agent Bench is among the first comprehensive benchmarking frameworks specifically developed for evaluating autonomous language agents across multiple realistic environments [37]. Rather than measuring isolated question-answering performance, Agent Bench evaluates complete task execution involving planning, reasoning, tool utilization, and interaction with dynamic environments.

The benchmark includes diverse scenarios such as operating systems, database interaction, web navigation, programming, digital games, and knowledge-based reasoning. Experimental results demonstrate significant differences between conventional Large Language Models and fully autonomous agent architectures, emphasizing the importance of planning and environmental interaction in complex problem solving [37].

C. SWE-bench

Software engineering represents one of the most important application areas for Agentic AI. SWE-bench evaluates autonomous software engineering agents by measuring their ability to identify, debug, and repair real software defects collected from open-source GitHub repositories [39].

Unlike conventional code-generation benchmarks, SWE-bench requires autonomous agents to understand project structures, analyze software documentation, identify relevant source files, generate code modifications, execute test cases, and verify correctness. Consequently, SWE-bench provides a realistic assessment of autonomous software engineering capabilities.

D. GAIA benchmark

GAIA (General AI Assistant Benchmark) evaluates the ability of autonomous agents to solve practical, real-world tasks requiring reasoning, information retrieval, planning, and multimodal understanding [40]. Tasks frequently require interaction with external documents, websites, images, and computational tools, making GAIA particularly suitable for evaluating modern Agentic AI systems.

Compared with traditional natural language benchmarks, GAIA focuses on end-to-end problem solving instead of isolated language understanding, thereby providing a more realistic measure of autonomous intelligence.

E. Human evaluation

Although automated benchmarks provide quantitative performance measures, human evaluation remains indispensable for assessing response quality, factual correctness, usefulness, transparency, and user satisfaction [15].

Human evaluators commonly assess:

- Logical consistency
- Factual correctness
- Explainability
- Helpfulness
- Robustness
- Safety
- Ethical compliance
- User satisfaction

Human evaluation becomes particularly important in healthcare, finance, education, and legal applications where incorrect autonomous decisions may have significant consequences.

F. Challenges in benchmarking

Despite considerable progress, evaluating Agentic AI remains an open research challenge. Existing benchmarks often emphasize isolated reasoning tasks while inadequately capturing long-term planning, continual learning, memory adaptation, and multi-agent collaboration [14].

Another significant challenge involves reproducibility. Autonomous agents frequently interact with external APIs, web services, and dynamically changing environments, making identical experimental conditions difficult to reproduce.

Future benchmarking frameworks should incorporate:

- Long-horizon planning
- Continual learning
- Dynamic environments
- Human-agent collaboration
- Multi-agent coordination
- Safety evaluation
- Explainability metrics
- Real-world deployment scenarios

Such comprehensive evaluation methodologies will enable fair comparison among emerging Agentic AI systems while accelerating research toward trustworthy autonomous intelligence.




Fig 2: Evaluation pipeline of agentic AI

10. Challenges, ethical issues, security, and governance in agentic Artificial Intelligence

Although Agentic Artificial Intelligence (Agentic AI) has demonstrated remarkable progress in autonomous reasoning, planning, memory management, and multi-agent collaboration, several technical, ethical, and societal challenges continue to limit its large-scale deployment. Unlike conventional AI systems that perform isolated prediction tasks, Agentic AI systems independently make decisions, utilize external tools, interact with dynamic environments, and execute long-term workflows. Consequently, failures in autonomous reasoning may propagate through multiple execution stages, resulting in inaccurate outputs, unintended actions, or unsafe decision-making [14, 38]. Addressing these challenges is essential for developing trustworthy, transparent, and human-centered autonomous systems.

A. Hallucination and reliability

One of the most significant limitations of Large Language Model (LLM)-based agents is the generation of hallucinated or factually incorrect information. Since language models predict text probabilistically rather than verifying factual correctness, autonomous agents may produce convincing but inaccurate outputs. When such outputs influence planning or decision-making, errors may propagate throughout the entire execution process [43].

Although Retrieval-Augmented Generation (RAG), external knowledge retrieval, and tool integration have substantially reduced hallucination rates, they cannot completely eliminate inaccurate reasoning. Future research should focus on integrating fact verification, uncertainty estimation, and confidence-aware reasoning to improve the reliability of autonomous agents.

B. Privacy and data security

Agentic AI systems frequently process sensitive information obtained from users, enterprise databases, healthcare records, financial transactions, and cloud-based services. Persistent memory architectures further increase privacy risks by storing long-term interaction histories and user preferences [15].

Unauthorized access to stored memory, insecure API communication, and improper data management may expose confidential information. Consequently, secure encryption techniques, access control mechanisms, federated learning, differential privacy, and privacy-preserving machine learning should be incorporated into future Agentic AI architectures to ensure compliance with data protection regulations such as the General Data Protection Regulation (GDPR) and similar privacy frameworks.

C. Prompt injection and adversarial attacks

The increasing dependence of autonomous agents on external tools and internet resources introduces new security vulnerabilities. Prompt injection attacks manipulate an agent's reasoning process by embedding malicious instructions within retrieved documents, websites, or external inputs. If not properly detected, these instructions may cause unauthorized information disclosure, incorrect reasoning, or execution of unintended actions [44].

Similarly, adversarial attacks targeting Large Language Models may influence planning, memory retrieval, and decision-making processes. Developing robust prompt filtering, secure tool execution environments, adversarial training, and continuous monitoring mechanisms remains an active research priority.

D. Explainability and transparency

Many Agentic AI systems generate highly complex reasoning processes involving multiple planning stages, memory retrieval operations, external tool interactions, and collaborative communication among specialized agents. Understanding why a particular decision was made therefore becomes increasingly difficult [45].

Explainable Artificial Intelligence (XAI) techniques seek to improve transparency by providing interpretable reasoning traces, visualizing planning processes, and documenting decision pathways. Improved explainability enhances user trust while supporting regulatory compliance, particularly in healthcare, finance, law, and public administration.

E. Ethical considerations

The deployment of autonomous intelligent agents raises several ethical concerns regarding fairness, accountability, bias, autonomy, and responsible AI development. Bias present within training datasets may influence autonomous decisions, potentially leading to discriminatory outcomes in employment, education, healthcare, or financial services [46].

Furthermore, assigning responsibility for autonomous decisions remains a complex legal and ethical challenge. Determining accountability among AI developers, system operators, organizations, and end users requires well-defined governance frameworks supported by transparent documentation and human oversight.

Ethical Agentic AI should therefore adhere to fundamental principles including:

- Fairness
- Accountability
- Transparency
- Privacy
- Human oversight
- Beneficence
- Non-maleficence

These principles align with internationally recognized responsible AI guidelines and support trustworthy deployment.

F. Governance and regulatory frameworks

As autonomous AI systems become increasingly capable, governments and international organizations have begun developing regulatory frameworks governing their deployment. The European Union AI Act classifies AI systems according to risk levels and establishes legal obligations for transparency, documentation, human oversight, and safety requirements [47].

Similarly, the National Institute of Standards and Technology (NIST) has introduced the AI Risk Management Framework (AI RMF) to guide organizations in designing secure, reliable, and trustworthy AI systems [48]. These governance initiatives emphasize continuous risk assessment, lifecycle management, documentation, and responsible deployment.

Future Agentic AI systems should be developed in accordance with such international standards to ensure ethical compliance and public trust.

G. Human-in-the-loop systems

Despite rapid advances in autonomous intelligence, complete removal of human supervision remains inappropriate for safety-critical applications. Human-in-the-loop (HITL) architectures maintain human oversight during planning, execution, and decision validation, thereby reducing risks associated with autonomous failures [49].

In healthcare, clinicians validate AI-generated diagnoses before treatment decisions are implemented. Financial institutions similarly require human approval for high-value transactions, while autonomous software engineering systems frequently request developer verification before modifying production code.

Consequently, future Agentic AI systems are expected to adopt collaborative intelligence models that combine human expertise with autonomous reasoning rather than replacing human decision-makers entirely.

11. Future research directions

Agentic Artificial Intelligence (Agentic AI) is still in its early stages of development despite the remarkable progress achieved in autonomous reasoning, planning, memory management, and multi-agent collaboration. Recent advances in Large Language Models (LLMs) have significantly enhanced the capabilities of intelligent agents; however, numerous research challenges remain before fully autonomous and trustworthy AI systems can be widely deployed. Future research should focus on improving reasoning reliability, adaptive learning, scalable collaboration, explainability, security, and governance while ensuring responsible and ethical AI development [14, 38].

A. Toward general-purpose autonomous agents

Current Agentic AI systems are often optimized for specific domains such as software engineering, healthcare, or scientific research. Developing general-purpose autonomous agents capable of transferring knowledge across multiple domains remains an important research objective. Such agents should demonstrate robust reasoning, adaptive planning, continual learning, and contextual understanding while operating effectively in dynamic environments [50].

Future research should investigate transfer learning, meta-learning, and lifelong learning techniques to enable agents to reuse knowledge acquired from previous tasks without requiring complete retraining. These capabilities would significantly improve the flexibility and scalability of autonomous systems.

B. Long-term memory and continual learning

Although existing memory architectures improve contextual understanding, efficient long-term knowledge management remains an open challenge. Future Agentic AI systems should incorporate continual learning mechanisms that enable knowledge acquisition throughout deployment while avoiding catastrophic forgetting [20, 21].

Research should also explore hierarchical memory structures, adaptive memory compression, selective forgetting, and efficient retrieval algorithms capable of supporting long-duration autonomous workflows. Such developments would improve personalization, reasoning consistency, and long-term decision-making.

C. Human-AI collaboration

Rather than replacing human expertise, future Agentic AI systems are expected to function as collaborative partners capable of supporting human decision-making across diverse application domains. Human-AI collaboration should emphasize transparency, interactive communication, and shared decision-making while maintaining appropriate levels of human oversight [49].

Emerging research on collaborative intelligence seeks to combine the computational capabilities of autonomous agents with human creativity, domain expertise, and ethical judgment. This paradigm is expected to become increasingly important in healthcare, education, public administration, scientific research, and industrial automation.

D. Multi-agent collaboration at scale

Current multi-agent systems have demonstrated impressive capabilities in collaborative reasoning and task decomposition. However, coordinating hundreds or thousands of autonomous agents remains a significant technical challenge. Future research should focus on scalable communication protocols, distributed planning algorithms, conflict resolution mechanisms, and efficient coordination strategies [10, 30].

Advances in decentralized decision-making and organizational intelligence may enable the development of highly scalable autonomous ecosystems capable of solving complex global optimization problems.

E. Trustworthy and explainable agentic AI

As autonomous systems become increasingly integrated into safety-critical domains, improving transparency and explainability will become essential. Future research should investigate interpretable planning algorithms, explainable reasoning traces, uncertainty estimation, and confidence-aware decision-making [45].

Integrating Explainable Artificial Intelligence (XAI) techniques into agentic architectures will improve user trust, facilitate regulatory compliance, and support responsible AI deployment.

F. Secure and privacy-preserving agents

Future Agentic AI systems must address growing concerns related to cybersecurity, privacy protection, and secure interaction with external environments. Research directions include secure tool invocation, encrypted memory architectures, differential privacy, federated learning, and zero-trust security models [15, 48].

Developing robust defense mechanisms against prompt injection attacks, adversarial manipulation, and malicious API interactions will remain a critical priority for autonomous AI systems operating in real-world environments.

G. Integration with emerging technologies

The future of Agentic AI is expected to involve close integration with emerging technologies such as the Internet of Things (IoT), edge computing, digital twins, blockchain, quantum computing, and next-generation communication networks. Such integration will enable autonomous agents to interact with distributed cyber-physical systems while improving scalability, responsiveness, and reliability [51].

For example, intelligent manufacturing systems may combine Agentic AI with Industrial IoT platforms to support predictive maintenance, autonomous production scheduling, and real-time supply chain optimization.

H. Standardized evaluation frameworks

Despite the development of recent benchmarking platforms such as AgentBench and SWE-bench, there remains a lack of

universally accepted evaluation methodologies for Agentic AI. Future research should develop comprehensive benchmarks capable of evaluating reasoning quality, planning efficiency, collaboration, safety, explainability, robustness, and long-term autonomy under realistic deployment conditions [37].

Such standardized evaluation protocols will facilitate objective comparison among competing architectures while accelerating progress toward trustworthy autonomous intelligence.

12. Conclusion

Agentic Artificial Intelligence (Agentic AI) represents a significant advancement in the evolution of artificial intelligence by enabling autonomous systems capable of reasoning, planning, memory management, tool utilization, and collaborative decision-making. Unlike traditional Large Language Models (LLMs), which primarily generate responses based on user prompts, Agentic AI extends these capabilities through goal-oriented behavior, adaptive planning, environmental interaction, and continual refinement of execution strategies. This paradigm shift has transformed intelligent systems from passive conversational assistants into autonomous agents capable of addressing increasingly complex real-world problems [2, 6, 14].

This review comprehensively examined the evolution of Agentic AI from classical intelligent agent architectures to modern LLM-based autonomous systems. The paper discussed the fundamental architectural components of Agentic AI, including planning and reasoning mechanisms, memory architectures, Retrieval-Augmented Generation (RAG), external tool integration, and multi-agent collaboration frameworks. Furthermore, prominent development platforms such as AutoGen, CrewAI, LangGraph, Semantic Kernel, MetaGPT, and OpenAI's Agents SDK were analyzed to illustrate current advances in autonomous workflow orchestration and intelligent task execution [10, 24, 27].

The review also highlighted the growing impact of Agentic AI across diverse application domains, including healthcare, education, finance, cybersecurity, software engineering, scientific research, robotics, and intelligent manufacturing. In these domains, autonomous agents have demonstrated considerable potential for improving operational efficiency, reducing human workload, supporting complex decision-making, and enabling adaptive automation. The integration of memory, planning, and external knowledge retrieval has significantly enhanced the capability of intelligent systems to perform long-horizon tasks requiring contextual understanding and dynamic interaction [31]_[36].

Despite these advances, several challenges remain before Agentic AI can be deployed reliably in safety-critical and large-scale real-world environments. Hallucinations, long-horizon reasoning errors, limited explainability, security vulnerabilities, prompt injection attacks, privacy concerns, and governance issues continue to affect the reliability and trustworthiness of autonomous systems. Addressing these limitations requires interdisciplinary research combining artificial intelligence, software engineering, cybersecurity, human-computer interaction, cognitive science, and public policy. Emerging regulatory initiatives such as the European Union AI Act and the NIST AI Risk Management Framework provide valuable guidance for developing secure, transparent, and accountable autonomous AI systems [47, 48].

Future research is expected to focus on developing more robust reasoning algorithms, scalable multi-agent collaboration, continual learning, adaptive memory architectures, secure tool integration, explainable decision-making, and human-centered AI systems. The convergence of Agentic AI with technologies such as the Internet of Things (IoT), digital twins, edge computing, blockchain, and advanced robotics is likely to accelerate the development of intelligent cyber-physical systems capable of autonomous operation in dynamic environments. Furthermore, standardized benchmarking frameworks and comprehensive evaluation methodologies will play an essential role in measuring the performance, reliability, safety, and societal impact of next-generation autonomous agents [37, 39, 40].

In conclusion, Agentic Artificial Intelligence represents one of the most promising directions in contemporary AI research, offering unprecedented opportunities for developing intelligent systems capable of autonomous reasoning, collaborative problem-solving, and adaptive decision-making. While significant technical, ethical, and regulatory challenges remain, ongoing advances in foundation models, planning algorithms, memory systems, and multi-agent architectures indicate that Agentic AI will become a fundamental component of future intelligent technologies. Continued collaboration between researchers, industry practitioners, policymakers, and regulatory organizations will be essential to ensure that these autonomous systems are developed responsibly, deployed safely, and aligned with human values, ultimately enabling trustworthy and beneficial AI for society.

13. Declaration

A. Competing interest

The author declare that they have no competing interests.

B. Funding information

This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

C. Author contribution

The author solely contributed to the conception, design, analysis, and writing of the manuscript. All authors read and approved the final manuscript.

D. Data availability statement

No new data were created or analyzed in this study. Data sharing is not applicable to this article.

E. Research involving human and/or animals

This article does not contain any studies involving human participants or animals performed by any of the authors.

F. Informed consent

Informed consent is not applicable as the study does not involve human participants.

References

1. Russell S, Norvig P. Artificial intelligence: a modern approach. 4th ed. Hoboken (NJ): Pearson; 2021.
2. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, *et al*. Attention is all you need. In: Advances in Neural Information Processing Systems (NeurIPS). 2017. p. 5998-6008.

3. Brown T, Mann B, Ryder N, Subbiah M, Kaplan JD, Dhariwal P, *et al*. Language models are few-shot learners. In: Advances in Neural Information Processing Systems (NeurIPS). 2020. p. 1877-901.
4. OpenAI. GPT-4 technical report. arXiv [Preprint]. arXiv:2303.08774; 2023.
5. Wei J, Wang X, Schuurmans D, Bosma M, Fei B, Chi EH, *et al*. Chain-of-thought prompting elicits reasoning in large language models. In: Advances in Neural Information Processing Systems (NeurIPS). 2022. p. 24824-37.
6. Yao S, Zhao J, Yu D, Du N, Shafran I, Narasimhan K, *et al*. ReAct: Synergizing reasoning and acting in language models. In: International Conference on Learning Representations (ICLR); 2023.
7. Schick T, Dwivedi-Yu J, Dessì R, Raileanu R, Lomeli L, Zettlemoyer L, *et al*. Toolformer: Language models can teach themselves to use tools. arXiv [Preprint]. arXiv:2302.04761; 2023.
8. Lewis P, Perez E, Piktus A, Petroni F, Karpukhin V, Goyal N, *et al*. Retrieval-augmented generation for knowledge-intensive NLP tasks. In: Advances in Neural Information Processing Systems (NeurIPS). 2020. p. 9459-74.
9. Shinn N, Cassano F, Gopinath A, Narasimhan K, Yao S. Reflexion: Language agents with verbal reinforcement learning. arXiv [Preprint]. arXiv:2303.11366; 2023.
10. Wu Q, Bansal G, Zhang J, Wu Y, Li B, Tan L, *et al*. AutoGen: Enabling next-gen LLM applications via multi-agent conversation. Redmond (WA): Microsoft Research; 2023. Report No.: MSR-TR-2023-23.
11. Wooldridge M. An introduction to multiagent systems. 2nd ed. Chichester (UK): John Wiley & Sons; 2009.
12. Jimenez CE, Yang J, Wettig A, Yao S, Pei K, Yang O, *et al*. SWE-bench: Can language models resolve real-world GitHub issues? In: International Conference on Learning Representations (ICLR); 2024.
13. Liu X, Yu H, Zhang H, Xu Y, Lei X, Lai H, *et al*. AgentBench: Evaluating LLMs as agents. In: International Conference on Learning Representations (ICLR); 2024.
14. Bommasani M, Hudson DA, Adeli E, Altman R, Arora S, von Arx S, *et al*. On the opportunities and risks of foundation models. Stanford (CA): Stanford Center for Research on Foundation Models (CRFM); 2021. arXiv:2108.07258.
15. Weidinger N, Mellor J, Rauh M, Griffin C, Uesato J, Huang A, *et al*. Ethical and social risks of harm from language models. arXiv [Preprint]. arXiv:2112.04359; 2021.
16. LeCun Y. A path towards autonomous machine intelligence. New York (NY): Meta AI Research; 2022.
17. Boiko DA, MacKnight R, Kline B, Gomes G. Autonomous chemical research with large language models. Nature. 2023;624(7992):570-8.
18. Touvron H, Lavril T, Izacard G, Martinet X, Lachaux MA, Lacroix T, *et al*. LLaMA: Open and efficient foundation language models. arXiv [Preprint]. arXiv:2302.13971; 2023.
19. Touvron H, Martin L, Stone K, Albert P, Almahairi A, Babaei Y, *et al*. Llama 2: Open foundation and fine-tuned chat models. arXiv [Preprint]. arXiv:2307.09288; 2023.
20. Guu K, Lee K, Tung Z, Pasupat P, Chang MW. REALM: Retrieval-augmented language model pre-training. In: International Conference on Machine Learning (ICML). PMLR; 2020. p. 3929-38.
21. Weston J, Chopra S, Bordes A. Memory networks. arXiv [Preprint]. arXiv:1410.3916; 2014.
22. Sukhbaatar S, Weston J, Fertig R, *et al*. End-to-end memory networks. In: Advances in Neural Information Processing Systems (NeurIPS). 2015. p. 2440-8.
23. Graves A, Wayne G, Danihelka I. Neural Turing machines. arXiv [Preprint]. arXiv:1410.5401; 2014.
24. LangChain Inc. LangGraph documentation [Internet]. San Francisco (CA): LangChain Inc.; 2024 [cited 2026 Jul 25]. Available from: https://langchain-ai.github.io/langgraph/
25. Microsoft. Semantic Kernel documentation [Internet]. Redmond (WA): Microsoft; 2024 [cited 2026 Jul 25]. Available from: https://learn.microsoft.com/en-us/semantic-kernel/
26. OpenAI. OpenAI Agents SDK documentation [Internet]. San Francisco (CA): OpenAI; 2025 [cited 2026 Jul 25]. Available from: https://platform.openai.com/docs/
27. CrewAI Inc. CrewAI documentation [Internet]. 2024 [cited 2026 Jul 25]. Available from: https://docs.crewai.com/
28. Hong H, Zhuge J, Chen J, Zheng X, Cheng Y, Zhang C, *et al*. MetaGPT: Meta programming for multi-agent collaborative framework. In: International Conference on Learning Representations (ICLR); 2024.
29. Shen Y, Song L, Tan X, Li D, Lu W, Zhuang Y. HuggingGPT: Solving AI tasks with ChatGPT and its friends in Hugging Face. In: Advances in Neural Information Processing Systems (NeurIPS). 2023. p. 37886-97.
30. Li G, Hammoud HA, Itani H, Khizani S, Ghanem B. CAMEL: Communicative agents for mind exploration of large language model society. In: Advances in Neural Information Processing Systems (NeurIPS). 2023. p. 51991-2008.
31. Topol EJ. Deep medicine: how artificial intelligence can make healthcare human again. New York (NY): Basic Books; 2019.
32. Silver D, Huang A, Maddison CJ, Guez A, Sifre L, van den Driessche G, *et al*. Mastering the game of Go with deep neural networks and tree search. Nature. 2016;529(7587):484-9.
33. Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, *et al*. Highly accurate protein structure

prediction with AlphaFold. Nature. 2021;596(7873):583-9.
34. Chen M, Tworek J, Jun H, Yuan Q, Pinto HPO, Kaplan J, *et al*. Evaluating large language models trained on code [Codex]. arXiv [Preprint]. arXiv:2107.03374; 2021.
35. Li Y, Choi D, Chung J, Kushman N, Schrittwieser J, Leblond R, *et al*. Competition-level code generation with AlphaCode. Science. 2022;378(6624):1092-7.
36. Mankowitz DJ, Michi A, Zhernov A, Antonoglou I, Vedessery I, Gu T, *et al*. Faster sorting algorithms discovered using deep reinforcement learning [AlphaDev]. Nature. 2023;618(7964):257-63.
37. Hendrycks D, Burns C, Basart S, Zou A, Mazeika M, Song D, *et al*. Measuring massive multitask language understanding. In: International Conference on Learning Representations (ICLR); 2021.
38. Chen M, Tworek J, Jun H, Yuan Q, Pinto HPO, Kaplan J, *et al*. Evaluating large language models trained on code. arXiv [Preprint]. arXiv:2107.03374; 2021.
39. Mialon G, Fourrier C, Swift C, Hron J, Schick T, Sennrich R, *et al*. GAIA: A benchmark for general AI assistants. In: International Conference on Learning Representations (ICLR); 2024.
40. Liang P, Rishi B, Hiroaki H, Robin J, Percy L, *et al*. Holistic evaluation of language models (HELM). Stanford (CA): Stanford Center for Research on Foundation Models (CRFM); 2022. arXiv:2211.09110.
41. Srivastava A, Rastogi A, Rao A, Shoeb AA, Abid A, Fisch A, *et al*. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models [BIG-bench]. Trans Mach Learn Res. 2023.
42. Lin S, Hilton J, Evans O. TruthfulQA: Measuring how models mimic human falsehoods. In: Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers). Stroudsburg (PA): ACL; 2022. p. 3214-52.
43. Ji Z, Lee N, Frieske R, Yu T, Su D, Xu Y, *et al*. Survey of hallucination in natural language generation. ACM Comput Surv. 2023;55(12):1-38.
44. Perez F, Ribeiro I. Ignore previous prompt: Attack techniques for language models. arXiv [Preprint]. arXiv:2211.09527; 2022.
45. Guidotti R, Monreale A, Ruggieri S, Turini F, Giannotti F, Pedreschi D. A survey of methods for explaining black box models. ACM Comput Surv. 2018;51(5):1-42.
46. Floridi L, Cowls J. A unified framework of five principles for AI in society. Harv Data Sci Rev. 2019;1(1).
47. European Union. Regulation (EU) 2024/1689 of the European Parliament and of the Council of 13 June 2024 laying down harmonised rules on artificial intelligence (Artificial Intelligence Act). Off J Eur Union. 2024;L2024/1689.
48. National Institute of Standards and Technology. Artificial intelligence risk management framework (AI RMF 1.0). Gaithersburg (MD): U.S. Department of Commerce; 2023. NIST AI 100-1.
49. Shneiderman B. Human-centered AI. Oxford: Oxford University Press; 2022.
50. Bengio Y. The consciousness prior. arXiv [Preprint]. arXiv:1709.08568; 2017.
51. Ashton K. That "Internet of Things" thing. RFID Journal. 2009;22(7):25-6.