Discover Internet of Things

REVIEW Open Access

Autonomous governance integrating agentic AI and zero trust for intelligent cybersecurity in distributed enterprise ecosystems

Supreet Nagi[1], Manpinder Singh Panesar[2] and Svarmit Singh Pasricha[3*]

*Correspondence:
Svarmit Singh Pasricha
svarmit@gmail.com
[1]Northwestern Mutual, Franklin, WI 5313, USA
[2]Amazon Web Services, Ashburn, VA 20148, USA
[3]Amazon, Washington 98012, USA

Abstract

The fast adoption of enterprise infrastructures into distributed, cloud-native, and API-based ecosystems has presented sophisticated security requirements that cannot be effectively handled with more traditional frameworks based on perimeters and rules. The growing number of multi-cloud ecosystems, micro services, Internet of Things (IoT) gadgets, and AI-to-AI interactions have broadened the attack surface, creating the need to deploy more adaptive and intelligent security measures.

This paper is a complete framework of autonomous security by uniting Zero Trust Architecture (ZTA) and Agentic Artificial Intelligence (AI) to provide context-sensitive and real-time threat detection and response. The offered Autonomous Governance Framework (AGF) takes advantage of multi-layered architecture that includes data acquisition, behavioral analytics, decision intelligence, enforcement, and feedback learning in order to provide constant monitoring and adjusting policymaking. The framework facilitates moving risk scoring dynamically and autonomous decision making by using generative AI to predictively model threats and machine learning-based behavioral analytics. One of the main contributions of this work is the idea of self-healing identity perimeters, in which credentials are automatically revoked and reissued according to a risk assessment based on context, thus limiting the use of compromised credentials. Moreover, the framework incorporates automated orchestration and real-time Data Loss Prevention (DLP) to enhance the protection of sensitive data in distributed environments. Context-aware API security provides a controlled access to data flows and is also consistent with the principle of Zero Trust that constantly verifies. Implementation considerations in multi-cloud and enterprise systems are also discussed in the paper emphasizing scalability, performance, and interoperability issues.

1 Introduction

The fast-changing nature of modern enterprise IT infrastructures, which are no longer centralized, but rather highly distributed, cloud-native, and API-driven ecosystems has fundamentally changed the cybersecurity landscape. The modern business is becoming more dependent on microservices structures, multi-cloud implementation, Internet

© The Author(s) 2026. **Open Access** This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit http://creativecommons.org/licenses/by/4.0/.

of Things (IoT) gadgets, and autonomous computer agents to provide the services in a scalable and intelligent manner. Although these developments are beneficial to operational efficiency and flexibility, they provoke a new history of security issues as they are dynamic in nature, with system interconnections, and real-time exchange of data [1]. The old paradigms of security that rely on the static rules, perimeter security, and manual security are no longer effective to counter the sophistication and speed of new threats. Traditionally, the concept of the clearly defined perimeter was at the center of enterprise security, with the internal networks regarded as safe, and the external ones being viewed as potentially threatening. But with the upsurge in cloud computing, work environments at home, and decentralized applications, there is no longer a concept of any one perimeter. Such a change has resulted in the appearance of Zero Trust Architecture (ZTA) that is based on the principle of never trust, verify. Zero Trust models authenticate, authorize and validate every access request, no matter what its origin is. Although ZTA is a major improvement of the conventional methods, most of the implementations are stagnant and policy based and do not have the flexibility needed to counter new threats in a real time manner [2].

The growth of API-driven ecosystems also makes security management more challenging. APIs are the foundation of modern-day applications, which allow smooth communication between services, platforms, and users. Nevertheless, both API endpoints present a possible vulnerability that can be used by malicious organizations. Multiclouds where the applications are spread across the various cloud service providers pose even greater difficulty in ensuring that the same security policies are maintained. Misconfigured access controls, secret sprawl, and inconsistent practices of identity management issues may result in massive data breaches and unauthorized access. Additionally, the number of API interactions per se makes monitoring a manual process not that viable and requires an automated and intelligent security mechanism. One of the most important trends carried out in the last years is the emergence of AI-to-AI communication in the ecosystem of enterprises. Machine learning and generative AI enable autonomous agents to engage with one another more often to process data and make decisions, as well as optimize the system. Although the agents are productive, they also introduce new attack vectors that cannot be managed by the conventional security frameworks. As an example, malicious instructions can be spread by compromised AI agents in interconnected systems, causing cascading failures or data leakage. The interactive and independent character of these relations necessitates a new concept of security that is as smart and responsive. The response to all these has been the realization of the idea of autonomous security as a revolutionary solution. Autonomous security systems are based on artificial intelligence, real-time analytics and self-healing to constantly monitor, detect, and automatically react to the threat without human intervention. Autonomous security structures can learn the behavioral patterns, anticipate the possible threats, and dynamically modify security policies, unlike the traditional systems that may use a set of rules to make decisions. This reactive to proactive security change is necessary to protect distributed enterprise ecosystem in the era of intelligent automation [3].

The integration of agentic AI is one of the most significant aspects of autonomous security and the ability of the systems to become independent decision-making bodies. Such systems are able to analyze the factual data, gauge the level of risk and make relevant decisions, including the provision of access, credential rotation, or the blocking

Table 1 Evolution of security paradigms in enterprise ecosystems

Security paradigm	Key characteristics	Limitations	Relevance in modern systems
Perimeter-Based Security	Network-centric, firewall-driven	Ineffective in cloud environments	Low
Rule-Based Security	Static policies, manual updates	Cannot adapt to dynamic threats	Moderate
Zero Trust Architecture	Continuous verification, identity-centric	Limited automation and adaptability	High
Autonomous Security	AI-driven, self-adaptive, real-time response	Emerging, requires trust in AI systems	Very High




Fig. 1 Autonomous security framework in distributed enterprise ecosystem

of questionable data streams. Also, Data Loss Prevention (DLP) mechanisms may be implemented in real-time in the data processing pipeline to make sure that sensitive information is secure at all of the stages of its lifecycle. Autonomous security systems can deliver finer-grained and flexible protection by considering each transaction as a context-driven event, which is consistent with the evolving character of modern business [4]. The shift to autonomous security also requires the reconsideration of identity and access control. The identity in distributed environments is no longer restricted to human users but also encompasses devices, applications, and AI agents. To operate these identities, there should be constant authentication, dynamic credential management and effective authentication methods. Self-healing perimeters of identity Autonomous frameworks present the concept of self-healing identity perimeters, credentials are automatically revoked and reissued according to real-time risk assessments. This will reduce the danger of credential compromise and make sure that the access privileges are in accordance with the current security environment. As can be seen in Table 1, the paradigms of enterprise security changed through the years, and autonomous approaches must be implemented. Figure 1 represent the autonomous security framework in distributed enterprise ecosystem.

Figure 1 illustrates the overall architecture of the proposed Autonomous Security Framework. Security telemetry is continuously collected from heterogeneous data sources including IoT devices, enterprise applications, APIs, cloud platforms, and end users through the Data Sources Layer. These observations are transmitted through the

Communication Layer, where API gateways and multi-cloud interfaces normalize and securely forward the collected events. Within the Core Security Layer, AI-driven behavioral analytics continuously examine user and system activities to establish behavioral baselines and compute dynamic risk scores. The Policy Enforcement Engine integrates these contextual risk assessments with Zero Trust policies to determine appropriate security actions. Depending on the evaluated threat level, the Response Layer automatically performs credential rotation, privilege revocation, or DLP enforcement. Security logs, AI models, and historical telemetry are stored within the Cloud and Data Storage Layer, which continuously updates analytical models through feedback learning. This closed-loop architecture enables continuous adaptation of security policies while minimizing manual intervention.

2 Literature survey

The study published in ref. [5] presented a systematic review methodology based on the analysis of over 140 primary studies on agentic AI systems. The methodology involved classification of agentic systems according to planning, memory, reflection, and goal-driven reasoning mechanisms. The architecture discussed was predominantly large language model (LLM)-driven agentic frameworks, integrating components such as reasoning engines, memory modules, and tool-use interfaces. These architectures followed a perception–reasoning–action loop, enabling adaptive and autonomous decision-making with both centralized and distributed coordination models. The authors adopted a conceptual and analytical methodology focusing on embedding "agency" into AI systems by integrating decision-making and autonomy. The architecture emphasized data-driven pipelines combined with autonomous decision layers, where AI systems were designed to process contextual data and execute actions independently. It incorporated feedback loops for continuous learning and relied on cloud-based infrastructures to support scalability and real-time decision-making [6]. The authors proposed a hybrid methodology combining machine learning and autonomous agent frameworks. The system architecture was based on multi-agent collaboration, where multiple intelligent agents interacted through communication protocols to solve complex tasks. Each agent maintained local state, memory, and specialized functionality, while coordination was achieved through either centralized orchestration or decentralized negotiation mechanisms, improving scalability and robustness in dynamic environments [7]. The work employed a data-driven experimental methodology using deep learning and reinforcement learning techniques. Its architecture was centered on deep reinforcement learning (DRL)-based agents, where agents learned optimal policies through interaction with the environment. The framework included perception modules, reward optimization mechanisms, and policy networks, enabling adaptive decision-making in uncertain and evolving scenarios [8]. In ref. [9], the methodology focused on integration of generative AI with enterprise systems, particularly enterprise resource planning and workflow automation. The architecture followed a compound AI model, combining LLMs, retrieval systems, and external APIs under a centralized orchestration layer. This architecture supported sequential workflows such as data extraction, validation, and execution, ensuring efficient automation while maintaining control and interpretability. The authors proposed a framework-oriented methodology for intelligent systems design. The architecture was based on multi-layer cognitive models, integrating perception, world modeling, goal

management, planning, and execution modules. This modular architecture enhanced explainability and supports adaptive decision-making by enabling interaction between cognitive layers [10]. The authors introduced a design-oriented methodology emphasizing explainability and accountability in agentic systems. The architecture incorporated explainability-by-design principles, embedding monitoring, evaluation, and interpretability modules throughout the system lifecycle. It supported system-level transparency by integrating oversight mechanisms across goal formulation, interaction, and outcome evaluation stages, ensuring trustworthy AI deployment [11]. Table 2 represents the comparative evaluation of existing autonomous security frameworks and the proposed AGF.

Table 3 illustrates that although recent studies have investigated Zero Trust, Agentic AI, or autonomous cybersecurity independently, very few integrate these concepts into a unified governance framework capable of predictive threat modeling, self-healing identity management, adaptive policy enforcement, and continuous learning. The proposed AGF attempts to bridge these research gaps through a comprehensive architecture integrating intelligent decision-making with real-time governance.

2.1 Comparative positioning of the proposed autonomous governance framework

Although recent studies have significantly advanced the understanding of agentic AI, Zero Trust security, and autonomous cybersecurity, most existing frameworks

Table 2 Comparative evaluation of existing autonomous security frameworks and the proposed AGF

Author(s) & Year	Methodology	Dataset (if used)	Advantages	Disadvantages	Architecture used
Bandi et al. (2025) [5]	Systematic Literature Review of 143 studies; classification of frameworks, architectures, evaluation metrics	Secondary datasets	Comprehensive taxonomy; unified view of agentic AI components	No experimental validation; lacks benchmark comparison	Multi-agent systems with planning, memory, reasoning modules
Acharya et al. (2025) [6]	Survey of autonomous AI systems focusing on goal-driven intelligence and autonomy	Not dataset-specific	Strong conceptual foundation of agentic AI; links theory with implementation	Limited empirical validation; high-level abstraction	Agentic architectures integrating LLMs and decision-making modules
Raheem and Hossain (2025) [7]	Domain-agnostic framework enabling autonomous automation using LLMs	Likely synthetic and enterprise datasets	Generalizable across domains; scalable automation	Dependency on LLM performance; resource intensive	LLM-based multi-agent orchestration frameworks
Sheth et al. (2025) [8]	Conceptual and implementation framework linking autonomy with decision-making	Not specified	Bridges philosophy of "agency" with technical AI systems	Lack of dataset benchmarking; theoretical orientation	Autonomous decision-making AI systems with feedback loops
Murugesan (2025) [9]	Integration of AI/ML into systems	Real-world enterprise datasets	Practical applicability; industry relevance	Domain-specific limitations	Hybrid ML and AI decision-support architectures
Ali et al. (2025) [10]	Comprehensive review of AI/ML techniques and emerging architectures	Literature datasets	Broad coverage of AI techniques; identifies research gaps	Generalized conclusions; lacks specific benchmarking	Deep learning and hybrid AI architectures
Ibrahim et al. (2026) [11]	Policy and technical framework for governing agentic AI systems	Policy datasets / literature	Addresses ethical, regulatory, and deployment risks	Limited technical depth; no experimental validation	Governance-aware AI architecture with control layers

Table 3 Research gaps in existing literature and the proposed method of autonomous governance framework to mitigate

Research gap identified in existing studies	Limitation in current literature	How proposed AGF addresses the gap
Static Zero Trust implementations	Limited adaptive response to evolving threats	Integrates Agentic AI for autonomous policy adaptation and continuous verification
Limited predictive threat intelligence	Mostly signature-based or historical detection	Employs Generative AI for predictive threat modeling and attack simulation
Lack of autonomous identity management	Manual credential rotation and revocation	Introduces self-healing identity perimeters with automated credential orchestration
Insufficient context-aware API protection	Fixed API security policies	Implements dynamic API security using contextual risk evaluation
Weak integration of AI decision making with governance	AI models operate independently from policy engines	Combines AI-driven decision intelligence with governance and enforcement layers
Limited end-to-end Data Loss Prevention	DLP usually reactive	Embeds real-time DLP within autonomous enforcement architecture
Lack of continuous learning	Security policies rarely evolve automatically	Uses feedback learning loops for continuous optimization

concentrate on specific aspects of intelligent security rather than delivering an integrated governance architecture. Survey-oriented studies primarily classify agentic AI architectures and discuss reasoning mechanisms, planning strategies, and autonomous decision-making capabilities. Other works emphasize explainability, ethical AI deployment, or policy-oriented governance without providing comprehensive mechanisms for operational security enforcement in distributed enterprise environments. The proposed Autonomous Governance Framework (AGF) distinguishes itself by integrating multiple security capabilities into a unified autonomous governance architecture. Unlike existing frameworks that primarily focus on autonomous reasoning or isolated AI-driven security functions, AGF combines ZTA, behavioral analytics, generative AI-based threat prediction, self-healing identity management, real-time DLP, context-aware API security, and continuous feedback learning within a single multilayer architecture. Another distinguishing contribution is the introduction of dynamic identity orchestration through automated credential revocation and regeneration based on continuously evolving contextual risk scores. Existing approaches generally perform identity verification or policy enforcement independently, whereas AGF tightly couples identity governance with AI-driven behavioral analytics and adaptive policy enforcement. Furthermore, the proposed framework incorporates continuous feedback learning, enabling security policies and detection models to evolve with changing attack patterns rather than relying on static rule updates. Table 4 summarizes the principal differences between representative studies and the proposed framework.

3 Foundations of zero trust architecture and data-centric security

The accelerating development of distributed enterprise ecosystems with multiple cloud deployments, API-based interactions, and self-directed agents has come to disrupt the classical perimeter-based security frameworks. Traditional strategies, based on implicit trust when a user or system is allowed to access the network, are becoming less sufficient to deal with the current threat environments. ZTA has consequently become a paradigm shift that has redefined security in that it eradicates implicit trust and imposes constant verification through all levels of interaction [12].

Table 4 Comparative positioning of existing frameworks and the proposed AGF

Feature	Existing agentic AI frameworks	Proposed AGF
Zero Trust Integration	Partial	✓ Comprehensive
Autonomous Decision Intelligence	✓	✓
Behavioral Risk Scoring	Limited	✓ Real-time
Self-Healing Identity	Rarely addressed	✓ Dynamic credential orchestration
Context-aware API Security	Limited	✓ Integrated
Real-time DLP	Mostly absent	✓ Native component
Feedback Learning	Limited	✓ Continuous adaptive learning
Enterprise Governance Focus	Partial	✓ End-to-end governance

3.1 Principles of zero trust network architecture (ZTNA)

Zero Trust Network Architecture is based on the idea of never trust, always verify. In contrast to the traditional models, which presuppose the internal network entities to be honest, ZTNA considers all access requests both inside and outside the network as potentially malicious. This method will guarantee that authentication and authorization are undertaken in a continuous manner, and not on a single occasion. ZTNA is fundamentally based on three principles. To begin with, it implements stringent identity verification of users, devices and applications before they are allowed access. This encompasses multi-factor authentication, posture determination by the device and posture-based contextual validation depending on location, behavior and level of risk. Second, it embraces the least privilege principle of access, whereby entities receive as little permission as necessary to do their duties. Third, it uses micro-segmentation where the network is broken into small, isolated segments to avoid the subsequent movement of threats laterally. Continuous monitoring and ongoing policy enforcement is another important aspect of ZTNA. In place of fixed access rules, a policy is dynamic and context sensitive and reacts to real-time variations in user behavior or system state. To illustrate, once an abnormality is noted in the access pattern of a user, the system may automatically revoke their access or limit it. This active enforcement is especially essential in those settings when AI agents and automated systems can interact with each other, but there is no human control over these interactions [13].

3.2 Identity, access, and secret management in modern systems

Identify forms a new security perimeter in Zero Trust environments. Each entity be it human users, devices, applications or AI agents has a unique identity, which has to be authenticated and authorized before gaining access to resources. IAM systems are at the core of implementing these controls, combining authentication processes with policy engines to make the decision to access information secure. Contemporary enterprise systems do not just define IAM as the identities of normal users but also machine identities (service accounts, containers, and APIs). This is especially relevant in cloud-native systems, where human-originated requests are sometimes outnumbered by the interactions between microservices. Consequently, it has made it a significant issue to manage machine identities and credentials therein. The other critical element of data-centric security is secret management. Authentication and authorization between systems are done using secrets, which could be in the form of API keys, tokens, certificates, and encryption keys. In a more dynamic environment where both services are often created and destroyed, the static secret storage mechanisms are susceptible to vulnerabilities like leakage and misuse. These issues are tackled using modern Zero Trust systems by using

automated secret management solutions which allow the generation of credentials, their storage, rotation and revocation. These systems make sure secrets are temporary, contextual and highly attached to identity and admission policies. Moreover, sensitive information is encrypted and tokenized to safeguard the data at rest and in transit to make sure that, in the event of data intercept, the information is not understandable by unauthorized parties [14].

3.3 Limitations of static and rule-based security models

Although they are widely used, the traditional models of security which depend on static rules and predefined policies are becoming more ineffective within contemporary settings. These models are highly manualized and make the assumption that threat patterns can be predicted. Threat vectors have, however, become very dynamic and adaptive with the emergence of more advanced cyberattacks, some of which are fueled by autonomous AI agents. The major drawback of the statically security models is that they are not able to react in real time to new threats. Pre-defined policies might not cover new attack patterns making systems prone to exploitation. Moreover, the models used by static models do not tend to be contextual, with all access requests being treated similarly, no matter what is happening with the user, whether the device is in good health or the surrounding environment is in poor health. Another critical issue is scalability. With the increased complexity of enterprise systems, it becomes harder and harder to maintain static rules in different environments. This tends to cause configuration and policy errors and vulnerabilities. Moreover, the use of static models is inappropriate to model machine-to-machine interactions, as they need quick and automated decision-making at scale [15].

A more powerful alternative is data-centric security that aims to protect data as opposed to the infrastructure. Through direct data flow protection and a policy-based protection at the access point, organizations can guarantee a uniform protection of data if it is on a hard disk or accessed online. Nevertheless, to establish real data-centric protection, dynamic and intelligence-driven mechanisms that will effectively adapt to changing threats are needed. In this context, the limitations of traditional approaches highlight the need for more advanced frameworks that combine Zero Trust principles with AI-driven automation. These frameworks have the potential to facilitate ongoing monitoring, adaptive policy implementation, and autonomic response to threats, and self-governing security systems in distributed enterprise ecosystems. According to Fig. 1 the simplest ZTA involves users/devices making access requests with an identity layer, then authenticated by an Identity Provider (IdP) is the next layer [16]. A policy engine analyzes contextual parameters like risk score, device posture and behavioral analytics. The Policy Enforcement Point (PEP) implements decisions about access, allowing secure access to protected resources (applications, databases, APIs). This is through continuous monitoring and feedback loops that guarantee dynamic updates in policies and mitigation of threats. Figure 2 shows the simple ZTA.

Figure 2 presents the operational workflow of the ZTA adopted within the proposed framework. Every access request first passes through the Zero Trust Gateway, where user identity, device posture, and contextual information are authenticated using multi-factor authentication and identity providers. The Policy Engine subsequently evaluates contextual parameters including behavioral risk scores, device trustworthiness, historical activities, and environmental conditions before generating an access decision. The




Fig. 2 The basic zero trust architecture

Policy Enforcement Point executes this decision by either granting access, requesting additional authentication, restricting privileges, or denying access altogether. Continuous monitoring allows the framework to reassess trust throughout the active session, enabling adaptive authorization instead of one-time authentication.

4 Agentic AI in cybersecurity: concepts and capabilities

The fast development of distributed enterprise ecosystems, which is multi-cloud infrastructure, interaction based on API, and self-integration of autonomous systems has led to the necessity of revising the approach to cybersecurity mechanisms. The human and rule-based frameworks of security are becoming more insufficient in responding to the magnitude, pace and intricacies of the contemporary cyber threats. In this context, Agentic AI emerges as a transformative approach, enabling systems to operate with autonomy, adaptability, and contextual intelligence. Agentic AI Agentic AI systems are those that are able to perceive environments, make decisions and take action on their own choice to meet predefined security goals. In the context of cybersecurity, this paradigm presents a self-governing, proactive model which keeps pace with the dynamism of AI-to-AI interactions and decentralized systems [17].

4.1 Generative AI for threat modeling and prediction

Generative AI is essential in improving threat modeling, allowing predictive and simulation based analysis of security. In contrast to the conventional approaches which use the history of attack signatures, generative AI systems are capable of creating the possible attacker scenarios due to learning various datasets, such as network traffic, behavior history, and established attack patterns. These systems involve cutting-edge technologies like large language models and generative adversarial networks to model attack vectors, detect vulnerabilities, and anticipate emerging threats prior to their realization. Generative AI can generate risk-aware threat models in real time, and dynamically analyze request patterns in modern enterprise environments, where APIs are the main interface of communication. Such an ability can enable organizations to transition to predictive security posture instead of reactive defense measures. As an example, AI can predict

lateral movement attempts on a network or identify anomalies in API use which can be evidence of credential compromise or an attempt to exfiltrate data. Moreover, AI can be used to generate the policies automatically through the use of generative AI, which allows the security systems to dynamically respond to the changes in the threat environment [18].

Recent industrial deployments further demonstrate the practical value of generative AI in cybersecurity. Security operation centers increasingly employ large language models (LLMs) to automate threat intelligence summarization, malware behavior analysis, phishing email detection, and incident response recommendations. Microsoft Security Copilot leverages generative AI to assist analysts by correlating security alerts, generating incident summaries, and recommending mitigation strategies, thereby reducing analyst workload and accelerating response time. Similarly, Google's Gemini-powered security services assist cloud defenders in identifying misconfigurations, analyzing attack chains, and automating vulnerability prioritization across distributed infrastructures. Enterprise security platforms such as CrowdStrike Charlotte AI and Palo Alto Networks Precision AI further demonstrate how generative AI supports autonomous threat hunting, behavioral anomaly detection, and contextual risk assessment. These real-world deployments indicate that generative AI is rapidly evolving from an experimental technology into an operational cybersecurity capability that complements ZTAs through intelligent automation and predictive security analytics.

4.2 Autonomous decision-making in security systems

One of the most notable features of agentic AI is its autonomy in making decisions without having to be under constant human constraints. This is translated in cybersecurity to systems capable of detecting, analyzing and responding to threats in real time. The reinforcement learning, adaptive control systems, and rule-learning mechanisms provide autonomous decision-making which constantly develops on the basis of environmental feedback. In real-world applications, the agentic AI systems observe network traffic, calculate the risk score, and take relevant measures like blocking suspicious traffic, revoking compromised credentials, or isolating the affected systems. This is especially essential where there are extreme data flows and numerous interdependences that cannot be subjected to manual intervention, which would be unacceptable. Besides, autonomous systems facilitate self-healing security design, identity boundaries and controls being dynamically reconfigured following perceived threat. As an example, when an anomaly in user behavior has been detected, the system has the ability to automatically perform multi-factor authentication, restrict access privileges, or regenerate cryptographic secrets. Such a constant changing approach will guarantee that the security measures will be up-to-date with the latest risk state, which will improve the resistance against advanced threats [19].

4.3 AI-driven behavioral analytics and risk scoring

At the core of agentic AI-powered cybersecurity lies behavioral analytics. By continuously tracking how users behave, how systems are interacted with, and how data moves across networks, AI platforms construct baseline profiles and flag any activity that strays from the norm a common indicator of malicious intent. Unlike older, rule-based detection methods that rely on fixed thresholds, AI-powered analytics leverage machine

learning to keep these baselines current, adapting to legitimate changes while still catching subtle irregularities. This is further strengthened by risk scoring, which evaluates both the likelihood and potential impact of any flagged anomaly. These scores factor in a range of variables who the user is, what device they're on, what level of access they typically have, and how they've behaved historically. In agentic AI environments, these scores aren't static; they shift in real time and serve as triggers for automated responses, ensuring that the security reaction is proportionate to the actual threat level. A minor anomaly might simply result in heightened surveillance, while something more serious could prompt an immediate intervention, such as terminating a session or cutting off access to sensitive data. This tiered, context-aware approach helps organizations walk the fine line between robust protection and operational efficiency clamping down on genuine threats without flooding teams with unnecessary false alarms [20].

4.4 Explainable AI for trustworthy autonomous security decisions

Although autonomous decision-making significantly improves cybersecurity responsiveness, it also introduces challenges concerning transparency, accountability, and user trust. Explainable Artificial Intelligence (XAI) addresses these concerns by providing interpretable justifications for security decisions generated by AI agents. Instead of functioning as opaque "black-box" systems, explainable models identify the features, behavioral indicators, and contextual factors responsible for triggering security actions such as credential revocation, network isolation, or access denial. In enterprise environments, transparency is essential for regulatory compliance, forensic investigations, and organizational governance. Security analysts must understand why autonomous systems classified a user, device, or application as malicious before accepting automated remediation actions. Explainability therefore enhances human oversight while maintaining autonomous operation. Auditability represents another important requirement for agentic security systems. Every autonomous decision should generate immutable logs containing model confidence scores, evaluated contextual attributes, policy rules, and recommended actions. Such audit trails facilitate compliance with cybersecurity frameworks including NIST AI Risk Management Framework, ISO/IEC 42,001, and emerging AI governance regulations. Trustworthiness further depends on fairness, robustness, and resilience against adversarial manipulation. Integrating explainable AI with behavioral analytics allows organizations to validate autonomous decisions, minimize false positives, and continuously improve decision policies through expert feedback. Consequently, explainability should be considered a foundational component of future autonomous cybersecurity governance frameworks rather than an optional feature.

4.5 Limitations and risks of autonomous decision-making

Despite the significant advantages offered by Agentic AI, autonomous cybersecurity systems introduce several technical and operational challenges that must be carefully managed. One major concern is model drift, where machine learning models gradually lose predictive accuracy because of evolving user behavior, changing enterprise environments, or emerging attack techniques. Continuous retraining and validation are therefore necessary to maintain reliable security decisions. Another important challenge is adversarial manipulation. Sophisticated attackers may deliberately craft adversarial inputs or poison training datasets to evade anomaly detection systems or manipulate

autonomous decision processes. Robust adversarial training, secure model update mechanisms, and continuous integrity verification are therefore essential components of trustworthy autonomous security systems. Autonomous systems may also produce false-positive or false-negative decisions, particularly when behavioral patterns rapidly evolve or when contextual information is incomplete. Excessive automation without human oversight could unintentionally revoke legitimate credentials, interrupt critical business operations, or generate unnecessary security alerts. Consequently, human-in-the-loop validation should remain available for high-impact security decisions. Table 5 describes the various capabilities of agentic AI in cybersecurity systems.

5 Autonomous governance framework: architecture and components

One of the paradigm shifts between the functioning of the static security mechanisms and the functioning of the rule-based mechanisms and the functioning of the dynamic security ecosystems that are intelligent, self-regulating and dynamic is the AGF. As opposed to the historical Zero Trust designs, where the primary focus is made on the predefined policies and manually controlled environment, AGF introduces an agentic AI-based design that is able to respond to the dynamic threat environment. The architecture is devised to work within distributed enterprise ecosystems, which are multi-cloud based, API-based interactions, and autonomous machine-to-machine interactions. In its simplest form, AGF is created as a multi-layered architecture wherein each layer contributes to the further monitoring, analysis and execution of security policies. These layers have data acquisition, behavioral analytics, decision intelligence, enforcement and feedback learning. The framework treats every interaction in particular API calls as events with context, enabling the identity, access and data flow to be carefully controlled [21].

5.1 Multi-layered security design

AGF architecture consists of interlocked layers which work together so as to provide real time governance. The data acquisition layer collects the telemetry of different sources such as APIs, user interactions, IoT devices, and cloud services. This data is then collected by the behavioral analytics layer which utilizes AI models to interpret trends, spot irregularities, and give risk assessment. The brain of the framework is the decision intelligence layer that employs generative AI and compels learning to determine risks and the correct decisions. They are enforced with the help of the enforcement layer that

Table 5 Capabilities of agentic AI in cybersecurity systems

Capability	Description	Enabling techniques	Security application	Impact on cyber defense
Predictive Threat Modeling	Anticipates potential attack scenarios	Generative AI, GANs	Vulnerability assessment, threat simulation	Proactive threat prevention
Autonomous Decision-Making	Executes real-time security actions	Reinforcement learning	Intrusion response, access control	Reduced response time
Behavioral Analytics	Monitors and analyzes user/system behavior	Machine learning, anomaly detection	Insider threat detection	Improved anomaly detection accuracy
Dynamic Risk Scoring	Assigns real-time risk levels to activities	Statistical modeling, AI inference	Adaptive authentication	Context-aware security enforcement
Self-Healing Security	Automatically adapts and recovers system states	AI orchestration, automation	Credential rotation, system isolation	Enhanced system resilience

dynamically enforces the policies such as the access control, credential or data masking revocation. Finally, feedback layer would ensure that learning is an ongoing process through the updating of models based on the results that are observed, and in such a manner, would improve resilience of the systems over time. This layered design is sure to ensure modularity, scalability and even adaptability hence AGF fits in the complex enterprise environment.

5.2 Self-healing identity and credential orchestration

The fact that AGF is capable of implementing self-healing identity mechanisms is one of its most peculiar characteristics. Traditional identity and access control systems employ hardened credentials that are easily attacked. On the other hand, AGF can measure the trust in identity in real-time by using telemetry. The system is also able to automatically revoke compromised credentials and automatically issue new credentials in case of aberrant behavior. Such a process is facilitated by dynamic credential orchestration that is rotating secrets such as API keys, tokens, and certificates, to rotate risks on demand, or on a periodical basis based on risk scores. The self-healing process also lowers the size of the attack surface by decreasing the duration of the exposed credentials and restricting the movement in the network [22].

5.3 Real-time data loss prevention mechanisms

The real time DLP is applied on the level of data processing by AGF, and not surveillance once the event has happened. The framework improves security of sensitive information by incorporating DLP policies within the enforcement layer, encompassing transmission, storage and processing. The data, in the case of AI-based models, is divided based on its sensitivity and context and the respective controls can be implemented by the system such as encryption, redaction, or access restrictions. Such active DLP is especially significant in the distributed setting where information is moving across the various services and jurisdictions [23].

5.4 API-level context-aware security enforcement

APIs are the main service interface in the modern enterprise infrastructure. AGF proposes context-sensitive API security, whereby the API calls are considered according to various parameters, such as user identity, device posture, location, past behavior, and real-time risk score. As opposed to the traditional API gateways that implement rules that are fixed, AGF is dynamic and adapts access policies according to the contextual insights. This will make sure that legitimate users are continuously authenticated, which complies with the principles of Zero Trust. In addition, the framework facilitates microsegmentation, which isolates services and only accesses what is significant to a particular interaction [24]. This will minimize the chances of unauthorized access to data and the internal flow of data inside the system. Table 6 shows the different key components of AGF.

Figure 3 illustrates the multilayer AGF. Security events collected from distributed enterprise resources first enter the Data Acquisition Layer for preprocessing and normalization. The Behavioral Analytics and Risk Scoring Engine extracts behavioral features, identifies anomalies, and computes continuously updated risk values. These outputs are supplied to the Decision Intelligence Layer, where agentic AI combines

Table 6 Key components of autonomous governance framework

Component layer	Core function	Technologies used	Key features	Security impact
Data Acquisition	Collect telemetry and interaction data	APIs, IoT sensors, logs	Real-time data ingestion	Enhanced visibility
Behavioral Analytics	Analyze patterns and detect anomalies	ML, Deep Learning	Risk scoring, anomaly detection	Early threat identification
Decision Intelligence	Evaluate risks and generate actions	Generative AI, Reinforcement Learning	Autonomous decision-making	Reduced human dependency
Enforcement Layer	Enforce security policies dynamically	Policy engines, API gateways	Access control, credential rotation	Immediate threat mitigation
Feedback Learning	Continuous model improvement	AI feedback loops	Adaptive learning, system tuning	Long-term resilience

generative reasoning with reinforcement learning to determine optimal security actions. The Enforcement Layer automatically executes security controls including adaptive access management, credential orchestration, API policy enforcement, and DLP mechanisms. Finally, the Feedback Loop captures operational outcomes and updates machine learning models, enabling continuous improvement of threat detection accuracy and governance policies over time.

6 Secret orchestration and data protection in dynamic environments

The high-speed development of distributed enterprise ecosystems, especially microservices, APIs, and multi-cloud systems, has made it much more difficult to control sensitive information. The keys to secrets like API keys, encryption credentials, access tokens, and certificates are the foundation of a secure service-to-service communication. Nevertheless, in dynamic settings, where there is the continuous deployment, temporary loads, and interactions with AI, the traditional static secret management methods are no longer adequate. Secret orchestration should become an intelligent, automated, and context-aware process as outlined in the proposed AGF to support sound data protection [25].

6.1 Automated secret rotation and lifecycle management

The secret rotation automation is an essential element of contemporary cybersecurity solutions. Secrets are also often leaked in dynamic environments where scaling is quick, and containers and cross-platform integration happen. Automated lifecycle management will take care of the generation, distribution, rotation, and revocation of secret without human intervention. This minimizes the credential compromise risk and the attack surface. The AI-based orchestration systems improve this process by adding contextual intelligence [26]. An example is that secrets can be dynamically rotated on the basis of behavioral anomalies, risk scores, or predefined policies. In case of a suspicious API access pattern, the system is able to revoke any existing credentials and issue new ones instantly. This self-healing feature is consistent with Zero Trust, where there are no pre-trusted parties, and access requests are constantly verified. Secure storage and access control is also part of lifecycle management. Recent developments use encrypted vaults, hardware security modules (HSMs), and decentralized identity models to make sure that secrets are not revealed in plaintext. Moreover, just-in-time (JIT) access controls can provide temporary credentialing to minimize sensitivity data retention in the system.




Fig. 3 Autonomous governance framework

6.2 Mitigation of secret sprawl and credential leakage

Secret sprawl refers to the uncontrolled proliferation of credentials across applications, repositories, and infrastructure layers. In agile and DevOps-driven environments, developers often embed secrets within codebases or configuration files, leading to increased vulnerability. Credential leakage, whether through misconfigured repositories or compromised endpoints, remains one of the most significant security threats. To address this challenge, intelligent secret orchestration systems implement centralized governance combined with distributed enforcement. AI-based scanners continuously monitor code repositories, logs, and network traffic to detect exposed credentials. Once identified, these secrets are automatically revoked and replaced, ensuring minimal exposure time. Another effective strategy is the adoption of ephemeral secrets. Unlike static credentials, ephemeral secrets are short-lived and dynamically generated for each session or transaction. This significantly reduces the risk of misuse, even if a credential is intercepted. Additionally, policy-driven access control ensures that secrets are only accessible to authorized entities under specific conditions, such as device trust level, geographic location, or behavioral profile [27].

6.3 Secure data flow governance in distributed systems

Beyond secret management, protecting data flows in dynamic environments is equally critical. Data in transit between microservices, APIs, and external systems must be continuously monitored and secured. Traditional perimeter-based security models are ineffective in such scenarios, as data flows across multiple trust boundaries. Secure data flow governance involves real-time inspection, classification, and enforcement of data protection policies. AI-powered DLP mechanisms analyze data streams to identify sensitive information such as personally identifiable information (PII), financial data, or intellectual property. Based on predefined policies, the system can block, mask, or encrypt data before it leaves the organization's control. Context-aware security plays a crucial role in this process. Each data transaction is evaluated based on multiple parameters, including user identity, device posture, network conditions, and behavioral patterns. This ensures that data access is granted only when the contextual risk is within acceptable limits. For example, an API request originating from an untrusted device or anomalous location may trigger additional authentication or be denied altogether. Furthermore, integration with ZTAs ensures end-to-end security. Encryption protocols, tokenization, and secure API gateways are employed to safeguard data throughout its lifecycle. Combined with continuous monitoring and automated response mechanisms, these approaches enable organizations to maintain data integrity and confidentiality in highly dynamic environments [28]. The comparative analysis of secret orchestration strategies is represented in the Table 7.

7 Implementation perspectives in multi-cloud and enterprise systems

The implementation of autonomous security frameworks in multi-cloud and enterprise systems represents a critical step toward operationalizing the theoretical constructs of ZTA, Agentic AI, and the AGF. Modern enterprise environments are characterized by heterogeneous infrastructures, distributed workloads, and continuous integration pipelines, making security implementation both complex and dynamic. This section explores practical considerations for deploying such frameworks, focusing on integration with

Table 7 Comparative analysis of secret orchestration strategies

Strategy type	Key features	Advantages	Limitations	Use case example
Static Secret Storage	Fixed credentials, manual updates	Simple implementation	High risk of leakage	Legacy enterprise systems
Centralized Vault	Encrypted storage, access control	Improved security and auditability	Single point of failure	Cloud-based applications
Automated Rotation	Periodic credential updates	Reduced exposure time	Requires orchestration tools	DevOps pipelines
Ephemeral Secrets	Short-lived, session-based access	Minimizes misuse risk	Increased system complexity	Microservices architectures
AI-Driven Orchestration	Context-aware, self-healing security	Adaptive and proactive protection	High computational overhead	Multi-cloud enterprise ecosystems

cloud-native architectures, performance and scalability challenges, and real-world industrial applications [29].

7.1 Integration with cloud-native and microservices architectures

The transition toward cloud-native computing has fundamentally reshaped enterprise system design, emphasizing modularity, scalability, and resilience. Microservices architectures, containerization technologies (e.g., Docker), and orchestration platforms (e.g., Kubernetes) enable applications to be deployed as loosely coupled, independently scalable services. However, this architectural paradigm introduces significant security challenges due to increased inter-service communication, ephemeral workloads, and decentralized control. Implementing autonomous security within such environments requires seamless integration with existing DevOps and cloud-native ecosystems. The AGF can be embedded into the microservices lifecycle by integrating with API gateways, service meshes (such as Istio), and container orchestration platforms. Service meshes play a particularly vital role by enabling secure service-to-service communication through mutual TLS (mTLS), traffic encryption, and policy enforcement at the network layer.

In this context, identity becomes the cornerstone of security. Each microservice, container, or function is assigned a unique machine identity, which is continuously authenticated and authorized using dynamic credentials. The AGF enhances this process by introducing self-healing identity mechanisms, where credentials are automatically rotated or revoked based on behavioral anomalies. This ensures that compromised services cannot persist within the system. Another critical aspect is the integration of security into the CI/CD pipeline, often referred to as DevSecOps. Security policies, vulnerability scanning, and compliance checks are embedded into the development lifecycle, enabling early detection and mitigation of risks. AI-driven tools can analyze code repositories, detect exposed secrets, and enforce secure coding practices in real time. As highlighted in the proposed framework, automated secret orchestration and ephemeral credentialing significantly reduce the risks associated with secret sprawl and credential leakage. Furthermore, API-centric security enforcement is essential in microservices environments. Each API call is treated as a context-aware event, evaluated against multiple parameters such as identity, device posture, and risk score. This aligns with Zero Trust principles, ensuring continuous verification and minimizing unauthorized access. By embedding AGF components directly into API gateways and service meshes, organizations can achieve granular, real-time security enforcement without disrupting application workflows [30].

7.2 Performance, scalability, and latency considerations

Autonomous security structures introduce performance, scalability and latency challenges in their implementation though have great benefits of flexibility and mitigation of threat. Enterprise systems especially those used in a multi-cloud environment need to process large amounts of transactions with little delay. Security mechanisms should therefore be streamlined in order to make them not to be bottlenecks. The amount of computational overhead of AI-inspired analytics and decision-making is one of the key issues [31]. Behavioral analytics, risk scoring and generative threat modeling are highly processing intensive, particularly in real-time. In solving this, the organizations may have distributed computing models where the security functions are placed in edge nodes, cloud regions, and local clusters. The method minimizes latency by doing work near its source and spreads out the workload. Another important factor is scalability. Multi-cloud environments dynamically scale the workloads in relation to demand and hence the security frameworks must dynamically adapt with the requirement. The AGF facilitates horizontal scalability, as it utilizes a deployment of its components in kind of microservices. All components of the framework, such as data acquisition, analytics and enforcement are scalable and therefore will behave consistently at different workloads [32].

The special concern in services that need real-time response, including financial transactions, health care systems, and autonomous internet of things, are latency considerations. Excessive delays in security decision-making can impact user experience and operational efficiency. To overcome this, it is possible to use lightweight artificial intelligence models and edge inference. An example here is that initial risk evaluations can be done out on the edge, with more sophisticated analysis done at centralized cloud setups [33]. Caching and asynchronous processing is used to optimize performance, too. Policies and credentials accessed repeatedly can be dropped in a cache to eliminate repeated computations, whereas non-critical security operations can be done asynchronously. Also, event-driven architectures facilitate effective processing of security events, which means that the priority of critical threats is set, and they are addressed as soon as possible. The other significant factor is the interoperability with several cloud providers. Every cloud service (e.g., AWS, Azure, Google Cloud) consists of security tools, APIs and identity management systems. To ensure the implementation of an integrated security structure, standardization and abstraction layers are necessary, which can be used uniformly in these environments. Standardized systems like OpenAuth 2.0, OpenID Connect, and SPIFFE (Secure Production Identity Framework for Everyone) may allow the interoperability and proper integration [34]. Despite their significant operational advantages, agentic AI systems introduce additional computational overhead resulting from continuous behavioral monitoring, large language model inference, reinforcement learning, and real-time policy optimization. These processes require increased CPU/GPU resources, memory capacity, and network bandwidth, particularly within large-scale enterprise environments. Furthermore, maintaining distributed knowledge bases, vector databases, and continuous feedback mechanisms contributes to storage and communication overhead. To mitigate these challenges, lightweight AI inference models, edge computing, model compression, adaptive sampling, and hierarchical decision-making architectures can substantially reduce computational cost without sacrificing security effectiveness. Hybrid deployments that perform preliminary inference at the edge while delegating

complex reasoning tasks to centralized cloud infrastructures provide an effective balance between latency, scalability, and resource utilization. Consequently, computational efficiency should remain an important design consideration in future implementations of autonomous governance frameworks.

7.3 Case studies and industrial applications

Real life applications of autonomous security models can be more easily appreciated through real world applications in different industries. Such case studies underscore the potential of multi-cloud and enterprise systems to use AI-driven security to tackle intricate issues.

I. Financial services (multi-cloud banking platforms)

Banking systems in the modern world are deployed in numerous cloud platforms to achieve redundancy, scalability, and regulatory compliance. Microservices in such systems deal with activities like processing transactions, fraud detection, and customer authentication. With AGF, financial institutions will be able to have real-time fraud detection with the use of behavioral analytics and risk scoring. An example is that in case a suspicious transaction pattern is identified, the system may automatically add an extra authentication or prevent the transaction. The secret rotation is also automated, which means that API keys and tokens in the inter-service communication can be kept safe, and the threat of credential compromise can be minimized.

II. Healthcare systems (secure patient data management)

Healthcare organizations are sensitive to patient information and are, therefore, one of the main targets of a cyberattack. Multi-cloud healthcare systems frequently have data that is shared among hospitals, laboratories and insurance companies. AGF allows Governance of data flow security by integrating DLP mechanisms into the data processing pipeline. Classification done through AI makes sure that information deemed sensitive is encrypted or masked down before transmitting. Also, independent identity management will guarantee that only authorized systems and personnel have access to patient records, which increases their adherence to regulations, including HIPAA.

III. Industrial IoT (smart manufacturing)

IoT devices and sensors are constantly sending and sharing data with the distributed systems in smart manufacturing environments. Such devices frequently have resource-limited conditions, and the conventional security strategies are not feasible. The autonomous security frameworks overcome this challenge by implementing lightweight AI models on the edge that can be used to detect and respond to threats in real-time. As an example, when one sensor acts abnormally, it can be isolated by the system and no additional data can be sent by the system, safeguarding the entire network.

IV. E-commerce and digital platforms

APIs are essential to E-commerce platforms that link frontend applications, payment gateways, and in-store-room. Large volumes of transactions and dynamic user interaction expose such platforms to attacks like API abuse and credential stuffing. Through context-aware API security, organizations will be able to identify and counter such

Table 8 Practical benefits of autonomous governance framework

Application domain	Performance improvement
Banking	Reduced fraud response time through automated risk scoring
Healthcare	Faster protection of sensitive patient information using real-time DLP
Smart Manufacturing	Improved anomaly detection and faster isolation of compromised IoT devices
E-Commerce	Reduced credential abuse and faster API threat mitigation

threats on the fly. The risk-based authentication system ensures that there is less friction on legitimate users and suspicious activities are dealt with in real-time. These case studies indicate that effective execution of autonomous security frameworks should be a mixture of innovative technologies, standard protocols, and domain-specific modifications. When AGF is incorporated into multi-cloud and enterprise systems, it not only increases the level of security but it also boosts the level of operational efficiency and resilience.

Across these representative applications, the proposed AGF demonstrates measurable operational improvements including reduced incident response time through autonomous remediation, enhanced threat detection accuracy using AI-driven behavioral analytics, lower credential exposure through automated secret rotation, and improved regulatory compliance via continuous monitoring and audit logging as shown in Table 8. Although quantitative performance depends on deployment environments, existing industrial reports consistently indicate that AI-assisted security operations substantially reduce analyst workload while improving detection efficiency and operational resilience.

8 Conclusion

As enterprises increasingly shift toward distributed, cloud-native, and AI-powered infrastructures, the cybersecurity landscape has undergone a profound reinvention. Conventional security models largely built around rigid policy enforcement and perimeter-based defenses struggle to keep pace with the fluid, unpredictable threat surfaces introduced by technologies like microservices, multi-cloud deployments, and autonomous AI agents. In response to this gap, this paper explores a comprehensive approach to autonomous security, examining how ZTA can be meaningfully combined with Agentic AI to build security systems that are not only intelligent and adaptive, but capable of governing themselves. The proposed AGF demonstrates how layered architectural designs can enable continuous monitoring, real-time threat identification, and automated incident response all working in concert. This shift fundamentally repositions security from a reactive discipline to a proactive one. Predictive models powered by generative AI anticipate threats before they materialize, while behavioral analytics inform dynamic, context-sensitive risk assessments. Self-healing identity boundaries and automated credential orchestration work together to dramatically reduce exposure to secret sprawl and credential-based attacks. Complementing these capabilities, real-time DLP mechanisms and context-aware API security protocols ensure that sensitive data remains protected across even the most dispersed environments. The paper also addresses practical deployment considerations including scalability, performance tuning, and cross-platform interoperability in multi-cloud settings and draws on real-world applications in finance, healthcare, and IoT to illustrate how autonomous security frameworks translate from theory into practice. Beyond reviewing existing developments in ZTA and Agentic AI, this work makes several important theoretical and practical

contributions. Theoretically, it proposes a unified AGF that integrates autonomous decision intelligence, generative AI-based threat modeling, behavioral analytics, self-healing identity management, real-time Data Loss Prevention, and context-aware API security into a single architectural model. Practically, the review synthesizes current industrial practices and demonstrates how these technologies can be deployed across multi-cloud enterprise environments to improve operational resilience, adaptive security enforcement, and automated incident response. Unlike existing survey papers that primarily discuss individual technologies independently, this review presents an integrated governance perspective that connects AI autonomy, Zero Trust principles, and enterprise cybersecurity implementation within a comprehensive framework suitable for next-generation intelligent infrastructures.

Author contributions
Supreet Nagi: Conceptualization, Methodology, Formal analysis, Investigation, Data curation, Writing – Original Draft, Writing – Review & Editing, Visualization.Manpinder Singh Panesar: Conceptualization, Methodology, Formal analysis, Investigation, Data curation, Writing – Original Draft, Writing – Review & Editing, Visualization.Svarmit Singh Pasricha: Conceptualization, Methodology, Formal analysis, Investigation, Data curation, Writing – Original Draft, Writing – Review & Editing, Visualization.All authors contributed equally to the research work and manuscript preparation. All authors have read and approved the final version of the manuscript.

Funding
This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

Data availability
No datasets were generated or analysed during the current study.

Declarations

Ethics approval and consent to participate
Not applicable.

Consent for publication
Not applicable.

Human participants involvement
Not applicable.

Competing interests
The authors declare no competing interests.

Received: 22 April 2026 / Accepted: 11 September 2026
Published online: 17 September 2026

References

1. Lin Y-R, Joshi J. Agentic AI in uncharted domains: risks, ethics, trust, and human alignment. In: 2025 IEEE 7th International Conference on Cognitive Machine Intelligence (CogMI). https://doi.org/10.1109/CogMI67134.2025.00069.
2. Sarkar S, Choudhary G, Shandilya SK, Hussain A, Kim H. Security of zero trust networks in cloud computing: A comparative review. Sustainability. 2022;14:11213.
3. Syed NF, Shah SW, Shaghaghi A, Anwar A, Baig Z, Doss R. Zero trust architecture (zta): A comprehensive survey. IEEE access. 2022;10:57143–79.
4. Chen X, Feng W, Ge N, Zhang Y. Zero trust architecture for 6G security. IEEE Network. 2023;38:224–32.
5. Bandi A, Kongari B, Naguru R, Pasnoor S, Vilipala SV. The rise of agentic ai: A review of definitions, frameworks, architectures, applications, evaluation metrics, and challenges. Future Internet. 2025;17:404.
6. Acharya DB, Kuppan K, Divya B. Agentic AI: Autonomous intelligence for complex goals—A comprehensive survey. IEEe Access. 2025;13:18912–36.
7. Raheem T, Hossain G. Agentic AI systems: opportunities, challenges, and trustworthiness. In: 2025 IEEE International Conference on Electro Information Technology (eIT). 2025. pp. 618–24.
8. Sheth A, Achanta A, Matam P, Patel A, Sharma P, Janapareddy NVP, et al. AI driven self-healing cybersecurity systems with agentic AI for adaptive threat response and resilience. In: 2025 IEEE Cloud Summit. 2025. pp. 147–53.
9. Murugesan S. The rise of agentic AI: implications, concerns, and the path forward. IEEE Intell Syst. 2025;40:8–14.
10. Abou Ali M, Dornaika F, Charafeddine J. Agentic AI: a comprehensive survey of architectures, applications, and future directions. Artif Intell Rev. 2025;59:11.
11. Ibrahim A, Olaniyi Sadiq B, Nuhu Shuaibu A, Ibrahim Danjuma Y, Maninti V, Joe M. Designing ethically aligned agentic AI systems for cybersecurity: a conceptual framework. AI Ethics. 2026;6:158.

12. Kasula VK, Addula SR, Ayyamgari S, Tumma C. Agentic AI-driven CBDC: a privacy-preserving and regulatory-compliant digital payment framework. In: International Conference on Applied Machine Learning and Data Analytics. 2024. pp. 74–88.
13. Ahmadi S. Autonomous identity-based threat segmentation for zero trust architecture. Cyber Secur Appl. 2025;3:100106.
14. Arora S, Hastings J. Securing agentic AI systems-a multilayer security framework. In: 2025 5th International Conference on Robotics, Automation, and Artificial Intelligence (RAAI). 2025. pp. 509–14.
15. Ghaemi MS. Shadow management: leveraging responsible agentic AI to revolutionize safe decision-making in complex organizations. In: Proceedings of the Future Technologies Conference. 2025. pp. 1–25.
16. Huang J, Huang K, Jackson K, Hughes C. AI agent safety and security considerations. In: Agentic AI: Theories and practices. Springer; 2025. pp. 369–407.
17. Huang K, Hughes C. The commercial landscape of agentic AI security. In: Securing AI agents: foundations, frameworks, and real-world deployment. Springer; 2025. pp. 347–73.
18. Huang K, Hughes C. Securing multi-modal agentic AI systems. In: Securing AI agents: foundations, frameworks, and real-world deployment. Springer; 2025. pp. 253–85.
19. Huang K, Hughes C. Agentic AI security in critical sectors: finance, healthcare, and autonomous driving. In: Securing AI agents: foundations, frameworks, and real-world deployment. Springer; 2025. pp. 321–46.
20. Hughes L, Dwivedi YK, Malik T, Shawosh M, Albashrawi MA, Jeon I, et al. AI agents and agentic systems: A multi-expert analysis. J Comput Inform Syst. 2025;65:489–517.
21. Kumurdjieva M, Doukovska L, Ghouaiel N, Dhanani A. Governance of AI and agentic systems: challenges and methodologies. In: 2025 International Conference on Big Data, Knowledge and Control Systems Engineering (BdKCSE). 2025. pp. 1–5.
22. Malpure S, Kanungo R, Loomis BR, Reza SS. Securing AI and agentic systems in medical devices: methods, risks, and defenses. In: 2025 Third International Conference on Cyber Physical Systems, Power Electronics and Electric Vehicles (ICPEEV). 2025. pp. 1–8.
23. Nashwan S, Jebreen I, Al-Qerem A, Almomani A, Saleh M, Aldweesh A. Autonomous agents in a zero-trust world: architecting secure, auditable AI workflows. In: 2025 10th International Conference on Information Technology Trends (ITT). 2025. pp. 259–64.
24. Palavali DR. Agentic AI for Self-Sovereign Identity: A Decentralized Zero Trust Framework for Autonomous Microservices. Int J Comput Math Ideas (IJCMI). 2025;17:17347–60.
25. Polamarasetti A, Yammanur V, Ravuri N, Bokka VVRM, Vadisetty R. Agentic AI-driven cybersecurity for cloud-connected automotive systems. In: International Conference on Intelligence-Based Transformations of Technology and Business Trends. 2025. pp. 697–707.
26. Senapati B, Naeem AB, Matam P, Upadhyay C, Achanta A, Gudur V, et al. Agentic AI for self-evolving malware defense in develops security automation in battery cell manufacturing driven business. In: 2025 5th International Conference on Electrical, Computer, Communications and Mechatronics Engineering (ICECCME). 2025. pp. 1–8.
27. Tzanis E, Adams LC, D'Antonoli TA, Bressem KK, Cuocolo R, Kocak B, et al. Agentic systems in radiology: principles, opportunities, privacy risks, regulation, and sustainability concerns. Diagn Interv Imaging. 2025. https://doi.org/10.1016/j.diii.2025.10.002.
28. Khalil RA, Ahmad K, Ali H. Redefining elderly care with agentic AI: challenges and opportunities. IEEE Open J Comput Soc. 2026. https://doi.org/10.1109/OJCS.2026.3650842.
29. Pachaiyappan N. Agentic commerce: a comprehensive analysis of cybersecurity risks, privacy challenges, and trust mechanisms in autonomous AI-driven marketplaces. In: 2026 IEEE 5th International Conference on AI in Cybersecurity (ICAIC). 2026. pp. 1–6.
30. Pan G, Tao Y, Yang Z, Li J, Peng Y, Bao X, et al. Generative AI-empowered signal processing for collaborative embodied agents: a survey on agentic security. IEEE Trans Cogn Commun Netw. 2026. https://doi.org/10.1109/TCCN.2026.3676045.
31. Tran GT, Le Dinh T, Le TD. Agentic AI across technologies, applications, and development domains: a systematic literature review. In: International Conference on Data Analytics & Management. 2026. pp. 587–601.
32. Senbagavalli M, Debnath S, Vaneeta M, Arumugam T, Beena B, Prajapat S. Adaptive semantic integrity and privacy shielding in agentic AI networks for trustworthy 6G cognitive communication system. IEEE Commun Stand Magazine. 2026. https://doi.org/10.1109/MCOMSTD.2026.3661577.
33. Ragupathy V. Secure agent-based architectures for decentralized AI identity management: the DAIS framework. In: 2026 IEEE 5th International Conference on AI in Cybersecurity (ICAIC). 2026. pp. 1–6.
34. Radanliev P, Santos O, Maple C. Threats and vulnerabilities in artificial intelligence and agentic AI models. Front Artif Intell. 2026;9:1731566.

Publisher's Note

Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.