

Computational Astrophysics

2019

Exercises 08. Root Finding

Curve Fitting: The $M_{\text{BH}} - \sigma_*$ Relation

The code `solution8ab.py` implements the routine to read the data files using the `astropy` command `ascii`. The data is stored in `numpy` arrays. We also implemented a function to perform the linear fit in the form

$$\log\left(\frac{M_{\text{BH}}}{M_{\odot}}\right) = \alpha + \beta \log\left(\frac{\sigma_*}{\sigma_0}\right) \quad (1)$$

with the equations presented in class, including data uncertainties. The reference value in the dispersion velocity is $\sigma_0 = 200 \text{ km s}^{-1}$. The linear fit function returns the coefficients α and β together with the corresponding uncertainties σ_{α} and σ_{β} .

For the given data, without errors, the $M_{\text{BH}} - \sigma_*$ relation is given by the linear fit with parameters

$$\alpha = 7.663 \pm 0.183 \quad (2)$$

$$\beta = 2.925 \pm 0.547, \quad (3)$$

which can be seen in Figure 1.




Figure 1: Linear fit without data errors.

In `solution8c1.py` we include the error data for the black hole mass. The resulting linear fit has the parameter

$$\alpha = 7.779 \pm 0.015 \quad (4)$$

$$\beta = 3.232 \pm 0.061, \quad (5)$$

and the corresponding plot is given in Figure 2.

Finally, including data errors in both variables, the linear fit has the parameters

$$\alpha = 7.680 \pm 1.462 \quad (6)$$

$$\beta = 2.912 \pm 4.917, \quad (7)$$

and the corresponding plot is given in Figure 3.




Figure 2: Linear fit with data error in $\log(M_{BH}/M_\odot)$.




Figure 3: Linear fit with data errors in $\log(M_{BH}/M_\odot)$ and σ_* .