

Time Series: A First Course with Bootstrap Starter

Contents

Lesson 1: Takes and tools	2
Takes	2
Tools	2
Links to JD+	2
Lesson 1-1: Time Series Data	2
Example 1.1.3. U.S. Population	2
Example 1.1.4. Urban World Population	3
Example 1.1.5. Non-Defense Capitalization	4
Serial Dependence and Forecasting	5
Example 1.1.8. Dow Jones Industrial Average	5
Lesson 1-2: Cycles	7
Example 1.2.1. Sunspots	7
Example 1.2.2. Unemployment Insurance Claims	8
Example 1.2.3. Mauna Loa carbon Dioxide	9
Example 1.2.4. Retail Sales of Motor Vehicles and Parts Dealers	10
Example 1.2.5. Housing Starts	11
Lesson 1-3: Windows and Transforms	12
Windowing	12
Example 1.3.2. Industrial Production	12
Log Transformation	13
Example 1.3.4. Gasoline Sales	13
Example 1.3.5. Electronics and Appliance Stores	14
Lesson 1-4: Time Series Regression and Autoregression	15
Regression on Time Trend	15
Example 1.1.3. U.S. Population	15
Regression on Past of Self	16
Example 1.1.3. U.S. Population	17
Incorporate Time Trend	18

Lesson 1: Takes and tools

Takes

- smoothness: greater correlation easier forecasting
- log as reducer of variability : formal proof ?
- formalization of cycle: “High association can occur for non-adjacent random variables”
- rarely a good idea to regress on time only

Tools

- windowing, spanning and creating a movie

Links to JD+

algorithms, docs and related training


Lesson 1-1: Time Series Data

- A *time series* is a dataset where the observations are recorded at discrete time intervals.
- We denote the observation at time t by x_t , and the random variable by X_t .
- We have times $t = 1, 2, \dots, n$ for the *sample* X_1, X_2, \dots, X_n .
- Time series data might not be i.i.d. (Independent and Identically Distributed)!

Example 1.1.3. U.S. Population

- U.S. Population growth over the twentieth century.


```
pop <- read.table("USpop.dat")
pop <- ts(pop, start = 1901)
plot(pop*10e-7, xlab="Year", ylab="U.S. Population", lwd=1)
```



Example 1.1.4. Urban World Population

- Urban World Population trends upwards more strongly after WWII.


```
urban <- read.table("urbanpop.dat")
urban <- ts(urban[67:1,], start = 1951)
plot(urban*1e-9,xlab="Year",ylab="Urban Population",lwd=1)
```



Example 1.1.5. Non-Defense Capitalization

- Non-Defense Capitalization (New Orders) shows non-monotonic trend, and is more *noisy*.

```
ndc <- read.table("Nondefcap.dat")
ndc <- ts(ndc[,2],start=c(1992,3),frequency=12,names= "NewOrders")
plot(ndc,xlab="Year",ylab="Non-defense Cap")
```




Serial Dependence and Forecasting

- Smoothness corresponds to high positive association (correlation) between adjacent variables.
- High association means forecasting (prediction of future values) is easier.

Example 1.1.8. Dow Jones Industrial Average


- Dow Jones Industrial Average has trend, but is hard to forecast one day ahead.

```
dow <- read.table("dow.dat")
dow <- ts(dow, start=c(2008,164), frequency=252)
plot(dow, xlab="Year", ylab="Dow Levels")
```



- We can plot the log returns (consecutive difference of logged data), which shows how volatility is not constant.

```
dow.diff <- diff(log(dow[,1]))  
plot(dow.diff,xlab="Year",ylab="Dow Log Returns")
```




Lesson 1-2: Cycles

- High association can occur for non-adjacent random variables.
- For some fixed $h > 1$, we may have X_t and X_{t-h} associated for all t .
- This is a *periodic* effect, called a *cycle*, of period h .

Example 1.2.1. Sunspots

- Wolfer sunspots series measures number of sunspots recorded each month.
- Cycles are roughly 11 years (so $h \approx 132$).


```
wolfer <- read.table("wolfer.dat")
wolfer <- ts(wolfer, start=1749, frequency=12)
plot(wolfer, xlab="Year", ylab="Sunspots")
```



Example 1.2.2. Unemployment Insurance Claims

- Weekly measurements of claims for unemployment insurance (pre-Covid).
- There is a weekly cyclical pattern, corresponding to a cycle of annual period ($h = 52$).


```
ui <- read.table("ui.dat")  
ui <- ts(ui, start=1967, frequency=52)  
plot(ui, ylab="UI Claims", xlab="Year")
```

Example 1.2.3. Mauna Loa carbon Dioxide

- Monthly measurements of CO₂ levels on mount Mauna Loa.
- Apparent upward trend and monthly ($h = 12$) cycle.


```
mau <- read.table("mauna.dat",header=TRUE,sep="")  
mau <- ts(mau,start=1958,frequency=12)  
plot(mau,ylab="Mauna Loa CO2",xlab="Year")
```



Example 1.2.4. Retail Sales of Motor Vehicles and Parts Dealers

- Monthly measurements of retail sales.
- Shows trend, monthly ($h = 12$) cycle, and Great Recession.


```
Ret441 <- read.table("retail441.b1", header=TRUE, skip=2)[,2]
Ret441 <- ts(Ret441, start = 1992, frequency=12)
plot(Ret441, ylab="Motor Retail Sales", xlab="Year")
```



Example 1.2.5. Housing Starts

- Monthly measurements of housing construction started (West Region).
- Shows trend, monthly ($h = 12$) cycle, and some recessions/expansions.

```
Wstarts <- read.table("Wstarts.b1",header=TRUE,skip=2)[,2]
Wstarts <- ts(Wstarts,start = 1964,frequency=12)
plot(Wstarts, ylab="West Starts",xlab="Year")
```



Lesson 1-3: Windows and Transforms

- To better visualize a time series, we may examine sub-spans, or use a transformation.


Windowing

- Focusing on a sub-section of the time series is called *windowing*.
- A *window* has a fixed width, and the starting and ending times change as it slides through the data.
- Windowing is useful for exploratory analysis, to visualize changes.

Example 1.3.2. Industrial Production

- Industrial Production is a monthly time series, starting in 1949.
- It has strong trend and moderate seasonality.

```
indprod <- read.table("ind.dat")
indprod <- ts(indprod,start=1949,frequency=12)
plot(indprod,xlab="Year",ylab="Industrial Production")
```



- We can create a moving window through the data.

```
### Movie
movie <- FALSE
delay <- 0
window <- 20
n <- length(indprod)/12
if(movie) {
  for(t in 1:(n-window +1))
  {
    Sys.sleep(delay)
    subsamp <- indprod[((t-1)*12+1):((t-1+window)*12)]
    newyear <- 1948 + t
    plot(ts(subsamp,start=newyear,frequency=12),ylab="")
  }
}
```

Log Transformation


- To visualize and model time series better, sometimes we apply a log transform (if the data is positive).
- If cycle amplitude depends on trend level, applying a log may separate this effect so that cycle amplitude is no longer growing.
- Some extreme effects can be attenuated through the log transform.

Example 1.3.4. Gasoline Sales

- Monthly measurements of sales at gasoline stations.

- Variation depends on level, so we apply a log transformation.

```
gas <- read.table("GasRaw_2-11-13.dat")[,1]
loggas <- log(gas)
gas_trans <- ts(cbind(gas,loggas),start = 1992,frequency=12)
plot(gas_trans,xlab="Year",main="Gas Sales")
```




Example 1.3.5. Electronics and Appliance Stores

- Monthly measurements of sales at electronics stores
- Large seasonal movements due to December sales
- We apply a log transformation

```
elec <- read.table("retail443.b1",header=FALSE,skip=2)[,2]
logelec <- log(elec)
elec_trans <- ts(cbind(elec,logelec),start = 1992,frequency=12)
plot(elec_trans, xlab="Year",main="Electronics Sales")
```

Electronics Sales



Lesson 1-4: Time Series Regression and Autoregression

- It is tempting to regress time series data on time $t = 1, \dots, n$, as a covariate.

Rarely does this provide satisfactory results (when used alone).

Regression on Time Trend

- Regression model with time trend:

$$X_t = \beta_0 + \beta_1 t + Z_t.$$

Is $\{Z_t\}$ i.i.d.? Usually: **No**.


Example 1.1.3. U.S. Population

- Try out time trend regression for U.S. population.

```
pop <- read.table("USpop.dat")
pop <- ts(pop, start = 1901)
n <- length(pop)
time <- seq(1,n)
model1 <- lm(pop ~ time)
summary(model1)
```

```
##
## Call:
## lm(formula = pop ~ time)
```

```
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -14549597 -4786782  1606479  4952580 10891620
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) 63186029   1432136   44.12  <2e-16 ***
## time        2016351     24868    81.08  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 7071000 on 97 degrees of freedom
## Multiple R-squared:  0.9855, Adjusted R-squared:  0.9853
## F-statistic: 6575 on 1 and 97 DF,  p-value: < 2.2e-16
plot(ts(model1$residuals))
```



- **Highly structured residuals!** We could add higher order polynomial effects to time trend, but it won't really help.

Regression on Past of Self

- Let past values of the time series be the covariates. Called *Autoregression*.
- Autoregressive model:

$$X_t = \rho X_{t-1} + Z_t.$$


Assume $\{Z_t\}$ i.i.d.

Example 1.1.3. U.S. Population

- Try out autoregression for U.S. population.
- Here we include a constant regressor as well.

```
model2 <- lm(pop[-1] ~ pop[-n])  
summary(model2)
```

```
##  
## Call:  
## lm(formula = pop[-1] ~ pop[-n])  
##  
## Residuals:  
##      Min       1Q   Median       3Q      Max   
## -1025866 -289498  -73620   301639 1164336   
##  
## Coefficients:  
##              Estimate Std. Error  t value Pr(>|t|)      
## (Intercept) 9.705e+05  1.522e+05   6.376 6.33e-09 ***  
## pop[-n]      1.006e+00  8.814e-04 1141.752 < 2e-16 ***  
## ---  
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1  
##  
## Residual standard error: 499900 on 96 degrees of freedom  
## Multiple R-squared:  0.9999, Adjusted R-squared:  0.9999  
## F-statistic: 1.304e+06 on 1 and 96 DF,  p-value: < 2.2e-16  
  
plot(ts(model2$residuals))
```




- Residuals are less structured, though maybe still not i.i.d.
- Why does this seem to work?

```
cor(pop[-1],pop[-n])
```

```
## [1] 0.9999632
```

```
plot(pop[-1],pop[-n],xlab="X Past",ylab="X Present")
```



Incorporate Time Trend

- We can incorporate time trend into an autoregression.
- One way to do it:

$$X_t = \rho X_{t-1} + \beta_0 + \beta_1 t + Z_t,$$

- This makes the mean $\mathbf{E}[X_t]$ depend on ρ .
- Another way to do it:

$$Y_t = \beta_0 + \beta_1 t + X_t$$

$$X_t = \rho X_{t-1} + Z_t.$$

```
model3 <- lm(pop[-1] ~ pop[-n] + time[-1])
summary(model3)
```


```
##
```

```
## Call:
```

```
## lm(formula = pop[-1] ~ pop[-n] + time[-1])
```

```
##
```

```
## Residuals:
##      Min       1Q   Median       3Q      Max
## -1094117  -273594   -31978   350442  1023219
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) 1.636e+06  4.538e+05   3.606 0.000498 ***
## pop[-n]      9.952e-01  7.201e-03 138.202 < 2e-16 ***
## time[-1]     2.269e+04  1.458e+04   1.556 0.122985
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 496200 on 95 degrees of freedom
## Multiple R-squared:  0.9999, Adjusted R-squared:  0.9999
## F-statistic: 6.615e+05 on 2 and 95 DF,  p-value: < 2.2e-16
plot(ts(model3$residuals))
```



- This implements the first approach
- Notice slope coefficient β_1 is not significant, and residuals resemble those of the pure autoregressive model. So not much benefit to using time covariate.