

# TSACE WEBINAR, WEDNESDAY DECEMBER 14TH 2022



## Using JDemetra+ in R: from version 2 to version 3 Presentation 1: General Outline of the R-JDemetra+ universe

ANNA SMYK AND TANGUY BARTHELEMY  
With the collaboration of Alain Quartier-la-tente

# Contents

---

## 1. Introduction

## 2. Accessing JDemetra+ core routines: from v2 to v3

## 3. Setting up your work environment

# Outline of the webinar

---

`**(PUSH record button)**`

Scope of the webinar: Seasonal Adjustment with X13-Arima and Tramo-Seats (leaving the rest aside...for future webinars ?)

Four presentations (approx 90')

- P1: introduction
  - highlighting the main evolutions between version 2 and 3
  - outlining the global scope of R tools for JDemetra+
  - working environment set-up
- P2: Focus on SA with X13-Arima or Tramo-Seats in R and related tools.

## 10' Coffee Break

- P3: Working in R with JDemetra+ workspaces
- P4: Quality assessment and production in R

Resources on GitHub: slides, code, additional papers and beamers  
[https://github.com/annasmyk/Tsace\\_RJD\\_Webinar\\_Dec22](https://github.com/annasmyk/Tsace_RJD_Webinar_Dec22)

# JDemetra+ : a library of algorithms for time series analysis

JDemetra+ is a library of algorithms on:

- Seasonal Adjustment (GUI and R)
- Trend and cycle estimation (R only)
- Benchmarking and temporal disaggregation (GUI and R)
- Nowcasting (R and Plug-in)

They can be accessed via graphical user-interface (GUI) and/or R and/or plug-ins.

The available output, functions or tools are in general not identical using R or GUI for example, it is often fruitful to combine them.

JDemetra+ also offers general utilities for time series analysis: tests, auto-correlation functions, Arima modelling, spectral analysis tools ... (in GUI and R)

# Why R packages ?



---

Before 2019: access only through GUI and plug-ins.

Why add R packages ?

Allows to immerse JD+ algorithms in the R universe, with all its pre-existing statistical functions and user-community.

In March 2019, RJDemetra (containing X-13 Arima and Tramo-Seats) was published on CRAN:

- first  package that enables to use Tramo-Seats
- faster than existing  packages on seasonal adjustment

# Ever-growing R ecosystem

---

Since, many more packages have been developed as JDemetra+ Core was upgraded from version 2 to version 3

Extension of scope:

- High-frequency data (extended)
- STL
- refresh policies for SA
- new tools

Modifications of existing functions and output organisation

# Contents

---

1. Introduction

2. **Accessing JDemetra+ core routines: from v2 to v3**

3. Setting up your work environment

## From v2 to v3: changing gears

---

### Version 2:

- RJDemetra (X13-Arima, Tramo-Seats, functions for workspace wrangling)
- additional packages based on RJDemetra: rjdworkspace, ggdemetra, rjdqa (see paper on v2)
- more specific packages like rjdhighfreq, rjdsts

(corresponding to the version 2.x family of JD+ Core)

### The mindset of version 3 is:

- modular organisation: independent more specific functions
- more “stand alone” tools (not only retrieving results from SA processing)


### Version 3: A suite of packages (see below)

- corresponding to the version 3.x family of JD+ Core
- still under construction, moving perimeters



# Organisation of the rjd3 packages

## Overview



<https://github.com/palatej?tab=repositories>

## Seasonal adjustment algorithms in JDemetra+ version 3

---

For seasonal adjustment, specifically, JDemetra+ contains:

- X13-Arima (GUI and R)
- Tramo-Seats (GUI and R)
- STL (R only)
- Structural Time Series (SSF framework) (R only)

All of these algorithms can be used with HF data.

For X13-Arima and Tramo-Seats some illustrations are available only in GUI. (auxiliary tools like: spectral analysis, sliding spans, revision history. . . )

Scope of this webinar: SA with X-13 and Tramo-Seats, including HF data

# Contents

---

## 1. Introduction

## 2. Accessing JDemetra+ core routines: from v2 to v3

## 3. Setting up your work environment

## Installing packages (1/2)

---


Version 2: RJDemetra is on CRAN

```
install.packages("RJDemetra")  
library("RJDemetra")
```

In part 3 and 4 we will also use

- JDCruncheR (based on cruncher output) To install it: download the **.zip** or **.tar.gz** file from <https://github.com/InseeFr/JDCruncheR/releases>.
- rjdworkspace (based on RJDemetra) To install it: download the **.zip** or **.tar.gz** file from <https://github.com/InseeFrLab/rjdworkspace/releases>.

You can run v2 and v3 simultaneously

Version 3 requires Java   $\geq 17$  (see <https://github.com/jdemetra/rjdemetra/wiki/Installation-manual>)

## Installing packages (2/2)

---

Installing latest version from GitHub (as not on CRAN yet)

```
# install.packages("remotes")

remotes::install_github("palatej/rjdemetra3")

remotes::install_github("palatej/rjd3toolkit", ref = "v0.6.0")

remotes::install_github("palatej/rjd3modelling", ref = "v0.6.0")
remotes::install_github("palatej/rjd3arima", ref = "v0.6.0")
remotes::install_github("palatej/rjd3sa", ref = "v0.6.0")

remotes::install_github("palatej/rjd3tramoseats", ref = "v0.6.0")
remotes::install_github("palatej/rjd3x13", ref = "v0.6.0")
remotes::install_github("palatej/rjdemetra3", ref = "v0.6.0")

remotes::install_github("palatej/rjd3sts", ref = "v0.5.0")
remotes::install_github("palatej/rjd3highfreq", ref = "v0.5.0")
remotes::install_github("palatej/rjd3stl", ref = "v0.5.0")
```