



Download

- [Binaries](#)
- [Source Code](#)
- [Developer Zone](#)

Help

- [CC3D User Forum](#)
- [Manuals](#)
- [Tutorials](#)
- [F.A.Q.](#)

Demos

- [Simulation Movies](#)
- [Screenshots](#)
- [Model Repository](#)

Publications

- [Publications](#)
- [Theses](#)
- [Talks and Posters](#)

Events

- [Workshops](#)

About

- [People](#)
- [Contact Us](#)
- [Mailing List](#)

Search Site

Building CompuCell3D on FedoraCore Linux

Building CompuCell3D from source on Unix/Linux systems is fairly straightforward once all of it's dependencies have been satisfied. The following commands should build and install CC3D on [FedoraCore](#) systems.

Prerequisites

Hardware

CompuCell3D may build and run with less capable hardware, but has been tested with the following:

- 1024MB RAM
- Hardware 3D Graphics Acceleration (most modern graphics cards)

Build Tools and Dependencies

In addition to the common Unix/Linux build tools, interpreters and, libraries, building and running CompuCell3D requires:

- Qt (version 4.6 or higher recommended)
- PyQt (with OpenGL modules)
- SWIG (version 2.x recommended)
- VTK (with Python wrappers, version 5.4 or higher recommended)
- Qwt (and PyQwt, version 4.2 or higher recommended)
- QScintilla (version 1.7 or higher recommended)
- CMake (CMake-GUI is recommended)
- Python (version 2.6 or higher recommended)

On Fedora-based distributions the following command should install all the required dependencies (make sure you are **root** before executing yum commands. Othrwise you will geet notification abuot insufficient privileges):

```
yum install qt4-devel PyQt4 vtk-devel vtk-qt qwt-devel qwt5-qt4-devel PyQwt-devel swig qscintilla-devel cmake-gui PyOpenGL vtk-python python2-devel libxml2-devel qscintilla-python gcc-c++ git
```

Source Code

Once the dependencies have been satisfied make directory where you want to store source code, in my case it is in **/home/m/CC3D_GIT**

```
mkdir /home/m/CC3D_GIT
cd /home/m/CC3D_GIT
```

Once the directory has been created, obtain the source code from our GIT repository using the following command:

```
git clone https://github.com/CompuCell3D/CompuCell3D.git .
```


This will clone CC3D Git repository into current directory (remember about the **.** at the end of last command - it is important)

Build Configuration: Starting CMake


CompuCell3D is configured using the CMake build system. The following command starts the CMake GUI:

```
cmake-gui
```

That will start the build system, click **Browse Source...** and select the **CompuCell3D** source directory from the CompuCell3D GIT directory we have created above - in my case the CompuCell3D source directory is located in **/home/m/CC3D_GIT/CompuCell3D**:




in addition to specifying source directory we also specify the location of the build directory i.e. a directory where compilation files will be stored. in my case it is **/home/m/CC3D_GIT_build/CompuCell3D**




Build Configuration: Selecting Build System

We are ready to click **Configure**. A dialog box asking to create the build directory will appear:



and then one asking about the build system:




Select **Unix Makefiles** for the generator, select **Use default native compilers** and then click **Finish**. CMake will begin the configuration process. CMake will attempt to locate all of the dependencies installed above. If the following error occurs, ignore it:

```
CMake Error: Could not open file for write in copy operation /usr/local/pythonSetupScripts/Version.py.tmp
CMake Error: : System Error: No such file or directory
CMake Error at core/post_install_tasks/CMakeLists.txt:134 (configure_file):
  configure_file Problem configuring file
```


After the initial configuration has completed select **Grouped** and **Advanced** to make entering configuration values easier.

Build Configuration: CMAKE


In **CMAKE** confirm that CMake has located all the build tools. In the **CMAKE_BUILD_TYPE** field you may enter **Debug**, **RelWithDebInfo** or **Release** to specify the type of the binary you want to have - if you are developing extra modules compiling in the **Debug** or **RelWithDebInfo** can be helpful. By default CompuCell3D build type is set to **Release**:



In the **CMAKE_INSTALL_PREFIX** field enter the directory you would like to install CompuCell3D into - this is important. We recommend that unless necessary you should install CC3D into local directory - in my case it is **/home/m/CC3D_install**, .



Click on **Configure** to have all the values updated. Click on **Configure** and then click on **Generate** to generate the Makefiles, ignore any warnings. Exit CMake




Building


To begin compiling CompuCell3D enter the build directory specified in the **Where to build the binaries** field of CMake earlier and use the following command:

In my case I type:

```
cd /home/m/CC3D_GIT_build/CompuCell3D
make
```



After the build begins you may see screen like this one:



Installing

Once compiling has completed CompuCell3D can be installed into the directory specified in the `CMAKE_INSTALL_PREFIX` field earlier by issuing the following command:

```
make install
```


FileEditViewBookmarksSettingsHelp

```
/home/m/CC3D_GIT/CompuCell3D/core/BasicUtils/BasicException.h:153: Warning 314: 'print' is a python key
word, renaming to '_print'
/home/m/CC3D_GIT/CompuCell3D/core/BasicUtils/BasicException.h:153: Warning 314: 'print' is a python key
word, renaming to '_print'
/home/m/CC3D_GIT/CompuCell3D/core/Utils/Coordinates3D.h:49: Warning 362: operator= ignored
/home/m/CC3D_GIT/CompuCell3D/core/CompuCell3D/Field3D/Point3D.h:65: Warning 362: operator= ignored
/home/m/CC3D_GIT/CompuCell3D/core/CompuCell3D/Field3D/Dim3D.h:52: Warning 362: operator= ignored
/home/m/CC3D_GIT/CompuCell3D/core/CompuCell3D/Field3D/Dim3D.h:96: Warning 389: operator[] ignored (cons
ider using %extend)
/home/m/CC3D_GIT/CompuCell3D/core/CompuCell3D/Field3D/Field3D.h:142: Warning 389: operator[] ignored (c
onsider using %extend)
/home/m/CC3D_GIT/CompuCell3D/core/BasicUtils/BasicException.h:168: Warning 503: Can't wrap 'operator <<
' unless renamed to a valid identifier.
/home/m/CC3D_GIT/CompuCell3D/core/CompuCell3D/Field3D/Point3D.h:106: Warning 503: Can't wrap 'operator
<<' unless renamed to a valid identifier.
/home/m/CC3D_GIT/CompuCell3D/core/CompuCell3D/Field3D/Dim3D.h:98: Warning 503: Can't wrap 'operator <<'
unless renamed to a valid identifier.
Scanning dependencies of target _Fields
[100%] Building CXX object core/pyinterface/Fields/CMakeFiles/_Fields.dir/FieldsPYTHON_wrap.o
In file included from /usr/include/python2.7/numpy/ndarraytypes.h:1728:0,
                 from /usr/include/python2.7/numpy/ndarrayobject.h:17,
                 from /usr/include/python2.7/numpy/arrayobject.h:15,
                 from /home/m/CC3D_GIT_build/CompuCell3D/core/pyinterface/Fields/FieldsPYTHON_wrap.cxx:
3476:
/usr/include/python2.7/numpy/npymath/npymath.h:11:2: warning: #warning "Using deprecated NumPy API,
disable it by #defining NPY_NO_DEPRECATED_API NPY_1_7_API_VERSION" [-Wcpp]
Linking CXX shared module _Fields.so
[100%] Built target _Fields
m@m-Vostro-220-Series:~/CC3D_GIT_build/CompuCell3D$ make install[]
```

CompuCell3D: bash

m: mc


Running


After CompuCell3D has finished installing you can start CompuCell3D by entering the installation directory (in my case it is in **/home/m/CC3D_install**):

```
cd /home/m/CC3D_install
```

and issuing the following command:

```
./compuCell3d.sh
```



Maintained by [IU](#) and the [Biocomplexity Institute](#)
CC3D® and  The CompuCell 3D Environment® logo are registered trademarks.