1 **Time-of-Flight Mass Spectrographs – From Ions to Neutral Atoms**

2 **E. Möbius, A.B. Galvin, L.M. Kistler, H. Kucharek, and M.A. Popecki**

3 Space Science Center and Department of Physics, University of New Hampshire, Durham, NH

4 Corresponding author: Eberhard Möbius (eberhard.moebius@unh.edu)

5 **Key Points:**

6 • Review of time-of-flight mass spectrographs

7 • Versatile application of time-of-flight spectrographs for ions and neutral atoms

8 • Simultaneous determination of velocity distribution and composition

9 **Abstract**

10 After their introduction to space physics in the mid 1980's time-of-flight (TOF) spectrographs
11 have become a main staple in space borne mass spectrometry. They have largely replaced mag-
12 netic spectrometers, except when extremely high mass resolution is required to identify complex
13 molecules, for example in the vicinity of comets or in planetary atmospheres. In combination
14 with electrostatic analyzers and often solid state detectors, TOF spectrographs have become key
15 instruments to diagnose space plasma velocity distributions, mass and ionic charge composition.
16 With a variety of implementation schemes that also include isochronous electric field configura-
17 tions, TOF spectrographs can respond to diverse science requirements. This includes a wide
18 range in mass resolution to allow the separation of medium heavy isotopes or to simply provide
19 distributions of the major species, such as H, He, and O, to obtain information on source tracers
20 or mass fluxes. With a top hat analyzer at the front end, or in combination with deflectors for 3-
21 axis stabilized spacecraft, the distribution function of ions can be obtained with good time reso-
22 lution. Most recently, the reach of TOF ion mass spectrographs has been extended to include en-
23 ergetic neutral atoms. After selecting the arrival direction with mechanical collimation, followed
24 by conversion to ions, adapted TOF sensors form a new branch of the spectrograph family tree.
25 We review the requirements, challenges, and implementation schemes for ion and neutral atom
26 spectrographs, including potential directions for the future, while largely avoiding overlap with
27 complementary contributions in this special issue.

28 **1. Introduction**

29   The measurement of particle populations in space, electrically charged and neutral alike,
30 is undertaken to provide essential information toward several key objectives that are behind typi-
31 cal heliophysics missions, such as:
32 - Origin or source population of locally detected particles
33 - Heating of plasmas and neutral gases
34 - Transport and interaction of charged and neutral particles
35 - Acceleration of charged particles to high energies
36 For the evaluation of particle populations to address these questions it is essential to determine
37 all parameters that characterize each individual particle and then to synthesize the observable
38 distributions separately for all these parameters. The relevant key observables for particles are:
39 - Elemental and sometimes isotopic composition, or particle mass A
40 - Charge state composition, or the Ionic Charge Q of the particle
41 - Particle speed v, as well as arrival direction θ and ϕ
42 Subdivided into small increments in speed and angle, the particle count rate accumulated over
43 pre-defined time intervals can be turned into the velocity distribution function $f(v, \theta, \Phi, t)$, in-
44 cluding its variation over time t, for ions, electrons, and neutral atoms, separate for individual
45 species. In this paper, we will concentrate on ion and neutral atom distributions. We will treat
46 atoms as particles with charge state $Q = 0$. For a plasma physicist, the velocity distribution func-
47 tion f is the key to physical processes that control the interaction in plasmas. Instead of observing
48 directly the particle velocity, particle sensors usually return the kinetic particle energy E along
49 with the arrival direction. The energy E is linked to the speed v with the particle mass A, or spe-
50 cies. With the geometric factor G the observable particle count rate can be translated into the dif-
51 ferential particle flux $\Delta J(E, \theta, \Phi, t)/\Delta E\Delta\Omega$, which is related to the distribution function via:

52
$$\frac{\Delta J\left(E,\theta,\Phi,\,t\right)}{\Delta E\,\Delta\Omega} = \frac{v^2}{A m_p} f\left(v,\theta,\Phi,\,t\right)$$
(1)

53   where $\Delta\Omega$ is the field-of-view (FoV) and ΔE the energy resolution of the sensor. By integration
54   over a small phase space volume a particle detector obtains the count rate R in a selected angular
55   sector with center angles θ and ϕ and at a selected center energy E, according to:

56
$$R(\theta,\phi,E,t) = \frac{\Delta J\left(E,\theta,\Phi,\,t\right)}{\Delta E\,\Delta\Omega} \cdot G \cdot \Delta E\,\Delta\Omega$$
(2)

57   The situation is depicted schematically in Figure 1.

58   Any particle counting sensor with energy
59   resolution and a constrained FoV that is either a
60   sub-division of a larger FoV or can be swept
61   across the sky provides the crucial differential par-
62   ticle flux. However, to distinguish and thus accu-
63   mulate separately particle species according to M
64   and Q, requires additional diagnostics. In the early
65   days of space exploration, the combination of elec-
66   trostatic and magnetic deflection was employed
67   [e.g. Coplan et al., 1978; Shelley et al., 1978] to
68   provide mass resolution for bulk plasmas up to
69   about 10 keV/Q. This technique is still very im-
70   portant for very high mass resolution in connection
71   with in-situ sampling of planetary, lunar, and com-
72   etary atmosphere environments [e.g. Balsiger et
73   al., 2007]. For energetic particle populations, such
74   as solar, anomalous, and galactic cosmic rays, par-
75   ticle telescopes are used that obtain the energy loss

Fig. 1: Schematic view of a particle velocity distribution function $f(v,\,\theta,\,\phi)$ and how a particle detector system selects a certain portion as differential particle flux $\Delta J/\Delta E\Delta\Omega$.

76   ΔE in a thin detector and measure the residual energy E_R in a thick detector, where the particles
77   are stopped, to obtain species resolution. These telescopes make use of the nuclear charge Z and
78   mass A dependent specific energy loss in bulk material. When including gas proportional coun-
79   ters as ΔE elements [Hovestadt & Vollmer 1971; Hovestadt et al., 1978], this technique covers
80   energies down to <100 keV/nucleon. The two aforementioned methods still left a substantial gap
81   in energy coverage, in particular in the crucial suprathermal regime where ions are accelerated
82   out of their source populations, until the arrival of time-of-flight (TOF) mass spectrographs in
83   the 1980's [Gloeckler & Hsieh 1979; Gloeckler 1990]. Wüest [1997] provided a review in the
84   first symposium on space plasma instrumentation.

85   In this paper, we will give a current overview of TOF mass spectrometry for ion and neu-
86   tral atom populations with simultaneous diagnostics of their distribution functions. It is largely
87   based on a presentation at the conference on Measurement Techniques in Solar and Space Phys-
88   ics and avoids substantial overlap with concurrent presentations by Gilbert, McFadden, Pascha-
89   lidis, and Zurbuchen on TOF spectrometry and by Barabash and Funsten on neutral atom imag-
90   ing. Where related sensors are addressed in papers for this special issue, they are cross-
91   referenced in the appropriate Section. Section 2 will provide a brief introduction to the TOF
92   method, its strengths and challenges. TOF spectrographs for suprathermal and energetic particle

93 populations will be covered in Section 3, those for thermal plasma populations and the solar
94 wind in Section 4, high-resolution mass spectrographs in Section 5, and neutral atom imagers
95 with mass resolution in Section 6. Section 7 contains a brief summary and indicates where TOF
96 spectrographs may be key in the near future.

2. Brief Introduction to the Time-of-Flight Method

98 Compared with simple particle detectors that typically count single signals and thus are
99 vulnerable to any noise or background count, a TOF detector, by means of its method, is a genu-
100 ine coincidence detection system, which provides intrinsic noise and background suppression. As
101 the name implies, for each incoming particle the measurement of the flight time τ between a start
102 and a stop detector across a known distance d is obtained, which requires two independent detec-
103 tions of the same particle. Two generic TOF configurations are shown in Figure 2. The start sig-
104 nal is obtained in most cases from the passage of a thin foil, typically made of carbon, where the
105 particle generates secondary electrons. These
106 are accelerated and steered to an electron
107 multiplying detector (channeltron or micro-
108 channel plate, MCP) by means of appropriate
109 electrostatic field configurations. The stop
110 signal may be detected directly or, again,
111 through secondary electrons. In the left panel
112 of Figure 2, the electrons from the start and
113 stop location are accelerated toward the cen-
114 ter of the sensor, cross each other, and are
115 deflected by a transverse field to a start and
116 stop MCP at each end. In the right panel a
117 configuration with electrostatic mirrors is
118 shown, which reflect the start and stop elec-
119 trons to start and stop MCP at opposite sides
120 of the sensor perpendicular to the particle
121 trajectory. While the former configuration
122 contains fewer grids that reduce the sensor
123 transparency and generate more scattered
124 particles, the latter configuration allows to
125 obtain the start and stop position in two di-
126 mensions from the signals. The choice de-
127 pends on the measurement requirements.

Fig. 2: Schematic view of generic TOF sensors. Particles enter through a thin C-foil from the left and traverse the TOF path d to a detector on the right. Secondary electrons are guided by electric fields to start and stop MCPs. Structure in black is held at 1-2 kV positive relative to structure in grey. The detector on the right may be an MCP or a solid-state detector to measure energy (see Section 3). Left: Electrons cross before reaching the start and stop MCP. Grids after the foil and in front of the detector at positive potential are often used to accelerate the electrons more quickly to reduce dispersion. Right: Electrons are reflected by a dual electrostatic mirror, which also facilitates 2-D position sensing.

128 The main objective of the TOF section is to determine the speed v of the particles and
129 thus their energy E per mass unit A in front of the entrance foil according to:

$$\frac{E_{TOF}}{A} = \frac{1}{1-\alpha_1} \frac{Da}{2} \left(\frac{d}{\tau}\right)^2 \qquad [3]$$

131 Da (1 Dalton) is the atomic mass unit (1/12 of the carbon atom mass), α_1 is a parameter that re-
132 flects the energy loss in the entrance foil. For each TOF sensor this energy loss is determined by
133 a combination of simulation [e.g. Ziegler et al., 2015] and calibration. The TOF resolution $\Delta\tau/\tau$
134 depends mainly on three characteristics:

135   1) The energy loss in the foil is a statistical process and thus associated with energy straggling
136   that increases with foil thickness, decreasing particle energy, and increasing mass. Large ef-
137   forts have gone into reducing the foil thickness [e.g. McComas et al., 2004] and/or into
138   boosting the energy of incoming ions with a high post-acceleration voltage, as described in
139   Section 4.1 and 4.2.

140   2) The secondary electrons arrive at each MCP with a time dispersion, which can be minimized
141   by their immediate acceleration with a grid on the positive acceleration potential right in
142   front of the foil and the detector at the end, as shown in the electrostatic mirror configuration
143   in the right panel of Figure 2. Such grids have also been used in the overcrossing configura-
144   tion on the left, for example in AMPTE SULEICA [Möbius et al., 1985a].

145   3) Due to a finite FoV angle range and additional angular scattering in the foil that is causally
146   connected with the energy straggling, the actual flight *d'* path may be longer than *d* according
147   to *d' = d/cosθ*, where *θ* is the angle of the flight path relative to the normal direction of the
148   foil plane. The angular range may be reduced by a long and slender TOF system geometry.
149   Alternatively, in the electrostatic mirror configuration, the start and stop position can be
150   measured with MCP position sensing, providing the information to correct the flight path *d'*.

151   Typically, energy straggling (1) dominates the overall TOF resolution $\Delta\tau/\tau$ at low ener-
152   gies because it becomes rather strong. For high-energy or high-speed particles, the electron time
153   dispersion (2) along with the timing accuracy of the electronics dominate, because this is a fixed
154   amount for a given instrument concept, while the TOF τ decreases with speed. A finite angular
155   range (3) leads to a fixed ratio $\Delta\tau/\tau$ and thus a constant contribution to the overall resolution.

156   As is evident, to measure the TOF τ both the start and the stop signal are needed, thus
157   providing a natural double coincidence, with intrinsic background and noise suppression by or-
158   ders of magnitude compared with single signal detection techniques. Assuming a noise or back-
159   ground detection rate R_N with a single MCP the statistical background contribution R_{BG} to the
160   TOF rate that competes with a TOF signal with timing resolution $\Delta\tau$ can be estimated as:

$$R_{BG} = R_N^2 \cdot \Delta\tau \tag{4}$$

161

162   For a TOF resolution of a few nsec even noise rates of a few kHz are reduced to rates
163   well below 0.1 sec^{-1}. However, the presence of a majority species, typically H, can provide chal-
164   lenges to the detection of minor species with abundances many orders of magnitude below that
165   of H. The detection efficiency for secondary electrons is always lower than 100%. Therefore,
166   particles whose start signal was not detected but their stop signal was may produce chance coin-
167   cidence events with other ions that had a start signal. Assuming an incoming rate R_{IN} of the ma-
168   jority species, the resulting chance coincidence background rate R_{BG} is:

$$R_{BG} = (1 - \mu_{Start}) \cdot \mu_{Stop} \cdot R_{IN}^2 \cdot \Delta\tau \tag{4a}$$

169

170   where μ_{Start} and μ_{Stop} are the start and stop efficiencies for the majority species. While Equation
171   (4a) still contains the coincidence related background suppression term $R_{IN}\Delta\tau$, the background
172   rate now increases with the square of the incoming rate.

173   In general, a TOF sensor provides a speed or energy per mass measurement, while simul-
174   taneously giving noise and background suppression. This detection technique works equally well
175   for incoming ions or neutral atoms. In order to determine the mass number *A* and/or the ionic

176 charge state Q (where a neutral atom has $Q = 0$) of the combination of a TOF system with other
177 measurements that determine the total energy E and/or the energy per ionic charge E/Q is neces-
178 sary. From the combination of different energy analysis techniques with a TOF subsystem a fam-
179 ily of TOF sensors emerges, each of whose members can be optimized for a suitable range of
180 specific applications tailored to the goals of a space mission. A number of technological chal-
181 lenges with TOF spectrographs are addressed by McFadden [2016].

3. Suprathermal/Energetic TOF Spectrographs

183 As pointed out in the introduction, the suprathermal energy range had been challenging to
184 cover with species-sensitive particle sensors before the advent of the TOF method. Indeed the
185 first TOF spectrographs were implemented for this energy range on satellites in the 1980's. The
186 first mission to contain several TOF spectrographs was the Active Magnetospheric Particle Trac-
187 er Explorers (AMPTE) mission [Bryant et al., 1985], with three such instruments, the Medium
188 Energy Particle Analyzer (MEPA) [McEntire et al., 1985] and the CHarge Energy Mass
189 (CHEM) [Gloeckler et al., 1985] sensor on the Charge Composition Explorer (CCE) and the SU-
190 prathermal Low Energy Ion Charge Analyzer (SULEICA) [Möbius et al., 1985a] on the Ion Re-
191 lease Module [IRM].

192 The MEPA sensor is an example for
193 the combination of a TOF system with solid-
194 state detectors (SSD) to determine separately
195 the residual energy E_{Res}, i.e. the energy of E of
196 the incoming article reduced by the fraction α_1
197 lost in the entrance foil and the fraction α_2 in
198 the contact layer of the SSD. This detector,
199 where the particles are stopped and deposit
200 their energy, is included in the schematics in
201 Fig. 2. Having determined the energy per mass
202 E/A in Equation (3) we now obtain the atomic
203 mass A of the particle according to:

Fig. 3: Schematic view of an ESA-TOF combination with an SSD. The ESA serves as E/Q filter. The TOF spectrograph provides the energy per mass E/A according to Equation 3. The SSD measures the residual energy E_{Res}, and thus allows a separate determination of E, A, and Q.

$$A = \frac{E_{Res}}{(1-\alpha_2)\cdot E_{TOF}/A} \tag{5}$$

205 As α_1 the energy loss α_2 is energy and species dependent and is determined by calibration with
206 known ion beams at an accelerator. It is evident that the total energy E can also be determined.

207 The MEPA sensor was implemented with the electrostatic mirror. To cope with the high
208 intensity of penetrating radiation in the radiation belts and ring current, MEPA included a second
209 foil at the center grid of the electrostatic mirror. From here the secondary electrons were acceler-
210 ated to a third MCP in the corner of the sensor to provide another independent coincidence
211 measurement, which substantially reduced the background. Other examples of this sensor type
212 are SAMPEX LICA [Mason et al., 1990; Mason et al., 1993], ACE ULEIS [Mason et al., 1998],
213 and STEREO SIT [Mason et al., 2008]. To boost TOF resolution and reduce background, ULEIS
214 contains two consecutive electrostatic mirror TOF sections. This sensor allowed abundance
215 measurements of [3]He in small impulsive energetic particle events even below 1%, thus establish-
216 ing that selective acceleration of [3]He is indeed a hallmark of all impulsive events. Enhanced [3]He

217   abundances were even found in coronal mass ejections indicating re-acceleration of remnant im-
218   pulsive populations [Mason et al., 2005; Desai et al., 2006].

219   To separately determine E, A, and the ionic charge state Q of incoming ions the combina-
220   tion with an electrostatic analyzer (ESA) at the sensor entrance is needed. The AMPTE CHEM
221   and SULEICA instruments were the first satellite borne TOF spectrographs to provide that capa-
222   bility. A schematic view of the SULEICA sensor is shown in Fig. 3. The ESA acts as energy per
223   charge filter, which passes ions within a narrow band with a specific E/Q and resolution ΔE/Q.
224   The mass per charge ratio is determined as:

225
$$\frac{A}{Q} = \frac{E/Q}{E_{TOF}/A} \tag{6}$$

226   making use of $E/Q = E_{TOF}/Q$, where E_{TOF} is obtained from Equation (3). As a consequence, the
227   full energy range is covered by changing the ESA voltage in logarithmic steps. The number of
228   energy steps n determines the duty cycle of the sensor, and its effective geometric factor is re-
229   duced by the factor n. We will turn to potential improvements in Section 4.2.

230   Typically, the ions are first separated according to A/Q with the combined resolution of
231   the ESA and the TOF section according to:

232
$$\frac{\Delta A/Q}{A/Q} = \sqrt{\left(\frac{\Delta E/Q}{E/Q}\right)^2 + 2\left(\frac{\Delta \tau}{\tau}\right)^2} \tag{6a}$$

233   The ESA resolution is constant for a given analyzer, whereas the TOF resolution varies with spe-
234   cies and energy. The resolution in mass A is a combination of the TOF resolution and the energy
235   resolution of the SSD.

236
$$\frac{\Delta A}{A} = \sqrt{\left(\frac{\Delta E_{Res}}{E_{Res}}\right)^2 + 2\left(\frac{\Delta \tau}{\tau}\right)^2} \tag{6b}$$

237   Equations (6a) and (6b) are good approximations as long as the contributing resolution ratios are
238   small compared to one. Both the TOF and the energy resolution increase rapidly for low particle
239   energies. Because the energy range of CHEM extends into the bulk plasmas of the magneto-
240   sphere and the solar wind, this sensor includes post-acceleration to boost the ion energy for the
241   TOF and energy measurement [Gloeckler et al., 1985], as discussed in Section 4.3.

242   The A/Q resolution of SULEICA alone was key for the discovery of interstellar He^+
243   pickup ions [Möbius et al., 1985b] in conjunction with detecting Li^+ [Möbius et al., 1986] from
244   the cloud experiments in the solar wind conducted with the AMPTE IRM satellite [Haerendel et
245   al., 1985]. The combination of A/Q resolution and total energy measurement allowed the unam-
246   biguous identification of energetic NO^+ and O_2^+ ions in a post-storm ring current [Klecker et al.,
247   1986], because molecular ions typically break up when passing the TOF entrance foil. In this
248   way, suprathermal TOF mass spectrographs opened the door for many studies, which were not
249   possible before. Other examples of this sensor type are WIND STICS [Gloeckler et al., 1995]
250   and SOHO STOF [Hovestadt et al., 1995].

4. Low Energy TOF Spectrographs for Bulk Plasmas

251

252   Until the 1980's magnetic mass spectrometers dominated the instrumentation in the
253 thermal and bulk plasma regime. However, their limitation to energies below about 15 keV/Q,
254 along with the difficulty to provide a wide angular FoV and their relatively low geometric factor,
255 provided formidable challenges to measure 3-dimensional distribution functions with mass and
256 charge resolution and a reasonably high time resolution.

257   4.1 Distribution Function Analyzers with A/Q resolution

258   The realization that only small contributions of a few percent of O^+ ions to magnetospher-
259 ic plasmas or 10% of He^{2+} ions to the solar wind would have a substantial contribution to the
260 momentum balance in physical processes, such as reconnection and bulk acceleration led to an
261 alternate approach that includes the TOF method. Thus, for Cluster and simultaneously for FAST
262 and Equator-S a sensor concept was developed based on a marriage between a top-hat ESA, as
263 used successfully in the 3D Plasma instrument [Paschmann et al., 1985], and the TOF section of
264 the SULEICA sensor [Möbius et al., 1985a], both on AMPTE IRM. For the new sensor, the TOF
265 section was expanded to a fully rotationally symmetric cylindrical geometry [Möbius et al.,
266 1998a; Réme et al., 1997; Klumpar et al., 2001]. Because the most important ion species in the
267 magnetosphere (H^+, He^{2+}, He^+, O^{2+}, and O^+) are separated in A/Q by subsequent factors of two
268 an implementation could be chosen that consists solely of an ESA and a TOF section to deter-
269 mine E/Q and E/A, albeit with post acceleration of the ions between ESA and TOF section with a
270 negative voltage up to -20 kV.

271   Figure 4 includes a cross-sectional and a
272 top view of the COmposition and DIstribution
273 Function (CODIF) sensor. The top-hat ESA, for
274 which the lower part of Fig. 4 represents a radial
275 cut of the fully rotationally symmetric configura-
276 tion, allows instantaneous coverage up to 360^o in
277 elevation angle θ and typically $\Delta\phi = 6\text{-}15^o$ in azi-
278 muth. Each spin is sub-divided into 32 spin angle
279 (ϕ) sectors during each of which the ESA voltage
280 is swept through its full range to provide energy
281 coverage. For Cluster CODIF and Equator-S
282 ESIC, each sweep is sub-divided into 128 loga-
283 rithmically spaced steps, while FAST TEAMS
284 uses 192 steps. The Cluster CODIF and the Equa-
285 tor-S ESIC sensors have a split FoV with two
286 180^o wide apertures and geometric factors that
287 differ by about x50 to increase the dynamic range
288 and to allow accommodation of a retarding poten-
289 tial analyzer for the lowest energies [Réme et al.,
290 1997]. FAST TEAMS makes use of the full 360^o
291 aperture with identical geometric factor and thus
292 obtains a full distribution function within ½ spin.
293 The relevant E/Q for the TOF section includes the

Fig. 4: Top view and cross-sectional view of the CODIF sensor. The top-hat ESA provides imaging of elevation angle θ to a position at the exit, which the start electrons map to 16 sectors of the start MCP. Spin covers azimuth ϕ because the sensor symmetry axis is oriented at 90^o relative to the spin axis.

294   post-acceleration voltage U_{PAC}, thus modifying Equation (6) to:

295    $$\frac{A}{Q} = \frac{E/Q + U_{PAC}}{E_{TOF}/A} \qquad (7)$$

296   The design challenges and choices for this sensor were described by Möbius et al., [1997] in
297   connection with the previous space instrumentation symposium and in the instrument papers, and
298   thus shall not be repeated here. The sensors on Cluster, FAST, and Equator-S have led to numer-
299   ous studies that would have been impossible without the fast coverage of the distribution func-
300   tion and the species identification, for example: differential acceleration of ions in the auroral
301   region [Lund et al., 1998; Möbius et al., 1998b], acceleration of He[+] by electromagnetic ion cy-
302   clotron waves in the inner magnetosphere [Mouikis et al., 2002], the importance of the cusp as a
303   source for O[+] in the magnetotail [Kistler et al., 2010], and the role that O[+] plays in magnetic re-
304   connection in the magnetotail [Liu et al, 2015] and at the magnetopause [Wang et al., 2015].

305   4.2 TOF Sensors with Post-Acceleration that Provide Charge State

306   While the most abundant ion species in the Earth's magnetosphere as well as interstellar
307   pickup ions can be distinguished unambiguously with an ESA – TOF combination, a meaningful
308   composition analysis of the solar wind and related suprathermal particles requires a three-
309   dimensional analysis [E/Q, E/A, E], including residual energy measurement with an SSD. To dis-
310   tinguish between neighboring charge states of, for example, C and O, a combined resolution in A
311   and Q of better than ΔA, $\Delta Q \leq 1$ is needed. To achieve such resolution post-acceleration voltages
312   in excess of 20 kV [Gloeckler et al., 1992], ultra-thin C-foils [Funsten, et al., 1994], and SSDs
313   with very good energy resolution and thin dead layers are needed. A typical instrument for solar
314   wind composition measurements is Ulysses and ACE SWICS [Gloeckler et al., 1992; 1998]. The
315   sensor is similar to the one in Fig. 3, but with post-acceleration between the ESA and the TOF
316   section. Now the entire TOF section, including SSD and analog electronics is at the post-
317   acceleration potential. Like AMPTE SULEICA and Cluster CODIF, SWICS takes advantage of
318   the spinning Ulysses and ACE spacecraft to obtain angular distributions. With the spin axis
319   pointing close to the Sun, the SWICS FoV of 70[o] in the direction perpendicular to the spin plane
320   guarantees almost continuous coverage of the solar wind and extensive coverage of pickup ions.

321   The other two solar wind composition TOF spectrographs, SOHO CELIAS CTOF
322   [Hovestadt et al., 1995] and STEREO PLASTIC [Galvin et al., 2008], were implemented on
323   three-axis stabilized spacecraft that were optimized for Sun viewing optical and EUV cameras.
324   With the large collecting power of its 180[o] hemispherical electrostatic analyzer situated between
325   two quadrupole lenses and un-interrupted coverage of the solar wind, CTOF provided the first
326   high time resolution measurements of solar wind composition. Like its predecessor CTOF,
327   STEREO PLASTIC provides un-interrupted and high time resolution for solar wind ion meas-
328   urements, but PLASTIC also provides the first full directional information for solar wind heavy
329   ions. The entrance system for PLASTIC [Blush et al., 2005] is a 360[o] top-hat electrostatic ana-
330   lyzer that incorporates three different geometrical factors. In the sunward direction, two sets of
331   electrostatic deflectors are also used in order to provide 40[o] coverage in the out-of-ecliptic direc-
332   tion. For solar wind ions, the largest geometric factor is reduced automatically by electrostatical-
333   ly switching to the smallest aperture during each ESA stepping cycle, when high He[2+] and H[+]
334   fluxes are encountered [Galvin et al., 2008]. In this manner, reliable measurements over the en-
335   tire dynamic range of suprathermal and solar wind ion populations can be obtained in each 1-

336 minute cycle. In contrast, on other missions, an additional sensor is included in the payload for
337 the purpose of measuring solar wind protons and alphas. Like SWICS and CTOF, the PLASTIC
338 TOF section incorporates SSDs to allow full mass and charge measurements.

339 Among others, Ulysses and ACE SWICS have allowed great advances toward the com-
340 position, velocity distribution, and spatial distribution of pickup ions [Gloeckler & Geiss 1998;
341 Gloeckler et al., 2004; Chen et al., 2013]. They have demonstrated distinct mass and charge
342 composition differences between fast and slow solar wind and their variations with solar activity
343 [vonSteiger et al., 2000] as well as great insight into coronal mass ejection related solar wind
344 [Lepri et al., 2001] and their likely source populations. The unique high angular resolution of
345 STEREO PLASTIC has recently allowed the unambiguous demonstration that interstellar He$^+$
346 pickup ions maintain a narrow toroidal velocity distribution from the original injection for quite a
347 while during their transport with the solar wind [Drews et al., 2015]. The temporal resolution of
348 SOHO CTOF and STEREO PLASTIC (e.g., 5-10 minute for an iron spectrum) has enabled dis-
349 tinguishing differences in the magnetic field and ion compositional boundaries of solar wind
350 structures [e.g., Aellig et al., 1998; Galvin et al., 2013; Winslow et al., 2016].

351 4.3 Efforts to Improve Resolution, Temporal Cadence, and Reduce Sensor Size

352 One key capability of the various plasma TOF spectrographs is their ability to separate
353 individual species and charge states. However, to resolve unambiguously the charge states of
354 neighboring elements, the minimum energy before entry of the TOF section has to be boosted by
355 post-acceleration to relatively high voltages and/or the energy resolution of SSDs has to be im-
356 proved, in particular for low energy ions. However, providing isotope resolution requires a dif-
357 ferent TOF section concept that sacrifices ionic charge resolution and will be discussed in Sec-
358 tion 5. An extremely challenging method to improve the overall resolution, albeit with some re-
359 cent success in the laboratory, is to push the post-acceleration voltage to 50 - 100 kV, as present-
360 ed by Gilbert et al. [2016], which would lead to energy, mass, and charge resolution comparable
361 to a suprathermal or energetic particle sensor. Alternatively, the use of an ultra-thin window and
362 low noise SSDs in the form of Avalanche Photodiodes (APD) or novel diamond detectors
363 [Ogasawara et al., 2015], is being explored, which may also allow the combination of energy
364 measurement and stop detection in the same detector and thus could reduce sensor complexity.

365 The increased complexity of instruments like PLASTIC to provide angular coverage and
366 resolution as well as simultaneous optimization for full mass and charge resolution of the solar
367 wind proper, along with the dual need to increase time resolution for reconnection studies and to
368 reduce the size and complexity of sensors for smaller spacecraft missions, have prompted the
369 search for alternative sensor concepts. One key obstacle to improving time resolution and reduc-
370 ing sensor size, while maintaining a high effective geometric factor, is the intrinsic requirement
371 to step through the ESA voltage. Including the scan in at least one angle, either via the spacecraft
372 spin or with a deflector system, this amounts to nested scans in two dimensions of velocity space.
373 This greatly impacts both time resolution and effective geometric factor because of the low
374 measurement duty cycle. Therefore, several attempts have been and are being made to eliminate
375 one of the scans, either in energy or angle by a scheme that allows simultaneous coverage.

376 The MESSENGER FIPS sensor is a successful attempt to reduce the sensor size and
377 eliminate the need of angular scanning by combining a wide-open ESA with a collimator and
378 position sensing at the interface between ESA and TOF section to obtain the arrival angle for a
379 selected *E/Q* range [Andrews et al., 2007; Zurbuchen et al., 2016]. A somewhat different and

380 conceptually simplified way to obtain a simultaneous image of the velocity distribution with a
381 FoV of almost 2π has been presented by Skoug et al. [2016]. Here, the ESA is the region be-
382 tween a planar entrance plate with a center pinhole aperture and a filterplate at the exit, which
383 only passes ions of a pre-determined ratio $E/(Q\,U_{ESA})$. Yet ions that arrive from a range of eleva-
384 tion angles θ are identified simultaneously, where θ translates into a unique radial position $r(\theta)$.
385 A challenge of this design is obtaining a reasonable energy resolution for particles that arrive at
386 elevation angles close the center axis of the sensor because the deflection field is almost in the
387 direction of motion. To improve this resolution an additional center cone at the potential of the
388 collimator plate is introduced, which provides a radial deflection field component.

389   Another attempt to improve the temporal cadence by providing partial imaging of a com-
390 bination of elevation angles and energy per charge has been made with an ESA curvature that
391 depends on the azimuth angle of the instrument aperture. The Advanced Mass and Ionic Charge
392 Composition Experiment (AMICCE) provides simultaneous coverage over a range of energies,
393 thus reducing the number of energy steps by about a factor of ten [Allegrini et al., 2009; 2016].
394 With a "flower-shaped" ESA that has a wide opening at the entrance and exit, but is narrow in its
395 middle, the SupraThermal Ion Monitor (STIM) provides simultaneous coverage over a range in
396 energy and imaging of about 40^{o} in elevation angle [Desai et al., 2015; Desai et al., 2016]. Eleva-
397 tion angle and E/Q are obtained by position sensing at the detector.

5. High-Resolution TOF Spectrographs

399   Linear TOF spectrographs are limited in their resolution by the spread in energy E and
400 angle θ due to scattering in the C-foil according to $\Delta\tau/\tau \sim \sqrt{\Delta E/E}$ and $\Delta\tau/\tau \sim \sqrt{1-cos2\Delta\theta}$.
401 Uncertainties in the TOF electronics can be held at typically <0.5 ns and are mostly negligible.
402 As discussed already in Section 2, the energy and angle scattering are inherent in the design of
403 linear TOF spectrographs and, as discussed in Section 4, can only be mitigated within limits by
404 the choice of very thin C-foils and/or high post-acceleration voltages. Because the TOF resolu-
405 tion is directly linked to the M/Q and M resolution of the instrument (Equation 3a and 3b) sepa-
406 ration of neighboring elements and isotopes call for a different instrument concept. Alternate
407 TOF spectrometry concepts that avoid a foil as start sensing element are in use for specific appli-
408 cations. A rotating electric field, which ties the start timing to the phase of the field, provides a
409 successful alternative to magnetic gas analyzers, but without access to the velocity distribution
410 function. An example is the STROFIO sensor on Bepi Colombo [Orsini et al., 2010; Livi 2016].
411 Gated TOF spectrographs that derive the timing by short opening pulses of the system are useful
412 to diagnose high bulk ion fluxes when a small duty cycle of the sensor due to the short opening
413 pulse compared with the TOF window can be afforded [Orsini et al., 2010; Paschalidis 2016].
414 Here, we concentrate on isochronous TOF geometries.

415   5.1 Isochronous TOF Spectrographs

416   To eliminate the uncertainties related to the energy and angle straggling, a TOF configu-
417 ration has been implemented, in which the ions follow a ballistic trajectory in a retarding electric
418 field whose strength increases linearly with distance from the common plane of the entrance foil
419 and stop detector as shown in Fig. 5 [e.g. Managadze 1986]. The linearly increasing electric field
420 $E(y) = k \cdot y$ turns the TOF sensor into a harmonic oscillator and τ becomes half the oscillator pe-
421 riod, which solely depends on the ion mass per charge A/Q. The majority of ions in the energy

422 range 1 to 30 keV/e leaves the entrance foil of the TOF system as neutral atoms or as singly
423 charged ions [Gonin et al., 1992]. For the ions, the τ obeys:

$$\tau = \frac{\pi}{\omega} = \pi\sqrt{\frac{A \cdot Da}{ek}} \tag{8}$$

425 which requires a retarding potential of $\approx$20 kV for 45^o trajectories. Neither initial energy nor in-
426 coming angles affect the resulting TOF τ in the reflecting section, which solely depends A for
427 singly charged ions, thus making the mass resolution also independent of the ESA *E/Q* resolu-
428 tion. For an earlier review see Wüest [1998]. Neutral atoms that leave the TOF section on a
429 straight line can be analyzed in an additional linear TOF section (in purple in Fig. 5). To obtain
430 also the energy of the ions an electrostatic *E/Q* filter is placed in front of the TOF entrance.

431   The reflecting electric field, which increases linearly with distance from the plane that
432 contains entrance foil and stop MCP, is key to the harmonic oscillator behavior. Such a field con-
433 figuration can be implemented with a series of potential shaping electrodes, as in CASSINI
434 CAPS [McComas, et al., 1998], or the bounding electrodes are shaped such that they represent
435 the appropriate boundary conditions for the solution of Laplace's equation for a potential that
436 increases with the square of the distance from the entrance plane. This condition has been
437 achieved with a set of V-shaped electrodes for a mostly planar geometry of the ion trajectories in
438 the TOF section, as depicted in Fig. 5, for WIND MASS [Gloeckler et al., 1995] and SOHO

439 CELIAS MTOF [Hovestadt et al., 1995]. The
440 ROSINA experiment on ROSETTA to study
441 elementary, isotopic, and molecular composi-
442 tion of comet 67P/Churyumov–Gerasimenko
443 contains the isochronous TOF sensor RTOF,
444 but also includes a magnetic spectrometer for
445 the mass resolution required to separate neigh-
446 boring heavy molecular species [Balsiger et al.,
447 2007]. To potentially combine a reflecting
448 TOF section with a top hat ESA that can obtain
449 instantaneously a 360^o slice of the ion velocity
450 distribution, a cylindrically symmetric poten-
451 tial configuration is used in the CYLMAS con-
452 cept [Möbius et al., 1990; Gubler et al., 1995].

Fig. 5: Schematic view of a reflecting TOF spectrograph. In the linearly increasing electric field ions that leave the start foil perform half a harmonic oscillation, whose TOF τ only depends on M/Q, before reaching the stop MCP. Particles that leave the foil as neutral atoms can be analyzed in a linear TOF section (in purple). To obtain the original energy, an E/Q filter may be added to the sensor entrance.

5.2 Solar Wind Isotope Observation

454   WIND MASS [Gloeckler et al., 1995]
455 and SOHO CELIAS MTOF [Hovestadt et al.,
456 1995] have indeed provided great insight into
457 the solar wind isotope composition and have
458 expanded on the initial measurements taken with solar wind collector foils during the Apollo
459 missions on the moon's surface [Geiss et al., 1972]. The isotope composition of the solar wind is
460 the best proxy that we can currently obtain on the Sun's isotope composition, which in turn is an
461 archive of the element forming processes in the galaxy [Geiss & Reeves 1972] and of the frac-
462 tionation processes during the solar system formation [Marti & Bochsler 2012]. The solar corona
463 and thus the solar wind do not necessarily share an unbiased isotope composition with the Sun's

464 interior [Bochsler 2000]. Thus any variations of the isotope ratios with solar wind type and speed
465 will help to unravel fractionation processes between the Sun and the solar wind. To this end,
466 measurements with isochronous TOF sensors have enabled the differentiation between solar
467 wind types, whereas the foil collector technique largely provided average values. A compilation
468 of solar wind composition, with substantial emphasis on isotopes, may be found in the paper by
469 Wimmer-Schweingruber [2002]. The Isochronous TOF mass spectrographs have expanded the
470 number of elements now accessible to solar wind isotope observations, including elements up to
471 the mass of iron.

472 Wimmer-Schweingruber [2002] compared solar wind isotope ratios, among them for Ne
473 and Ar, as obtained with SOHO MTOF [Kallenbach. et al., 1997] and with the Apollo foil col-
474 lectors [Geiss et al., 1972]. All values agree within their observational uncertainties, which
475 serves as a validation of both techniques. Furthermore, the Mg isotope ratios [Bochsler et al.,
476 1997; Wimmer-Schweingruber et al., 1999] show a significant difference between fast and slow
477 solar wind. The values for coronal mass ejections appear to agree within their uncertainties with
478 those of the slow solar wind. This isotope fraction appears to be connected to a dependence of
479 the Mg isotope ratios on solar wind speed [Kucharek et al., 1998], also confirmed by Kallenbach
480 et al., [1998]. A likely reason for this fractionation may be found in the inefficient Coulomb drag
481 in the corona [Bodmer & Bochsler 1998].

482 5.3 Improvement of TOF Mass Resolution without Reflection

483 While the reflecting TOF scheme appears to be an ideal solution for an isotope-resolving
484 TOF mass spectrograph, it comes with challenges and shortcomings. Firstly, the reflecting elec-
485 tric field requires an additional high voltage supply for rather high voltages to cover a reasonable
486 energy range. Secondly, the retarding field naturally defocuses
487 the ion trajectories. As a consequence, the already existing angu-
488 lar dispersion after the entrance foil increases substantially so
489 that only a small fraction of the incoming ions are detected at the
490 stop detector, thus reducing the effective geometric factor of this
491 spectrograph typically by more than one order of magnitude over
492 that of a linear TOF system. Therefore, alternatives to improve
493 TOF resolution needed.

494 What limits the TOF resolution of a linear TOF spectro-
495 graph most severely is the energy and angle straggling during the
496 ion passage through the foil. Therefore, much effort has gone in-
497 to reducing the foil thickness [Funsten et al., 1994; McComas et
498 al., 2004]. A potential alternative is the suggestion to replace the
499 foil as the secondary electron generating element with a single-
500 stage MCP [Devoto et al., 2008]. Instead of penetrating the mate-
501 rial of a thin foil, the ions bounce off the surface inside the elec-
502 tron multiplication channels of the MCP at glancing angles. In
503 this way, the energy loss and thus the energy straggling is very
504 small, and the range of angles into which the ions are scattered is
505 very narrow around the angle of specular reflection. The very
506 long and narrow MCP channels restrict the angle range further.
507 In addition, the number of secondary electrons leaving the MCP

Fig. 6: TOF spectra of 11, 12.7 and 16 keV Ar using a ≈3.5 µg/cm² C-foil (top) and a single stage MCP (bottom) as start window.

508 may already be amplified by a factor that depends on the voltage applied across the MCP.

509 For a side-by-side comparison of the C-foil and MCP performance in an identical sensor
510 configuration, the C-foil has been replaced by a single-stage MCP in one of the 16 sectors of the
511 TOF section. A 3.5 µg/cm^2 C-foil was compared with an MCP, whose channels have a 25 µm
512 diameter and a length to diameter ratio $l/d = 20$. Figure 6 shows TOF spectra taken with an Ar$^+$
513 beam at energies of 11, 12.7 and 16 keV. The C-foil spectra are shown on the left and the ones
514 with the MCP on the right. A remarkable reduction in the width of the TOF spectra with the
515 MCP entrance is evident. For 11 keV, the full width at half maximum is reduced by almost a fac-
516 tor of 3 from ≈125 to ≈45 TOF channels. Because of its high mass, Ar is usually an extremely
517 challenging species to obtain a TOF spectrum at such low energies. Building on advanced atomic
518 layer deposition, this test setup is also being used to test the reflectivity, scattering characteris-
519 tics, and secondary electron yield of several different MCP channel coatings.

520 The finite open area ratio of the MCPs and their limited opening solid angle reduces the
521 transparency of the sensor entrance window and consequently the start efficiency of the TOF
522 section. Results presented by Cadu et al. [2016] show that such efficiency reductions are partial-
523 ly compensated by the MCP gain and that they are definitely much smaller than the effective ge-
524 ometric factor reduction of isochronous TOF systems compared with linear TOF systems.

6. Energetic Neutral Atom Spectrographs

526 TOF mass spectrographs work just as well for neutral atoms as they do for ions. Whether
527 a neutral atom or an ion passes through the thin entrance foil does not affect the number of sec-
528 ondary electrons emitted, and the average charge state upon exit from the foil only depends on
529 the energy and species of the particle [Gonin et al., 1992]. Therefore, TOF spectrographs can al-
530 so be used to analyze energetic neutral atoms [ENAs]. Neutral atom populations are ubiquitous
531 in the solar system, in planetary, lunar, and cometary atmospheres, as well as in the interstellar
532 gas flow through the heliosphere.

533 The simultaneous presence of plasmas and neutral gas provides for a very effective re-
534 mote sensing technique of ion velocity distributions in the heliosphere for populations that are
535 found at a large distance from the observer. Because charge exchange occurs through the transfer
536 of an electron from the neutral gas atom, with the electron mass negligible compared to that of
537 the parent ion, the daughter ENA maintains the original ion momentum. Therefore, the ENA ve-
538 locity distribution mimics that of the parent ion distribution, modified by any speed dependence
539 in the charge exchange cross-section $\sigma_{ChEx}(v)$. ENAs are not deflected by electric or magnetic
540 fields on their way to the observer and arrive on straight trajectories, only modified by gravita-
541 tional deflection [e.g. Kucharek et al 2015], radiation pressure, ionization losses [Bzowski et al.,
542 2013], and collisions. Before corrections for the aforementioned effects, the observed differential
543 ENA fluxes J_{ENA} as function of energy E and solid angles θ and ϕ are related to the parent ion
544 velocity distribution $f_i(v, \theta, \phi)$ according to:

$$\frac{dJ_{ENA}(E,\theta,\phi)}{dEd\Omega} = n_a\sigma_{ChEx}(v)\Delta l \cdot \frac{v^2}{m_i} f_i(v,\theta,\phi) \tag{9}$$

546 n_a is the density of the surrounding neutral gas, Δl is the length along the line-of-sight over which
547 the charge exchange interaction occurs, and m_i is the mass of the ion. The factor v^2/m_i provides
548 the transformation from velocity distribution to differential flux as in Equation (1). One of the
549 biggest challenges to making reliable observations of ENAs is the competition from typically

550 much higher fluxes of ions at comparable energies. These ions must be suppressed before enter-
551 ing the sensor, or they must be carefully distinguished inside the sensor system, because the de-
552 tectors are equally sensitive to ions and neutral atoms. Of course, other background sources for
553 particle measurements, such as photons, electrons, and penetrating cosmic rays have to be elimi-
554 nated or at least well characterized.

555   6.1 Suprathermal Neutral Atom Spectrometers

556   Because ions and neutral atoms produce secondary electrons at the TOF entrance foil
557 with comparable efficiencies suprathermal and energetic particle TOF spectrographs without an
558 ESA entrance system, such as SAMPEX LICA or ACE ULEIS [Mason et al., 1998], can also
559 work as ENA mass spectrographs. However, they need an electrostatic suppression scheme at the
560 entrance aperture so that ENAs can be identified unambiguously. The first sensor equipped in
561 this way is the SOHO CELIAS HSTOF section of the STOF sensor [Hovestadt et al., 1995]. A
562 schematic view of this sensor is shown in Fig. 7. The entrance collimator consists of a set of
563 plates that deflect ions of energies up to the upper limit of the ENA energy range E_U/Q to hit the
564 plates, and thus they do not enter the sensor system. Ions with energies higher than E_U/Q will
565 enter, and thus this sensor will serve a dual purpose, as ENA sensor for $E_{ENA} < E_U$, and as ion
566 sensor for $E_{Ion}/Q > E_U/Q$. HSTOF is the high-energy ion section of the CELIAS STOF sensor,
567 with a substantial overlap with STOF over the energy range $150 - 600$ keV/Q. This overlap al-
568 lows an additional validation and separation of ion fluxes that might interfere with the ENA
569 spectrum.

570   These unique capabilities have ena-
571 bled the HSTOF sensor to obtain heliospher-
572 ic ENA distributions in the energy range 55-
573 150 keV [Hilchenbach et al., 1998]. They
574 used the fact that the energy spectra of H
575 ENAs and H$^+$ seen by HSTOF and STOF
576 above 150 keV match to conclude that there
577 is indeed a substantial excess of H ENAs
578 below 150 keV, increasing toward lower
579 energies. This comparison validated that

Fig. 7: Schematic view of a suprathermal ENA mass spectrograph. A mechanical collimator (left) with electrostatic deflection filters out incoming ions in the energy range of the ENA observation. The TOF section (right) is similar as in section 3.

580 HSTOF indeed sees H ENAs, unambiguously distinguished from interfering backgrounds. The
581 maximum of this ENA flux appears to come from the heliotail direction [Hilchenbach et al.,
582 1998]. In addition, He ENAs have been identified with HSTOF [Czechowski et al., 2004].

583   While SOHO HSTOF was primarily designed as an energetic ion TOF mass spectrograph
584 and the ENA separation capability was included only during the implementation phase, other
585 ENA detectors were optimized specifically for that purpose. As part of the Imager for Magneto-
586 pause-to-Aurora Global Exploration (IMAGE) mission the High Energy Neutral Atom (HENA)
587 imager [Mitchell et al., 2000] was optimized specifically for the imaging of magnetospheric
588 ENAs, largely using the same physical principles used in HSTOF. The HENA sensor provided
589 valuable insight into the global dynamics of energetic particles during geomagnetic storms [e.g.
590 Mitchell et al., 2001]. The Cassini probe carries the Ion-Neutral CAmera [INCA; Mitchell et al.,
591 1996] as part the Magnetosphere IMaging Instrument (MIMI) package [Krimigis et al., 2004].
592 INCA was designed and optimized to image Saturn's magnetosphere and its interaction with the
593 moons, but it also provides images of the heliospheric boundary region [Krimigis et al., 2009]

594   through ENAs at energies above the range covered by the Interstellar Boundary Explorer (IBEX)
595   mission [McComas et al., 2009a].

6.2 Low Energy Neutral Atom Spectrographs

597   In a similar way, low energy ion TOF mass spectrographs can be used for low energy
598   neutral atoms as well. The main challenge is that neutral atoms cannot be manipulated with elec-
599   tric and magnetic fields like ions. In particular, an ESA is needed to determine the energy of low
600   energy particles, and, as discussed in Section 4, ions at energies below about 10 keV/Q need to
601   be post-accelerated to obtain a reasonable TOF and thus mass resolution. Therefore, in all low
602   energy sensors ENAs are converted into ions after they have passed a collimator at the entrance,
603   which allows the determination of their arrival direction.

604   All low energy ENA sensors con-
605   tain the same building blocks as shown in
606   Fig. 8. The sensor aperture and electro-
607   static deflection and/or repeller scheme
608   rejects electrons and ions from entering
609   the collimator. A mechanical collimator
610   selects the arrival direction and deter-
611   mines the sensor FoV for the incoming
612   ENAs. Then the ENAs are converted to
613   ions. For medium low energies, typically
614    $0.5 - 10$ keV, an ultra-thin C-foil is used
615   to strip off electrons to convert atoms to
616   positive ions. The fraction of neutrals that
617   become ions depends on species and en-
618   ergy [Gonin et al., 1992]. Such a sensor

Fig. 8: Schematics radial cut of IBEX-lo. A top view of the signal anodes is shown in the upper right with the 4 quadrant anodes in the Stop portion (B) of the MCP, which are connected by delay lines. All 4 TOF measurements (TOF0, 1, 2, 3) are indicated.

619   has been built and optimized for magnetospheric imaging for IMAGE as the Medium Energy
620   Neutral Atom (MENA) imager [Pollock et al., 2000]. For ENA energies between 0.01 and 2
621   keV, the ENAs undergo a reflection at glancing incidence angles on a highly polished surface
622   and are converted to negative ions, as implemented for IMAGE in the Low Energy Neutral Atom
623   (LENA) imager [Moore et al., 2000] and developed further in Livi et al. [2003]. Fig. 8 shows a
624   configuration of the low energy version of the ENA sensor with reflection off a conversion sur-
625   face. After conversion, the emerging ions pass an ESA for energy selection and then are post-
626   accelerated. The final functional block is a TOF mass spectrograph, or, if mass analysis is not
627   needed, a coincidence detector system. The implementation of a coincidence system becomes
628   very important for ENA cameras because the expected ENA fluxes are generally extremely low
629   compared with those of ions in the same energy range and also compared to any background
630   generating signals. Therefore, the coincidence of two or more related signals that are generated
631   by the incoming ENAs are required to distinguish the weak signal from any kind of background.
632   Low energy ENA imagers that employ surface conversion to positive ions and the subsequent
633   bounce on a surface with secondary electron generation as start signal are used for planetary ap-
634   plications [e.g. Barabash et al. 2006, 2009]. Here, we concentrate on heliospheric applications
635   with their background related challenges.

636   IBEX takes ENA imaging to its current limits by obtaining images of the Heliosphere
637   boundary and sampling directly the neutral interstellar gas flow through the inner heliosphere

638   [McComas et al., 2009a]. To achieve these goals, particular attention to background and noise
639   suppression was necessary at all steps, as mentioned above [Wurz et al., 2009], because the sig-
640   nal rates that make up the ENA sky maps are extremely low, so that some individual pixels of
641   the maps contain only a few ENA counts per day. Therefore, the IBEX detector units are
642   equipped with genuine triple coincidence systems. IBEX contains two cameras, IBEX-Lo for the
643   low energy range 0.01 – 2 keV [Fuselier et al., 2009] with ENA to negative ion conversion and
644   IBEX-Hi for the medium low energy range 0.3 – 6 keV [Funsten et al., 2009] with stripping of
645   ENAs to positive ions. Funsten et al. [2016] discuss IBEX-Hi and related sensors. Here we will
646   concentrate on the IBEX-Lo TOF spectrograph.

647   The IBEX-Lo TOF system is adapted from Cluster CODIF [Reme et al., 1997]. Because
648   background suppression is so important for IBEX, two similar TOF sections are nested to pro-
649   vide genuine triple coincidence. Figure 8 shows a schematic radial cut. At the first C-foil, each
650   incoming ion generates secondary electrons that are guided to the outermost section (A) of a sin-
651   gle two-stage MCP, while electrons from the second foil reach the innermost section (C). The

652   ions are stopped at the center section, which con-
653   sists of 4 quadrants (B0-3) for additional back-
654   ground characterization. All sections are electrically
655   separated on the signal anode (upper right in Fig. 8).
656   TOF measurements are made between each of the
657   foils and the MCP (TOF0, TOF1) and between the
658   two foils (TOF2). For additional background char-
659   acterization, the quadrant position is derived from a
660   delay line along B0-B3 (TOF3).

661   During the IBEX-Lo background characteri-
662   zation each of the three TOF coincidence rates was
663   lower than 10^{-3} s^{-1}, indicating a very clean and low
664   noise TOF section. Next we turn to the advantages
665   of a triple TOF configuration to reduce chance sig-
666   nal coincidences due to orphaned start and stop sig-
667   nals, as already indicated in Equation 4 and 4a. The
668   additional TOF signal reduces the background rate
669   by another factor $R_{Start} \cdot \Delta\tau$, where $\Delta\tau$ is the TOF
670   resolution. Figure 9 shows how requiring more TOF
671   signals and successive constraints improve the
672   background response with TOF2 (H1, H2) and
673   TOF0 (H3, H4) histograms and TOF1 vs. TOF0
674   scatter plots (S1 – S4) from an H atom test with 16
675   kV post-acceleration. S1, H1, and H3 contain all
676   events with at least one of the three TOF measure-
677   ments valid. Except for an easily identifiable peak
678   near 0 ns in TOF2 (related to electrons) and two
679   very small "ghosts" (also in S1) near 0 ns in TOF0
680   the single TOF histograms provide already a clean
681   H distribution [Möbius et al., 2008].

Fig. 9: Sequence of TOF2 histograms H1 and H2, TOF1 versus TOF0 scatter plots that shows the successive removal of background and ghost signals from S1 through S4, and TOF0 histograms H3 and H4, as described in the text [adapted from Möbius et al., 2008; reproduced with the permission of the Institute of Geophysics-UNAM].

682   S2 and H2 only include events with four valid TOF measurements and which fulfill the
683 checksum condition: |TOF0 + TOF3 − TOF1 − TOF2| < 1ns. Clearly all events with TOF = 0 in
684 one of the channels (no valid TOF) are gone and most of the events outside the H peak region. In
685 H3, S1, and S2 two distinct peaks (connected by arrows) are seen, which come from neighboring
686 MCP quadrants with different delay times. In S3, S4, and H4 this is corrected by using TOF0 +
687 TOF3/2 and TOF1 - TOF3/2 instead, perfectly aligning the H distribution. Only events inside the
688 (dashed) H box remain and a few along two diagonal lines with slopes of 1 and 0.5 (faint dashed
689 lines in S4), due to H energy straggling in the second or first foil, respectively. S3 and S4 show a
690 residual <0.5% peak on the slope 1 line, which stems from cross-talk to the delay line anode and
691 thus also contains legitimate H events. Like the H ENA selection in the flight data, in S4 only
692 events have been selected in TOF2 (H2) that belong to the H peak down to the 1% level, thus
693 requiring consistency between all three TOFs. During a background run over 2.5 days no triple H
694 count was recorded, thus exceeding even our ambitious goal of less than 1 count per day.

695   In spite of its emphasis on excellent background suppression, the IBEX-Lo TOF subsys-
696 tem also provides high detection efficiency, which is very homogenous over the entire unit. For
697 highest background suppression triple coincidence is used, and for highest counting statistics any
698 single TOF measurement is accepted. Both efficiencies have been derived from calibrations with
699 neutral beams for the nominal post-acceleration voltage. Even with a post-acceleration voltage
700 that is now reduced to 7 kV from 16 kV after a discharge during a long eclipse, IBEX-Lo works
701 very effectively. It still fulfills all science objectives, except for observations of the O and Ne
702 interstellar gas flow. The TOF efficiencies for H ENAs and the sputtered H component from the
703 neutral interstellar He flow are reduced by about a factor of two, and the background is slightly
704 elevated, but these changes do not impact the ENA observations significantly. In other words,
705 IBEX-Lo still takes very clean observations.

706   6.3 Heliospheric Low Energy ENA Observations

707   The excellent noise and background suppression, good mass resolution, and large collect-
708 ing power of IBEX-Lo has made several important heliospheric discoveries possible. During the
709 implementation phase of IBEX it was not evident whether the H ISN flow would be detectable at
710 1 AU because of its very high ionization losses and the generally higher background susceptibil-
711 ity at the low H energies of $10 - 30$ eV. Following the discovery of the He ISN flow with Ulys-
712 ses GAS [Witte et al. 1996] and observations with IMAGE LENA [Collier et al. 2004], IBEX-Lo
713 clearly identified the H ISN flow, along with the expected He and O ISN signal [Möbius et al.
714 2009]. For the first time, the effect of solar radiation pressure on the H ISN flow could be de-
715 duced quantitatively from direct particle observations [Schwadron et al., 2013].

716   By comparing the observed ratio of sputtered C and converted O in the O ISN flow signal
717 with calibration results using an O and a Ne beam it was even possible to identify a Ne compo-
718 nent in the ISN flow and to determine the Ne/O ratio of the interstellar gas outside the solar sys-
719 tem [Bochsler et al., 2012; Park et al., 2014]. The resulting ratio for the pristine interstellar me-
720 dium agrees with findings from pickup ion observations by Gloeckler and Geiss [1998], but the-
721 se values suggest a higher Ne/O ratio than found in the solar system. This raises the question
722 whether there are genuinely different abundances in the solar system compared with the local
723 neighborhood or whether a substantial amount O may be locked in interstellar dust.

724   Most recently, IBEX-Lo has revealed secondary ISN flow components for O [Möbius et
725 al., 2009; Park et al., 2015] and He [Kubiak et al., 2014]. These are thought to arise from charge

726 exchange between the diverted interstellar plasma in the outer heliosheath and the neutral inter-
727 stellar flow. Such a component was predicted for O, but thought to be very weak for He [Müller
728 & Zank 2004]. Their characteristics will shed light on the interaction process in the outer heli-
729 osheath and on the plasma diversion caused by the interstellar magnetic field.

7. Conclusions and Outlook

731 TOF spectrographs for space applications have come a long way since their first use on
732 satellites in the mid 1980's. They can be adapted to a variety of uses and parameter ranges by
733 combining several different building blocks and optimizing them based on prior experience and
734 new needs. The inclusion of novel technologies, such as the potential replacement of C-foils by a
735 single-stage MCP to achieve better TOF resolution, advanced ESA concepts to improve the ef-
736 fective geometric factor and duty cycle, as well as the use of modern solid state detector concepts
737 to combine timing and energy measurement, ensures that the reach of TOF instrumentation will
738 go even further. Large-scale integration technologies reduce the resource requirements of the
739 electronics, and modern processor technologies help to optimize the data stream and to further
740 reduce resources so that the electronics for TOF instruments can be reduced in size. The actual
741 sensors are scaled based on the required collection capability, the required TOF path length, and
742 high voltage constraints, so these aspects are much harder to miniaturize. TOF instruments have
743 a wide range of applications from ionospheric and magnetospheric physics, via solar, interplane-
744 tary and interstellar physics to planetary applications.

745 With their tremendous achievements in the IBEX mission, TOF spectrographs also have
746 paved the way to a more ambitious follow-on mission, the Interstellar Mapping and Acceleration
747 Probe (IMAP). This mission, when implemented, will bring the ENA mapping of the heliosphere
748 boundary and the sampling of the interstellar gas flow to the next level of resolution and collect-
749 ing power. It will combine this capability with the crucial pickup ion diagnostics of the interstel-
750 lar gas population and high cadence observations of suprathermal and energetic particles to trace
751 their acceleration from the parent population to high energies. IMAP has been promoted as the
752 highest priority for solar terrestrial probes in the recent Heliophysics Decadal Survey [Baker et
753 al. 2013]. The scientific objectives of this mission depend crucially on a complement of TOF
754 spectrographs, which are optimized for neutral atoms over an extended energy range compared
755 with IBEX and for ions from pickup ion energies to about 1 MeV/nuc. The ENA TOF spectro-
756 graphs can be optimized based on ample test, calibration, and flight experience with IBEX and
757 CASSINI, and the PUI and suprathermal sensor will be the first dedicated instrument for this
758 purpose based on ample experience from Ulysses, ACE, and STEREO. Without the advances
759 made over the past 30 years in TOF technology and supporting sensor modules such mission
760 would not be possible.

References

Aellig, M. R., et al., (1998), Iron freeze-in temperatures measured by SOHO/CELIAS/CTOF, *J. Geophys. Res.*, **103**, 17215, doi: 10.1029/98JA00588.

Allegrini, F., et al., (2009), The entrance system laboratory prototype for an advanced mass and ionic charge composition experiment, *Rev. Sci. Instr.*, **80**, 104502, doi: 10.1063/1.4873327.

Allegrini, F., et al. (2016), A comprehensive suprathermal ion sensor suite, *this volume*.

Andrews, B., et al., (2007), The Energetic Particle and Plasma Spectrometer Instrument on the MESSENGER Spacecraft, *Space Sci. Rev.*, **131**, 523, doi:10.1007/s11214-007-9272-5.

Baker, D.N., et al., (2013), Solar and Space Physics, a Science for a Technological Society, The National Academies Press, Washington, D.C., ISBN 978-0-309-16428-3.

Balsiger, H., et al., (2007), Rosina Rosetta Orbiter Spectrometer for Ion and Neutral Analysis, *Space Sci. Rev.*, **128**, 745-801, doi: 10.1007/s11214-006-8335-3.

Barabash, S., et al. (2006), The Analyzer of Space Plasmas and Energetic Atoms (ASPERA-3) for the Mars Express Mission, *Space Sci. Rev.*, **126**, 113, doi: 10.1007/s11214-006-9124-8.

Barabash, S., et al. (2009), Investigation of the solar wind–Moon interaction onboard Chandrayaan-1 mission with the SARA experiment, Curr. Sci., 96, 526.

Blush, L.M., F. et al., (2005), Development and calibration of major components for the STEREO/PLASTIC (plasma and suprathermal ion composition) instrument, *Adv. Space Res*. **36**, 1556, doi: 10.1016/j.asr.2005.07.028.

Bochsler, P., et al., (1997), Limits of the efficiency of isotope fractionation processes in the solar wind derived from the magnesium isotopic composition as observed with the WIND/MASS experiment, *Phys. Chem. Earth*, **22**, 401.

Bochsler, P., et al., (2012), Estimation of the neon/oxygen abundance ratio at the heliospheric termination shock and in the local interstellar medium from IBEX observations, *Astrophys. J. Suppl.*, **198**:13, doi:10.1088/0067-0049/198/2/13.

Bodmer, R., & P. Bochsler (1998), The helium isotopic ratio in the solar wind and ion fractionation in the corona by inefficient Coulomb drag, *Astron. Astrophys.*, **337**, 921.

Bryant, D.A., S.M. Krimigis, & G. Haerendel (1985), Outline of the Active Magnetospheric Tracer Explorers (AMPTE) Mission, *IEEE Trans. on Geosci. El.*, **GE-23**, 177.

Bzowski, M., J.M. et al., (2013), Solar Parameters for Modeling the Interplanetary Background, In: Cross-Calibration of Far UV Spectra of Solar System Objects and the Heliosphere, *ISSI Scientific Report Series*, **13**, 67, Springer, New York.

Cadu et al. (2016), Grazing incidence time-of-flight mass spectrometer: prototype results and possible improvements, *this volume*.

Chen, J., et al., (2013), Observational Study of the Cooling Behavior of Interstellar Helium Pick Up Ions in the Inner Heliosphere, *J. Geophys. Res.*, **118**, 1, doi:10.1002/jgra.50391.

Collier, M. R., et al. (2004), An unexplained 10-40 degree shift in the location of some diverse neutral atom data at 1 AU, *Adv. Space Res.,* **34**, 166, doi: 10.1016/j.asr.2003.03.068.

Coplan, M.A., K.W. Ogilvie, P.A. Bochsler, & J. Geiss (1978), Ion Composition Experiment, *IEEE Trans. Geosci. El.*, **GE-16**, 185.

Czechowski, A., K. C., Hsieh, M. Hilchenbach, J. Kota, & A. W. Shaw (2004), Anomalous helium ions as the source of energetic helium atoms in the outer heliosphere, *Adv. Space Res.*, **34**, 104, doi: 10.1016/j.asr.2003.03.054.

Desai, M.I., G.M. et al., (2006), Heavy-Ion Elemental Abundances in Large Solar Energetic Particle Events and Their Implications for the Seed Population, *Astrophys. J.*, **649**, 470, doi: 10.1086/505649.

Desai, M. I., et al., (2015), An integrated time-of-flight versus residual energy subsystem for a compact dual ion composition experiment for space plasmas, *Rev. Sci. Instr.*, **86**, 054501, doi: 10.1063/1.4921706.

Desai, M., et al. (2016), Compact Dual Ion Composition Experiment for Space Plasmas – CoDICE, *this volume*.

Devoto, P., J.-L. Medale, J.-A. Sauvaud, J. Rouzaud, & C. Aoustin (2008), A mass spectrometer for investigations of the ion populations of the planetary environments using a new distributed grazing incidence technique, 37th COSPAR Sci. Assembly Montréal, Canada, p.707, Paper number: C32-0051-08.

Drews, C., et al., (2015), 2D He$^+$ pickup ion velocity distribution functions: STEREO PLASTIC observations, *Astron. & Astrophys.*, **575**, A97, doi:10.1051/0004-6361/201425271.

Funsten, H.F., B.L. Barraclough, & D.J. McComas (1994), Interactions of slow H, H$_2$, and H$_3$ with thin carbon foils, *Nucl. Instr. Meth. B*, **90**, 24, doi: 10.1016/0168-583X(94)95503-4.

Funsten, H.O., et al., (2009), The Interstellar Boundary Explorer High Energy (IBEX-Hi) Neutral Atom Imager, *Space Sci. Rev.*, **146**, 75, doi: 10.1007/s11214-009-9504-y.

Fuselier, S. A., et al., (2009), IBEX-Lo Sensor, *Space Sci. Rev.*, **146**, 117, doi: 10.1007/s11214-009-9495-8.

Funsten, H. F. (2016), Particle Measurements in Challenging Environments, *this volume*.

Galvin, A.B., L. et al., (2008), The Plasma and Suprathermal Ion Composition (Plastic) Investigation on the STEREO Observatories, *Space Sci. Rev.*, **136**, 437, doi: 10.1007/s11214-007-9296-x.

Galvin, A.B., K.D.C. Simunac, L.K. Jian, C.J. Farrugia, & M.A. Popecki (2013), Solar wind ion observations: comparison from the depths of solar minimum to the rising of the cycle, In: Proc. of the 13th Int. Solar Wind Conf., *AIP Conf. Proc.*, **1539**, 15, doi: 10.1063/1.4810978.

Geiss, J., F. Bühler, H. Cerutti, P. Eberhardt, & C. Filleux (1972), Solar wind composition experiment, in Apollo 16 Prelim. Sci. Rep., pp. 14.1-14.10, NASA SP-315.

Geiss, J., & H. Reeves (1972), Cosmic and Solar System Abundances of Deuterium and Helium-3, *Astron. Astrophys.*, **18**, 126.

Gilbert, J., et al. (2016), The Pickup Ion Composition Spectrometer, *this volume*.

Gloeckler, G., & K.-C. Hsieh (1979), Time-of-Flight Technique for Particle Identification of Energies from 2 to 400 keV/nucleon, *Nucl. Instr. Meth.*, **165**, 537.

Gloeckler, G., et al., (1985), The Charge-Energy-Mass Spectrometer for 0.3-300 keV/e Ions on the AMPTE CCE, *IEEE Trans. on Geosci. El.*, **GE-23**, 234.

Gloeckler, G. (1990), Ion composition measurement techniques for space plasmas, *Rev, Sci. Instr.*, **61**, 3613, doi: 10.1063/1.1141708.

Gloeckler, G., et al., (1992), The Solar Wind Ion Composition Spectrometer, *Astron. Astrophys. Suppl. Ser.*, **92**, 267.

Gloeckler, G., et al., (1995), The Solar Wind and Suprathermal Ion Composition Investigation on the WIND Spacecraft, *Space Sci. Rev.*, **71**, 79, doi: 10.1007/BF00751327.

Gloeckler, G., et al., (1998), Investigation of the composition of solar and interstellar matter using solar wind and pickup ion measurements with SWICS and SWIMS on the ACE spacecraft, *Space Sci. Rev.*, **86**, 497, doi: 10.1023/A:1005036131689.

Gloeckler, G., & J. Geiss (1998), Interstellar and Inner Source Pickup Ions Observed with SWICS on ULYSSES, *Space Sci. Rev.*, **86**, 127, doi: 10.1023/A:1005019628054.

Gloeckler, G., et al., (2004), Observations of the Helium Focusing Cone with Pickup Ions, *Astron. Astrophys.*, **426**, 845, doi: 10.1051/0004-6361:20035768.

Gonin, M., Buergi, A., Oetliker, M., & Bochsler, P. (1992), Interaction of solar wind ions with thin carbon foils: Calibration of time-of-flight spectrometers, *Proc. of the First SOHO Workshop: Coronal Streamers, Coronal Loops, and Coronal and Solar Wind Composition, ESA-SP*, pp. 381-384.

Gubler, L., P. Wurz, P. Bochsler, & E. Möbius (1995), High Resolution Isochronous Mass Spectrometer for Space Plasma Applications, *Int. J. Mass Spectr. and Ion Proc.*, **148**, 77.

Haerendel G., A. et al., (1985), The Li/Ba Release Experiments of the Ion Release Module, *IEEE Trans. on Geosci. El.*, **GE-23**, 253.

Hovestadt, D., & O. Vollmer (1971), A Satellite Experiment for Detecting Low Energy Heavy Cosmic Rays, *Proc. 12th Int. Cosmic Ray Conf.*, **4**., 1608.

Hovestadt, D., et al., (1978), The nuclear and ionic charge distribution particle experiments on the ISEE-1 and ISEE-C spacecraft, *IEEE Trans. on Geosci. El.*, **GE-16**, 166.

Hilchenbach, M., et al., (1998), Detection of 55 - 80 keV Hydrogen Atoms of Heliospheric Origin by CELIAS/HSTOF on SOHO, *Astrophys. J.*, **503**, 916, doi: 10.1086/306022.

Hovestadt, D., et al., (1995), CELIAS - Charge, Element and Isotope Analysis System for SOHO, *Sol. Phys.*, **162**, 441, doi: 10.1007/BF00733436.

Kallenbach, R., et al., (1997), Isotopic Composition of Solar Wind Neon Measured by CELIAS/MTOF onboard SOHO, *J. Geophys. Res.*, **102**, 26895, doi: 10.1029/97JA02325.

Kallenbach, R., et al., (1998), Fractionation of Si, Ne, and Mg isotopes in the solar wind as measured by SOHO/CELIAS/MTOF, *Space Sci. Rev.*, **85**, 357, doi: 10.1086/311702.

Kistler, L.M., et al., (2002), Motion of auroral ion outflow structures observed with CLUSTER and IMAGE FUV, *J. Geophys. Res.*, **107**, doi: 101029/2001JA005075.

883   Kistler, L.M., C. Mouikis, B. Klecker, & I. Dandouras (2010), The cusp as a source for oxygen
884   in the plasma sheet during geomagnetic storms, *J. Geophys. Res.*, **115**, A03209, doi:
885   10.1029/2009JA014838.

886   Klecker, E., et al., (1986), Discovery of energetic molecular ions (NO^+ and O_2^+) in the storm
887   time ring current, *Geophys. Res. Lett.*, **13**, 632, doi: 10.1029/GL013i007p00632.

888   Klumpar, D.M., et al., (2001), The Time-of-Flight Energy, Angle, Mass Spectrograph (TEAMS)
889   Experiment for FAST, *Space Sci. Rev.*, **98**, 197, doi: 10.1023/A:1013127607414.

890   Krimigis, S.M., et al., (2004), Magnetosphere Imaging Instrument (MIMI) on the Cassini Mis-
891   sion to Saturn/Titan, *Space Sci. Rev.*, **114**, 233, doi: 10.1007/s11214-004-1410-8.

892   Krimigis, S. M., D. G. Mitchell, E. C. Roelof, K. C. Hsieh, & D. J. McComas (2009), Imaging
893   the Interaction of the Heliosphere with the Interstellar Medium from Saturn with Cassini,
894   *Science*, **326**, 971, doi: 10.1126/science.1181079.

895   Kubiak, M. A., et al., (2014), Warm Breeze from the starboard bow: a new population of neutral
896   helium in the heliosphere, *Astrophys. J. Suppl.*, **213**:29, doi: 10.1051/0004-
897   6361/201321166.

898   Kucharek, H., et al., (1998), Magnesium isotopic composition as observed with the
899   CELIAS/MTOF experiment on the SOHO spacecraft, *J. Geophys. Res.*, **103**, 26805, doi:
900   10.1029/98JA02542.

901   Kucharek, H., et al., (2015), Impact of Planetary Gravitation on High Precision Neutral Atom
902   Measurements, *Astrophys. J. Suppl.*, **220**:35, doi:10.1088/0067-0049/220/2/35.

903   Lepri, S.T., et al., (2001), Iron Charge Distributions as an Identifier of Interplanetary Coronal
904   Mass Ejections, *J. Geophys. Res.,* **106**, 29231, doi: 10.1029/2001JA000014.

905   Liu, Y. H., et al., (2015), The heavy ion diffusion region in magnetic reconnection in the Earth's
906   magnetotail, *J.Geophys. Res.*, **120**, 3535, doi: 10.1002/2015JA020982.

907   Livi, S., E. Möbius, D. Haggerty, M. Witte, & P. Wurz, (2003), An Interstellar Neutral Atom De-
908   tector, *AIP Conf. Proc.*, **679**, 850, doi: 10.1063/1.1618724.

909   Livi, S. (2016), STROFIO: A Novel Neutral Mass Spectrograph for Sampling Mercury's Exo-
910   sphere Rams: A Miniature Ram Angle and Magnetic Field Sensor, *this volume.*

911   Lund, E J, et al., (1998), FAST observations of preferentially accelerated He^+ in association with
912   auroral electromagnetic ion cyclotron waves, *Geophys. Res. Lett.*, **25**, 2049, doi:
913   10.1029/98GL00304.

914   Managadze, G.G. (1986), Time-of-flight Ion Mass Analyzer, *U.S. Patent* Number 4, 611, 118.

915   Marti, K., & P. Bochsler (2012), Solar Wind and Solar System Matter After Mission Genesis, In:
916   Exploring the solar wind, Ch. 4, DOI: 10.5772/36974, M. Lazar, ed., InTech, ISBN: 978-
917   953-51-0399-4.

918   Mason, G. M., et al., (1990), SAMPEX Mission Overview, *AIP Conf. Proc.*, **203**, 44, doi:
919   10.1063/1.39140.

920   Mason, G. M., et al., (1993), LEICA: A Low Energy Ion Composition Analyzer for the Study of
921   Solar and Magnetospheric Heavy Ions, *IEEE Trans. on Geosci. Rem. Sens.*, **31**, 549.

Mason, G. M., et al., (1998), The Ultra-Low-Energy Isotope Spectrometer (ULEIS) for the ACE spacecraft, *Space Sci. Rev.*, **86**, 409, doi: 10.1023/A:1005079930780.

Mason, G. M., Desai, M. I., Mazur, J. E., & Dwyer, J. R. (2005), Energetic Particles Accelerated by Shocks in the Heliosphere: What is the Source Material? In: The Physics of Collisionless Shocks: *AIP Conf. Proc.*, **781**, 219, doi: 10.1063/1.2032700.

Mason, G. M., et al., (2008), The Suprathermal Ion Telescope (SIT) For the IMPACT/SEP Investigation, *Space Sci. Rev.*, **136**, 257, doi: 10.1007/s11214-006-9087-9.

McComas, D.J., J.E. Nordholt, J.-J. Berthelier, J.-M. Illiano, & D.T. Young (1998), The Cassini Ion Mass Spectrometer, In: Measurement Techniques in Space Plasmas, R. Pfaff, J. Borowski, D. Young eds., *Geophys. Monogr.* **102**, 187.

McComas, D.J., et al., (2004), Ultrathin (≈10 nm) carbon foils in space instrumentation, *Rev. Sci. Instr.*, **75**, 4863, doi: 10.1063/1.1809265.

McComas, D.J., et al., (2009a), IBEX - Interstellar Boundary Explorer, *Space Sci. Rev.*, **146**, 11, doi: 10.1007/s11214-009-9499-4.

McComas, D. J., et al., (2009b), Global Observations of the Interstellar Interaction from the Interstellar Boundary Explorer (IBEX), *Science*, **326**, 959, doi: 10.1126/science.1180906.

McEntire, R. W., E. P. Keath, D. E. Fort, A. T. Y. Lui, & S. M. Krimigis (1985), The Medium-energy particle analyzer (MEPA) on the AMPTE CCE spacecraft, *IEEE Trans. on Geosci. El.*, **GE-23**, 230.

McFadden, J.M. (2016), Technology Challenges for Space Plasma Measurements, *this volume*.

Mitchell, D. G., et al., (1996), Imaging-neutral camera (INCA) for the NASA Cassini mission to Saturn and Titan, *Proc. SPIE*, **2803**, 154.

Mitchell, D. G., et al., (2000), The High-Energy Neutral Atom (HENA) Imager for the IMAGE mission, *Space Sci. Rev.*, **91**, 67, doi: 10.1023/A:1005207308094.

Mitchell, D.G., et al., (2001), Imaging Two Geomagnetic Storms in Energetic Neutral Atoms. *Geophys Res. Lett.*, **28**, 1151, doi: 10.1029/2000GL012395.

Möbius, E., et al., (1985a), The time-of-flight spectrometer SULEICA for ions of the energy range 5-270 keV/charge on the AMPTE/IRM, *IEEE Trans. on Geosci. El.*, **GE-23**, 274.

Möbius, E., et al., (1985b), Direct observation of He$^+$ pick-up ions of interstellar origin in the solar wind, *Nature*, **318**, 426, doi: 10.1038/318426a0.

Möbius, E., et al., (1986), Observation of lithium pick-up ions in the 5 to 20 keV energy range following the AMPTE solar wind releases, *J. Geophys. Res.*, **91**, 1325, doi: 10.1029/JA091iA02p01325.

Möbius, E., P. Bochsler, A.G. Ghielmetti, & D.C. Hamilton (1990), High mass resolution isochronous Time-of-flight spectrograph for three-dimensional space plasma measurements, *Rev. Sci. Instr.*, **61**, 3609, doi: 10.1063/1.1141580.

Möbius, E., et al., (1998a), The 3-D Plasma Distribution Function Analyzers With Time-of-Flight Mass Discrimination for CLUSTER, FAST and Equator-S, In: Measurement Techniques in Space Plasmas, R. Pfaff, J. Borowski, D. Young eds., *Geophys. Monogr.* **102**, 243.

Möbius, E, et al., (1998b), Species dependent energies in upward directed ion beams over auroral arcs as observed with FAST TEAMS, *Geophys. Res. Lett.*, **25**, 2029, doi: 10.1029/98GL00381.

Möbius, E., et al., (2008), Time-of-Flight Detector System of the IBEX-Lo Sensor with Low Background Performance for Heliospheric ENA Detection, *Proc. of the 30th Int. Cosmic Ray Conf.*, **Vol. 1**, 841-844, Universidad Nacional Autónoma de México, Mexico.

Möbius, E., et al., (2009), Direct Observations of Interstellar H, He, and O by the Interstellar Boundary Explorer, *Science*, **326**, 969, doi: 10.1126/science.1180971.

Moore, T. E., et al., (2000), The Low-Energy Neutral Atom (LENA) Imager Investigation, *Space Sci. Rev.*, **91**, 155, doi: 10.1023/A:1005211509003.

Mouikis, C. G., et al., (2002), Equator-S observations of He$^+$ energization by EMIC waves in the dawnside equatorial magnetosphere, *Geophys. Res. Lett.*, **29**, 74, doi: 10.1029/2001GL013899.

Müller, H.-R., & G. P. Zank (2004), Heliospheric filtration of interstellar heavy atoms: Sensitivity to hydrogen background, *J. Geophys. Res.*, **109**, A07104, doi: 10.1029/2003JA010269.

Ogasawara, K., et al., (2015), Single crystal chemical vapor deposit diamond detector for energetic plasma measurement in space, *Nucl. Instr. Meth. A*, **777**, 131, doi:10.1016/j.nima.2014.12.098.

Orsini, S., et al., (2010), SERENA: A suite of four instruments (ELENA, STROFIO, PICAM and MIPA) on board BepiColombo-MPO for particle detection in the Hermean environment, *Planet. Space Sci.*, **58**, 166, doi:10.1016/j.pss.2008.09.012.

Park, J., et al., (2014), The Ne to O abundance ratio of the interstellar medium from the IBEX-Lo observations, *Astrophys. J.*, **795**:97, .

Park, J., et al., (2015), Statistical analysis of the heavy neutral atoms measured by IBEX, *Astrophys. J. Suppl.*, **220**:34, doi: 10.1088/0004-637X/795/1/97.

Paschalidis, N. (2016), Advanced gated time of flight mass spectrometers for Small Satellites and Cubesats, *this volume*.

Paschmann, G., et al., (1985), The Plasma Instrument for the AMPTE IRM, *IEEE Trans. on Geosci. El.*, **GE-23**, 262.

Pollock, C. J., et al., (2000), Medium Energy Neutral Atom (MENA) Imager for the IMAGE Mission, *Space Sci. Rev.*, **91**, 113, doi: 10.1023/A:1005259324933.

Rème, H., et al., (1997), The CLUSTER Ion Spectrometry Experiment, *Space Sci. Rev.*, **79**, 303, doi: 10.1023/A:1004929816409.

Schwadron, N.A., et al., (2013), Solar Radiation Pressure and Local Interstellar Medium Flow Parameters from Interstellar Boundary Explorer Low Energy Hydrogen Measurements, *Astrophys. J.*, **775**, 86, doi: 10.1088/0004-637X/775/2/86.

Shelley, E. G., et al., (1978), *IEEE Trans. on Geosci. El.*, **GE-16**, 266.

Skoug, R., et al., (2016), Wide Field-of-View Plasma Spectrometer, *this volume*.

von Steiger, R., et al., (2000), Composition of quasi-stationary solar wind flows from Ulysses/Solar Wind Ion Composition Spectrometer, *J. Geophys. Res.* **105**, 27217, doi: 10.1029/1999JA000358.

Wang, S., L. M. Kistler, C. G. Mouikis, & S. M. Petrinec (2015), Dependence of the dayside magnetopause reconnection rate on local conditions, *J. Geophys. Res.*, **120**, 6386, doi: 10.1002/2015JA021524.

Wimmer-Schweingruber, R.F., et al., (1999), On the bulk isotopic composition of magnesium and silicon during the May 1998 CME: ACE/SWIMS, *Geophys. Res. Lett.*, **26**, 165, doi: 10.1029/1999GL010676.

Wimmer-Schweingruber, R.F. (2002), The Composition of the Solar Wind, *Adv. Space Res.*, **30**, 23, doi: 10.1016/S0273-1177(02)00262-4.

Winslow, R.M., et al., (2016), A perfect conjunction between Messenger and STEREO A: Development of ICME Complexity through Stream Interactions, *J. Geophys. Res.*, subm.

Witte, M., Banaszkiewicz, M., & Rosenbauer, H., (1996), Recent results on the parameters of the interstellar helium from the ULYSSES/GAS experiment, *Space Sci. Rev.*, **78**, 289, doi: 10.1007/BF00170815.

Wüest, M. (1998), Time-of-Flight Ion Composition Measurement Technique for Space Plasmas, in: *Measurement Techniques in Space Plasmas – Particles*, R. F. Pfaff, J. E. Borovsky and D. T. Young eds., *Geophys. Monograph* 102, p. 141.

Wurz, P., et al., (2009), IBEX Backgrounds and Signal to Noise Ratio, *Space Sci. Rev.*, **146**, 173, doi:10.1007/s11214-009-9515-8.

Ziegler, J.F., J.P. Biersack, & M.D. Ziegler (2015), SCRIM – The Stopping and Range of Ions in Matter, 15[th] edition, Lulu Press Company.

Zurbuchen, T., et al. (2016), Innovations in Plasma Analyzers, *this volume*.