

```
(Run: "touch ~/.hushlogin" to hide this message)
(Anusha@AnnemAnusha) - [/mnt/c/WINDOWS/system32]
$ hydra
Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service
organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Syntax: hydra [[[ -l LOGIN | -L FILE ] [-p PASS | -P FILE]] | [-C FILE]] [-e nsr] [-o FILE] [-t TASKS] [-M FILE]
[-T TASKS]] [-w TIME] [-W TIME] [-f] [-s PORT] [-x MIN:MAX:CHARSET] [-c TIME] [-ISOuvVd46] [-m MODULE_
OPT] [service://server[:PORT][/OPT]]

Options:
-l LOGIN or -L FILE login with LOGIN name, or load several logins from FILE
-p PASS or -P FILE try password PASS, or load several passwords from FILE
-C FILE colon separated "login:pass" format, instead of -L/-P options
-M FILE list of servers to attack, one entry per line, ':' to specify port
-D XoFY Divide wordlist into Y segments and use the Xth segment.
-t TASKS run TASKS number of connects in parallel per target (default: 16)
-U service module usage details
-m OPT options specific for a module, see -U output for information
-h more command line options (COMPLETE HELP)
server the target: DNS, IP or 192.168.0.0/24 (this OR the -M option)
service the service to crack (see below for supported protocols)
OPT some service modules support additional input (-U for module help)

Supported services: adam6500 asterisk cisco cisco-enable cobaltstrike cvs firebird ftp[s] http[s]-{head|
get|post} http[s]-{get|post}-form http-proxy http-proxy-urlenum icq imap[s] irc ldap2[s] ldap3[-{cram|di
gest}md5][s] memcached mongodb mssql mysql nntp oracle-listener oracle-sid pcanynwhere pcnfs pop3[s] post
gres radmin2 rdp redis rexec rlogin rpcap rsh rtsp s7-300 sip smb smb2 smtp[s] smtp-enum snmp socks5 ssh
sshkey svn teamspeak telnet[s] vmauthd vnc xmpp

Hydra is a tool to guess/crack valid login/password pairs.
Licensed under AGPL v3.0. The newest version is always available at;
https://github.com/vanhauser-thc/thc-hydra
Please don't use in military or secret service organizations, or for illegal
purposes. (This is a wish and non-binding - most such people do not care about
laws and ethics anyway - and tell themselves they are one of the good ones.)

Example: hydra -l user -P passlist.txt ftp://192.168.0.1

(Anusha@AnnemAnusha) - [/mnt/c/WINDOWS/system32]
$ hydra -U ssh
Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service
organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-10-08 14:43:05

Help for module ssh:
=====
The Module ssh does not need or support optional parameters
```

```
(Anusha@AnnemAnusha)-[/mnt/c/WINDOWS/system32]
$ hydra -h
Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service
organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Syntax: hydra [[[-l LOGIN|-L FILE] [-p PASS|-P FILE]] | [-C FILE]] [-e nsr] [-o FILE] [-t TASKS] [-M FILE]
[-T TASKS]] [-w TIME] [-W TIME] [-f] [-s PORT] [-x MIN:MAX:CHARSET] [-c TIME] [-ISOuvVd46] [-m MODULE_
OPT] [service://server[:PORT][OPT]]

Options:
-R          restore a previous aborted/crashed session
-I          ignore an existing restore file (don't wait 10 seconds)
-S          perform an SSL connect
-s PORT    if the service is on a different default port, define it here
-l LOGIN or -L FILE login with LOGIN name, or load several logins from FILE
-p PASS or -P FILE try password PASS, or load several passwords from FILE
-x MIN:MAX:CHARSET password bruteforce generation, type "-x -h" to get help
-y          disable use of symbols in bruteforce, see above
-r          use a non-random shuffling method for option -x
-e nsr     try "n" null password, "s" login as pass and/or "r" reversed login
-u          loop around users, not passwords (effective! implied with -x)
-C FILE    colon separated "login:pass" format, instead of -L/-P options
-M FILE    list of servers to attack, one entry per line, ':' to specify port
-D XofY    Divide wordlist into Y segments and use the Xth segment.
-o FILE    write found login/password pairs to FILE instead of stdout
-b FORMAT  specify the format for the -o FILE: text(default), json, jsonv1
-f / -F    exit when a login/pass pair is found (-M: -f per host, -F global)
-t TASKS   run TASKS number of connects in parallel per target (default: 16)
-T TASKS   run TASKS connects in parallel overall (for -M, default: 64)
-w / -W TIME wait time for a response (32) / between connects per thread (0)
-c TIME    wait time per login attempt over all threads (enforces -t 1)
-4 / -6    use IPv4 (default) / IPv6 addresses (put always in [] also in -M)
-v / -V / -d verbose mode / show login+pass for each attempt / debug mode
-O          use old SSL v2 and v3
-K          do not redo failed attempts (good for -M mass scanning)
-q          do not print messages about connection errors
-U          service module usage details
-m OPT     options specific for a module, see -U output for information
-h          more command line options (COMPLETE HELP)
server     the target: DNS, IP or 192.168.0.0/24 (this OR the -M option)
service    the service to crack (see below for supported protocols)
OPT        some service modules support additional input (-U for module help)
```

Supported services: adam6500 asterisk cisco cisco-enable cobaltstrike cvs firebird ftp[s] http[s]-{head|get|post} http[s]-{get|post}-form http-proxy http-proxy-urlenum icq imap[s] irc ldap2[s] ldap3[-{cram|digest|md5}[s] memcached mongodb mssql mysql nntp oracle-listener oracle-sid pcanywhere pcnfs pop3[s] postgres radmin2 rdp redis rexec rlogin rpcap rsh rtsp s7-300 sip smb smb2 smtp[s] smtp-enum snmp socks5 ssh sshkey svn teamspeak telnet[s] vmauthd vnc xmpp

Hydra is a tool to guess/crack valid login/password pairs.

Licensed under AGPL v3.0. The newest version is always available at;

<https://github.com/vanhauser-thc/thc-hydra>

Please don't use in military or secret service organizations, or for illegal purposes. (This is a wish and non-binding - most such people do not care about laws and ethics anyway - and tell themselves they are one of the good ones.)

These services were not compiled in: afp ncp oracle sapr3.

Use HYDRA_PROXY_HTTP or HYDRA_PROXY environment variables for a proxy setup.

E.g. % export HYDRA_PROXY=socks5://l:p@127.0.0.1:9150 (or: socks4:// connect://)

% export HYDRA_PROXY=connect_and_socks_proxylist.txt (up to 64 entries)

% export HYDRA_PROXY_HTTP=http://login:pass@proxy:8080

% export HYDRA_PROXY_HTTP=proxylist.txt (up to 64 entries)

Examples:

```
hydra -l user -P passlist.txt ftp://192.168.0.1
```

```
hydra -L userlist.txt -p defaultpw imap://192.168.0.1/PLAIN
```

```
hydra -C defaults.txt -6 pop3s://[2001:db8::1]:143/TLS/DIGEST-MD5
```

```
hydra -l admin -p password ftp://[192.168.0.0/24]/
```

```
hydra -L logins.txt -P pws.txt -M targets.txt ssh
```

(Anusha@AnnemAnusha) - [/mnt/c/WINDOWS/system32]

\$