| WIZ750Jr V1.0 Partlist | | | | | |
|------------------------|------|---------------------------------|------------------------|--|----------------|
| Item | Q.ty | Reference | Part | Tech. Characteristics | Package |
| 1 | 8 | C10,C12,C13,C14,C16,C18,C20,C21 | 0.1uF | 50V-5% Ceramic | CASE 0402 |
| 2 | 2 | C2,C6 | 1uF | 50V-5% Ceramic | CASE 0402 |
| 3 | 5 | C1,C5,C9,C11,C15 | 10uF/16V | Tantal CAP, A Size, 10uF/16V, +/-20% | EIA/IECQ 3216 |
| 4 | 2 | C3,C4 | 30pF | 25V-5% Ceramic | CASE 0402 |
| 5 | 2 | C7,C8 | 27pF | 25V-5% Ceramic | CASE 0402 |
| 6 | 2 | J1,J3 | 2.00mm Pin haeder 1x1 | 2.00mm Pin haeder 1x12, Male | DIP |
| 7 | 2 | L1,L2 | HH-1M1608-121JT | Bead for Power Line, 120[ohm] | CASE 0603 |
| 8 | 1 | LD1 | Red LED | CHIP-LED, Red | CASE 0603 |
| 9 | 1 | LD2 | Blue LED | CHIP-LED, Red | CASE 0603 |
| 10 | 4 | LD3,LD4,LD5,LD6 | Green LED | CHIP-LED, Red | CASE 0603 |
| 11 | 4 | R19,R20,R21,R22 | 3.3R | 1/10W-5% SMD | CASE 0402 |
| 12 | 5 | R3,R6,R23,R24,R25 | 330R | 1/10W-5% SMD | CASE 0402 |
| 13 | 3 | R4,R26,R27 | 1K | 1/10W-5% SMD | CASE 0402 |
| 14 | 4 | R2,R5,R17,R29 | 4.7K | 1/10W-5% SMD | CASE 0402 |
| 15 | 5 | R7,R8,R9,R11,R12 | 5.1K | 1/10W-5% SMD | CASE 0402 |
| 16 | 1 | R10 | 6.19K 1% | 1/10W-1% SMD | CASE 0402 |
| 17 | 1 | R1 | 1 M | 1/10W-5% SMD | CASE 0402 |
| 18 | 1 | U1 | W7500 | WIZnet ARM Cortex-M0 | TQFP64 |
| 19 | 1 | U2 | IP101GRI | Single Port 10/100 MII/RMII/TP/Fiber Fast Ethernet Transceiver | QFN32(0.4/4X4) |
| 20 | 1 | U4 | SN74LVC1G04DBVR | IC, INVERTER, SINGLE, SMD | SOT-23-5 |
| 21 | 1 | U6 | SN74LVC125ARGYR | Quadruple Bus Buffer Gate With 3-State Outputs | S-PVQFN-N14 |
| 22 | 2 | Q1,Q2 | Q-MMBT4403 | PNP General-Purpose Amplifier | SOT23 |
| 23 | 1 | Y1 | 12MHz (TZ1067B-12MH | X-tal 12MHz,3.2x2.5 SMD, CL=30pF | SMD3225, 4-PAD |
| 24 | 1 | Y2 | 82J0626-25.000MHz | X-tal 25MHz,3.2x2.5 SMD, CL=27pF,Industrial,ITTI | SMD3225, 4-PAD |
| 25 | 2 | C17,C19 | 0.1uF | Not Mount | CASE 0402 |
| 26 | 1 | J2 | 2.00mm Pin haeder 1x12 | Not Mount | DIP |
| 27 | 1 | J4 | 1.27mm Pin haeder 1x5 | Not Mount | DIP |
| 28 | 1 | J5 | 2.54mm Pin haeder 1x6 | Not Mount | DIP |
| 29 | 4 | R13,R14,R15,R16,R28 | 4.7K | Not Mount | CASE 0402 |
| 30 | 1 | R18 | 0R | Not Mount | CASE 0402 |
| 31 | 1 | U3 | AT45DB161E-SHF-T | Not Mount | SO-08-EIAJ |
| 32 | 1 | U5 | 24AA16T-I/OT | Not Mount | SOT-23-5 |
| 33 | 1 | | PCB | 4-Layer 50mm x 30mm | |

