| WIZ750SR-105 V1.0 Partlist | | | | | |
|----------------------------|------|---|--------------------------|--|-----------------|
| Item | Q.ty | Reference | Part | Tech. Characteristics | Package |
| 1 | 10 | C10,C12,C13,C14,C16,C17,C19,C22,C23,C25 | 0.1uF | 50V-5% Ceramic | CASE 0603 |
| 2 | 2 | C2,C6 | 1uF | 50V-5% Ceramic | CASE 0603 |
| 3 | 5 | C1,C5,C9,C11,C15 | 10uF/16V | Ceramic CAP, 3216 size 10uF/16V, +/-20% | CASE 3216 |
| 4 | 2 | C3,C4 | 30pF | 25V-5% Ceramic | CASE 0603 |
| 5 | 2 | C7,C8 | 27pF | 25V-5% Ceramic | CASE 0603 |
| 6 | 1 | C18 | 1nF/2kV | 1nF/2kV Ceramic | CASE 1808(4520) |
| 7 | 1 | J4 | 2.00mm Pin Header 2x6 SM | 2.00mm Pin Header 2x6 Male SMD Type | SMD |
| 9 | 2 | L1,L2 | HH-1M1608-121JT | Bead for Power Line, 120[ohm] | CASE 0603 |
| 10 | 1 | LD5 | Red LED | CHIP-LED, Red | CASE 0603 |
| 11 | 1 | LD3 | Blue LED | CHIP-LED, Red | CASE 0603 |
| 12 | 5 | LD1,LD2,LD4,LD6,LD7 | Green LED | CHIP-LED, Red | CASE 0603 |
| 13 | 1 | P1 | BS-RB10005 | Transformer + RJ45 + LED, Industrial, UDE | DIP |
| 14 | 2 | Q1,Q2 | Q-MMBT4403 | PNP Transistor General-Purpose Amplifier | SOT-23-3L |
| 15 | 4 | R17,R18,R19,R20 | 3.3R | 1/10W-5% SMD | CASE 0603 |
| 16 | 8 | R3,R5,R7,R8,R10,R12,R22,R24 | 330R | 1/10W-5% SMD | CASE 0603 |
| 17 | 3 | R1,R4,R6 | 1K | 1/10W-5% SMD | CASE 0603 |
| 18 | 5 | R9,R13,R27,R28,R31 | 4.7K | 1/10W-5% SMD | CASE 0603 |
| 19 | 5 | R14,R15,R16,R23,R25 | 5.1K | 1/10W-5% SMD | CASE 0603 |
| 20 | 1 | R21 | 6.19K 1% | 1/10W-1% SMD | CASE 0603 |
| 21 | 1 | R2 | 1 M | 1/10W-5% SMD | CASE 0603 |
| 22 | 1 | U1 | W7500 | WIZnet ARM Cortex-M0 | TQFP64 |
| 23 | 1 | U2 | IP101GRI | Single Port 10/100 MII/RMII/TP/Fiber Fast Ethernet Transceiver | QFN32(0.4/4X4) |
| 24 | 1 | U3 | SN74LVC125ARGYR | Quadruple Bus Buffer Gate With 3-State Outputs | S-PVQFN-N14 |
| 25 | 1 | U5 | MIC811SUY | Microprocessor Reset Circuits | SOT-143 |
| 26 | 1 | U7 | TPD4S009DBVR | 4-Channel ESD Protection IC | SOT-23(DBV) |
| 27 | 1 | Y1 | 12MHz (TZ1067B-12MHz) | X-tal 12MHz,3.2x2.5 SMD, CL=30pF | SMD3225, 4-PAD |
| 28 | 1 | Y2 | 82J0626-25.000MHz | X-tal 25MHz,3.2x2.5 SMD, CL=27pF,Industrial,ITTI | SMD3225, 4-PAD |
| 29 | 2 | C20,C21 | 0.1uF | Not Mount | CASE 0603 |
| 30 | 2 | J1,J2 | 2.54mm Pin Header 1x6 | Not Mount | DIP |
| 31 | 1 | J3 | 1.27mm Pin haeder 1x5 | Not Mount | DIP |
| 32 | 2 | J5,J6 | 2.54mm Pin haeder 1x2 | Not Mount | DIP |
| 33 | 4 | R11,R26,R29,R30 | 4.7K | Not Mount | CASE 0603 |
| 34 | 1 | U4 | AT45DB161E-SHF-T | Not Mount | SO-08-EIAJ |
| 35 | 1 | U6 | 24AA16T-I/OT | Not Mount | SOT-23-5 |
| 36 | 1 | | РСВ | 4-Layer 50mm x 30mm | |

