WizArduino MEGA WIFI Ver1.0 Partlist

Item	Q.ty	Reference	Part	Tech. Characteristics	Package
1	1	ON	Red LED	Chip-LED, Red	CASE 0805
2	3	L, TX, RX	Green LED	Chip-LED, Green	CASE 0805
3	2	WIFI, MODE	Yellow LED	Chip-LED, Yellow	CASE 0805
4	2	C21, C22	22uF/16V	Tanltal CAP, B Size, 22uF/16V, +/-20%	EIA/IECQ 3528
5	10	C1, C2, C7, C9, C10, C11, C15, C18, C20, C23	0.1uF/50V	50V-10% Ceramic	CASE 0603
6	2	C14, C19	10nF/50V	50V-10% Ceramic	CASE 0603
7	4	C5, C6, C16, C17	22pF/50V	50V-10% Ceramic	CASE 0603
8	1	C13	1uF/16V	16V-10% Ceramic	CASE 0603
9	4	C3, C4, C8, C12	10uF/16V	Tantal CAP, A Size, 10uF/16V, +/-20%	EIA/IECQ 3216
10	1	D1	M7	1.0A 1000V Rectifier Diode	SMA
11	2	D2, D3	CD1206-S0157	Switching Diode	CASE 1206
12		F1	FSMD050R	500mA Fuse	CASE 4532
13		IC4, IC6	SN74LVC1G125DCKR	Single Bus Buffer Gate With 3-State Output	SC70-5
14		IC3	ATMEGA2560-16AU	Microcontroller	TOFP100
15		IC5	ATMEGA16U2-AU	Microcontroller	TQFP32
16		IC1	LM1117S-5.0V(IL1117C-5.0)	5.0V/1A Voltage Regulator	SOT-223
17		IC2	LM1117S-3.3V(IL1117C-3.3)	3.3V/1A Voltage Regulator	SOT-223
18		JK1	POWER-SUPPLY	DC-JACK 2PHI	POWERSUPPLY DC-21MM
19		JP2, JP3	ICSP	2.54mm 2x3 Pin Header DIP, Male	DIP
20		JP1	MCU-WIFI Jumper Pin	2.54mm 2x2 Pin Header DIP, Male	DIP
21	1	JP4	ATMEGA16U2 External Pin	2.54mm 2x2 Pin Header DIP, Male	Not Mount
22	3	L1, L2, L3	HCB2012KF-300T30	Chip Ferrite Bead	CASE 0805
23		PB1	YST1157(3.1)	Tact Switch, 6.2 x 6.5 SMD	TS42
24		Q1, Q2	16MHz	X-tal 16MHz, 3.2 x 2.5 SMD, CL=22pF	SMD3225, 4-PAD
25		R3, R5, R6	10K	1/10W-5% SMD	CASE 0603
26	1	R2	330R	1/10W-5% SMD	CASE 0603
27		R1, R4	1M	1/10W-5% SMD	CASE 0603
28		R7, R8, R10	100k	1/10W-5% SMD	CASE 0603
29	1	R9	52k3	1/10W-5% SMD	Not Mount
30		RN2	10k		SMD3216
		RN3, RN4	1k	1/10W-5% CHIP-ARRAY SMD 1/10W-5% CHIP-ARRAY SMD	SMD3216 SMD3217
31 32			470R	1/10W-5% CHIP-ARRAY SMD	
		RN1 TR2	-		SMD3216
33		TR1	PMV48XP	20 V, 3.5 A P-channel Trench MOSFET	SOT-23
34			2N7002	N channel FET - Field Effect Trasistor	SOT-23
35		TVS1	SMBJ12CA	Transient Voltage Suppressor	SMB
36		USB1	47346-0001	MICRO USB CONNECTOR	USB-MICRO-B(SMD)
37		Z1, Z2	AVL5M 03 300	Chip varistor(ESD Protector), Vdc : 5.5V, Peak current : 30A	Not Mount
38		J1, J3	2.54mm 1x8 Pin Header Socket DIP	2.54mm 1x8 Pin Header Socket DIP, Female	DIP
39		J2	2.54mm 1x6 Pin Header Socket DIP	2.54mm 1x6 Pin Header Socket DIP, Female	DIP
40		J4	2.54mm 1x10 Pin Header Socket DIP	2.54mm 1x10 Pin Header Socket DIP, Female	DIP
41		MODULE1	WIZFI310CON	WIZFI310CON	
42	2		JUMPER CAP	2.54mm Mini Header Jumper Cap Short Circuit Connectors	
43	1		ANTENA(W5I-BO-07)	I-PEX MHF	
44	1		PCB	2-Layer, 68.58mm x 53.848mm, PCB Color : sky blue, Silk Color : White	