Lab 3.5: Adding a Rebar

In this lab, you will implement a rebar.

To see a demonstration of the lab solution, click this icon.
(CD-ROM plays the demonstration, "Lab 3.5 Demonstration.")

Estimated time to complete this lab: **15 minutes**

To complete the exercises in this lab, you must have the required software. For detailed information about the labs and setup for the labs, see Labs in this course.

The code that forms the starting point for this lab is located in the folder \Labs\Ch03\Lab3.5\Ex01.

The solution code for this lab is located in the folder \Labs\Ch03\Lab3.5\Ex01\Solution.

Objectives

After completing this lab, you will be able to:

- Create a **CReBar** object.
- Add a dialog bar and a toolbar to rebar.

Prerequisites

Before working on this lab, you should be familiar with the following:

- Toolbars
- Dialog bars

Exercises

The following exercise provides practice working with the concepts and techniques covered in this chapter:

Exercise 1: Implementing a Rebar

In this exercise, you will create a rebar and add a toolbar and a dialog bar to it.

79 Exercise 1: Implementing a Rebar

The code that forms the starting point for this lab is in \Labs\Ch03\Lab3.5\Ex01.

In this exercise, you will create a rebar and add a toolbar and a dialog bar to it.

▶ **Implement a rebar**

☐ 1. Open the file MainFrm.h.

☐ 2. Add a protected **CReBar** member to the class definition:

```
CReBar m_wndReBar;
```

☐ 3. Open MainFrm.cpp and scroll to the **OnCreate** function.

☐ 4. Create a **CReBar** object and add controls to it by using the **AddBar** function as follows:

```
if (!m_wndReBar.Create(this) ||
        !m_wndReBar.AddBar(&m_wndToolBar) ||
        !m_wndReBar.AddBar(&m_wndDialogBar))
    {
        TRACE0("Failed to create rebar\n");
        return -1;      // fail to create
    }
```

To see an example of how your code should look, click this icon.

(CD-ROM displays the following sample code.)

```
int CMainFrame::OnCreate(LPCREATESTRUCT lpCreateStruct)
{
    if (CFrameWnd::OnCreate(lpCreateStruct) == -1)
        return -1;

    if (!m_wndToolBar.Create(this) ||
        !m_wndToolBar.LoadToolBar(IDR_MAINFRAME))
    {
        TRACE0("Failed to create toolbar\n");
        return -1;      // fail to create
    }

    if (!m_wndStatusBar.Create(this) ||
        !m_wndStatusBar.SetIndicators(indicators,
          sizeof(indicators)/sizeof(UINT)))
    {
        TRACE0("Failed to create status bar\n");
        return -1;      // fail to create
    }

    m_wndToolBar.SetBarStyle(m_wndToolBar.GetBarStyle() |
        CBRS_TOOLTIPS | CBRS_FLYBY);
```

(Code continues on following page.)

Notes

```
    m_wndDialogBar.Create( this,    //Parent window is the main frame
                   IDD_DIALOGBAR,  //The graphic resource
                   CBRS_TOP,       //Align to the top of the frame
                   ID_VIEW_DIALOGBAR); //Control's ID

    m_wndDialogBar.SetBarStyle(m_wndDialogBar.GetBarStyle() |
        CBRS_TOOLTIPS | CBRS_FLYBY);
    if (!m_wndReBar.Create(this) ||
        !m_wndReBar.AddBar(&m_wndToolBar) ||
        !m_wndReBar.AddBar(&m_wndDialogBar))
    {
        TRACE0("Failed to create rebar\n");
        return -1;      // fail to create
    }
    return 0;
}
```

☐ 5. Build and run the application.

For more information about creating rebars, see Creating a Rebar in this chapter.

The solution code for this exercise is located in the folder \Labs\Ch03\Lab3.5\Ex01\Solution.

Notes