Lab 9.3: Adding an HTML View

In this lab, you will create an application with an HTML view.

To see a demonstration of the solution for this lab, click this icon.
(CD-ROM plays the demonstration, "Lab 9.3 Demonstration.")

Estimated time to complete this lab: **15 minutes**

To complete the exercise in this lab, you must have the required software. For detailed information about the labs and setup for the labs, see Labs in this course.

The solution code for this lab is located in the folder \Labs\Ch09\Lab9.3\Ex01\Solution.

Objectives

After completing this lab, you will be able to:

- Use an HTML view in an application.

Prerequisites

There are no prerequisites for this lab.

Exercises

The following exercise provides practice working with the concepts and techniques covered in this chapter.

Exercise 1: Adding an HTML View

In this exercise, you will use the HTML view to add the functionality of the **Web Browser** control. You will add handlers to browse forward and backward through the previously browsed sites on the World Wide Web.

302 Exercise 1: Adding an HTML View

In this exercise, you will use the HTML view to add the functionality of the **Web Browser** control. You will add handlers to browse forward and backward through the previously browsed sites on the World Wide Web.

▶ Create an SDI-based application by using MFC AppWizard

- Name the new project workspace **Web**.
- In Step 6, derive **CWebView** from **CHtmlView**, rather than **CView**.
- Finish and create the new project.

▶ Add toolbar items

☐ 1. Open the IDR_MAINFRAME toolbar resource.

☐ 2. Add two toolbar items, giving them the IDs ID_GOBACK and ID_GOFORWARD, respectively.

Your toolbar should look like the toolbar in the following illustration.

☐ 3. Save the Web.rc file.

▶ Add command handlers for the toolbar items

☐ 1. Invoke ClassWizard.

☐ 2. Add a handler for the ID_GOBACK message to **CWebView**, and accept the default **OnGoback** function name. Similarly, add a handler for the ID_GOFORWARD message.

▶ Implement the command handlers for ID_GOBACK and ID_GOFORWARD toolbar items

☐ 1. In the **OnGoback** function of the WebView.cpp file, invoke the following function to allow navigation to the previous item in the history list:

```
CHtmlView::GoBack();
```

☐ 2. In the **OnGoforward** function of WebView.cpp, invoke the following function to allow navigation to the next item in the history list:

```
CHtmlView::GoForward();
```

☐ 3. Save WebView.cpp.

▶ Implement navigation

☐ 1. Open WebView.cpp.

☐ 2. In the call to **Navigate2** function of **OnInitialUpdate**, replace the string "www.microsoft.com" with the Web site name created by Personal Web Server.

▶ Build and run your application

- Run your application and navigate the Web using the toolbar buttons you created.

The solution code for this exercise is located in the folder \Labs\Ch09\Lab9.3\Ex01\Solution.

Notes