CREATE DATABASE EMPLOYEE

```
create database employee;

use employee;
```

#1 CREATE table ---department location and employees with the provided schema

```
create table departments (
department _ id INT PRIMARY KEY,
department _name VARCHAR (100)
);


CREATE TABLE location (
Location _id INT PRIMARY KEY ,
location VARCHAR (30)
);


CREATE TABLE employees (
Employee _id INT PRIMARY KEY,
Employee _name VARCHAR (50),
gender enum ('M','F'),
age INT,
```

```
hire _date INT,
designation VARCHAR (100),
department _id INT,
location _id INT,
salary decimal (10.2)
);
```

#2 Table ALTER

#---Add a new column named "email" to the Employees table to store employee email addresses.

```
ALTER Table employees
ADD email varchar (50);
```

#-- Modify the data type of the "designation" column in the Employees table to support a wider range of values.

```
ALTER Table employees
MODIFY COLUMN designation VARCHAR (100);
```

#--Drop the “age” column from the Employees table.

```
ALTER TABLE employees
DROP COLUMN age;
```

#--Rename the “hire _date” column to “date _of _joining”.

```
ALTER TABLE employees
```

RENAME COLUMN hire _date TO date _of _joining;

#3 --RENAME TABLE NAME

--Rename the "Departments" table to "Departments _Info".

-- Rename the "Location" table to "Locations".

RENAME TABLE departments TO departments _info,

location TO Locations;

#4. TRUNCATE

#--Table Truncation (TRUNCATE): Write an SQL statement to truncate the Employees table.

TRUNCATE TABLE employees;

#5 DROP

#--DROP: Write the SQL statements to drop the Employees table and then the "employee" database.

DROP Table employees;

DROP DATABASE employee;

#DATABASE RECREATION EMPLOYEE

```
DROP DATABASE IF EXISTS employee;

CREATE DATABASE EMPLOYEE;

USE EMPLOYEE;
```

CREATE TABLE Department-Department id unique--Department name not null and duplicate

```
CREATE TABLE Department (
Department _Id INT PRIMARY KEY,
Department _name VARCHAR (100)
NOT NULL UNIQUE
);
```

CREATE TABLE Location--auto increment unique location id--prevent null and duplicate location

```
CREATE TABLE Location (
Location _Id INT AUTO_INCREMENT PRIMARY KEY,
Location _name VARCHAR (50) NOT NULL UNIQUE
);
```

#--Create table employees--with auto increment employee id--not null employee name--gender -M or F only--age -18 or above only--hire date current date as default--department _id and location id as foreign key

```
CREATE TABLE Employees (
Employee _Id INT AUTO_INCREMENT PRIMARY KEY,
Employee _name VARCHAR (50) NOT NULL,
gender enum ('M','F') NOT NULL,
age INT CHECK (Age >=18),
hire _ date   DATE DEFAULT(CURRENT_DATE),

Department _Id INT,
Location _Id INT,
```

#---defining foreign key

```
CONSTRAINT fk   _Employee _Department
FOREIGN KEY (Department _Id)
REFERENCES Department (Department _Id)
ON DELETE SET NULL,

CONSTRAINT fk _ Employee _Location
 FOREIGN KEY (Location _Id)
 REFERENCES Location (Location _Id)
 ON DELETE SET NULL
 );
```