



beaker-rspec and you: module testing for a brighter future

Alice Nodelman, QE



things break





Alice Nodelman

alice@puppetlabs.com

anode (freenode #puppet-dev)

alicenode (twitter)

anodelman (github)



acceptance testing

we make promises, we test to keep them



what's beaker?





we set things on fire, so that users don't get burnt





the formula

```
Ruby
+ DSL
+ virtualized SUTs
= success
```



why ruby?

we know it and so do other people





the DSL

rubydoc.info

Method Summary

Methods included from Patterns

#block on

Methods included from InstallUtils

#add_system32_hosts_entry, #build_ignore_list, #check_for_package, #copy_module_to, #
#do_higgs_install, #do_install, #extract_repo_info_from, #fetch_puppet, #fetch_puppet
#fetch_puppet_on_windows, #find_git_repo_versions, #get_module_name, #higgs_installer
#install_dev_puppet_module_on, #install_from_git, #install_higgs, #install_package, #
#install_puppet_from_deb, #install_puppet_from_dmg, #install_puppet_from_gem, #install
#install_puppet_from_rpm, #install_puppet_module_via_pmt, #install_puppet_module_via
#install_puppetlabs_release_repo, #installer_cmd, #link_exists?, #parse_for_modulenar
#split author modulename, #upgrade package, #upgrade pe

Methods included from EZBakeUtils

#ezbake_config, #ezbake_stage, #ezbake_tools_available?, #install_ezbake_deps, #insta

Methods included from Helpers

#apply_manifest, #apply_manifest_on, #confine, #confine_block, #create_remote_file, #



```
test_name "say hello to all my hosts!"
hellos = 0
@hosts_each do |host|
  step "i'm going to stay hello to #{host}"
  on host, 'echo hello'
  hellos += 1
end
#make sure that i've been polite!
assert_equal(hellos, hosts.length, \
             "#{hellos} <> #{hosts.length}")
```

what you see in the console

```
Begin tests/confirm.rb
say hello to all my hosts!
 * i'm going to stay hello to pe-ubuntu-lucid
pe-ubuntu-lucid 11:09:10$ echo hello
Created ssh connection to pe-ubuntu-lucid, user: root, opts: {:config=>false, :paranoid=>false, :timeout=>300, :auth
_methods=>["publickey"], :port=>22, :forward_agent=>true, :keys=>["/Users/anode/.ssh/id_rsa"], :user_known_hosts_fil
e=>"/Users/anode/.ssh/known hosts", :user=>"root"}
hello
pe-ubuntu-lucid executed in 0.69 seconds
 * i'm going to stay hello to pe-centos6
pe-centos6 11:09:11$ echo hello
Created ssh connection to pe-centos6, user: root, opts: {:config=>false, :paranoid=>false, :timeout=>300, :auth_meth_
ods=>["publickey"], :port=>22, :forward_agent=>true, :keys=>["/Users/anode/.ssh/id_rsa"], :user_known_hosts_file=>"/
Users/anode/.ssh/known hosts". :user=>"root"}
hello
```



console summary

```
Test Suite: tests @ 2015-01-05 11:09:10 -0800

    Host Configuration Summary -

        - Test Case Summary for suite 'tests' -
 Total Suite Time: 0.83 seconds
Average Test Time: 0.83 seconds
        Attempted: 1
           Passed: 1
           Failed: 0
          Errored: 0
          Skipped: 0
          Pending: 0
            Total: 1
```



Beaker Junit Output - so pretty!

Beaker Puppet Labs Automated Acceptance Testing System

Elapsed Tim	ne: 3278.00423				
		Total: 268	Failed: 0	Skipped: 48	Pendi
pre_suite	Elapsed Time: 86.3	39030 sec Failed: 0	Skipped: 0	Pending: 0	
tests	Elapsed Time: 319 Total: 264	91.61392 sec Failed: 0	Skipped: 48	Pending: 1	
Properties					

virtualization


- vSphere
- fusion
- vagrant
- openstack
- docker
- AWS
- GCE
- aix + solaris



```
pe-ubuntu-lucid:
             roles:
               agent
               dashboard
               database
               master
             vmname : pe-ubuntu-lucid
             platform: ubuntu-10.04-i386
             snapshot : clean-w-keys
             hypervisor: fusion
           pe-centos6:
             roles:
               agent
             vmname : pe-centos6
             platform: el-6-i386
             hypervisor: fusion
             snapshot: clean-w-keys
         CONFIG:
           nfs_server: none
KICKOFF
           consoleport: 443
```

HOSTS:


the workflow





Throw Away, Start Fresh

so, beaker-rspec?



RSpec

```
# bowling spec.rb
require 'bowling'
describe Bowling, "#score" do
  it "returns 0 for all gutter game" do
    bowling = Bowling.new
    20.times { bowling.hit(0) }
    bowling.score.should eq(0)
  end
end
```



Serverspec

```
describe file('/etc/passwd') do
  it { should be_file }
end
describe package('httpd') do
  it { should be_installed }
end
describe iptables do
  it { should have_rule('-P INPUT ACCEPT') }
end
```



a beaker-rspec test

```
context 'service_ensure => running:' do
  it 'runs successfully' do
    pp = "class { 'ntp': service_ensure => running }"
    apply_manifest(pp, :catch_failures => true) do |r|
      expect(r.stderr).not_to match(/error/i)
    end
  end
end
```



console output

Finished in 5 minutes 4 seconds 94 examples, 0 failures, 17 pending





Workshop!



Run Tests Included in a Puppet Supported Module





part 1

Steps

- install testing dependencies
- clone puppetlabs-inifile module
- set test parameters
- execute the puppetlabs-inifile beakerrspec tests



dependencies

git

Ruby 1.9+

RubyGems

Bundler

Vagrant 1.5.2

VirtualBox



clone puppetlabs-inifile

\$ git clone https://github.com/puppetlabs/puppetlabs-inifile

```
anode@eum ~$ git clone https://github.com/puppetlabs/puppetlabs-inifile
Cloning into 'puppetlabs-inifile'...
remote: Counting objects: 1151, done.
remote: Total 1151 (delta 0), reused 0 (delta 0)
Receiving objects: 100% (1151/1151), 193.31 KiB | 191.00 KiB/s, done.
Resolving deltas: 100% (426/426), done.
Checking connectivity... done.
```



setup your test parameters

```
$ cd puppetlabs-inifile/
$ export SPEC_FORGE="http://module-staging.puppetlabs.com"
$ export BEAKER_debug=true
$ export BEAKER_destroy=no
$ export BEAKER setfile=spec/acceptance/nodesets/ubuntu-server-12042-x64.yml
```

```
anode@eum ~$ cd puppetlabs-inifile/
anode@eum puppetlabs-inifile (master)$ export SPEC_FORGE="http://module-staging.puppet
labs.com"
anode@eum puppetlabs-inifile (master)$ export BEAKER_debug=true
anode@eum puppetlabs-inifile (master)$ export BEAKER_destroy=no
anode@eum puppetlabs-inifile (master)$ export BEAKER_setfile=spec/acceptance/nodesets/
ubuntu-server-12042-x64.yml
anode@eum puppetlabs-inifile (master)$
```



install!

```
$ bundle install --path=vendor/bundle
```

anode@eum puppetlabs-inifile (master)\$ bundle install --path=vendor/bundle



execute the tests

\$ bundle exec rspec spec/acceptance

```
anode@eum puppetlabs-inifile (master)$ bundle exec rspec spec/acceptance
Hypervisor for ubuntu-server-12042-x64 is vagrant
Beaker::Hypervisor, found some vagrant boxes to create
created Vagrantfile for VagrantHost ubuntu-server-12042-x64
Bringing machine 'ubuntu-server-12042-x64' up with 'virtualbox' provider...
==> ubuntu-server-12042-x64: Importing base box 'ubuntu-server-12042-x64-vbox4210-nocm'
==> ubuntu-server-12042-x64: Matching MAC address for NAT networking...
==> ubuntu-server-12042-x64: Setting the name of the VM: ubuntu-server-12042-x64yml ubu
ntu-server-12042-x64 1420499775611 97519
==> ubuntu-server-12042-x64: Clearing any previously set forwarded ports...
==> ubuntu-server-12042-x64: Clearing any previously set network interfaces...
==> ubuntu-server-12042-x64: Preparing network interfaces based on configuration...
    ubuntu-server-12042-x64: Adapter 1: nat
    ubuntu-server-12042-x64: Adapter 2: hostonly
```



What's that setfile?

\$ ls spec/acceptance/nodesets
\$ cat spec/acceptance/nodesets/ubuntu-server-12042-x64.yml

```
HOSTS:
ubuntu-server-12042-x64:
roles:
- master
platform: ubuntu-12.04-amd64
box: ubuntu-server-12042-x64-vbox4210-nocm
box_url: http://puppet-vagrant-boxes.puppetlabs.com/ubuntu-server-12042-x64-vbox42
10-nocm.box
hypervisor: vagrant

CONFIG:
type: foss
```



spec_helper_acceptance.rb

\$ cat spec/spec_helper_acceptance.rb

```
anode@eum puppetlabs-inifile (master)$ cat spec/spec_helper_acceptance.rb
require 'beaker-rspec/spec_helper'
require 'beaker-rspec/helpers/serverspec'
unless ENV['RS PROVISION'] == 'no'
  # This will install the latest available package on el and deb based
  # systems fail on windows and osx, and install via gem on other *nixes
  foss opts = { :default action => 'gem install' }
  if default.is pe?; then install pe; else install puppet( foss opts ); end
  hosts.each do |host|
    if host['platform'] =~ /debian/
      on host, 'echo \'export PATH=/var/lib/gems/1.8/bin/:${PATH}\' >> ~/.bashrc'
      on host, "mkdir -p #{host['distmoduledir']}"
    end
  end
end
```



the tests

\$ ls spec/acceptance

```
anode@eum puppetlabs-inifile (master)$ ls spec/acceptance/
ini_setting_spec.rb ini_subsetting_spec.rb nodesets
```



ENV vars for defining SUTs



ENV vars for controlling SUTs

```
BEAKER_provision or RS_PROVISION =>
should we provision new hosts (yes/no)?

BEAKER_destroy or RS_DESTROY =>
should we destroy hosts after testing (yes/no)?
should we destroy hosts only on passing tests (onpass)?
```



additional ENV vars

```
BEAKER_keyfile or RS_KEYFILE =>

use this ssh key to log into test hosts
```

```
BEAKER_debug or RS_DEBUG =>
```

should we print debug during testing?



SUTs for you

```
$ cd .vagrant/beaker_vagrant_files/ubuntu-server-12042-
x64.yml/
$ vagrant status
$ vagrant ssh ubuntu-server-12042-x64
```

```
anode@eum puppetlabs-inifile (master)$ cd .vagrant/beaker_vagrant_files/ubuntu-serve
12042-x64.vml/
anode@eum ubuntu-server-12042-x64.yml (master)$ vagrant status
Current machine states:
ubuntu-server-12042-x64 running (virtualbox)
The VM is running. To stop this VM, you can run `vagrant halt` to
shut it down forcefully, or you can run `vagrant suspend` to simply
suspend the virtual machine. In either case, to restart it again,
simply run `vagrant up`.
anode@eum ubuntu-server-12042-x64.yml (master)$ vagrant ssh ubuntu-server-12042-x64
Welcome to Ubuntu 12.04.2 LTS (GNU/Linux 3.5.0-23-generic x86 64)
* Documentation: https://help.ubuntu.com/
New release '14.04.1 LTS' available.
Run 'do-release-upgrade' to upgrade to it.
Last login: Tue Jan 6 17:10:40 2015 from 10.0.2.2
vagrant@ubuntu-server-12042-x64:~$ ls
base.sh cleanup.sh vagrant.sh virtualbox.sh zerodisk.sh
vagrant@ubuntu-server-12042-x64:~$
```



part 2

Steps

- clone beaker-rspec-demo
- write Beaker DSL based tests
- write Serverspec based tests
- write a combination Beaker + Serverspec test!



clone beaker-rspec-demo

```
$ git clone <a href="https://github.com/anodelman/beaker-rspec-demo">https://github.com/anodelman/beaker-rspec-demo</a>
```

```
anode@eum ~$ cd beaker-rspec-demo/
anode@eum beaker-rspec-demo (master)$ ls
LICENSE README.md user-demo
anode@eum beaker-rspec-demo (master)$ cd user-demo/
anode@eum user-demo (master)$ ls
Gemfile Rakefile manifests spec vendor
README.md lib metadata.json tests
```



install & execute demo tests

```
$ bundle install --path vendor/bundle
$ export BEAKER_debug=true
$ export BEAKER_destroy=no
$ bundle exec rspec spec/acceptance
<--- test output here --->
```



what's really running here?


\$ vi spec/acceptance/demo_spec.rb

```
require 'spec helper acceptance'
describe "my tests" do
  # an example using the beaker DSL
  # use http://www.rubydoc.info/github/puppetlabs/beaker/Beaker/DSL
  it "should say hello!" do
    result = shell( 'echo hello' )
    expect(result.stdout).to match(/hello/)
  end
  # an example using Serverspec
  # use http://serverspec.org/resource_types.html
  describe package('puppet') do
    it { should be installed }
  end
end
```



write your own tests

CHALLENGE ACCEPTED





Beaker DSL Challenge (1 of 2)

- Use create_remote_file to create a file called 'demo.txt' with contents 'foo\nfoo\nfoo\n'
 - a. Use on to grep the file for 'foo'
 - b. Use *on* to grep the file for 'bar' and catch the error



Beaker DSL Challenge (2 of 2)

2. Use apply_manifest to execute these manifests, use expect_changes as required:

```
a. user {'foo':
       ensure => present,}
b. user {'foo':
       ensure => absent,}
c. user {'root':
       ensure => present,}
```



Serverspec Challenge

- Write a test that uses Serverspec to ensure that sshd is running
- 2. Write two tests and ensure that:
 - a. 'root' user exists
 - b. 'foo' user does not exist



Together: The Final Challenge

- 1. Use apply_manifest to create a remote file (/tmp/demo.txt) with the contents 'this is my file'
- 2. Use Serverspec to check that the file is present and has the correct contents.







resources

git

Ruby 1.9+

RubyGems

Bundler

Vagrant 1.5.2

VirtualBox

Beaker Code

Beaker-rspec Code

Beaker DSL

Pretty Beaker Junit Output

Serverspec Resource Types

Beaker-rspec Demo Code

PuppetLabs Inifile Module

Puppet Supported Modules



contact




Alice Nodelman Kevin Imber

Hipchat: QE-QA

freenode irc: #puppet-dev

Jira Beaker Bug Backlog







Beaker DSL Challenge (1 of 2)

SOLUTION

```
it "can create and confirm a file" do
    shell( 'rm -f demo.txt' )
    create_remote_file(default, 'demo.txt', 'foo\nfoo\nfoo\n')
    shell( 'grep foo demo.txt' )
    shell( 'grep bar demo.txt', :acceptable_exit_codes => [1] )
end
```



Beaker DSL Challenge (2 of 2) SOLUTION

```
it "should be able to apply manifests" do
 manifest 1 = "user {'foo':
        ensure => present,}"
 manifest_2 = "user {'foo':
        ensure => absent,}"
 manifest_3 = "user {'root':
        ensure => present,}"
 apply_manifest( manifest_1, :expect_changes => true )
 apply_manifest( manifest_2, :expect_changes => true )
 apply_manifest( manifest_3 )
end
```



Serverspec Challenge

SOLUTION

```
describe service('sshd') do
  it { should be_running }
end
describe user('root') do
  it { should exist }
end
describe user('foo') do
  it { should_not exist }
end
```



Together: The Final Challenge

SOLUTION

```
context "can use both serverspec and Beaker DSL" do
 it "can create a file" do
    shell( 'rm -f /tmp/demo.txt' )
   manifest = "file {'demofile':
      path => '/tmp/demo.txt',
      ensure => present,
     mode => 0640
     content => \"this is my file.\",
   apply_manifest(manifest, :expect_changes => true)
 end
 describe file('/tmp/demo.txt') do
    it { should be file }
 end
 describe file('/tmp/demo.txt') do
   it { should contain 'this is my file.' }
 end
end
```

